This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Э

NEW MEXICO OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 Revised June 10, 2003

Operator <u>Cheuron</u> Lease Name <u>Rincon</u> No. 223 A

Well

Location Of Well: Unit Letter _____ Sec <u>34</u> Twp <u>27</u> Rge <u>7</u> API # 30-0<u>39 - 22646</u>

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion Pi	Clure cliff	QCS	Flow	TBS
Lower	est wede / Dakoin	gas	Plunger	TBS

Pre-Flow Shut-In Pressure Data

Upper Hour Date, Shut-In Completion 9^3 9^{-10-14}	Length of Time Shut-In ころをいん	SI Press. Psig	Stabilized? (Yes or No)
LowerHour, Date, Shut-InCompletion $Q^{3.4}$ Q^{-10}	Length of Time Shut-In 25 シングル	SI Press. Psig	Stabilized? (Yes or No)

		the second s	Flow T	est No	.1	
Commenced a	t (hour, date)* 1	1 9-1	1-14	Zone	producing (Up	oper or Lower): lower
Tune	Lapsed Time		ssure		Prod. Zone	Remarks
(Hour, Date)	Since*	Upper Compl.	Lower Com	pl.	Temp.	i di seconda di second
1,05	^	1.0	2.			compress Running no chaqui uppe
11. 500	Smir	65	21			no chapit Uppe
1125	15mir	65	13			nochage in upper
						RCVD SEP 19'14
		-				OIL CONS. DIV.
<u> </u>		<u></u>				DIST. 3
						Liono
		<u></u>				
· · · · ·						
Due divetion note	<u> </u>	<u>l</u>				

Production rate during test

<u>`</u> ~''	DODD 1			<u>^</u>	000	
Oil:	BOPD based on	Bbis.	In Hr			
011.	DOLD Dasca on	D015.	111 111	.8. 014	1V. 00K	
		······	······································	·		

MCFPD; Test thru (Orifice or Meter): meTer Gas: ///

è

Mid-Test Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion				
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	· · ·		_	
				· · · · · · · · · · · · · · · · · · ·

(Continue on reverse side)

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

· · · ·			Flow Te	st No.	. 2			
Commenced at (hour, date)**				Zone	producing (U	pper or Lower):		
Time	Lapsed Time	Pre	ssure		Prod. Zone	Remarks		
(Hour, Date)	Since**	Upper Compl. Lower Compl.		1.	Temp.			
				1				
	· · · · · · · · · · · · · · · · · · ·					<u></u>		
			(
						1	<u> </u>	
						1		
Droduction note		<u> </u>						
Production rate		<u>.</u>						
Oil:	BOPD base	d on	_Bbls. In		Hrs	Grav	GOR	
Gas:	MCFF	D; Test thru (Ori	fice or Meter):					
Remarks:								

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved 4/22 2015	Operator Ctleuron
New Mexico Oil Conservation Division	By Randy Calcote
By Brd Pall	Title <u>Calder service</u>
Title DEPUTY DIL & GAS INSPECTAR	E-mail Address <u>Randy . C. Q. Culdo-ser</u>
DISTRICT #3	Date 9-11-14
Northwest New Mexico Packer Les	akage Test Instructions

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.

4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. <u>Note</u>: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shal remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests immediately prior to the beginning of each flow-period, at fifteen-minut intervals during the first hour thereof, and at hourly intervals thereafter including one pressure measurement immediately prior to the beginnin of each flow period, at least one time during each flow period (a approximately the midway point) and immediately prior to the conclusio of each flow period. Other pressures may be taken as desired, or may b requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Page 2