1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Santa Fe, NM 87505

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application Oil Cons. DIV DIST. 3
Type of action:
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method MAY 07 2015
Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
I. OCHER II. 779
Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Ridenour Gas Com 1A
API Number:3004522454OCD Permit Number:
U/L or Qtr/QtrP Section13 Township31N Range11W County:San Juan
Center of Proposed Design: Latitude 36.894318 Longitude -107.93597 NAD: ☐1927 ☐ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. ☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4.
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Form C-144

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock	
watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
☐ A List of wells with approved application for permit to drill associated with the pit. ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	.15.17.9 NMAC
and 19.15.17.13 NMAC	
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Falternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
	D Ve-D M
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure pby a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19 Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards can Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe to the best of my knowledge.	lief.
Name (Print):	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including cosure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 5/12 Title: OCD Permit Number:	1/2015
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do no section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do no	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do no section of the form until an approved closure plan has been obtained and the closure activities have been completed.	t complete this

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure required	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Signature:	Date:May 4, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Ridenour Gas Com 1A API No. 3004522454 Unit Letter P, Section 13, T31N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

						OPERA	ГOR		Initia	al Report	\boxtimes	Final Report
Name of Company: BP Address: 200 Energy Court, Farmington, NM 87401						Contact: Jeff Peace						
				M 87401	,	Telephone No.: 505-326-9479						
Facility Nar	ne: Roden	our Gas Con	ı 1A]	Facility Typ	e: Natural gas v	well				
Surface Ow	ner: Privat	te		Mineral O	wner: I	Private			API No	. 30045224	54	
				LOCA	TION	OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/V	Vest Line	County: Sa	n Juan	
P	13	31N	11W	1,150	South		790	East		, , , , , ,		
		Lati	tude36	.894318		_ Longitud	le107.93597_					
				NAT	URE	OF REL	EASE					
Type of Relea							Release: N/A			lecovered: N		02 100 0
Source of Rel	ease: belov	v grade tank –	95 bbl			Date and H N/A	Iour of Occurrenc	ce:	Date and	Hour of Disc	covery:	N/A
Was Immedia	te Notice (Yes	No Not Rec	quired	If YES, To	Whom?	·				
By Whom?						Date and H						
Was a Watero	course Reac	ched?	Yes 🛛	No		If YES, Vo	lume Impacting t	the Wate	rcourse.			
If a Watercou	rse was Im	pacted, Descri	be Fully.*									
				n Taken.* Samplin and chlorides below					g removal t	o ensure no	soil im	pacts from
				en.* BGT was ren ctive well area.	noved a	nd the area u	nderneath the BG	T was sa	ampled. Th	ne area unde	the Bo	GT was
regulations all public health should their o	l operators or the envir perations h ment. In a	are required to conment. The ave failed to a ddition, NMO	report an acceptance dequately CD accep	is true and comple d/or file certain re e of a C-141 repor investigate and re- tance of a C-141 re-	lease no t by the mediate	otifications ar NMOCD ma contamination	nd perform correct arked as "Final Ro on that pose a thre	tive action of the control of the co	ons for rele oes not reli- ound water	eases which is eve the operation, surface wat	nay en ator of er, hur	danger liability nan health
0		2 0					OIL CONS	SERV.	ATION	DIVISIO	N	
Signature: Printed Name	· Jeff Peace	ope				Approved by	Environmental S _I	pecialist	:			
Title: Field Er			r		F	Approval Dat	e:	E	Expiration I	Date:		
E-mail Addre	ss: peace.je	ffrey@bp.com	1			Conditions of		•		Attached		
Date: May 4,	2015	P	hone: 505	-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, E	NGINEERING, INC. BLOOMFIELD, NM 8 05) 632-1199	7413	API #: 3004522 TANK ID (if applicble):	
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER	2:	PAGE #:	of 1
SITE INFORMATION	I: SITE NAME: RIDEN	OUR GC #1A		DATE STARTED: 02/2	24/15
QUAD/UNIT: P SEC: 13 TWP:	31N RNG: 11W PM	: NM CNTY: SJ S	ST: NM	DATE FINISHED:	
1/4-1/4/FOOTAGE: 1,150'S / 790	D'E SE/SE LEASE	TYPE: FEDERAL / STATE FEE	/ INDIAN	ENVIRONMENTAL	
LEASE#:	PROD. FORMATION: DK C	STRIKE ONTRACTOR: MBF - B. SCH	UMAN	SPECIALIST(S): J	CB
REFERENCE POINT	: WELL HEAD (W.H.) GPS	s coord.: 36.89455 X	107.93584	GL ELEV.: 5	,729'
		.894318 X 107.93597	DISTANCE/BEAF	RING FROM W.H.: 76', S2	27W
2)	GPS COORD.:		DISTANCE/BEAF	RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEAF	RING FROM W.H.:	
4)	DISTANCE/BEAF	RING FROM W.H.:			
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # 0	OR LAB USED: HALL			OVM READING (ppm)
1) SAMPLE ID: 95 BGT 5-pt. (@ 5' SAMPLE DATE:02/24	/15 SAMPLETIME: 1328 LABAN	VALYSIS: 801	5B/8021B/300.0 (CI)	0.0
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB AN	NALYSIS:		
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB AN	VALYSIS:		
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB AN	NALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND	SILT / SILTY CLAY / CLAY / GRAVEL / 01	THER		
SOIL COLOR: MODERATION OF SOIL COLOR: MODERATION (ALL OTHERS): NON COHESIVE (SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST/MOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIST/WOIS	COHESIVE COHESIVE / HIGHLY COHESIVE OSE FIRM / DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS. 5	PLASTICITY (CLAYS): NON PLASTIC / SLIC DENSITY (COHESIVE CLAYS & SILTS HC ODOR DETECTED: YES NO EXPL ANY AREAS DISPLAYING WETNESS: YE): SOFT/FIRM/S ANATION -	STIFF / VERY STIFF / HARD	LY PLASTIC
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMENT	T: YES NO EXPLANATION -			
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: WELL PAD SHARED WITH CAN	YES NO EXPLANATION - 95 LOV	V PROFILE ABOVE-GRADE TANK	TO BE SET ATO	OP BGT LOCATION.	
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. XNA	ft. X NA ft. EX	CAVATION EST	IMATION (Cubic Yards) :	NA
DEPTH TO GROUNDWATER: <50' N	EAREST WATER SOURCE: <1,000	NEAREST SURFACE WATER: <	200' NMOC	D TPH CLOSURE STD: 10	0 ppm
SITE SKETCH	BGT Located: off on sit	PLOT PLAN circle:	attached	CALIB. READ. = 52.1 pp	m RF =0.52
	\oplus		♦ own	CALIB. GAS = 100 pp	
	W.H.		TIME:	12:20 am/pm DATE: 02	//24/15
	BERM	CANEPLE GC B # 1 W.H.	'	MISCELL. NO	ΓES
ANIMAS R.	050404700	\oplus	w	O:	
PBGTL T.B. ~ 5'	SEPARATOR		RE	EF. #: P-51	
B.G.			Pł		
		SOUND	10	#: Z2-006Q0	
1 °			RUN —	ermit date(s): 06/14	22.00
FENCE		COMPRESSOR	Tan	3	
		COMPRESSOR	A		N)
		V	S.P.D.	BGT Sidewalls Visible: Y /	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	ON DEPRESSION; B.G. = BELOW GRADE: B = B			BGT Sidewalls Visible: Y /	N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLE	OW-GRADE TANK LOCATION; SPD = SAMPLE F	POINT DESIGNATION; R.W. = RETAINING WALL;	NA-NOT M	agnetic declination: 10	°E
NOTES:		ONSITE: 02/24/15			

Analytical Report

Lab Order 1502A07

Date Reported: 2/26/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-PT @ 5'

Project: Ridenour GC 1A

Collection Date: 2/24/2015 1:28:00 PM

Lab ID: 1502A07-001

Matrix: MEOH (SOIL) Received Date: 2/25/2015 7:30:00 AM

Analyses	Result	RL Qu	ual Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS				Analyst	BCN
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	2/25/2015 11:58:13 AM	17889
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	2/25/2015 11:58:13 AM	17889
Surr: DNOP	98.1	63.5-128	%REC	1	2/25/2015 11:58:13 AM	17889
EPA METHOD 8015D: GASOLINE RANG	GE				Analyst	NSB
Gasoline Range Organics (GRO)	ND	3.9	mg/Kg	1	2/25/2015 11:21:15 AM	R24505
Surr: BFB	99.4	80-120	%REC	1	2/25/2015 11:21:15 AM	R24505
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.039	mg/Kg	1	2/25/2015 11:21:15 AM	R24505
Toluene	ND	0.039	mg/Kg	1	2/25/2015 11:21:15 AM	R24505
Ethylbenzene	ND	0.039	mg/Kg	1	2/25/2015 11:21:15 AM	R24505
Xylenes, Total	ND	0.078	mg/Kg	1	2/25/2015 11:21:15 AM	R24505
Surr: 4-Bromofluorobenzene	108	80-120	%REC	1	2/25/2015 11:21:15 AM	R24505
EPA METHOD 300.0: ANIONS					Analyst:	LGT
Chloride	ND	30	mg/Kg	20	2/25/2015 11:21:57 AM	17897

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1502A07

26-Feb-15

Client:

Blagg Engineering

Project:

Ridenour GC 1A

Sample ID MB-17897

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

Batch ID: 17897

RunNo: 24517

2/25/2015

Analysis Date: 2/25/2015

SeqNo: 721944

Units: mg/Kg

RPDLimit

Qual

Analyte Chloride

Result ND

SPK value SPK Ref Val %REC PQL 1.5

LowLimit

HighLimit

%RPD

%RPD

TestCode: EPA Method 300.0: Anions

Client ID:

Prep Date:

Prep Date:

Sample ID LCS-17897 LCSS

2/25/2015

SampType: LCS

Batch ID: 17897

RunNo: 24517

SeqNo: 721945

LowLimit

Units: mg/Kg

HighLimit

Analyte

Analysis Date: 2/25/2015

14

SPK value SPK Ref Val PQL

0

%REC 93.4

90

RPDLimit

Qual

Chloride

Result

1.5

15.00

110

Qualifiers:

Value exceeds Maximum Contaminant Level

Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded H

ND Not Detected at the Reporting Limit P Sample pH Not In Range

Reporting Detection Limit

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1502A07

26-Feb-15

Client:

Blagg Engineering

Project:

Ridenour GC 1A

Sample ID MB-17889	SampTyp	e: MBL	K	TestCode: EPA Method 8015D: Diesel Range Organics						
Client ID: PBS	Batch II	D: 1788	9	RunNo: 24501						
Prep Date: 2/25/2015	Analysis Date: 2/25/2015			SeqNo: 721399			Units: mg/Kg			
Analyte	Result	PQL S	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.0		10.00		89.6	63.5	128			
	SampType: LCS TestCode: EPA Method 8015D: Diesel Range Organics									
Sample ID LCS-17889	SampTyp	e: LCS		Tes	Code: El	PA Method	8015D: Diese	el Range C	Organics	
Sample ID LCS-17889 Client ID: LCSS	. ,,	D: 1788			Code: El		8015D: Diese	el Range (Organics	
	. ,,	D: 1788	9	R		4501	8015D: Diese Units: mg/K		Organics	
Client ID: LCSS	Batch II	D: 1788 e: 2/25	9 5/2015	R	tunNo: 2	4501			Organics RPDLimit	Qual
Client ID: LCSS Prep Date: 2/25/2015	Batch II	D: 1788 e: 2/25	9 5/2015	R	eqNo: 7	4501 21400	Units: mg/K	(g		Qual

Sample ID	1502A07-001AMS	SampType	: MS	3	Tes	tCode: El	PA Method	8015D: Diese	el Range (Organics	
Client ID:	95 BGT 5-PT @ 5'	Batch ID	17	889	F	RunNo: 2	4501				
Prep Date:	2/25/2015	Analysis Date	2/	25/2015	S	SeqNo: 7	22007	Units: mg/K	(g		
Analyte		Result F	QL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Organics (DRO)	44	10	49.90	0	88.3	29.2	176			
Surr: DNOP		4.9		4.990		97.8	63.5	128			

Sample ID	1502A07-001AMS	SampTy	pe: MS	SD	Test	tCode: El	PA Method	8015D: Dies	el Range C	Organics			
Client ID:	ent ID: 95 BGT 5-PT @ 5' Batch ID: 17889					RunNo: 24501							
Prep Date:	2/25/2015	/25/2015 Analysis Date: 2/25/2015			S	SeqNo: 722008 Units: mg/Kg							
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range C	Organics (DRO)	44	10	50.25	0	88.3	29.2	176	0.751	23			
Surr: DNOP		5.1		5.025		101	63.5	128	0	0			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1502A07

26-Feb-15

Client:

Blagg Engineering

Project:

Ridenour GC 1A

Sample ID 5ML RB	SampType:	MBLK	Tes	tCode: E	PA Method	8015D: Gase	oline Rang	е			
Client ID: PBS	Batch ID:	R24505	F	RunNo: 24505							
Prep Date:	Analysis Date:	ysis Date: 2/25/2015 SeqNo: 721902 Units: mg/Kg				K g					
Analyte	Result PQ	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Gasoline Range Organics (GRO)	ND 5	.0									
Surr: BFB	930	1000		93.4	80	120					
Sample ID 2.5UG GRO LCS SampType: LCS TestCode: EPA Method 8015D: Gasoline Range											
Client ID: LCSS	Batch ID:	R24505	RunNo: 24505								
Prep Date:	Analysis Date:	2/25/2015	5	SeqNo: 7	21903	Units: mg/h	(g				
Analyte	Result PQ	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Gasoline Range Organics (GRO)	25 5	.0 25.00	0	98.8	64	130					
Surr: BFB	1000	1000		101	80	120					
Sample ID 1502A07-001AMS	SampType:	VIS	Tes	tCode: El	PA Method	8015D: Gaso	oline Rang	e			
Client ID: 95 BGT 5-PT @ 5'	Batch ID:	R24505	F	RunNo: 2	4505						
Prep Date:	Analysis Date:	2/25/2015	5	SeqNo: 7	21906	Units: mg/F	(g				
Analyte	Result PQI	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Gasoline Range Organics (GRO)	19 3	9 19.52	2.186	84.6	47.9	144					
Surr: BFB	770	780.6		98.9	80	120					

Sample ID	1502A07-001AMSD	SampTyp	e: MS	SD	Tes	tCode: El	PA Method	8015D: Gaso	line Rang	е	
Client ID:	R	RunNo: 2	4505								
Prep Date:		Analysis Dat	e: 2 /	25/2015	S	SeqNo: 7	21907	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range	e Organics (GRO)	18	3.9	19.52	2.186	80.4	47.9	144	4.48	29.9	
Surr BFB		760		780.6		97.8	80	120	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1502A07

26-Feb-15

Client: Project:

Blagg Engineering

Ridenour GC 1A

Sample ID 5ML RB	Samp7	уре: МЕ	BLK	Tes	TestCode: EPA Method 8021B: Volatiles							
Client ID: PBS	Batcl	Batch ID: R24505			RunNo: 24505							
Prep Date:	Analysis D	Date: 2/	25/2015	S	SeqNo: 7	21911	Units: mg/K	g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit %RPD		RPDLimit	Qual		
Benzene	ND	0.050										
Toluene	ND	0.050										
Ethylbenzene	ND	0.050										
Xylenes, Total	ND	0.10										
Surr: 4-Bromofluorobenzene	1.0		1.000		104	80	120					

Sample ID 100NG BTEX LC	S SampT	S	TestCode: EPA Method 8021B: Volatiles							
Client ID: LCSS	Batch	n ID: R2	4505	F						
Prep Date:	Date: Analysis Date: 2/25/2015				SeqNo: 7					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.0	0.050	1.000	0	105	80	120			
Toluene	1.0	0.050	1.000	0	101	80	120			
Ethylbenzene	1.0	0.050	1.000	0	100	80	120			
Xylenes, Total	3.0	0.10	3.000	0	100	80	120			
Surr: 4-Bromofluorobenzene	1.1		1.000		111	80	120			

Sample ID 1502A07-001AM	S Samp	SampType: MS TestCode: EPA Method 8021B: Volatiles									
Client ID: 95 BGT 5-PT @	5' Batc	h ID: R2	4505	RunNo: 24505							
Prep Date:	Analysis [Date: 2/	25/2015	5	SeqNo: 7	21915	Units: mg/K	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	0.86	0.039	0.7806	0	110	69.2	126				
Toluene	0.83	0.039	0.7806	0.01291	105	65.6	128				
Ethylbenzene	0.85	0.039	0.7806	0.008259	108	65.5	138				
Xylenes, Total	2.5	0.078	2.342	0.03392	107	63	139				
Surr: 4-Bromofluorobenzene	0.86		0.7806		110	80	120				

Sample ID	1502A07-001AMSD	Sampl	ype: MS	SD	TestCode: EPA Method 8021B: Volatiles						
Client ID:	95 BGT 5-PT @ 5' Batch ID: R24505				R						
Prep Date: Analysis Date: 2/25/2015			25/2015	S	SeqNo: 7						
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		0.81	0.039	0.7806	0	104	69.2	126	5.08	18.5	
Toluene		0.82	0.039	0.7806	0.01291	103	65.6	128	2.09	20.6	
Ethylbenzene		0.80	0.039	0.7806	0.008259	102	65.5	138	5.39	20.1	
Xylenes, Total		2.4	0.078	2.342	0.03392	99.9	63	139	6.51	21.1	
Surr: 4-Brom	nofluorobenzene	0.89		0.7806		114	80	120	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG		Work Order Number	1502	.07		Ropt	tNo: 1
Received by/date	e: /	tr	02/25/15					
Logged By:	Lindsay N	langin	2/25/2015 7:30:00 AM			Jimshy Hornes		
Completed By:	Lindsay N	angin	2/25/2015 7:46:33 AM			Jimehy Harry D		
Reviewed By:	A	1 15	2/25/15					
Chain of Cus	tody	1	2/- 2//3					,
1. Custody sea	ls intact on s	sample bottles?		Yes		No 🗌	Not Present	
2. Is Chain of C	Custody comp	plete?		Yes		No 🗌	Not Present	
3. How was the	sample deli	vered?		Cour	er			
Log In								
	mpt made to	cool the samples?		Yes		No 🗌	NA	
5. Were all san	nples receive	ed at a temperature	of >0° C to 6.0°C	Yes		No 🗌	NA	
6. Sample(s) in	n proper cont	tainer(s)?		Yes		No 🗌		
7. Sufficient sar	mple volume	for indicated test(s	;)?	Yes		No 🗌		
8. Are samples	(except VO	A and ONG) proper	ly preserved?	Yes		No 🗌		
9. Was preserv	ative added	to bottles?		Yes		No 🏕	NA	
10.VOA vials ha	ave zero head	dspace?		Yes		No 🗆	No VOA Vials	
		ners received broke	en?	Yes		No 🐼	[
							# of preserved bottles checked	d
12. Does paperw				Yes		No 🗌	for pH:	(<2 or >12 unless noted)
		hain of custody) entified on Chain of	Custody?	Yes		No 🗌	Adjusted	
14. Is it clear who			Custody?	Yes		No 🗆		
15. Were all hold				Yes		No 🗌	Checked	by:
(If no, notify	customer for	authorization.)						N
Cussial Hand	lling /if on	nlicable)						
Special Hand		-				N	NA	
16. Was client no	otified of all o	discrepancies with	his order?	Yes		No 🗆	NA	
Person	Notified:		Date:					
By Wh			Via:	eMa	il P	hone Fax	In Person	Mining.
Regard							and the second deposit delicated and the second delicated and the secon	MARKATO .
Client I	Instructions:	Personal Control of the Control of t						
17. Additional re	emarks:							
18. Cooler Info Cooler No	1	Condition S Good Ye		Seal Da	ite	Signed By		

Chain-of-Custody Record Client: BP America BLAGG Engr. Mailing Address: P. D. Box & 7				Turn-Around	Time:	RUSH NAV					1 & 1	. 1					BIB	45	BIT	· A I	
Client:	BPA	mente	i	☐ Standard	Rush	RUSH DAK SAME DAK	-												NT		
	BLAGG	Encor.		Project Name	e:	4 0			100					ironr							_
Mailing	Address:	P. B. B.	ox 87	KIDE	NOUR 60	. 1A		490	01 H	awkii								109			
-	Bloom.	field	NM 87413	Project #:						5-34				ax							
			20 - 1183									A	naly	/sis	Req	uest	1 10				
email or			a shador side	Project Mana	iger:		(8021)	only)	30)					04)							
QA/QC F Stan			□ Level 4 (Full Validation)	J-Blagg					30 / MI			SIMS)		,PO4,S	2 PCB's						
Accredi	tation	□ Othe	r	Sampler: J On Ice:	+ I MES	+ TPH (RO/D	118.1)	04.1)	8270	10	O3,NO2	s / 8082		(A)				or N)		
□ EDD	(Type)			Sample Tem	perature: /	2	世	rBE	3 (G	od 4	po g	0 0	etals	Z,	cide	(A	i-VC	DE			2
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO. 150ZA) 7	BTEX + WIBE	BTEX + MTBE	TPH 8015B (GRO / DRO / MRO)	TPH (Method 418.1)	EDB (Method 504.1)	PAH's (8310 or 8270 SIMS)	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			Air Bubbles (Y or N)
124/249	1328	SOIL	95 BET 5- PT C5	4 ~ X	COUL	-001	X		X								-	X		\top	
			,																	\perp	
										_	-									_	-
											\dashv								+	+	-
											\dashv									+	+
																					土
			9							_	\dashv								_	_	
										+	\dashv	\dashv							+	_	_
											1	-							\dashv	+	+
																				\top	\top
Date: 2015 Date:	Time:	Relinquish	1 Blogg	Received by: Received by:	Julane	Date Time Date Time Date Time	Rer	nark	Ĩ	BILL	EY						TZ				
24/15	1714 f necessary,	samples sub	mitted to Hall Environmental may be sub	contracted to other a	nu ho	02/25/15 25. This serves as notice of thi	s possi	bility.		enta ub-conti							the a	nalytica	al repor		

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

February 25, 2015

James and Susan Westhead 23 road 2645 Aztec, NM 87410

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: RIDENOUR GAS COM 001A

Dear Mr. & Mrs. Westhead,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about February 27, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

Jerry Van Riper

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

February 18, 2015

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

RIDENOUR GAS COM 001A API 30-045-22454 (H) Section 13 – T31N – R11W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around February 20, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



