District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

Alternative Method:

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or 12932 Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method MAY 28 2015
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit below grade tank or proposed alternative method
V Clasura of a nit halayy and a tank on managed alternative method
MAY 28 2015
☐ Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Gartner LS 6R
API Number:3004526951OCD Permit Number:
U/L or Qtr/QtrASection27 Township30N Range8W County:San Juan
Center of Proposed Design: Latitude36.78809 Longitude107.65838 NAD: □1927 ⋈ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. ☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:45.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thicknessmil

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No								
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 									
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Temporary Pit Non-low chloride drilling fluid									
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,									
or playa lake (measured from the ordinary high-water mark).									
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image									
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock									
watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Permanent Pit or Multi-Well Fluid Management Pit									
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa									
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No								
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of									
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc									
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC									
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	NMAC								
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC									
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC								
Previously Approved Design (attach copy of design) API Number: or Permit Number:									
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC									
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents and the second of the following items must be attached to the application.	cuments are								
attached. ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC									
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC									
 ☐ A List of wells with approved application for permit to drill associated with the pit. ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 	.15.17.9 NMAC								
and 19.15.17.13 NMAC									
 ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 									
Previously Approved Design (attach copy of design) API Number: or Permit Number:									

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19 15 17 9 NMAC	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Form C-144 Oil Conservation Division Page 3 of 6	

Oil Conservation Division

Form C-144

Page 4 of 6

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
7,	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed to the best of my knowledge and believed.	
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date:	2015
Title: OCD Permit Number:	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:11/28/2011	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

22.									
Operator Closure Certification:									
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.									
Name (Print):Jeff Peace	Title: Field Environmental Coordinator								
Signature: Jeff Peace	Date:May 26, 2015								
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479								

Page 6 of 6

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gartner LS 6R, BGT Tank A (45 bbl)

API No. 3004526951

Unit Letter A, Section 27, T30N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	23
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride were below the limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	catio	n and Co	orrective A	ction	1			
						OPERA	TOR		Initial	al Report	\boxtimes	Final Report
Name of Co	ompany: B	P				Contact: Je:	ff Peace					
Address: 20	Address: 200 Energy Court, Farmington, NM 87401						No.: 505-326-94	179				
Facility Nat	ne: Gartne	er LS 6R				Facility Typ	e: Natural gas v	well				
Surface Ow	Surface Owner: Private Mineral Owner								API No	. 30045269	951	
				LOCA	ATIO	N OF RE	LEASE					
Unit Letter A	Section 27	Township 30N	Range 8W	Feet from the 790		/South Line	Feet from the 1,190	East/V East	West Line	County: Sa	an Juan	ı
	Latitude36.78809Longitude107.65838											
				NAT	URE	OF REL	EASE					
Type of Rele	ase: none					Volume of	Release: N/A		Volume F	Recovered: N	V/A	
		w grade tank –	- 45 bbl, T	ank A			Hour of Occurrence	ce:	Date and	Hour of Dis	covery	:
Was Immedi	ate Notice (Yes [No Not Re	equired	If YES, To	Whom?					
By Whom?						Date and I	Hour					
Was a Water	course Read		Yes 🗵	No		If YES, V	olume Impacting t	the Wat	ercourse.			
If a Watercou	ırse was Im	pacted, Descr	ibe Fully.	*								
		F										
				n Taken.* Sampli and chloride belo					ng removal	to ensure no	soil im	pacts from
				ken.* BGT was re active well area.	moved	and the area u	inderneath the BG	T was s	sampled. T	he area unde	r the B	GT was
regulations a public health should their cor the environment.	Il operators or the envi- operations h nment. In a	are required to ronment. The lave failed to a	o report are acceptance acceptanc	e is true and comp nd/or file certain r ce of a C-141 report investigate and r otance of a C-141	release of ort by the remedia	notifications a ne NMOCD m te contaminat	nd perform correct arked as "Final Rion that pose a thr	ctive act eport" of eat to g	ions for rele loes not reli round water	eases which ieve the oper r, surface wa	may en ator of ter, hu	ndanger Tliability man health
Signature:	loff t	Peace					OIL CON	SERV	ATION	DIVISIO	<u>N</u>	
Printed Name	e: Jeff Peace	e				Approved by	Environmental S	pecialis	t:			
Title: Field E	nvironmen	tal Coordinate	or			Approval Da	te:		Expiration	Date:		
E-mail Addre	ess: peace.je	effrey@bp.com				Conditions o	f Approval:			Attached		
Date: May 2	6, 2015		Phone: 50	05-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BLO	INEERING, INC. OMFIELD, NM 8741 632-1199	3	API #: 3004526951 TANK ID (if applicble): A & B
FIELD REPORT:	(circle one): BGT CONFIRMATION / REL			PAGE #: 1 of 1
SITE INFORMATION QUAD/UNIT: A SEC: 27 TWP: 1/4-1/4/FOOTAGE: 790'N / 1,190	30N RNG: 8W PM: N'E NE/NE LEASE TYPE: PROD. FORMATION: MV CONTE WELL HEAD (W.H.) GPS COC GPS COORD.: 36.78 GPS COORD.: CHAIN OF CUSTODY RECORD(S) # OR LAR	MM CNTY: SJ ST: FEDERAL / STATE FEE INITERACTOR: BP - J. NUNEZ DRD.: 36.78772 X 1 799 X 107.65838 D BUSED: HALL SAMPLETIME: 1411 LABANALYSIS:	07.6582 ISTANCE/BEA ISTANCE/BEA ISTANCE/BEA	DATE STARTED: 11/10/11 DATE FINISHED: ENVIRONMENTAL SPECIALIST(S): JCB
3) SAMPLE ID: 4) SAMPLE ID:		SAMPLE TIME: LAB ANALYSIS: SAMPLE TIME: LAB ANALYSIS: SAMPLE TIME: LAB ANALYSIS:	410.170	01001002101000.0 (01)
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / W SAMPLE TYPE: GRAB (COMPOSITE) # OF PTS. DISCOLORATION/STAINING OBSERVED:	OWISH ORANGE COHESIVE / COHESIVE / HIGHLY COHESIVE OSE FIRM / DENSE / VERY DENSE T / SATURATED / SUPER SATURATED 5 YES NO EXPLANATION -		LYPLASTIC/C	COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC / FIRM / STIFF / VERY STIFF / HARD
ANY AREAS DISPLAYING WETNESS: YES NO ADDITIONAL COMMENTS: NO APPARE SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N	NT EVIDENCE OF A RELEASE OBSER			IMATION (Cubic Yards) : NA D TPH CLOSURE STD: 100 ppm
SITE SKETCH WOO R. PBGTL T.B. ~ 6' B.G.		PLOT PLAN circle: attach	OWN	MISCELL. NOTES 0: N1473373 0#: 62653 6: ZSCHWLLBGT 0#: Z2-00690-C ermit Date: 06/14/10 0CD Appr. Date: 06/08/11
	TO WELL HEAD Y ATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW-GRADE TANK LOCATION; SPD = SAMPLE SW-SINGLE WALL; DW-DOUBLE WALL; SB-SI 11/10/11	POINT DESIGNATION; R.W. = RETAINING W.	D. B	BGT Sidewalls Visible: Y / N / NA BGT Sidewalls Visible: Y / N / NA agnetic declination: 10° E

Hall Environmental Analysis Laboratory, Inc.

Date: 28-Nov-11 Analytical Report

CLIENT: Lab Order: Blagg Engineering

1111719

Project: Lab ID: Gartner LS 6R

1111719-01

Client Sample ID: 45 BGT 5-pt @ 6'

Collection Date: 11/10/2011 2:00:00 PM

Date Received: 11/17/2011

Matrix: SOIL

Analyses	Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS				***************************************	Analyst: JB
Diesel Range Organics (DRO)	25	10		mg/Kg	1	11/22/2011 8:55:55 AM
Surr: DNOP	96.5	77.4-131		%REC	1	11/22/2011 8:55:55 AM
EPA METHOD 8015B: GASOLINE RA	NGE					Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.6		mg/Kg	1	11/18/2011 6:50:24 PM
Surr: BFB	98.2	75.2-136		%REC	1	11/18/2011 6:50:24 PM
EPA METHOD 8021B: VOLATILES						Analyst: RAA
Benzene	ND	0.046		mg/Kg	1	11/18/2011 6:50:24 PM
Toluene	ND	0.046		mg/Kg	1	11/18/2011 6:50:24 PM
Ethylbenzene	ND	0.046		mg/Kg	1	11/18/2011 6:50:24 PM
Xylenes, Total	ND	0.092		mg/Kg	1	11/18/2011 6:50:24 PM
Surr: 4-Bromofluorobenzene	104	80-120		%REC	1	11/18/2011 6:50:24 PM
EPA METHOD 300.0: ANIONS						Analyst: BRM
Chloride	ND	7.5		mg/Kg	5	11/18/2011 10:41:14 PM
EPA METHOD 418.1: TPH						Analyst: JB
Petroleum Hydrocarbons, TR	23	20		mg/Kg	1	11/22/2011

Qualifiers:

- Value exceeds Maximum Contaminant Level
- Estimated value
- Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- MCL Maximum Contaminant Level
- ND Not Detected at the Reporting Limit
- Spike recovery outside accepted recovery limits

Page 1 of 2

Date: 20-1107-11

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project:

Gartner LS 6R

Work Order:

1111719

						_		77 01	K Oldel.	1111/19
Analyte	Result	Units	PQL	SPK Va SP	K ref	%Rec L	owLimit Hi	ghLimit %RPI	O RPDLimi	t Qual
Method: EPA Method 300.0:	Anions	MOLK				D			4440004	
Sample ID: MB-29439		MBLK				Batch ID:	29439	Analysis Date:	11/18/201	6:02:40 PN
Chloride	ND	mg/Kg	1.5			D-4-t ID-	E0 400	Abaic Deter	44/40/004	C-00 05 55
Sample ID: LCS-29439		LCS				Batch ID:	29439	Analysis Date:	11/18/201	6:20:05 PN
Chloride	14.08	mg/Kg	1.5	15	0	93.8	90	110		
Method: EPA Method 418.1: 7	PH									
Sample ID: MB-29465		MBLK				Batch ID:	29465	Analysis Date:		11/22/2011
Petroleum Hydrocarbons, TR	ND	mg/Kg	20							
Sample ID: LCS-29465		LCS				Batch ID:	29465	Analysis Date:		11/22/2011
Petroleum Hydrocarbons, TR	99.76	mg/Kg	20	100	0	99.8	87.8	115		
Sample ID: LCSD-29465		LCSD				Batch ID:	29465	Analysis Date:		11/22/2011
Petroleum Hydrocarbons, TR	99.76	mg/Kg	20	100	0	99.8	87.8	115 0	8.04	
Method: EPA Method 8015B:	Diesel Range	Organics					-			
Sample ID: MB-29431	Diesel Range	MBLK				Batch ID:	29431	Analysis Date:	11/21/2011	7:59:03 AN
Diesel Range Organics (DRO)	ND	mg/Kg	10					, , , , , , , , , , , , , , , , , , , ,		
Sample ID: LCS-29431	110	LCS	10			Batch ID:	29431	Analysis Date:	11/21/2011	8:33:42 AN
Diesel Range Organics (DRO)	46.96	mg/Kg	10	50	0	93.9	62.7	139		
							02.7	100		
Method: EPA Method 8015B:	Gasoline Ran	0 -								
Sample ID: MB-29420		MBLK				Batch ID:	29420	Analysis Date:	11/18/2011	2:31:00 PM
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0							
Sample ID: LCS-29420		LCS				Batch ID:	29420	Analysis Date:	11/18/2011	1:33:20 PM
Gasoline Range Organics (GRO)	27.21	mg/Kg	5.0	25	0	109	86.4	132		

-		_				
1		_		5	_	
0	ш	Ω	Iπ	11	ρ	re

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

R RPD outside accepted recovery limits

Page 1

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project:

Gartner LS 6R

Work Order:

1111719

Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec L	owLimit Hi	ghLimit	%RPD	RPDLimit	Qual
Method: EPA Method 8021B:	Volatiles										
Sample ID: 1111719-01AMSD		MSD				Batch ID:	29420	Analysi	s Date:	11/19/2011	1:33:49 AN
Benzene	0.9496	mg/Kg	0.049	0.982	0.0057	96.1	67.2	113	2.85	14.3	
Toluene	0.9955	mg/Kg	0.049	0.982	0.0151	99.8	62.1	116	2.58	15.9	
Ethylbenzene	1.013	mg/Kg	0.049	0.982	0	103	67.9	127	2.26	14.4	
Xylenes, Total	3.027	mg/Kg	0.098	2.947	0	103	60.6	134	1.60	12.6	
Sample ID: MB-29420		MBLK				Batch ID:	29420	Analysi	s Date:	11/18/2011	2:31:00 PM
Benzene	ND	mg/Kg	0.050								
Toluene	ND	mg/Kg	0.050								
Ethylbenzene	ND	mg/Kg	0.050								
Xylenes, Total	ND	mg/Kg	0.10								
Sample ID: LCS-29420		LCS				Batch ID:	29420	Analysi	s Date:	11/18/2011 2	2:02:11 PM
Benzene	0.9326	mg/Kg	0.050	1	0	93,3	83.3	107			
Toluene	0.9709	mg/Kg	0.050	1	0	97.1	74.3	115			
Ethylbenzene	0.9842	mg/Kg	0.050	1	0.0055	97.9	80.9	122			
Xylenes, Total	2.963	mg/Kg	0.10	3	0.0197	98.1	85.2	123			
Sample ID: 1111719-01AMS		MS				Batch ID:	29420	Analysi	s Date:	11/19/2011 1	:05:02 AM
Benzene	0.9229	mg/Kg	0.048	0.967	0.0057	94.8	67.2	113			
Toluene	0.9701	mg/Kg	0.048	0.967	0.0151	98.7	62.1	116			
Ethylbenzene	0.9902	mg/Kg	0.048	0.967	0	102	67.9	127			
Xylenes, Total	2.979	mg/Kg	0.097	2.901	0	103	60.6	134			

Qualifiers:

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

R RPD outside accepted recovery limits

Page 2

Hall Environmental Analysis Laboratory, Inc.

Sample Receipt Checklist

Client Name BLAGG				Date Receive	d:	11/17/2011
Work Order Number 1111719	, 111			Received by	. LNM	
Checklist completed by: Signature Matrix:	Carrier name:	Fedl	Date	Sample ID k	abels checked	by: Initials
Shipping container/cooler in good condition?		Yes	✓	No 🗆	Not Present	
Custody seals intact on shipping container/coo	ler?	Yes	~	No 🗌	Not Present	☐ Not Shipped ☐
Custody seals intact on sample bottles?		Yes		No 🗌	N/A	\checkmark
Chain of custody present?		Yes	\checkmark	No 🗆		
Chain of custody signed when relinquished and	d received?	Yes	\checkmark	No 🗆		
Chain of custody agrees with sample labels?	No 🗆					
Samples in proper container/bottle?		Yes	V	No 🗆		
Sample containers intact?		Yes	\checkmark	No 🗌		
Sufficient sample volume for indicated test?		Yes	\checkmark	No 🗌		
All samples received within holding time?		Yes	\checkmark	No 🗆		Number of preserve
Water - VOA vials have zero headspace?	No VOA vials subm	itted	\checkmark	Yes	No 🗌	bottles checked for pH:
Water - Preservation labels on bottle and cap n	natch?	Yes		No 🗌	N/A	
Water - pH acceptable upon receipt?		Yes		No 🗆	N/A	<2 >12 unless noted below.
			<6° C Acceptab		bolow.	
COMMENTS:				If given sufficient	time to cool.	
Client contacted	Date contacted:	•		Pers	on contacted	
Contacted by:	Regarding:					
Comments:						
						-
Corrective Action						

Chain-of-Custody Record	Turn-Around Time:	= =						
Client: BLAGE ENGINEERING INC.	Standard □ Rush	HALL ENVIRONMENTAL ANALYSIS LABORATORY						
BP AMERICA	Project Name:	www.hallenvironmental.com						
Mailing Address: P.O. Box 87	GARTNER LS GR	4901 Hawkins NE - Albuquerque, NM 87109						
BLOOMFIELD, NM 87413	Project #:	Tel. 505-345-3975 Fax 505-345-4107						
Phone #: 505 - 63Z-1199		Analysis Request						
email or Fax#:	Project Manager:							
QA/QC Package: Standard Level 4 (Full Validation)	J. BLAGG	# TMB's (8021) + TPH (Gas only) 015B (Gas/Diesel) 18.1) 04.1) 2AH) s / 8082 PCB's s / 8082 PCB's o / A)						
Accreditation	Sampler: J- BLAGE	1002, 1002, 1000,						
□ NELAP □ Other	On ices Yes IIINo	11 + 11 14 14 17 18 18 18 18 18 18 18						
□ EDD (Type)	Sample-Temperature: 27	AA) AA) AA) AA) AA) AA) AA) AA)						
Date Time Matrix Sample Request ID	Container Type and # Preservative Type HEAL No.	BTEX + WIBE + TWB's (8021) BTEX + MTBE + TPH (Gas only) TPH Method 8015B (Gas/Diesel) TPH (Method 418.1) EDB (Method 504.1) B310 (PNA or PAH) RCRA 8 Metals Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄) 8081 Pesticides / 8082 PCB's 8260B (VOA) 8270 (Semi-VOA) CACUALLE						
110/2011 1400 SOIL 45 BGT 6-	402×1 COOL	X X X X						
4 1111 11 95 BGT 5-Pt @6	11 - 1							
- Pies	funding the state of the state							
Date: Time: Relinquished by:	Received by: Date Time	Remarks: GRO + DRO ON BUIS						
16/211 1104 Jeff Blesc	Monta Weller 1/16/11 1104	N 1473373						
Date: Time: Relinquished by:	Received by: Date Time	ZSCHWLLBGT CONTACT: JEFF PEACE						
If necessary, samples submitted to Hall Environmental may be sub-	ocontracted to other accredited laboratories. This serves as notice of	this possibility. Any sub-contracted data will be clearly notated on the analytical report.						

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

October 31, 2011

Paul Velasquez Jr. PO Box 536 Blanco, NM 87412

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: GARTNER LS 006R-MV

Dear Paul Velasquez Jr.,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about November 1, 2011. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Coordinator/Business Security Representative

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

November 2, 2011

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GARTNER LS 006R-MV API 30-045-26951 (M) Section 27 – T30N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a \$\frac{4}{5}\$ bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



