2 2istrict I 1625 N. French Dr., Hobbs, NM 88240 District III 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Dit	Ral	OW-	Grade	Tanl	z or
1 11,	DCI	.UW-	Grauc	1 aiii	A, UI

Type of action: Below grade tank registration Permit of a pit or proposed alternative method JUN 0 2 2015 Closure of a pit, below-grade tank, or proposed alternative method Description to a pit of a pit or proposed alternative method Description to a pit of a pit or proposed alternative method Jun 0 2 2015 Description to a pit of a pit or proposed alternative method Description to a pit of a pit or proposed alternative method Description to a pit of a pit or proposed alternative method Description to a pit of a pit or proposed alternative method Description to a pit of a pit or proposed alternative method Description to a pit of a pit or proposed alternative method Description to a pit of a pit or proposed alternative method Description to a pit of a pit or proposed alternative method Description to a pit or pro
☐ Modification to an existing permit/or registration ☐ Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Atlantic A LS 9A
API Number:3004522492OCD Permit Number:
U/L or Qtr/QtrC Section27 Township30N Range10W County:San Juan
Center of Proposed Design: Latitude36.873261 Longitude107.873185 NAD: □1927 ⋈ 1983 Surface
Owner: Nederal State Private Tribal Trust or Indian Allotment
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ HDPE □ PVC □ Other
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ PVC □ Other
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ HDPE □ PVC □ Other
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ HDPE □ PVC □ Other
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined □ Liner type: Thickness
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined □ Liner type: Thickness
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined □ Liner type: Thickness
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined □ Liner type: Thickness

•	
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly ingrestions (If notting or seresping is not physically feasible)	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
8.	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ A List of wells with approved application for permit to drill associated with the pit.	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	.15.17.9 NMAC
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14. Wester Everyotion and Pamayal Closure Plan Charklists (10.15.17.12 NMAC) Instructions: Each of the following items must be	attached to the
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	L Tes L No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 423 Title: OCD Permit Number:	/2015
19.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date:4/7/2015	
20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-lo If different from approved plan, please explain.	op systems only)

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Seff Posee	Date:May 28, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Atlantic A LS 9A API No. 3004522492 Unit Letter C, Section 27, T30N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the

Certification section of C-144 has been completed.

approved closure plan.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141

Revised August 8, 2011

Release Notification and Corrective Action												
						OPERATOR					Final Repor	rt
Name of Co						Contact: Jeff Peace						
Facility Na		Court, Farmi	ngton, N	M 87401	-	_	No.: 505-326-94 be: Natural gas v					\dashv
							c. Natural gas v					_
Surface Ow	ner: Feder	al		Mineral C)wner:	Federal		API	No. 3004522	492		
				LOCA	TIO	N OF RE	LEASE					
Unit Letter C	Section 27	Township 30N	Range 10W	Feet from the 1,185	North North	/South Line	Feet from the 1,575	East/West Line West	County: S	3an Juar	1	
Latitude36.873261Longitude107.873185												
				NAT	URE	OF REL	EASE					
Type of Rele		u anada tanlı	05 1-1-1				Release: N/A		Recovered:		NT/ A	4
Source of Re	lease: belov	v grade tank –	95 001			N/A	Iour of Occurrenc	e: Date ar	d Hour of Di	scovery	: N/A	
Was Immedi	ate Notice (Yes	No Not Re	equired	If YES, To	Whom?					
By Whom?						Date and F						
Was a Water	course Read		Yes 🗵	No		If YES, Volume Impacting the Watercourse.						
If a Watercou	ırse was Im	pacted, Descri	ibe Fully.*	•								
	Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal to ensure no soil impacts from the BGT. Soil analysis resulted in TPH, BTEX and chlorides below standards. Analysis results are attached.											
	Describe Area Affected and Cleanup Action Taken.* BGT was removed and the area underneath the BGT was sampled. The area under the BGT was backfilled and compacted and is still within the active well area.											
regulations at public health should their or or the environ	Il operators or the environerations had nment. In a	are required to ronment. The lave failed to a	o report ar acceptant adequately OCD accep	is true and comp nd/or file certain r tee of a C-141 repo investigate and r stance of a C-141	elease r ort by th emediat	otifications as e NMOCD m e contaminati	nd perform correct arked as "Final Roon that pose a three	etive actions for report" does not reat to ground wa	eleases which elieve the ope ter, surface w	n may er erator of ater, hu	ndanger f liability man health	
(00	0					OIL CON	SERVATIO	N DIVISIO	\underline{NC}		
Signature:	JAB 1	earl				Approved by Environmental Specialist:						
Printed Name	e: Jeff Peace	e						F - 2.00.000				4
Title: Field E	nvironment	tal Coordinato	r			Approval Da	te:	Expiration	n Date:			
E-mail Addre	ess: peace.je	effrey@bp.com	n			Conditions of	f Approval:		Attached	d 🔲		
Date: May 2	8, 2015		Phone: 50)5-326-9479								

CLIENT: BP	BLAGG E P.O. BOX 87, B	TANK ID	04522492 A)		
	<u> </u>	05) 632-1199		(if applicble):	A	
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATIO	ON / OTHER:	PAGE #:	1 of 1	1
SITE INFORMATION	I: SITE NAME: ATLAN	TIC A LS #9A	A	DATE STARTED:	04/02/15	5
QUAD/UNIT: C SEC: 27 TWP:	31N RNG: 10W PM:	NM CNTY:	SJ ST: NN	DATE FINISHED:		
1/4-1/4/FOOTAGE: 1,185'N / 1,5	75'W NE/NW LEASE	TYPE: FEDERAL ST	TATE / FEE / INDIAN	ENVIRONMENTAL		
LEASE#: NM0606	PROD. FORMATION:PC/MV C	ONTRACTOR: MBF	KE - B. SCHUMAN	SPECIALIST(S):	JCB	
REFERENCE POINT				321 GLEI	_EV.: 6.144'	
1) 95 BGT (SW/DB)	GPS COORD.: 36.8			E/BEARING FROM W.H.:		
2)	GPS COORD.:					
3)	GPS COORD.:		DISTANC	E/BEARING FROM W.H.:		
4)	GPS COORD.:		DISTANC	E/BEARING FROM W.H.:		
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # 0	OR LAB USED:	HALL		OVM READIN	ING
1) SAMPLE ID: 95 BGT 5-pt. (8015B/8021B/300.	0 (CI) 0.0	_
2) SAMPLE ID:						_
3) SAMPLE ID:						_
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:			
SOIL DESCRIPTION SOIL COLOR: DARK YELLOW COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / WE SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES N	WISH ORANGE Y COHESIVE / COHESIVE / HIGHLY COHESIVE DOSE FIRMY DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS. 5	PLASTICITY (CLAYS): NON DENSITY (COHESIVE CL HC ODOR DETECTED: YES	PLASTIC / SLIGHTLY PLASTI AYS & SILTS): SOFT / FII S NO EXPLANATION -	RM / STIFF / VERY STIFF	/ HARD	TIC
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	D AND/OR OCCURRED : YES NO EXPL	ANATION:		OCATION.		
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA f	t. EXCAVATION	ESTIMATION (Cubic Y	ards): NA	
DEPTH TO GROUNDWATER: <50' N	EAREST WATER SOURCE: >1,000	NEAREST SURFACE W	ATER: <200' N	MOCD TPH CLOSURE ST	D: <u>100</u> p	ppm
SITE SKETCH	BGT Located: off on site	e PLOT PLAN	circle: attached	OVM CALIB. READ. = 5	2.2 ppm RF =0.	152
SOUND WALLS	TO W.H. COMPRESSOR	STEEL CONTAINMENT RING	N		DATE: 04/02/15	
SEPARATOR PBG T.B. B.C	~ 5'	PROITAN		REF. #: P - 47 PK: ZEVH0 PJ #: Z2-006 Permit date(s): OCD Appr. date(s):	Q0 06/14/10 11/20/14 nic Vapor Meter per million sible: Y (N)	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	BERM ON DEPRESSION; B.G. = BELOW GRADE; B = BE	ELOW, T.H. = TEST HOLE; ~= AP		BGT Sidewalls Vis	sible: Y / N	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELC APPLICABLE OR NOT AVAILABLE; SW-SINGLE	OW-GRADE TANK LOCATION; SPD = SAMPLE F E WALL; DW - DOUBLE WALL; SB - SINGLE BOT	POINT DESIGNATION; R.W. = RETOM; DB - DOUBLE BOTTOM.	TAINING WALL; NA - NOT	Magnetic declina	tion: 10°E	
NOTES: GOOGLE EARTH IMAGE	RY DATE: 11/17/2013.	ONSITE: 0	4/02/15			

Analytical Report

Lab Order 1504130

Date Reported: 4/7/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Project: Atlantic A LS 9A

Lab ID: 1504130-001

Client Sample ID: 95 BGT 5-pt @ 5'

Collection Date: 4/2/2015 2:00:00 PM

Received Date: 4/3/2015 7:55:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RAN	GE ORGANICS				Analyst	BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	4/3/2015 9:48:48 AM	18504
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	4/3/2015 9:48:48 AM	18504
Surr: DNOP	96.5	63.5-128	%REC	1	4/3/2015 9:48:48 AM	18504
EPA METHOD 300.0: ANIONS					Analyst	LGT
Chloride	ND	30	mg/Kg	20	4/3/2015 10:07:29 AM	18510
EPA METHOD 8260B: VOLATILES S	SHORT LIST				Analyst	cadg
Benzene	ND	0.041	mg/Kg	1	4/3/2015 12:47:16 PM	18490
Toluene	ND	0.041	mg/Kg	1	4/3/2015 12:47:16 PM	18490
Ethylbenzene	ND	0.041	mg/Kg	1	4/3/2015 12:47:16 PM	18490
Xylenes, Total	ND	0.083	mg/Kg	1	4/3/2015 12:47:16 PM	18490
Surr: 1,2-Dichloroethane-d4	102	70-130	%REC	1	4/3/2015 12:47:16 PM	18490
Surr: 4-Bromofluorobenzene	98.9	70-130	%REC	1	4/3/2015 12:47:16 PM	18490
Surr: Dibromofluoromethane	100	70-130	%REC	1	4/3/2015 12:47:16 PM	18490
Surr: Toluene-d8	94.8	70-130	%REC	1	4/3/2015 12:47:16 PM	18490
EPA METHOD 8015D MOD: GASOL	INE RANGE				Analyst	cadg
Gasoline Range Organics (GRO)	ND	4.1	mg/Kg	1	4/3/2015 12:47:16 PM	18490
Surr: BFB	114	67.4-150	%REC	1	4/3/2015 12:47:16 PM	18490

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1504130 07-Apr-15

Client:

Blagg Engineering

Project:

Atlantic A LS 9A

Sample ID MB-18510

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 18510

RunNo: 25318

Prep Date: 4/3/2015

SeqNo: 749017

Units: mg/Kg

Analysis Date: 4/3/2015

HighLimit

%RPD **RPDLimit**

RPDLimit

Qual

Qual

Analyte Chloride

Result PQL ND 1.5

Sample ID LCS-18510

SampType: LCS

TestCode: EPA Method 300.0: Anions

SPK value SPK Ref Val %REC LowLimit

Client ID: LCSS Batch ID: 18510

RunNo: 25318

Prep Date: 4/3/2015 Analysis Date: 4/3/2015

SeqNo: 749018

Units: mg/Kg

%RPD

%REC Analyte PQL SPK value SPK Ref Val LowLimit HighLimit Chloride 14 1.5 15.00 0 92.4 90 110

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

P Sample pH Not In Range

Reporting Detection Limit

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1504130

07-Apr-15

Client:

Blagg Engineering

Project:

Atlantic A LS 9A

Attaille	A LS 3A	
Sample ID MB-18504	SampType: MBLK	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: PBS	Batch ID: 18504	RunNo: 25271
Prep Date: 4/3/2015	Analysis Date: 4/3/2015	SeqNo: 747345 Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	ND 10	
Motor Oil Range Organics (MRO)	ND 50	
Surr: DNOP	9.8 10.00	97.8 63.5 128
Sample ID LCS-18504	SampType: LCS	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: LCSS	Batch ID: 18504	RunNo: 25271
Prep Date: 4/3/2015	Analysis Date: 4/3/2015	SeqNo: 747346 Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	44 10 50.00	0 88.3 67.8 130
Surr: DNOP	4.5 5.000	89.1 63.5 128
Sample ID LCS-18483	SampType: LCS	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: LCSS	Batch ID: 18483	RunNo: 25271
Prep Date: 4/2/2015	Analysis Date: 4/3/2015	SeqNo: 748608 Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Surr: DNOP	5.1 5.000	102 63.5 128
Sample ID MB-18483	SampType: MBLK	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: PBS	Batch ID: 18483	RunNo: 25271
Prep Date: 4/2/2015	Analysis Date: 4/3/2015	SeqNo: 748610 Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Surr: DNOP	10 10.00	100 63.5 128

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

0.50

0.55

0.46

0.5000

0.5000

0.5000

WO#:

1504130

07-Apr-15

Client:

Blagg Engineering

Project:

Atlantic A LS 9A

Sample ID mb-18490	TestCode: EPA Method 8260B: Volatiles Short List													
Client ID: PBS	BS Batch ID: 18490				RunNo: 25283									
Prep Date: 4/2/2015	Analysis Date: 4/3/2015			5	SeqNo: 7	47675	Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	ND	0.050												
Toluene	ND	0.050												
Ethylbenzene	ND	0.050												
Xylenes, Total	ND	0.10												
Surr: 1,2-Dichloroethane-d4	0.56		0.5000		111	70	130							
Surr: 4-Bromofluorobenzene	0.48		0.5000		96.9	70	130							
Surr: Dibromofluoromethane	0.56		0.5000		113	70	130							
Surr: Toluene-d8	0.45		0.5000		89.5	70	130							
Sample ID Ics-18490	Samp	Гуре: LC	s	Tes	tCode: El	PA Method	8260B: Volat	iles Short	List					
Client ID: LCSS Batch ID: 18490					RunNo: 2	5283								
Prep Date: 4/2/2015	Analysis [Date: 4/	3/2015	8	SeqNo: 7	47676	Units: mg/K	g						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	0.99	0.050	1.000	0	98.5	70	130							
Toluene	0.87	0.050	1.000	0	87.1	70	130							
Surr: 1,2-Dichloroethane-d4	0.54		0.5000		107	70	130							

100

109

91.1

70

70

70

130

130

130

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range

Surr: 4-Bromofluorobenzene

Surr: Dibromofluoromethane

Surr: Toluene-d8

- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1504130

07-Apr-15

Client:

Blagg Engineering

Project:

Atlantic A LS 9A

Sample ID mb-18490

SampType: MBLK

TestCode: EPA Method 8015D Mod: Gasoline Range

Client ID:

PBS

Batch ID: 18490

RunNo: 25283

Prep Date: 4/2/2015 Analysis Date: 4/3/2015

SeqNo: 747683

Units: mg/Kg

Analyte Gasoline Range Organics (GRO) Result PQL ND 5.0 SPK value SPK Ref Val %REC HighLimit

RPDLimit

Qual

Surr: BFB

580

500.0

116

%RPD

Sample ID Ics-18490

SampType: LCS

TestCode: EPA Method 8015D Mod: Gasoline Range

150

LCSS Client ID:

Batch ID: 18490

RunNo: 25283

LowLimit

LowLimit

67.4

Prep Date: 4/2/2015 Analysis Date: 4/3/2015

PQL

5.0

SeqNo: 747684 %REC

Units: mg/Kg

%RPD **RPDLimit** HighLimit Qual

Gasoline Range Organics (GRO)

27 570

Result

25.00 500.0

SPK value SPK Ref Val

106 114

79.9 67.4

135

Surr: BFB

Analyte

0

150

Qualifiers:

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

E Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

Sample pH Not In Range

H

Reporting Detection Limit

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquergue, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client	Name:	BLAGG		Work O	rder Numb	er: 15041	30		RcptNo:	1
Receiv	ved by/dat	e: AT	04/63/1	5					LAD ST	
Logge	d By:	Anne Thorr	ne	4/3/2015	7:55:00 AN	/I		anne Sham		
Comp	leted By:	Anne Thorr	ne n	4/3/2015	*			anne Am	_	
Reviev	wed By:	05/		04/0	3/15			Olivia Johnson		
Chain	of Cus	tody	7	0_110	71		_			
1. Custody seals intact on sample bottles?						Yes		No 🗆	Not Present 🗹	
2. Is Chain of Custody complete?						Yes	V	No 🗆	Not Present	
3. How was the sample delivered?						Cour	ier			
Log	<u>In</u>									
4. w	/as an atte	empt made to	cool the samp	es?		Yes	V	No 🗌	NA 🗆	
5. W	ere all sar	mples received	at a tempera	ture of >0° C t	to 6.0°C	Yes	V	No 🗆	NA 🗆	
6. Sample(s) in proper container(s)?						Yes	V	No 🗌		
7. Sufficient sample volume for indicated test(s)?						Yes	√	No 🗌		
8. Are samples (except VOA and ONG) properly preserved?						Yes	V	No 🗌		
9. Was preservative added to bottles?						Yes		No 🗸	NA 🗆	
10.VC	OA vials h	ave zero head:	space?			Yes		No 🗌	No VOA Vials	
11. W	lere any s	ample contain	ers received b	roken?		Yes		No 🗸	# - 6	
									# of preserved bottles checked	
12. Does paperwork match bottle labels?						Yes	V	No _	for pH:	r >12 unless noted)
(Note discrepancies on chain of custody) 13. Are matrices correctly identified on Chain of Custody?						Yes		No 🗌	Adjusted?	12 unioso notody
		nat analyses w				Yes		No 🗌		
		ding times abl				Yes		No 🗆	Checked by:	
		customer for								
		dling (if app								
16.W	as client r	notified of all di	screpancies w	ith this order?		Yes		No L	NA 🗹	7
	Perso	n Notified:			Date			70 m /4 × ×		
	By W	nom:		1 1 N N 1 1 N 1 1 N 1	Via:	_ eMa	ail [Phone Fax	☐ In Person	
	Regar			- 4-5-1			a batana in	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	of the contract that the contract of	
	Client	Instructions:							a series to the series of	
17. A	dditional i	remarks:								
18. <u>c</u>	cooler Info									
	Cooler N		Condition	Seal Intact	Seal No	Seal D	ate	Signed By		
1	1	1.0	Good	Yes						

Chain-of-Custody Record Silient: BP America			Turn-Around Time: SAME □ Standard				HALL ENVIRONMENTAL ANALYSIS LABORATORY														
																		BLAGG Eymery Tailing Address:		Project Name: ATLANTIC A LS 9A Project #:	
www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109																					
			Tel. 505-345-3975 Fax 505-345-4107																		
hone#: 505 - 320 - U83							THE REAL PROPERTY.	ACCRECATE VALUE OF THE PARTY.	/sis	STATE OF THE PARTY NAMED IN	NAME OF TAXABLE PARTY.	THE PERSON NAMED IN									
mail or Fax#:			Project Manager:				only)	Ô													
NA/QC Package: Standard □ Level 4 (Full Validation)			J. BUAGG				TPH (Gas or	DRO / MRO)			SIMS)		PO ₄ ,SC	/ 8082 PCB's							
ccreditation NELAP Other			Sampler: J. B.466 On Ice: Yes				+	(GRO/DF	118.1)	504.1)	8270	10	O3,NO2	s / 8082		(A)				or N)	
EDD (Type)			Sample Temperature:				MTBE	3 (G	od 4	po	0 0	etals	Z,	cide	(A)	-VC	SIDE			2	
Date	Time	Matrix	Sample Request ID	Container Type and # Muchky	Preservative Type	HEAL NO. 1504130	BTEX + MIR	BTEX + MT	TPH 8015B	TPH (Method 418.1)	EDB (Method 504.1)	PAH's (8310 or 8270	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			Air Bubbles (Y or N)
hais	1400	SOIL	95 BGT 5-P= @ 5'	402×1	LEVE	-01	X		X									х			
,																					
																				\top	
																					+-
											_								_	+	+
																			+	+	
						,				_		-				_			+	+	-
											-	\dashv	-					\neg	\dashv	+	
												-						\dashv	-	+	+
										-	\dashv									+	
										-		-	-			-			+	+	-
									\dashv	\dashv	\neg								\dashv	+	1
Date:	Time: 1416	1 1 . 2 .			Received by: Mistablela 12/514/6			Remarks: BILL BP Contact: Inff Peace													
Pate:	Time:	Reanquishe	ed by:	Received by: Date Time					F	Ark	ey	: 2	EVA	10	LBG						
415 1740 Christin Walle		Con 104/03/15				REFEVENCE: P-47															

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

March 13, 2015

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: ATLANTIC A LS 009A

API #: 3004522492

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about March 19, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

Jerry Van Riper

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

March 30, 2015

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ATLANTIC A LS 009A API 30-045-22492 (C) Section 27 – T31N – R10W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around April 2, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



