. This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator COF	0				Lease	Name REA	MES C	MC		Well No. 2	
Location of We	ell: Unit	Letter	B S	ec	19	Twp 026	N F	Rge (006W API	# 30-039-23172	
	Name of Reservoir or Pool			Type of Prod			Method of Prod		Prod Medium		
Upper Completion	FRC			Gas			Flow		Tubing		
Lower Completion	DK			Gas			Artificial Lift		Tubing		
				Pre	-Flow S	Shut-In Press	ure Dat	a			
Upper Completion	Hour, Date, Shut-In 5/14/2015			Length of Time Shut-In 153 hours			SI Press. PSIG		Stabilized?(Yes or No) Yes		
Lower Completion	Hour, Date, Shut-In 5/14/2015				Length of Time Shut-In 96 hours			SI Press. PSIG		Stabilized?(Yes or No) Yes	
					Flo	w Test No. 1					
Commenced	at:	5	/18/2015		110			g (Upper	or Lower): LC	WER	
Time (date/time)			apsed Time Since* Upp		PRESSURE Upper zone Lower zon			Prod Zone Temperature		Remarks	
5/19/2015 8:00:00 AM		8	32	120		92					
5/20/2015 9:33:53 AM		,	57		121	91					
Production rate	e during	test									
Oil:	BPOD Based on:		Bbl	Bbls. In		. Grav.		rav.	GOR		
Gas		MCF	PD; Test th	ru (Ori	fice or M	leter)					
				10.00	J T4 0	hut In Dusse	D-4				
Upper Completion				IVII		hut-In Press of Time Shut-In	SI Press. PSIG		. PSIG	Stabilized?(Yes or No)	
Lower	Hour, Date, S		n		Length of	Length of Time Shut-In		SI Press. PSIG		Stabilized?(Yes or No)	

(Continue on reverse side)

OIL CONS. DIV DIST. 3
MAY 26 2015

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Zone Producing (Upper or Lower)

Time	Lapsed Time	PRES	SURE	Prod Zone		
(date/time)	Since*	Upper zone	Lower zone	Temperature	9	Remarks
Draduation rate during	a toot					
Production rate during	g test					
Oil: BPO	BPOD Based on:		Bbls. In Hrs.		Grav.	GOR
Gas	MCFPD: Test t	hru (Orifice or M	leter)			
Odo	WOTT D, Test to	ina (Office of W				
Remarks:						
I hereby certify that th	e information herein o	contained is true	and complete	to the best of	my knowledge	
A	- 1-	20 1	0,000	COD		
	7/0	20 15	Opera	tor: COP		
• •			_			
• •	onservation Division		Ву:	Simon Rudo	der	
• •			By: Title:	Simon Rudo Multi-Skilled		
	onservation Division	SPECTOR			Operator	

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at:

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

^{5.} Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3