This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

OIL CONS. DIV DIST, 3

Northwest New Mexico Packer-Leakage Test MAY 1 1 2015 Revised June 10, 2003

Operator COF	>		Lease	Name SAN	Well No. 49		
Location of We	ell: Unit L	Letter A Se	ec 15	Twp 032N	Rge	008W API	# 30-045-25394
	N	Name of Reservoir or Pool		Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC		Gas	Gas			Casing
Lower Completion	MV		Gas	Gas			Tubing
			Pre-Flow S	hut-In Pressu	ıre Data		
Upper Completion	Hour, Date, Shut-In 4/20/2015		228	Length of Time Shut-In 228 hours		s. PSIG 354 s. PSIG	Stabilized?(Yes or No) No Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In 4/20/2015			Length of Time Shut-In 168 hours		360	Yes
Commenced	at:	4/27/2015	Flo	w Test No. 1 Zone Pro	oducing (Upper	or Lower): LC	WER
Time (date/time)		Lapsed Time Since*	PRES Upper zone	SURE Lower zone	Prod Zone Temperature	Remarks	
4/27/2015 11:51:48 AM		11	354	360		Line press = 114, started now	
4/28/2015 11:07:05 AM		35	358	99		2nd day of flow, 20 % crossover achieved	
4/29/2015 12:23:49 PM		60	358	111		completed test	
Production rat	e during t	est					
Oil:	BPOD	BPOD Based on: Bt		s. In Hrs.		Grav. GOR	
Gas		MCFPD; Test th	ru (Orifice or M	leter)			
			Mid-Test S	hut-In Pressu	ıre Data		
Upper Completion	Hour, Date, Shut-In			Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)
Lower Hour, Date, Shut-In Completion		Length o	Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)	

(Continue on reverse side)

Remarks

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Lower zone

PRESSURE

Upper zone

Zone Producing (Upper or Lower)

Prod Zone

Temperature

Production rate	during test BPOD Based on:	Bbls. In	Hrs.	C	Grav.	GOR				
Gas	MCFPD; Test thru (Orifice or Meter)									
Remarks:										
I hereby certify	that the information herein c	ontained is true a	and complete to	the best of r	my knowledge.					
Approved:	7/6/	2015	Operator	COP						
New Mexico	Oil Conservation Division	•		By: Jonathan Coulter						
Ву:	Title:	Title: Multi-Skilled Operator								
Title: UEPU	TY DIL R GAS INSP	FCTOR	Date:	Date: Monday, May 11, 2015						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

DISTRICT #3

Commenced at:

Time

(date/time)

Lapsed Time

Since*

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the
- atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.