¥		
District IEner1625 N. French Dr., Hobbs, NM 88240EnerDistrict II811 S. First St., Artesia, NM 88210District III1000 Rio Brazos Road, Aztec, NM 87410District IV1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico rgy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
F	Pit, Below-Grade Tank, or	
12948 Proposed Alternative	e Method Permit or Closure F	Plan Application OIL CONS. DIV DIST. 3
Type of action: Below grade ta	nk registration	UL CONS. DIV DIST. S
215 - 11057 🛛 Closure of a pit	or proposed alternative method , below-grade tank, or proposed alternation of an existing permit/or registration	ve method JUN 0 2 2015
Closure plan or	ily submitted for an existing permitted or	non-permitted pit, below-grade tank,
or proposed alternative method	tion (Form C-144) per individual pit, below	arade tank or alternative request
Please be advised that approval of this request does not relieve the environment. Nor does approval relieve the operator of its response.	ne operator of liability should operations result i	n pollution of surface water, ground water or the
^{1.} Operator: BP America Production Company	OGRID #:	778
Address:200 Energy Court, Farmington, NM 87		
Facility or well name:Florance 54		
API Number:3004511657		
U/L or Qtr/QtrOSection22Tow		
Center of Proposed Design: Latitude36.79249		
Owner: ⊠ Federal □ State □ Private □ Tribal Trust or I		
2.		
<u>Pit:</u> Subsection F, G or J of 19.15.17.11 NMAC		
Temporary: Drilling Workover		
Permanent Emergency Cavitation P&A		
Lined Unlined Liner type: Thickness String-Reinforced	mil 📋 LLDPE 📋 HDPE 🛄 PVC 🛄 Ot	her
Liner Seams: Welded Factory Other	Volume: bbl	Dimensions: L x W x D
3. Below-grade tank: Subsection I of 19.15.17.11 NMA	C Tank A	
Volume: 21.0 bbl Type of fluid:	Produced water	
Secondary containment with leak detection Visible		erflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only	Other _Single walled/double botto	omed
Liner type: Thicknessmil 🗌 HD	PE PVC Other	
4.		

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
 Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map 	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC 	uments are NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

•

 12. Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan 	locuments are
 Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well FI Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	uid Management Pit
 Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	nttached to the
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Pa 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

*

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain. - FEMA map	□ Yes □ No □ Yes □ No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plane by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Image: Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Image: Closure Plan (only) Image: OCD Conditions (see attachment) Title: Image: Closure Plan (only) Image: OCD Conditions (see attachment) OCD Representative Signature: Image: Closure Plan (only) Image: OCD Conditions (see attachment) Title: Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) Image: Occore Plan (only) <td< td=""><td>2015</td></td<>	2015
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:3/6/2015	
20. Closure Method: Image: Waste Excavation and Removal On-Site Closure Method Image: Image: Image: Image: Waste Excavation and Removal On-Site Closure Method Image: Ima	op systems only)
 21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please intermark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique 	dicate, by a check

×

22. Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge	and
belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.	

Name	(Print)):	Jeff	Peace

.

Signature: Off Pane

Title: Field Environmental Coordinator

_____ Date: __June 2, 2015____

e-mail address: __peace.jeffrey@bp.com

Telephone: __(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Florance 54 API No. 3004511657 Unit Letter O, Section 22, T30N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 No notice was sent. The BGT was removed as part of location stripping operations since the well has been plugged and abandoned. As a result the normal notification was not made.
- BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 No notice was sent. The BCT was removed as part of location stripping.

No notice was sent. The BGT was removed as part of location stripping operations since the well has been plugged and abandoned. As a result the normal notification was not made.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)

- c. Basin Disposal, Permit NM-01-0005 (Liquids)
- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 - All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. This area will be reclaimed since the well has been plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

10

•

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis D

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

<u>District IV</u> 1220 S. St. Fran	cis Dr., Santa	a Fe, NM 8750	5			e, NM 875						
			Rel	ease Notific	the second s		an english an an Training Article	ction				
						OPERA				al Report	\boxtimes	Final Repor
Name of Co	ompany: B	Р				Contact: Jef				1		1
Address: 20	0 Energy	Court, Farm	ington, N	M 87401			No.: 505-326-94					
Facility Nat	ne: Floran	ce 54				Facility Typ	e: Natural gas	well				
Surface Ow	ner: Feder	al		Mineral (Owner:]	Federal			API No	. 30045110	657	
				LOC	ATIO	N OF REI	LEASE					
Unit Letter O	Section 22	Township 30N	Range 9W	Feet from the 1,045		South Line	Feet from the 1,850	East/V East	Vest Line	County: S	an Juan	1
		Lat	itude3	6.79249		Longitud	e_107.76562_					
				NAT	TURE	OF RELI	EASE					
Type of Rele							Release: N/A			Recovered: N		
Source of Re	lease: below	v grade tank -	- 21 bbl			Date and H N/A	lour of Occurrence	ce:	Date and	Hour of Dis	covery:	: N/A
Was Immedi	ate Notice (Yes] No 🛛 Not R	equired	If YES, To	Whom?					
By Whom?						Date and H						
Was a Water	course Read		Yes 🛛	No		If YES, Vo	lume Impacting	the Wate	ercourse.			
				n Taken.* Sampli and chlorides belo					g removal	to ensure no	soil im	pacts from
backfilled an I hereby certi regulations a	d compacted fy that the i ll operators	d and will be information g are required t	reclaimed iven above o report ar	een.* BGT was re since the well has is true and comp nd/or file certain r	s been pl	ugged and ab ne best of my otifications ar	andoned. knowledge and und perform correct	inderstan	nd that purs	suant to NM0 eases which	OCD ru may en	iles and idanger
should their o	operations h nment. In a	ave failed to addition, NMC	adequately DCD accept	te of a C-141 report investigate and r stance of a C-141	emediate	e contaminati	on that pose a thr e the operator of	reat to gr responsi	ound water bility for co	, surface wa ompliance w	ter, hur vith any	man health
Signature:	eff Po	all					<u>OIL CON</u>			DIVISIC	DN	
Printed Name						Approved by	Environmental S	specialist	:			
Title: Field E	nvironment	tal Coordinate	or			Approval Dat	e:	F	Expiration	Date:		
E-mail Addre	ess: peace.je	effrey@bp.co	m			Conditions of	Approval:			Attached		
Date: June 2	, 2015]	Phone: 505	5-326-9479								

* Attach Additional Sheets If Necessary

DD		API# 30045011	1657		
CLIENT: BP	BLAGG E P.O. BOX 87, B	API #:	1057		
	(50	(if applicble): A			
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER:		PAGE #: of	1
SITE INFORMATION		NCE # 54		DATE STARTED: 03/04	4/15
QUAD/UNIT: O SEC: 22 TWP:		NM CNTY: SJ ST:	NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,045'S / 1,85 LEASE #: SF080003		TYPE: FEDERAL STATE / FEE / I STRIKE ONTRACTOR: MBF - S. GENTR		ENVIRONMENTAL SPECIALIST(S):	В
REFERENCE POINT	_	S COORD.: 36.79260 X 10		GL ELEV.: 5.	977'
1) 21 BGT (SW/DB)				RING FROM W.H.: 40', S1	
2)	GPS COORD.:		DISTANCE/BEAI	RING FROM W.H.:	
			DISTANCE/BEAI	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEAR	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # (DR LAB USED: HALL			OVM READING (ppm)
1) SAMPLE ID: 21 BGT 5-pt. (. ,	0.0
2) SAMPLE ID:					
3) SAMPLE ID:					_
		SAMPLE TIME: LAB ANALYS			
SOIL DESCRIPTION	SOIL TYPE: SAND/ SILTY SAND /	SILT / SILTY CLAY / CLAY / GRAVEL / OTHE	R		
SOIL COLOR: DARK YELLOW COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY /SLIGHTLY MOIST MOIST / W SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED: YES	COHESIVE / COHESIVE / HIGHLY COHESIVE COSE FIRM / DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS. 5	PLASTICITY (CLAYS): NON PLASTIC / SLIGHT DENSITY (COHESIVE CLAYS & SILTS): S HC ODOR DETECTED: YES NO EXPLANA ANY AREAS DISPLAYING WETNESS: YES	OFT / FIRM / :	STIFF / VERY STIFF / HARD	
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: GAS WELL WAS RECENTLY PL	D AND/OR OCCURRED : YES NO EXPL YES NO EXPLANATION -	ANATION:			
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft. EXCA	VATION EST	IMATION (Cubic Yards) :	NA
	EAREST WATER SOURCE: >1,000	NEAREST SURFACE WATER: <200	NMOC	D TPH CLOSURE STD: 100	ppm
/ E	BGT Located : off / on sit TO P & A MARKER PHEMERAL WASH 20' FROM CLOSEST EDGE OF BGT	e PLOT PLAN circle: atta		CALIB. READ. = 53.1 ppm CALIB. GAS = 100 ppm : 7:30 @mpm DATE: 03/0 MISCELL. NOT	04/15
FENCE	DU			10:	
PBGTL T.B. ~ 6' B.G. WOODEN R.W.	RM PROL TANK		RI PI P. Pe O(Tan ID	EF. #: P - 21 K: ZBEEBS0SJS J #: X7-0060P-E ermit date(s): 06/14/' CD Appr. date(s): 04/08/' OVM = Organic Vapor Mete	14
		X - S.		BGT Sidewalls Visible: Y / N	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO		ELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = WEL	L HEAD;	BGT Sidewalls Visible: Y / N	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGL	and a second s		MUI	lagnetic declination: 10°	E
NOTES:		ONSITE: 03/04/15			

*

.

Analytical Report Lab Order 1503181 Date Reported: 3/6/2015

Hall Environmental Analysis Laboratory, Inc.

.

CLIENT: Blagg Engineering Client Sample ID: 21 BGT 5ppt @ 6' Project: Florance 54 Collection Date: 3/4/2015 9:10:00 AM 1503181-001 Lab ID: Matrix: SOIL Received Date: 3/5/2015 8:30:00 AM Analyses Result **RL** Qual Units **DF** Date Analyzed Batch ----MALED DIESEL DANCE ODCANICO . alu -INAL

EPA METHOD 8015D: DIESEL RANGE		Analyst:	JME			
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	3/5/2015 10:21:16 AM	18002
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	3/5/2015 10:21:16 AM	18002
Surr: DNOP	96.6	63.5-128	%REC	1	3/5/2015 10:21:16 AM	18002
EPA METHOD 8015D: GASOLINE RANG	GE				Analyst:	NSB
Gasoline Range Organics (GRO)	ND	4.4	mg/Kg	1	3/5/2015 10:40:44 AM	17990
Surr: BFB	94.6	80-120	%REC	1	3/5/2015 10:40:44 AM	17990
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.044	mg/Kg	1	3/5/2015 10:40:44 AM	17990
Toluene	ND	0.044	mg/Kg	1	3/5/2015 10:40:44 AM	17990
Ethylbenzene	ND	0.044	mg/Kg	1	3/5/2015 10:40:44 AM	17990
Xylenes, Total	ND	0.087	mg/Kg	1	3/5/2015 10:40:44 AM	17990
Surr: 4-Bromofluorobenzene	102	80-120	%REC	1	3/5/2015 10:40:44 AM	17990
EPA METHOD 300.0: ANIONS					Analyst:	LGT
Chloride	ND	30	mg/Kg	20	3/5/2015 11:16:30 AM	18006

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method	od Blank
	E	Value above quantitation range	H	Holding times for preparation or analysi	s exceeded
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit	Page 1 of 5
	0	RSD is greater than RSDlimit	Р	Sample pH Not In Range	1 450 1 01 5
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit	
	S	Spike Recovery outside accepted recovery limits			

WO#:	1503181

06-Mar-15

Client: Project:		g Engineering ance 54							
Sample ID	MB-18006	SampType:	MBLK	Tes	tCode: EPA Meth	nod 300.0: Anior	15		
Client ID:	PBS	Batch ID:	18006	F	RunNo: 24667				
Prep Date:	3/5/2015	Analysis Date:	3/5/2015	S	GeqNo: 726998	Units: mg/ł	٢g		
Analyte		Result PC	L SPK value	SPK Ref Val	%REC LowLin	nit HighLimit	%RPD	RPDLimit	Qual
Chloride		ND	1.5						
Sample ID	LCS-18006	SampType:	LCS	Tes	tCode: EPA Meth	nod 300.0: Anior	ıs		
Client ID:	LCSS	Batch ID:	18006	F	RunNo: 24667				
Prep Date:	3/5/2015	Analysis Date:	3/5/2015	S	eqNo: 726999	Units: mg/k	٢g		
Analyte		Result PC	L SPK value	SPK Ref Val	%REC LowLir	nit HighLimit	%RPD	RPDLimit	Qual
Chloride		14 1	1.5 15.00	0	92.9	90 110			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 2 of 5

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#: 1503181

06-Mar-15

Client: Blagg H Project: Florance	Engineering ee 54									
Sample ID MB-18002	SampType: MBLK TestCode: EPA Method 8015D: Diesel Range Organics									
Client ID: PBS	Batch ID: 18002	RunNo: 24639								
Prep Date: 3/5/2015	Analysis Date: 3/5/2015	SeqNo: 726344	Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qua	al						
Diesel Range Organics (DRO)	ND 10									
Motor Oil Range Organics (MRO)	ND 50									
Surr: DNOP	7.9 10.00	78.7 63.5	128							
Sample ID LCS-18002	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: LCSS	Batch ID: 18002	RunNo: 24639								
Prep Date: 3/5/2015	Analysis Date: 3/5/2015	SeqNo: 726345	Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qua	al						
Diesel Range Organics (DRO)	45 10 50.00	0 89.0 67.8	130							
Surr: DNOP	4.1 5.000	81.4 63.5	128							
Sample ID LCS-17992	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: LCSS	Batch ID: 17992	RunNo: 24639								
Prep Date: 3/4/2015	Analysis Date: 3/5/2015	SeqNo: 726447	Units: %REC							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qua	al						
Surr: DNOP	4.1 5.000	81.2 63.5	128							
Sample ID MB-17992	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: PBS	Batch ID: 17992	RunNo: 24639								
Prep Date: 3/4/2015	Analysis Date: 3/5/2015	SeqNo: 726448	Units: %REC							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qua	al						
Surr: DNOP	8.3 10.00	82.6 63.5	128							

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 3 of 5

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

.

WO#: 1503181

06-Mar-15

Client: Blagg E Project: Floranc	Engineering e 54									
Sample ID MB-17990	SampTy	pe: ME	BLK	Tes	tCode: El	PA Method	8015D: Gaso	line Rang	e	
Client ID: PBS	Batch	ID: 17	990	F	RunNo: 2	4646				
Prep Date: 3/4/2015	Analysis Da	ate: 3/	5/2015	5	SeqNo: 7	26620	Units: mg/k	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO) Surr: BFB	ND 910	5.0	1000		91.3	80	120			
Sample ID LCS-17990	SampTy	pe: LC	S	Tes	tCode: El	PA Method	8015D: Gaso	line Rang	e	
Client ID: LCSS	Batch	ID: 17	990	F	RunNo: 2	4646				
Prep Date: 3/4/2015	Analysis Da	ate: 3/	5/2015	S	SeqNo: 7	26621	Units: mg/M	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	25	5.0	25.00	0	99.8	64	130			
Surr: BFB	970		1000		96.5	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 4 of 5

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering

.

Project: Florance 54

Sample ID MB-17990	Samp	SampType: MBLK TestCode: EPA Method						tiles						
Client ID: PBS	Batc	h ID: 17	990	F	RunNo: 2	4646								
Prep Date: 3/4/2015	Analysis E	Date: 3/	5/2015	S	SeqNo: 7	26635	Units: mg/Kg							
Analyte	Result	PQL	SPK value	e SPK Ref Val %REC LowLimit F			HighLimit	%RPD	RPDLimit	Qual				
Benzene	ND	0.050												
Toluene	ND	0.050												
Ethylbenzene	ND	0.050												
Xylenes, Total	ND	0.10												
Surr: 4-Bromofluorobenzene	1.0		1.000		104	80	120							
Sample ID LCS-17990	Sampl	Type: LC	S	Tes	tCode: E	PA Method	8021B: Vola	tiles						
Client ID: LCSS	Batc	h ID: 17	990	F	RunNo: 2	4646								
Prep Date: 3/4/2015	Analysis E	Date: 3/	5/2015	S	SeqNo: 7	26636	Units: mg/M	(g						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	1.1	0.050	1.000	0	111	80	120							
Toluene	1.1	0.050	1.000	0	108	80	120							
Ethylbenzene	1.1	0.050	1.000	0	111	80	120							
Xylenes, Total	3.3	0.10	3.000	0	111	80	120							
Surr: 4-Bromofluorobenzene	1.1		1.000		114	80	120							

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 5 of 5

06-Mar-15

1503181

WO#:

HALL
ENVIRONMENTAL.
ANALYSIS
LABORATORY

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Clie	ent Name:	BLAGG		Work Order	Number:	15031	81			RcptN	o: 1
Rec	eived by/dat	e:	7 03/0	5/15							
Log	ged By:	Anne Tho	rne	3/5/2015 8:30:	00 AM			anne.	Am	_	
Con	npleted By:	Annę Tho	rne	3/5/2015 j				anne	A		
Rev	viewed By:	Arlant	1	03/05/15				CAMA .			
Cha	in of Cus	tody	/								
	_		ample bottles?			Yes		No		Not Present	
2.	Is Chain of C	Custody comp	plete?			Yes	~	No		Not Present	
3.	How was the	e sample deliv	vered?			Couri	er				
Log	g In										
4.	Was an atte	mpt made to	cool the sample	s?		Yes	\checkmark	No		NA	
5.	Were all san	nples receive	d at a temperatu	re of >0° C to 6.0	°C	Yes	v	No		NA	
6.	Sample(s) ir	n proper cont	ainer(s)?			Yes	\checkmark	No			
7.	Sufficient sa	mple volume	for indicated tes	t(s)?		Yes	\checkmark	No			
8.	Are samples	(except VOA	and ONG) prop	erly preserved?		Yes	\checkmark	No			
9.	Was preserv	ative added t	o bottles?			Yes		No	\checkmark	NA]
10.	VOA vials ha	ave zero head	Ispace?			Yes		No		No VOA Vials 🗹]
11.	Were any sa	ample contain	ers received bro	ken?		Yes		No		# of preserved	
12		vork match bo	attle (abels?			Yes		No		bottles checked for pH:	
			nain of custody)			165	V	NO			2 or >12 unless noted)
13./	Are matrices	correctly ide	ntified on Chain	of Custody?		Yes	\checkmark	No		Adjusted?	
14.1	ls it clear what	at analyses w	vere requested?			Yes	\checkmark	No			
			le to be met? authorization.)			Yes	\checkmark	No		Checked by	
	(in no, noting (outionzation.y								
Spe	cial Hand	ling (if app	olicable)								
16.1	Was client no	otified of all d	iscrepancies wit	h this order?		Yes		No		NA 🗹]
	Person	Notified:			Date			1 SHORE			
	By Who	om:			Via:	eMa		Phone	Fax	In Person	
	Regard	ling:				•				·····	
	Client I	nstructions:	[Old yet	NY MINUTY						
17.	Additional re	emarks:									
18.	Cooler Info	rmation									
	Cooler No		Condition	Seal Intact Seal	No S	eal Da	te	Signed E	3y		
	1	1.1	Good Y	es		(N					

Chain-of-Custody Record			Turn-Around Time: SAME DAY										E	NIN	TE	0	NI N	AE	NT	10		
Client:	BP A	Menics	ĩ	□ Standard XRush					HALL ENVIRONMENTAL ANALYSIS LABORATORY													
	Z. M.	Fuel		Project Name:																		
Mailing	Address	: PR	0. Bux 87	FLORANCE 54				www.hallenvironmental.com 4901 Hawkins NE - Albuguerque, NM 87109														
BLOOMFIELD NM 87413				Project #:				Tel. 505-345-3975 Fax 505-345-4107														
Phone			20-1183]				-					A	naly	sis	Req	uest	:				12.25
email or Fax#:				Project Mana	ger:			(only)	MRO)					0 ₄)							
QA/QC Package:			Î Î	31,466			3021	IO SE	M			(S		4,S(CB's							
Star	ndard	×.	Level 4 (Full Validation)					s (8	(Ga	RO			SIMS)		PO	2 PC						
Accreditation □ NELAP □ Other				Sampler: J On Ice:	- BLAGA	⊆ No ,s.	anto de terror	+TMB's (8021)	+ TPH (Gas	0 / D	8.1))4.1)	8270		3,NO2	/ 8082		A)				r N)
) (Type)			Sample Tem	Contraction and the second	- [.]				(GR	d 41	d 50) or	tals	NO	des	()	NO/	A			20
Date	Time	Matrix	Sample Request ID		Preservative Type	HEAL	. No.	BTEX + MTBE	BTEX + MTBE	TPH 8015B (GRO / DRO /	TPH (Method 418.1)	EDB (Method 504.1)	PAH's (8310 or 8270	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	CHLORADE			Air Bubbles (Y or N)
4/15	0910	SOIL	21 BLT 5-Pt C. 6	402×1	COOL	P-0-:0	-00	X		x	-								×			
	9																					
								_														
Date: 2015 Date: 3/4/15	Time: 0944 Time:	Relinguish	1 Blogg	Received by: Received by: Received by:	phete n ~	Date 34 pate 0310	Time 944 Time 5/15 0830		nark	PP	4rk	BP EX EXT	XX	7-	- 0	OL	DS OP	TS -E	: RE	51		

.

.

If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.

