District I
4625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

## Pit, Below-Grade Tank, or

Santa Fe, NM 87505

Proposed Alternative Method Permit or Closure Plan Application
Type of action:  Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1.
Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Case A 18
API Number:3004527812OCD Permit Number:
U/L or Qtr/QtrNSection5Township31NRange11WCounty:San Juan
Center of Proposed Design: Latitude36.922738
Surface Owner:   Federal  State  Private  Tri
Pit: Subsection F, G or J of 19.15.17.11 NMAC   Temporary: Drilling Workover   Wolded Drilling Fluid yes no well site.   Permanent Emergency Cavitation P&A   DATE: 10/25 (505) 334-6178 Ext. 122   Chloride Drilling Fluid yes no mil LLDPE HDPE PVC Other   String-Reinforced   Wolded Feeters Other   Wolded Peeters Other   Wolded Peeters   Other   Other   Wolded Peeters   Other   Other   Other   Wolded Peeters   Other
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.    Below-grade tank: Subsection I of 19.15.17.11 NMAC
Liner type: Thickness mil
4.  Alternative Method:  Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify	hospital,					
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)						
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  Signed in compliance with 19.15.16.8 NMAC						
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.						
Siting Criteria (regarding permitting): 19.15.17.10 NMAC  Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source					
General siting						
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No					
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No					
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No					
Within a 100-year floodplain. (Does not apply to below grade tanks)  - FEMA map						
Below Grade Tanks						
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No					
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)						
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					

Page 2 of 6

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No							
application.								
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No							
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit Non-low chloride drilling fluid								
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site								
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site								
Permanent Pit or Multi-Well Fluid Management Pit								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa								
lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of								
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
10.	MAG							
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc								
attached.	and and							
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	NMAC							
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC								
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	15.17.9 NMAC							
Previously Approved Design (attach copy of design) API Number: or Permit Number:								
11.  Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC								
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	ruments are							
attached.  ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC								
☐ A List of wells with approved application for permit to drill associated with the pit. ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC							
and 19.13.17.13 NMAC  ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC								
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:								

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative  Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Fluid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable south provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval of	otained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and	Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology &	Mineral Resources; USGS; NM Geological	
Society; Topographic map		☐ Yes ☐ No
Within a 100-year floodplain FEMA map		☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the forby a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of Sub Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) Protocols and Procedures - based upon the appropriate requirements of 19.15.17.  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.1 Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill of Soil Cover Design - based upon the appropriate requirements of Subsection H of Re-vegetation Plan - based upon the appropriate requirements of Subsection H of Site Reclamation Plan - based upon the appropriate requirements of Subsection H of Site Reclamation Plan - based upon the appropriate requirements of Subsection H of Site Reclamation Plan - based upon the appropriate requirements of Subsection H of Site Reclamation Plan - based upon the appropriate requirements of Subsection H of Site Reclamation Plan - based upon the appropriate requirements of Subsection H of Site Reclamation Plan - based upon the appropriate requirements of Subsection H of Site Reclamation Plan - based upon the appropriate requirements of Subsection H of Site Reclamation Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the appropriate requirements of Subsection Figure Plan - based upon the	ments of 19.15.17.10 NMAC section E of 19.15.17.13 NMAC oriate requirements of Subsection K of 19.15.17. based upon the appropriate requirements of 19. 13 NMAC ments of 19.15.17.13 NMAC 5.17.13 NMAC cuttings or in case on-site closure standards cann 19.15.17.13 NMAC E19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accurate an	d complete to the best of my knowledge and beli	ef.
Name (Print):	Title:	
Signature:	Date:	
e-mail address:	Telephone:	
OCD Approval: Permit Application (including clo	litions (see attachment)	
OCD Representative Signature: DEN	Approval Date:	
Title:		
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMA Instructions: Operators are required to obtain an approved closure plan prior to import the closure report is required to be submitted to the division within 60 days of the consection of the form until an approved closure plan has been obtained and the closure	ementing any closure activities and submitting appletion of the closure activities. Please do not activities have been completed.	the closure report. complete this
	Closure Completion Date:10/4/2011	
20.  Closure Method:  Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative C☐ If different from approved plan, please explain.	losure Method   Waste Removal (Closed-lo	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division)  Proof of Deed Notice (required for on-site closure for private land only)  Plot Plan (for on-site closures and temporary pits)  Confirmation Sampling Analytical Results (if applicable)  Waste Material Sampling Analytical Results (required for on-site closure)  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)	ust be attached to the closure report. Please inc	licate, by a check
On-site Closure Location: Latitude 36.922738 Longitude	-108.014428 NAD: □1	927 🛛 1983

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure in belief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature:	Date:June 2, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

# BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

#### <u>Case A 18 – Tank B (95 bbl)</u> <u>API No. 3004527812</u> <u>Unit Letter N, Section 5, T31N, R11W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)

- c. Basin Disposal, Permit NM-01-0005 (Liquids)
- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	95 bbl, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

  Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notifi	catio	n and Co	orrective A	ction				
						OPERA'	ГOR		Initia	al Report	$\bowtie$	Final Repor
Name of Company: BP						Contact: Jeff Peace						1
Address: 20	Address: 200 Energy Court, Farmington, NM 87401						Telephone No.: 505-326-9479					
Facility Name: Case A 18						Facility Typ	e: Natural gas	well				
Surface Owner: Federal Mineral Own					Owner:	Federal			API No	. 3004527	812	
				LOC	ATIO	N OF RE	LEASE					
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	East/We	est Line	County: S	an Juar	1
N	5	31N	11W	1,270	South		1,625	West				
		Latit	ude 36	.922738		Longitud	e 108.014428					
					FUIDIE							
Tyma of Pale	20001 2020			NAI	UKE	OF REL		7	7 - 1 D	1.7	NT/A	
Type of Rele		v grade tank –	95 bbl T	ank B			Release: N/A  Iour of Occurrence			Recovered: 1 Hour of Dis		
Was Immedi			<i>75</i> 001, 1	ank D		If YES, To		LC.	Jaic and	riour or Dis	scovery.	•
			Yes	No 🛛 Not R	equired	11 125, 10	***************************************					
By Whom?						Date and H	Iour					
Was a Watercourse Reached?					If YES, Vo	olume Impacting	the Waterc	ourse.				
☐ Yes ☒ No												
If a Waterco	urse was Im	pacted, Descr.	ibe Fully.*	8								
Describe Car	ise of Proble	em and Remed	dial Action	Taken * Sampli	ing of th	e soil heneath	the BGT was do	ne during r	removal t	o ensure no	soil in	macts from
							is results are attac		i cino var t	o choure no	3011 1111	ipacis irom
						•						
Describe Are	a Affected a	and Cleanup A	Action Tak	en * BGT was re	moved	and the area ii	nderneath the BG	T was sam	nled Th	ne area unde	er the R	GT was
				ctive well area.	movea	and the area ti	nderneam me Bo	i was saii	ipica. 11	ic area unuc	A the D	G1 was
I hereby certi	fy that the i	nformation gi	ven ahove	is true and comp	lete to t	he heet of my	knowledge and u	understand :	that nurs	uent to NM	OCD r	ulac and
							id perform correct					
							arked as "Final R					
							on that pose a thr					
or the environ	nment. In a	ddition, NMO	CD accep	tance of a C-141	report d	oes not reliev	e the operator of	responsibil	lity for co	ompliance v	vith any	other
federal, state,	or local lav	vs and/or regu	lations.				OII COM	CEDVA	TION	DIVICIO	) N.T.	
	00	0 -					OIL CON	SERVA	HON	DIVISIC	<u>JIN</u>	
Signature:	1986	10sel	-									
310						Approved by	Environmental S	pecialist:				
Printed Name	e: Jeff Peace											
Title: Field E	nvironment	al Coordinato	r			Approval Dat	e:	Exp	piration I	Date:		
		cc										
E-mail Addre	ess: peace.je	ffrey@bp.con	1			Conditions of	Approval:			Attached		
Date: June 2	2015	D	hone: 505	-326-9479								

<sup>\*</sup> Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENG P.O. BOX 87, BLO	3	API#: 3004527812  TANK ID (if applicble): A & B	
FIELD REPORT:	(circle one): BGT CONFIRMATION / REL	EASE INVESTIGATION / OTHER:		(if applicble):
SITE INFORMATION QUAD/UNIT: N SEC: 5 TWP:  1/4 - 1/4/FOOTAGE: 1,270'S / 1,62  LEASE #: SF078095	31N RNG: 11W PM: N 25'W SE/SW LEASE TYPE:	E 18  IM CNTY: SJ ST:  FEDERAL/STATE/FEE/INI  ELKHORN  RACTOR: MBF - C. MCINNES		DATE STARTED: 09/20/11  DATE FINISHED: ENVIRONMENTAL SPECIALIST(S): NJV
REFERENCE POINT  1) 95 BGT (SW/DB) - A  2) 95 BGT (SW/DB) - B	WELL HEAD (W.H.) GPS COORD:: 36.923	36.92359 X 1 346 X 108.016304	108.016	39 GLELEV.: 6,197' ARING FROM W.H.: 87', S4W ARING FROM W.H.: 105', N58W
3)	GPS COORD.:			ARING FROM W.H.:
SAMPLING DATA:  1) SAMPLE ID: 5PC - TB @ 5' (9)  2) SAMPLE ID: 5PC - TB @ 5' (9)  3) SAMPLE ID: 4) SAMPLE ID:	The second of th	SAMPLE TIME: 1630 LAB ANALYSIS:	418.1/8	015B/8021/B/300.0 (CI) NA
SOIL DESCRIPTION  SOIL COLOR: DARK YEL  COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY  CONSISTENCY (NON COHESIVE SOILS): LC  MOISTURE: DRY SLIGHTLY MOIST MOIST W  SAMPLE TYPE: GRAB COMPOSITE # 0F PTS.  DISCOLORATION/STAINING OBSERVED	SOIL TYPE: SAND SILTY SAN  LOWISH BROWN  COHESIVE / COHESIVE / HIGHLY COHESIVE  DOSE FIRM DENSE / VERY DENSE  ET / SATURATED / SUPER SATURATED  5		TLYPLASTIC/C	COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC / FIRM / STIFF / VERY STIFF / HARD
ANY AREAS DISPLAYING WETNESS: YES NO ADDITIONAL COMMENTS: NO APPARE  SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: >100' N	NA ft. X NA ft.			IMATION (Cubic Yards) : NA D TPH CLOSURE STD: 100 ppm
SITE SKETCH	FENCE  WELL HEAD  HEAD	PLOT PLAN circle: attack	N OVM	CALIB. READ. = NA ppm RF = 0.52 CALIB. GAS = NA ppm RF = 0.52 CALIB. GAS = NA ppm DATE: NA  MISCELL. NOTES NO - N1435257 PO - 55397 PK - ZANDECALSL  Dermit Date: 06/08/10 DCD Appr. Date: 03/01/12
	'ATION DEPRESSION; B.G. = BELOW GRADE; B = B BELOW-GRADE TANK LOCATION; SPD = SAMPLE ;; SW-SINGLE WALL; DW-DOUBLE WALL; SB-SI	POINT DESIGNATION; R.W. = RETAINING V	WALL; B	BGT Sidewalls Visible: Y N / NA lagnetic declination: 10° E

## Hall Environmental Analysis Laboratory, Inc.

Date: 04-Oct-11

Analytical Report

CLIENT:

Blagg Engineering

1109910

Client Sample ID: 5PC-TB @5' (95 BGT-B)

Lab Order:

Collection Date: 9/20/2011 4:20:00 PM

Project: Lab ID: Case A #18 1109910-02 Date Received: 9/23/2011

Matrix: SOIL

Analyses	Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS		-	***		Analyst: JB
Diesel Range Organics (DRO)	ND	10		mg/Kg	1	9/28/2011 12:12:37 PM
Surr: DNOP	135	73.4-123	S	%REC	1	9/28/2011 12:12:37 PM
EPA METHOD 8015B: GASOLINE RA	NGE					Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.7		mg/Kg	1	9/30/2011 3:36:29 AM
Surr: BFB	93.7	75.2-136		%REC	1	9/30/2011 3:36:29 AM
EPA METHOD 8021B: VOLATILES						Analyst: RAA
Benzene	ND	0.047		mg/Kg	1	9/30/2011 3:36:29 AM
Toluene	ND	0.047		mg/Kg	1	9/30/2011 3:36:29 AM
Ethylbenzene	ND	0.047		mg/Kg	1	9/30/2011 3:36:29 AM
Xylenes, Total	ND	0.095		mg/Kg	1	9/30/2011 3:36:29 AM
Surr: 4-Bromofluorobenzene	102	80-120		%REC	1 .	9/30/2011 3:36:29 AM
EPA METHOD 300.0: ANIONS				,		Analyst: SRM
Chloride	ND	1.5		mg/Kg	1	9/29/2011 6:27:45 PM
EPA METHOD 418.1: TPH						Analyst: JB
Petroleum Hydrocarbons, TR	ND	19		mg/Kg	1	9/29/2011

#### Qualifiers:

- Value exceeds Maximum Contaminant Level
- E Estimated value
- Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- Analyte detected in the associated Method Blank B
- H Holding times for preparation or analysis exceeded
- MCL Maximum Contaminant Level
  - ND Not Detected at the Reporting Limit
  - Spike recovery outside accepted recovery limits

Date: 04-Oct-11

# **QA/QC SUMMARY REPORT**

Client:

Blagg Engineering

Project:

Case A #18

Work Order:

1109910

Project: Case A #18									Work	Order:	1109910
Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec L	owLimit Hi	ighLimit	%RPD	RPDLimit	Qual
Method: EPA Method 300.0: A	nions										
Sample ID: MB-28618		MBLK				Batch ID:	28618	Analys	sis Date:	9/29/2011	1:14:20 PM
Chloride	ND	mg/Kg	1.5								
Sample ID: LCS-28618		LCS				Batch ID:	28618	Analys	sis Date:	9/29/2011	1:31:45 PN
Chloride	13.91	mg/Kg	1.5	15	0	92.7	90	110			
Method: EPA Method 418.1: T	PH										
Sample ID: MB-28601		<b>MBLK</b>				Batch ID:	28601	Analys	sis Date:		9/29/2011
Petroleum Hydrocarbons, TR	ND	mg/Kg	20								
Sample ID: LCS-28601		LCS				Batch ID:	28601	Analys	sis Date:		9/29/2011
Petroleum Hydrocarbons, TR	100.5	mg/Kg	20	100	0	101	87.8	115			
Sample ID: LCSD-28601		LCSD				Batch ID:	28601		is Date:		9/29/2011
Petroleum Hydrocarbons, TR	103.2	mg/Kg	20	100	0	103	87.8	115	2.61	8.04	
											***
Method: EPA Method 8015B: I Sample ID: MB-28603	Diesel Range	Organics MBLK				Batch ID:	28603	Analys	is Date:	9/28/2011	9:54:16 AM
Diesel Range Organics (DRO)	ND	mg/Kg	10								
Sample ID: LCS-28603		LCS				Batch ID:	28603	Analys	is Date:	9/28/2011 10	0:28:40 AM
Diesel Range Organics (DRO)	55.22	mg/Kg	10	50	4.175	102	66.7	119			
Method: EPA Method 8015B: 0	Sasoline Rar	nge									
Sample ID: 1109910-01AMSD		MSD				Batch ID:	28595	Analys	is Date:	9/30/2011 1	1:21:12 PM
Gasoline Range Organics (GRO)	26.71	mg/Kg	4.7	23.26	0	115	72.4	149	3.20	19.2	
Sample ID: MB-28595		MBLK				Batch ID:	28595	Analys	is Date:	9/29/2011 1	1:45:48 PM
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0								
Sample ID: LCS-28595	110	LCS	0.0			Batch ID:	28595	Analys	is Date:	9/29/2011 10	0:48:10 PM
Gasoline Range Organics (GRO)	28.48	mg/Kg	5.0	25	0	114	86.4	132			
Sample ID: 1109910-01AMS	20.40	MS	0.0	20	U	Batch ID:	28595		is Date:	9/30/2011 10	)·52·22 PM
Gasoline Range Organics (GRO)	25.87	mg/Kg	4.8	23.76	0	109	72.4	149	is bate.	0/00/2011 10	7,02.22 1 10
		mgntg	4.0	20.70	0	100	72.7	140			
Method: EPA Method 8021B: V Sample ID: MB-28595	olatiles	MBLK				Batch ID:	28595	Analys	is Date:	9/29/2011 11	I-AE-AR DM
_	ND		0.050			Datell ID.	20080	Allalys	is Date.	31231201111	1.45.40 F W
Benzene	ND ND	mg/Kg	0.050								
Toluene Ethylbenzene	ND	mg/Kg mg/Kg	0.050								
Xylenes, Total	ND	mg/Kg	0.030								
Sample ID: LCS-28595	ND	LCS	0.10			Batch ID:	28595	Analys	is Date:	9/29/2011 11	1:16:59 PM
	1.019		0.050	4	0.0141	100	83.3	107			
Benzene Toluene	1.019	mg/Kg mg/Kg	0.050		0.0141	98.9	74.3	115			
Ethylbenzene	1.002	mg/Kg	0.050		0.0129	101	80.9	122			
Xylenes, Total	3.058	mg/Kg	0.10		0.0136	101	85.2	123			
Ayronos, Total	0.000	1119/119	0.10		2,0120		30.2	123			

0	ня	li	lie	rs

E Estimated value

R RPD outside accepted recovery limits

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

# Hall Environmental Analysis Laboratory, Inc.

### Sample Receipt Checklist

Client Name BLAGG	Date Receive	9/23/2011					
Work Order Number 1109910				Received by	: DA	M	
Checklist completed by: Signature	ð	1	Date	Sample ID la 9/26/1/	bels check	ked by:	Initials (M)
Matrix:	Carrier name:	Grey	hound				
Shipping container/cooler in good condition?		Yes	<b>V</b>	No	Not Pres	ent	
Custody seals intact on shipping container/coole	r?	Yes	<b>V</b>	No	Not Pres	ent .	Not Shipped
Custody seals intact on sample bottles?		Yes	1 !	No	N/A	~	
Chain of custody present?		Yes	<b>~</b>	No			
Chain of custody signed when relinquished and	eceived?	Yes	<b>~</b>	No			
Chain of custody agrees with sample labels?		Yes	<b>V</b>	No ·			
Samples in proper container/bottle?		Yes	<b>V</b>	No			
Sample containers intact?		Yes	<b>V</b>	No ·			
Sufficient sample volume for indicated test?		Yes	<b>V</b>	No			
All samples received within holding time?		Yes	<b>V</b>	No			Number of preserved
Water - VOA vials have zero headspace?	No VOA vials subm	itted	~	Yes	No		bottles checked for pH:
Water - Preservation labels on bottle and cap ma	itch?	Yes	1 1	No	N/A	V	
Water - pH acceptable upon receipt?		Yes		No :	N/A	<b>V</b>	<2 >12 unless noted below.
Container/Temp Blank temperature?		3.3	3°	<6° C Acceptable			Delow.
COMMENTS:				If given sufficient	time to co	ol.	~
			,				
Client contacted	Date contacted:			Perso	n contacte	d	
Contacted by:	Regarding:						
Comments:							

Chain-of-Custody Record		Turn-Around Time:						ь	4A		FI	NV	TE	20	N	W.F	NI	ГА				
Client: BLAGG ENGR. / BP AMERICA			HALL ENVIRONMENTAL ANALYSIS LABORATORY																			
		Standard Rush Project Name:				www.hallenvironmental.com																
Mailing Address: P.O. BOX 87			CASE A # 1	.8		490	01 H									7109	9					
BLOOMFIELD, NM 87413		Project #:				Tel. 505-345-3975 Fax 505-345-4107																
Phone #: (505) 632-1199		1								-	F 10 10 10	NAME OF TAXABLE PARTY.	10000	ques	THE OWNER OF THE OWNER,							
email or Fax#:		Project Manager:				_ =	(les															
	QA/QC Package:  Standard  Level 4 (Full Validation)			NELSON VELEZ			-(8021B)	TPH (Gas only)	as/Dies					41	PCB's						IPLE	
Accredit	Accreditation:		Sampler: NELSON VELEZ 920			1	H (G	B (G	1	1)			ance	/ 8082						SAMPLE	-	
	□ NELAP □ Other		On Ice: ⊃ Yes □ No				+ TP	3015	418.	504.1)	or PAH)	50	Bal	3/5		JA)	0.0)			E E	or	
□ EDD	(Type)	T	I	Sample Tempi	rature: 3.3		#	rBE.	od 8	por	pou	or	etals	nion	icide	(A(	ıi-VC	(30		1PLE	IPOS	> ⟨<
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX +-14	BTEX + MTBE +	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Method	8310 (PNA	RCRA 8 Metals	Cation / Anion Balance	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE (300.0)		GRAB SAMPLE	5 PT. COMPOSITE	Air Bubbles (Y or N)
9/20/11	1630	SOIL	5PO-TB @ 5' (95 BOT-A)	4 02 2	Cool	11099110-1	V		٧	٧								<b>V</b>			٧	-
9/20/11	1620	SOIL	5PC-TB @ 5' (95 BGT-B)	4 oz 2	Cool	ح2	٧		٧	٧								٧			٧	
													1									
Date:	Time:	Relinquished by:		Received by: Date Time		Remarks: TPH (8015B) - GRO & DRO ONLY.																
3/22/11	22/11/530 9/lm Uf		Christie Dolder 9/22/11/53x			BILL DIRECTLY TO BP:																
Date:				Received by: Date Time			Jeff Peace, 200 Energy Court, Farmington, NM 87401  Work Order: N1435Z57 Paykey: ZANDECRUSL															
123/11	23/11 810 Christin Voela			work Order: N1935231 Paykey: ZANDECNICL  which is possibility. Any sub-contracted data will be clearly notated on the analytical report.																		
,	if necessa	ary, samples s	submitted to Hall Environmental may be s	upcontracted to other	accredited laboratorie	s. This serves as notice of	this p	ossibi	irty. A	ny sub	o-cont	racted	data	will be	dear	ly nota	nted or	the a	nalytic	al repo	ort.	



