

State GC BW 001

Sec 32, T32N, R10W

API #: 30045-24960

Formation Tops

Ojo Alamo	1355
Kirtland	1485
Fruitland	2460
PC	2730

GL: 5919'

KB: 5932'

Surface Casing
Hole size: 12.25"
9 5/8" 32.3# H-40 ST&C @ 293'
Cmt w/ 350 sxs to surface

7" TOC unknown

DEPTH	DEVIATION
301	1/2
816	1/2
1341	1/2
1795	1/2
2293	3/4
2651	1

Production Tubing (Installed 6/2015)

2-3/8" 4.7# J-55
F-Nipple (1.78" ID) @ 2683'
EOT (Mule Shoe) @ 2703'

Production Casing

Hole size: 8.75"
7" 20# K-55 ST&C @ 2680'
Cmt w/ 540 sxs

TOL @ 2623'

F-Nipple @ 2683'
EOT @ 2703'

Fruitland Coal

Injected 40/60 mesh sand (1650#)
during original completion

Perforations

2708' - 2722' 4 spf, 0.73"
2688' - 2708' 4 spf, 0.73"
2680' - 2713' 4 spf, 0.73"

Underreamed to 13"
Hole size: 6.125"

Production Liner

5-1/2" 15.5# K-55 @ 2800'

PBTD: 2800'

TD: 2800'

Updated 6/22/2015

AV