District I -1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	Pit, Below-Grade Tank, or	
12961 Prope	osed Alternative Method Permit or Closure Plan Applic	ation
Type of action:		OIL CONS. DIV DIST. 3
115 0-000	Permit of a pit or proposed alternative method	
45-22397	☐ Closure of a pit, below-grade tank, or proposed alternative method ☐ Modification to an existing permit/or registration	JUN 09 2015
	Closure plan only submitted for an existing permitted or non-permitted	pit, below-grade tank,
or proposed alto	ernative method	

Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the

1. Operator: RP America Production Company	OGRID #:778
Facility or well name:Barnes LS 1A	
API Number:3004522397OCD I	Permit Number:
U/L or Qtr/Qtr B Section 24 Township 3	32NRange11WCounty:San Juan
Center of Proposed Design: Latitude36.975281	Longitude107.937342 NAD: ☐1927 ⊠ 1983
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or India	an Allotment
2. ☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC	
Temporary: Drilling Workover	
	Fluid Management Low Chloride Drilling Fluid yes no
	LDPE HDPE PVC Other
String-Reinforced	
	Volume:bbl Dimensions: Lx Wx D
3.	
	Tank B
Volume: 21.0 bbl Type of fluid: Produ	uced water
Tank Construction material: Steel	
☐ Secondary containment with leak detection ☐ Visible sidewalls,	liner 6-inch lift and automatic overflow shut-off
	inici, o-nicii iiit and automatic overnow shut-ori
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _	
	_Single walled/double bottomed; side walls not visible
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _ Liner type: Thicknessmil ☐ HDPE ☐ PVC 4.	_Single walled/double bottomed; side walls not visible
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☑ Other _ Liner type: Thicknessmil ☐ HDPE ☐ PVC 4. ☐ Alternative Method:	_Single walled/double bottomed; side walls not visible

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
· · ·	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
g.	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
	L res L No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
	L Tes L No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	NMAC
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	15 17 0 NMAC
and 19.15.17.13 NMAC	13.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	ruments are
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
☐ A List of wells with approved application for permit to drill associated with the pit. ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	15 17 9 NMAC
and 19.15.17.13 NMAC	io.i/i/ ittific
 ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

· - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC	11 NMAC
 □ Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot cannot cannot be soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	ot be achieved)
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print):	
Signature: Date:	
e-mail address: Telephone:	
e-mail address:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: OCD Permit Number: OCD Permit Number: Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 8/3/ Title: OCD Permit Number: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:1/18/2012	the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: OCD Permit Number: OCD Permit Number: Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.

Form C-144

22. Operator Closure Certification:							
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.							
Name (Print):Jeff Peace	Title: Field Environmental Coordinator						
Signature: Joff Peace	Date:June 9, 2015						
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479						

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Barnes LS 1A, BGT Tank B (21 bbl) API No. 3004522397 Unit Letter B, Section 24 T32N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	9,100
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX and chloride levels were below the stated limits. TPH was 9,100 ppm by Method 418.1 and was 5,900 ppm by Method 8015B. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release occurred. The release was addressed through the spill and release guidelines.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

						OPERA'	ΓOR			al Report		Final Repor
Name of Co						Contact: Jeff Peace						
		Court, Farmi	ngton, N	M 87401		Telephone No.: 505-326-9479						
Facility Na	ne: Barnes	LS 1A]	Facility Typ	e: Natural gas v					
Surface Ow	ner: Federa	al		Mineral O	wner: I	Federal			API No	. 30045223	397	
				LOCA	TION	OF RE	LEASE					
Unit Letter B	Section 24	Township 32N	Range 11W	Feet from the 800	North/ North	South Line	Feet from the 1,500	East/V East	/West Line County: San Juan			
Latitude36.975281Longitude107.937342												
NATURE OF RELEASE												
Type of Rele						Volume of	Release: unknow	'n		Recovered: n		
Source of Re	lease: below	grade tank –	21 bbl, Ta	ink B			Iour of Occurrence	e:		Hour of Dis	covery:	September
Was Immedi	ata Matias C	·····				unknown If YES, To	W/I 9		29, 2011;	11:20 AM		
was illilledi	ate Notice of		Yes 🛚	No 🗌 Not Re	quired	11 1 ES, 10	WHOIH?					
By Whom?						Date and H	lour			01		
Was a Water	course Reac	hed?	Yes 🛛	No		If YES, Vo	lume Impacting t	he Wat	ercourse.			
If a Watercou	If a Watercourse was Impacted, Describe Fully.*											
	il analysis re	esulted in BTI		Taken.* Samplir loride below stand								
Describe Are	a Affected a	and Cleanup A	ction Tak	en.* BGT was rer	noved a	nd the area u	nderneath the BG	T was s	sampled Sa	amnling resu	lts indi	cated a
release occur	red. The rel	ease was add	ressed thro	bugh the spill and d. The excavated	release g	guidelines. I	mpacted soil was	excavat	ted and tran	sported to a	landfar	
regulations a public health should their cor the environment.	I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.											
	00/	7					OIL CONS	SERV	ATION	DIVISIO	N	
Signature:	Jeff b.	evel										
Printed Name	e: Jeff Peace				1	Approved by	Environmental Sp	pecialis	t:			
Title: Field E	invironment	al Coordinato	r		1	Approval Dat	e:		Expiration l	Date:		
E-mail Addre	ess: peace.je	ffrey@bp.com	n		(Conditions of	Approval:			Attached		
Date: June 9	, 2015	P	hone: 505	-326-9479	1.11111111						_	

* Attach Additional Sheets If Necessary

nJK1521538542

CLIENT: BP		BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413							
			32-1199		(if applicble):	A & B			
FIELD REPORT:	(circle one): BGT CONFIRM	ATION / RELE	ASE INVESTIGATION / O	THER:	PAGE #: 1	of 1			
SITE INFORMATION			S #1A		DATE STARTED:	09/29/11			
	32N RNG: 11W			ST: NM	DATE FINISHED:				
1/4 - 1/4/FOOTAGE: 800'N / 1,500 LEASE #: SF078039	'E NW/NE L PROD. FORMATION: MV	-	FEDERAL/STATE) ELKHORN ACTOR: MBF - J. PC		ENVIRONMENTAL SPECIALIST(S):	JCB			
REFERENCE POINT					782 GL ELEV.:	6,215'			
1) 21 BGT (SW/DB) - A	GPS COORD.:		22 X 107.938066	7563 X 107.937		90', 354W			
2) 21 BGT (SW/DB) - B	GPS COORD.:	36.9752	81 X 107.937342	DISTANCE/BE	EARING FROM W.H.:	177', S52E			
3)	GPS COORD.:			DISTANCE/BE	EARING FROM W.H.:				
4)	GPS COORD.: _			DISTANCE/BE	EARING FROM W.H.:				
SAMPLING DATA:	CHAIN OF CUSTODY RECOR	RD(S) # OR LAB	USED: HAL	L		OVM READING			
1) SAMPLE ID: 21 BOT (TANK) 5-Pt (G' (A) SAMPLE DATE: 03	0/29/44	SAMPLE TIME: 1206	LAB ANALYSIS: 416.1/6	3015B/8021/B/300.	0 (CI) 0.0			
2) SAMPLE ID: 21 BGT (COMP) @	6' (B) SAMPLE DATE: 09	9/29/11	SAMPLETIME: 1120	LAB ANALYSIS: 418.1/8	8015B/8021/B/300.	0 (CI) 374			
3) SAMPLE ID:	SAMPLE DATE:		SAMPLE TIME:	LAB ANALYSIS:					
4) SAMPLE ID:	SAMPLE DATE:		SAMPLE TIME:	LAB ANALYSIS:					
SOIL DESCRIPTION	SOIL TYPE: SAND	SILTY SAND	SILT / SILTY CLAY / C	CLAY / GRAVEL / OT	HER				
	LOWISH BROWN								
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC					COHESIVE / MEDIUM PLASTIC / F F / FIRM / STIFF / VERY ST				
MOISTURE: DRY SLIGHTLY MOIST MOIST / W	ET / SATURATED / SUPER SATUR		`		ANATION - DISCOLOF				
SAMPLE TYPE: GRAB COMPOSITE # 0F PTS. DISCOLORATION/STAINING OBSERVED		DARK CR	BENEATH 21-B BGT		DADE				
DISCOLORATION/STAINING OBSERVED	TES NO EXPLANATION	- DAKK GK	AT BENEATH 21-B BG	TO 16 BELOW G	KADE				
ANY AREAS DISPLAYING WETNESS: YES NO									
ADDITIONAL COMMENTS: NO APPAREI RELEASE INVESTIGATION REQUIRED		SE OBSERVI	ED FROM 21 BOT -A.						
RELEASE INVESTIGATION REQUIREE	TOR 21 BGT - B.								
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <a <="" a="" href="c100">	? ft. X	? ft. >1,000' NEA	X ? ft. REST SURFACE WATER:		TIMATION (Cubic Yards) CD TPH CLOSURE STD:				
SITE SKETCH	\oplus		PLOT PLAN circl	le: attached 0VM	1 CALIB. READ. = 53.2	ppm RF = 0.52			
	WELL HEAD			♦ ovm	I CALIB. GAS = 100	ppm			
				N TIME	11:35 (am/pm DATE	09/29/11			
				'_	MISCELL. N	VOTES			
					WO - N1401074				
			(21-B) PBGTL		PO - 52199				
			T.B. ~ 6' B.G.	_	PK - ZSCHWLLB	GT			
			5.5.	-					
					Permit Date:	06/09/10			
	COMPRESSOR	>	(x x x)	_	OCD Appr. Date:				
	John NEGOVI			Tar ID	nk D				
)	(- S.P.D.	BGT Sidewalls Visible	(Y)/ N / NA			
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAV	ATION DEPRESSION; B.G. = BELOV	W GRADE; B = BE	LOW; T.H. = TEST HOLE; ~=	APPROX.;	BGT Sidewalls Visible				
T.B. = TANK BOTTOM; PBGTL = PREVIOUS NA-NOT APPLICABLE OR NOT AVAILABLE	3ELOW-GRADE TANK LOCATION; \$; <u>SW - SINGLE WALL;</u> DW - DOUBL	SPD = SAMPLE P LE WALL; SB - SIN	OINT DESIGNATION; R.W. = F GLE BOTTOM; DB - DOUBLE	BOTTOM.	Magnetic declination	: 10 E			
TRAVEL NOTES: CALLOUT:			ONSITE: 09/26/						

Hall Environmental Analysis Laboratory, Inc.

Date: 07-Oct-11

Analytical Report

CLIENT:

Blagg Engineering

Client Sample ID: 21 BGT (Comp) @ 16'

Lab Order:

er: 1109C47

Collection Date: 9/29/2011 11:20:00 AM

Project:

Barnes LS 1A

Date Received: 9/30/2011

Lab ID:

1109C47-01

Matrix: SOIL

Analyses	Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS					Analyst: JB
Diesel Range Organics (DRO)	5500	200		mg/Kg	20	10/4/2011 12:27:02 PM
Surr: DNOP	0	73.4-123	S	%REC	20	10/4/2011 12:27:02 PM
EPA METHOD 8015B: GASOLINE RA	NGE					Analyst: RAA
Gasoline Range Organics (GRO)	400	250		mg/Kg	50	10/3/2011 1:51:50 AM
Surr: BFB	124	75.2-136		%REC	50	10/3/2011 1:51:50 AM
EPA METHOD 8021B: VOLATILES						Analyst: RAA
Benzene	ND	2.5		mg/Kg	50	10/3/2011 1:51:50 AM
Toluene	ND	2.5		mg/Kg	50	10/3/2011 1:51:50 AM
Ethylbenzene	4.0	2.5		mg/Kg	50	10/3/2011 1:51:50 AM
Xylenes, Total	43	5.0		mg/Kg	50	10/3/2011 1:51:50 AM
Surr: 4-Bromofluorobenzene	100	80-120		%REC	50	10/3/2011 1:51:50 AM
EPA METHOD 300.0: ANIONS						Analyst: SRM
Chloride	ND	7.5		mg/Kg	5	10/4/2011 7:00:20 PM
EPA METHOD 418.1: TPH						Analyst: JB
Petroleum Hydrocarbons, TR	9100	200		mg/Kg	10	10/5/2011

Qualifiers:

- Value exceeds Maximum Contaminant Level
- E Estimated value
- J Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- MCL Maximum Contaminant Level
- ND Not Detected at the Reporting Limit
- S Spike recovery outside accepted recovery limits

Date: 07-Oct-11

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project:

Barnes LS 1A

Work Order:

1109C47

Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec. I	.owLimit Hi	ghLimit %RPD	RPDLimit Qual
Allalyte	Nosuit	Onits	1 0(L	I	OI ICIEI	, or GO L	OTLUME IN	Suranne VOLLED	N Deinit Qual
Method: EPA Method 300.0: A	nions	MOD				Datch ID.	20740	Analysis Date:	10/4/2014 7:05:40 53
Sample ID: 1109C47-01AMSD	15.00	MSD				Batch ID:	28716	Analysis Date:	10/4/2011 7:35:10 PM
Chloride	15.20	mg/Kg	7.5	15	0	101	79.6	112 2.78	20
Sample ID: MB-28716		MBLK				Batch ID:	28716	Analysis Date:	10/4/2011 11:45:00 AN
Chloride	ND	mg/Kg	1.5			B () IB			
Sample ID: LCS-28716		LCS				Batch ID:	28716	Analysis Date:	10/4/2011 12:02:25 PM
Chloride	14.31	mg/Kg	1.5	15	0	95.4	90	110	
Sample ID: 1109C47-01AMS		MS				Batch ID:	28716	Analysis Date:	10/4/2011 7:17:45 PM
Chloride	14.78	mg/Kg	7.5	15	0	98.5	79.6	112	
Method: EPA Method 418.1: Ti	PH								
Sample ID: MB-28722		MBLK				Batch ID:	28722	Analysis Date:	10/5/201
Petroleum Hydrocarbons, TR	ND	mg/Kg	20						
Sample ID: LCS-28722		LCS				Batch ID:	28722	Analysis Date:	10/5/201
Petroleum Hydrocarbons, TR	99.20	mg/Kg	20	100	0	99.2	87.8	115	
Sample ID: LCSD-28722		LCSD				Batch ID:	28722	Analysis Date:	10/5/201
Petroleum Hydrocarbons, TR	100.5	mg/Kg	20	100	0	101	87.8	115 1.34	8.04
Method: EPA Method 8015B: [Diesel Range	Organics							
Sample ID: MB-28688		MBLK				Batch ID:	28688	Analysis Date:	10/4/2011 3:56:24 AN
Diesel Range Organics (DRO)	ND	mg/Kg	10						
Sample ID: LCS-28688		LCS				Batch ID:	28688	Analysis Date:	10/4/2011 4:30:18 AN
Diesel Range Organics (DRO)	63.15	mg/Kg	10	50	3.818	119	66.7	119	
Method: EPA Method 8015B: 0	Sasolino Rar	100		The State of		***************************************			
Sample ID: MB-28671	zacomio itai	MBLK				Batch ID:	28671	Analysis Date:	10/1/2011 8:35:27 PM
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0					,	
Sample ID: LCS-28671	110	LCS	0.0			Batch ID:	28671	Analysis Date:	10/2/2011 12:53:21 PN
Gasoline Range Organics (GRO)	29.24	mg/Kg	5.0	25	0	117	86.4	132	
Method: EPA Method 8021B: V	/olatiles								10 100 111 101 101 101
Sample ID: MB-28671	Otaliies	MBLK				Batch ID:	28671	Analysis Date:	10/1/2011 8:35:27 PM
	ND		0.050			Duton ID.	20071	Analysis Date.	10/1/2011 0.00.27 1 1
Benzene Toluene	ND	mg/Kg mg/Kg	0.050						
Ethylbenzene	ND	mg/Kg	0.050						
Xylenes, Total	ND	mg/Kg	0.10						
Sample ID: LCS-28671		LCS	0.10			Batch ID:	28671	Analysis Date:	10/2/2011 5:14:14 AN
Benzene	0.9264	mg/Kg	0.050	1	0.0132	91.3	83.3	107	
Toluene	0.9480	mg/Kg	0.050	1	0.0132	94.8	74.3	115	
Ethylbenzene	1.019	mg/Kg	0.050	1	0	102	80.9	122	
Xylenes, Total	3.083	mg/Kg	0.10	3	0	103	85.2	123	
	0.000		-, 10	•					

	-	-	_	_
Oug	12	C.		

E Estimated value

R RPD outside accepted recovery limits

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

Hall Environmental Analysis Laboratory, Inc.

Sample Receipt Checklist

Client Name BLAGG				Date Receive	d:		9/30/2011
Work Order Number 1109C47				Received by	: All	ΛF	/
Checklist completed by: Signature	Ì	7	Date	9/30//)	abels chec	ked by:	Inibelis
Matrix:	Carrier name:	Grey	hound				
Shipping container/cooler in good condition?		Yes	V	No	Not Pres	ent	
Custody seals intact on shipping container/cooler	?	Yes	V	No	Not Pres	ent	Not Shipped
Custody seals intact on sample bottles?		Yes	1	No	N/A	~	
Chain of custody present?		Yes	V	No			
Chain of custody signed when relinquished and re	ceived?	Yes	V	No			
Chain of custody agrees with sample labels?		Yes	~	No · ·			
Samples in proper container/bottle?		Yes	~	No			
Sample containers intact?		Yes	V	No			
Sufficient sample volume for indicated test?		Yes	V	No			• 🛇
All samples received within holding time?		Yes	'	No			Number of preserved
Water - VOA vials have zero headspace?	No VOA vials subm	itted	*	Yes	No		bottles checked for pH:
Water - Preservation labels on bottle and cap mate	ch?	Yes		No	N/A	~	
Water - pH acceptable upon receipt?		Yes	1	No	N/A	~	<2 >12 unless noted below.
Container/Temp Blank temperature?		4.	7°	<6° C Acceptab			Delow.
COMMENTS:				If given sufficient	t time to co	ol.	
Client contacted D	ate contacted:			Pers	on contact	ed	
Contacted by:	egarding:						
Comments:							

Chain-of-Custody Record		Turn-Around Time:										-	NIX/		•		4-		CAI				
Client: BLAGG ENGINEERING INC. Standard Rush					=											TAI							
7	BP AMERICA Project Name:			ANALYSIS LABORATORY																			
Mailing Address: P.O. Bex 87 BARNES LS 1A		www.hallenvironmental.com																					
			IM 87413	Project #:	Project #:			4901 Hawkins NE - Albuquerque, NM 87109 Tel. 505-345-3975 Fax 505-345-4107															
			2-1199	-					1. 50	0-0-	0-0.	THE RESIDENCE	ELSE SHOW	DESCRIPTION OF	Req	-	100000						
email or		, , ,		Project Mana	ger:				only)	(le)													
QA/QC Package: Standard Level 4 (Full Validation)			J. BLAGG				s (8021)	(Gas on	(Gas/Diesel)					PO ₄ ,SC	PCB's								
Accreditation □ NELAP □ Other		Sampler: J. BLAGE On Ice: DEYes INO.			+ TMB's	+ TPH	5B	418.1)	504.1)	PAH)		D ₃ , NO ₂ ,	\$ / 8082		(A)				1	or N)			
□ EDD	(Type)_		1	Sample Tem	perature: 4,				MTBE	d 801	pd 4	od 5	or F	stals	N,	ides	(A	9	W			3	ح
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALNO	STATE OF THE PARTY	BTEX €MIB	BTEX + MT	TPH Method	TPH (Method	EDB (Method	8310 (PNA or F	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHLORADE				Air Bubbles (Y or N)
29/11	1120	SOIL	21 BGT (COMP) @ 16	402 X 1	COCL	1109047-	-1	X		X	X								×				
il	1206	18	21 BOT (TANK)		ic		7	×		_	~											1	
-il		11	5-ptc6 95 BGT (SEP)	1(tç		,2	1		^	$\overline{}$								$\overline{}$		\rightarrow	-	_
	1243		5-P6063				-	X		X	X								×				
																				- 2			
																						\dashv	
																							_
															×								
Date: 9/29/2011 Date:	Time: 1313 Time:	Relinquish Relinquish	1 Blogg	Received by:	e Walter	Date Time		WC PA	nark:	RDER	et h	114	TBE DIO.	74	0	N :	801	S B					
129/11	11242	1	Moto Weller	may		7/34// 130	00																

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

September 6, 2011

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: BARNES LS 001A-MV

Dear Bureau of Land Management,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about August 31, 2011. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Coordinator/Business Security Representative

BP America Production Company

Jarry D Valer

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

September 29, 2011

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BARNESA LS 001A API 30-045-22397 (M) Section 24 – T32N – R11W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 36 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



