District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

REVISED COORDINATES

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Gr	Pit, Below-Grade Tank, or			
Proposed Alternative Method Permit or Closure Plan Application				
Type of action: Below grade tank registration Permit of a pit or proposed alternated Closure of a pit, below-grade tank Modification to an existing permit	ative method s, or proposed alternative method t/or registration	OIL CONS. DIV DIST. 3 AUG 1 8 2015		
Closure plan only submitted for a or proposed alternative method	n existing permitted or non-permitted pit	t, below-grade tank,		
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request				
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.				
Operator: ConocoPhillips Company OGRID #:21781	7			
Address: P.O. Box 4289, Farmington, New Mexico 87499	<u> </u>			
Facility or well name: SJ 29-6 UNIT 22M				
API Number: 30-39-27507 OCD Permit Number:				
U/L or Qtr/QtrJ (NWSE) Section 12 Township 29N Range		_		
Center of Proposed Design: Latitude 36.736750°N Longitude -107.414				
Surface Owner: State Private Tribal Trust or Indian Allotment				
2.				
Pit: Subsection F, G or J of 19.15.17.11 NMAC				
Temporary: Drilling Workover				
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid M				
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid M ☐ Lined ☐ Unlined Liner type: Thickness 20 mil ☐ LLDPE ☐ HDPE				
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid M ☐ Lined ☐ Unlined Liner type: Thickness 20 mil ☐ LLDPE ☐ HDPE ☐ String-Reinforced	PVC Other			
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid M ☐ Lined ☐ Unlined Liner type: Thickness 20 mil ☐ LLDPE ☐ HDPE	PVC Other			
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other 3. ☑ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: Max 120 bbl Type of fluid: Produced Water	PVC Other	xwxb tes		
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other 3. Below-grade tank: Subsection I of 19.15.17.11 NMAC	Volume:bbl Dimensions: L Updated Coordina Accepted for Reco	xwxb tes		
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other 3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: Max 120 bbl Type of fluid: Produced Water Tank Construction material: Metal	Volume:bbl Dimensions: L Updated Coordina Accepted for Reco	xwxb tes		
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other 3. □ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: ■ Max 120 bbl Type of fluid: Produced Water Tank Construction material: ■ Metal □ Secondary containment with leak detection ☑ Visible sidewalls, liner, 6-	Volume:bbl Dimensions: L Updated Coordina Accepted for Reco	xwxb tes		
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced □ Getail String-Reinforced Liner Seams: □ Welded □ Factory □ Other 3. □ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: ■ Max 120 bbl Type of fluid: ■ Produced Water Tank Construction material: ■ Metal □ Secondary containment with leak detection □ Visible sidewalls, liner, 6- □ Visible sidewalls and liner □ Visible sidewalls only □ Other Liner type: Thickness ■ 45 mil □ HDPE □ PVC □ Construction 4.	Volume:bbl Dimensions: L Updated Coordina Accepted for Reco	xwxb tes		
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced □ Getail String-Reinforced Liner Seams: □ Welded □ Factory □ Other 3. □ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: ■ Max 120 bbl Type of fluid: ■ Produced Water Tank Construction material: ■ Metal □ Secondary containment with leak detection □ Visible sidewalls, liner, 6- □ Visible sidewalls and liner □ Visible sidewalls only □ Other Liner type: Thickness ■ 45 mil □ HDPE □ PVC □ Construction	Volume:bbl Dimensions: L Updated Coordina Accepted for Reco	tes ord		
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other 3. □ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: ■ Max 120 bbl Type of fluid: ■ Produced Water Tank Construction material: ■ Metal □ Secondary containment with leak detection □ Visible sidewalls, liner, 6- □ Visible sidewalls and liner □ Visible sidewalls only □ Other Liner type: Thickness 45 mil □ HDPE □ PVC □ C 4. □ Alternative Method:	Volume:bbl Dimensions: L Updated Coordina Accepted for Reco	res or consideration of approval.		
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other □ 3. □ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: □ Max 120 bbl □ Type of fluid: □ Produced Water Tank Construction material: □ Metal □ Secondary containment with leak detection □ Visible sidewalls, liner, 6-□ Visible sidewalls and liner □ Visible sidewalls only □ Other □ Liner type: Thickness □ 45 □ mil □ HDPE □ PVC □ Co 4. □ Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to 5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporal pits, temporal pits, temporal pits, temporal pits, six feet in height, two strands of barbed wire at top (Required if institution or church)	Volume:bbl Dimensions: L Updated Coordina Accepted for Reconstitution Accepted for Reconstitution Accepted for Reconstitution Solution Accepted for Reconstitution Solution So	res or consideration of approval.		
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid M □ Lined □ Unlined Liner type: Thickness 20 mil □ LLDPE □ HDPE □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other □	Volume:bbl Dimensions: L Updated Coordina Accepted for Reconstitution Accepted for Reconstitution Accepted for Reconstitution Solution Accepted for Reconstitution Solution So	res or consideration of approval.		

6			
Letting; Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)			
Screen Netting Other			
☐ Monthly inspections (If netting or screening is not physically feasible)			
7.			
Signs: Subsection C of 19.15.17.11 NMAC			
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers			
☑ Signed in compliance with 19.15.16.8 NMAC			
8.			
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.			
Please check a box if one or more of the following is requested, if not leave blank:			
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.			
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.			
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptions.	otable source		
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.			
General siting			
General String			
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☑ No ☐ NA		
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No		
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No		
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No		
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No		
Below Grade Tanks			
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ⊠ No		
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☒ No		
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)			
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image			
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Temporary Pit Non-low chloride drilling fluid		
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No	
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Permanent Pit or Multi-Well Fluid Management Pit		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No	
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC Previously Approved Design (attach copy of design) API Number:		
II.		
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:		

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Find Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC		
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.		
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No	
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA	
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA	
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No	
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No	
Within 300 feet of a wetland.		
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance		

	☐ Yes ☐ No		
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division			
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map			
Within a 100-year floodplain FEMA map	Yes No		
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief. Name (Print): Arleen White			
e-mail address:arleen.r.white@conocophillip.comTelephone:505-326-9517			
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)			
18,			
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)			
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date:			
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not			
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this		

Operator Closure Certification:			
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and			
belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.			
$N = \langle D^+ \rangle$	TOTAL .		
Name (Print):	Title:		
Signature:	Date:		
e-mail address:	Telephone:		