1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or	
Proposed Alternative Method Permit or Closure Plan Application	
Type of action: Below grade tank registration Oil CONS. DIV DIST. 3	
∠15 - 20655 ☐ Closure of a pit, below-grade tank, or proposed alternative method ☐ JUL 07 2015	
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,	
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request	
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.	
API Number:3004520655OCD Permit Number:	
Center of Proposed Design: Latitude36.62854 Longitude108.05663 NAD: □1927 ⋈ 1983 Surface	
Owner: ☐ Federal ☐ State ☐ Private ☒ Tribal Trust or Indian Allotment	
☐ String-Reinforced	
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D	
3.	
■ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A	
Volume:95.0bbl Type of fluid:Produced water	
Tank Construction material:Steel	
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible	
Liner type: Thicknessmil	

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) ☐ Screen ☐ Netting ☐ Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
 □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
<u>Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19	
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Fig. 15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 9/3 OCD Permit Number:	5/15
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date:5/14/2015_	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-logical of different from approved plan, please explain.	oop systems only)
Closure Report Attachment Checklist: _Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. □ Proof of Closure Notice (surface owner and division) □ Proof of Deed Notice (required for on-site closure for private land only) □ Plot Plan (for on-site closures and temporary pits) □ Confirmation Sampling Analytical Results (if applicable) □ Waste Material Sampling Analytical Results (required for on-site closure) □ Disposal Facility Name and Permit Number □ Soil Backfilling and Cover Installation □ Re-vegetation Application Rates and Seeding Technique □ Site Reclamation (Photo Documentation) On-site Closure Location: Latitude 36.62854 Longitude -108.05663 NAD: □1927 □	dicate, by a check

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Signature:	Date:July 6, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 265 API No. 3004520655 Unit Letter P, Section 25, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

 Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. This area will be reclaimed since the well has been plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe NIM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

				58	anta F	e, NW 8/3	03					
			Rele	ease Notific	catio	n and Co	rrective A	ction				
						OPERA	ГOR		Initia	al Report	\boxtimes	Final Repor
Name of Co	ompany: B	P				Contact: Jef	f Peace					
			ngton, N	M 87401		Telephone 1	No.: 505-326-94	179				
Surface Ow	ner Triba	1		Mineral ()wner:	Federal			API No	. 30045200	555	
Surface OW	ner. Triou	1							7111110	. 50045200		
** ** *	I G	m 1:	D					T - /**				
Unit Letter P	Section 25	1 ownship 28N	Range 12W	790	1		790	East/W East	est Line	County: S	an Juar	1
		Lat	itude3	6.62854		Longitud	e108.05663_					
				NAT	URE	OF REL	EASE					
									Volume R	ecovered: N	J/A	
Unit Letter Section Township Range Feet from the 790 Latitude _ 36.62854					Date and F N/A	Iour of Occurrence	ce:	Date and	Hour of Dis	covery	: N/A	
Was Immedia	ate Notice (Yes [No Not R	equired	If YES, To	Whom?					
By Whom? Date and Hour												
Was a Water	course Read		Yes 🛚	No		If YES, Vo	lume Impacting t	the Water	course.			
If a Watercou	ırse was Im	pacted, Descr	ibe Fully.*	¢								
Describe Cau the BGT. So	ise of Probl il analysis r	em and Reme esulted in TP	dial Action H, BTEX	n Taken.* Sampli and chlorides belo	ng of th	e soil beneath dards. Analys	the BGT was done is results are attack	ne during ched.	; removal t	o ensure no	soil in	ipacts from
backfilled and	d compacte	d and will be	eclaimed	since the wall has	s been p	lugged and ab	andoned.					
regulations al public health should their of or the environ	I operators or the envir operations hament. In a	are required to ronment. The ave failed to a ddition, NMC	acceptance acceptance dequately CD accep	nd/or file certain r te of a C-141 repo investigate and r	elease nort by the emediat	otifications ar e NMOCD m e contaminati	nd perform correct arked as "Final Ro on that pose a thre	tive action eport" do eat to gro	ons for rele ses not relie ound water,	ases which eve the oper surface wa	may er ator of ter, hu	ndanger Tliability man health
0						Approved by				DIVISIC	<u>N</u>	
Name of Company: BP				xpiration I	Date:							
E-mail Addre	ess: peace.je	effrey@bp.cor	n			Conditions of	Approval:			Attached		

Phone: 505-326-9479

Date: July 6, 2015

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, E	BLOOMFIEL	D, NM 87413	3	TANK ID		655		
FIFI D REPORT							1		
	L OFFILIE COLL A	4 005							
The state of the s			C.I.	A I IIA/I	DATE STARTED:	05/1	1/15		
					DATE FINISHED:				
FIELD REPORT: (circle one): BGT CONFIRMATION: RELEASE INVESTIGATION / OTHER: PAGE #: 1 of 1 SITE INFORMATION: SITENAME GCU # 265 QUADUUNIT: P SEC: 25 TAP. 28N RNG: 12W PM. NM CNTY. SJ ST. NM 1/4-14/PCOTAGE: 790'S / 790'E SE/SE LEASE TYPE: [FEDERAL] / STATE / FEE / INDIAN STRIKE SF078904A PROD. FORMATION: MISH CONTRACTOR: MISH - S. GENTRY REFERENCE POINT: WELL HEAD (W.H.) GPS COORD: 36.62813 X 108.05681 GL ELEV: 5,921' 1) 95 BGT (DW/DB) GPS COORD: 36.62854 X 108.05663 DISTANCEBEARING FROM WH: 2) GPS COORD: DISTANCEBEARING FROM WH: 3) GPS COORD: DISTANCEBEARING FROM WH: 4) GPS COORD: DISTANCEBEARING FROM WH: 5) SAMPLEID: SAMPLEID: SAMPLEID: SAMPLEID: DISTANCEBEARING FROM WH: 2) SAMPLEID: SAMPLEID: SAMPLEID: SAMPLEID: DISTANCEBEARING FROM WH: 3) SAMPLEID: SAMPLEID: SAMPLEID: SAMPLEID: DISTANCEBEARING FROM WH: 5OIL DESCRIPTION: SOILTYPE: [SAND] SILTY SAND] SILTY SILTY CLAY / CLAY / GRAVEL / OTHER POSTICT (CLAYS & SILTS). SOFT / FIRM / STIFF / WERY STIFF / HARD COMESSIONAL OTHERS, [NOT COMESSIVE] SOID STIPS SOIL SETTING FROM WHISH / CLAYS & SILTS). SOFT / FIRM / STIFF / WERY STIFF / HARD CONSISTENCY (NON COHESSIVE SOILS). [LOOSE FIRM) DENSE / WERY DENSE MOSTURE DRY SUGNITIVE MOST / MOST / WEST / SAND SILTY SAND SILTY SILTY SAND SILTY SILTY CLAY / CLAY / GRAVEL / OTHER MOSTURE DRY SUGNITIVE MOST / MOST / WEST / SAND SILTY SAND SILTY SILTY CLAY / CLAY / GRAVEL / OTHER MOSTURE DRY SUGNITIVE MOST / MOST / WEST / SAND SILTY SILTY CLAY / CLAY / GRAVEL / OTHER MOSTURE DRY SUGNITIVE MOST / MOST / WEST / SAND SILTY SILTY CLAY / CLAY / GRAVEL / OTHER MOSTURE DRY SUGNITIVE MOST / MOST / WEST / SAND SILTY SILTY CLAY / CLAY / GRAVEL / OTHER MOSTURE DRY SUGNITIVE MOST / MOST / WEST / SAND SILTY SILTY CLAY / CLAY / GRAVEL / OTHER MOSTURE DRY SUGNITIVE MOST / MOST / WEST /									
	_			5681	GL ELE	V.: 5 .	921'		
1) 95 BGT (DW/DB)									
2)	GPS COORD.:		DIS	ANCE/BEAF	RING FROM W.H.:				
SOLD BEPORT: Girde one): BGTCONFRINATION RELASE INVESTIGATION OTHER: PAGE #: 1 of 1									
4)	GPS COORD.:		DIS	ANCE/BEAF	RING FROM W.H.:				
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) #	OR LAB USED:	HALL				READING		
				8018	5B/8021B/300.0	(CI)	No. of the last of		
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:						
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:						
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:						
SOIL COLOR: DARK YELLOV COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY (SLIGHTLY MOIST) MOIST / W SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED: YES N SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:	WISH ORANGE Y COHESIVE COHESIVE / HIGHLY COHESIVE DOSE FIRM DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED F OF PTS. 5 D EXPLANATION - LOST INTEGRITY OF EQUIPMEN ED AND/OR OCCURRED : YES NO EXPLANATION -	PLASTICITY (CLAYS): NO DENSITY (COHESIVE HC ODOR DETECTED: ANY AREAS DISPLAYIN TT: YES NO EXPLANATION	ON PLASTIC / SLIGHTLY PL CLAYS & SILTS): SOFT YES NO EXPLANATION G WETNESS: YES NO	/ FIRM / \$	STIFF / VERY STIFF / H	HARD			
SOIL IMPACT DIMENSION ESTIMATION:	NAft. XNA	ft. X NA	ft. EXCAVAT	ON EST	IMATION (Cubic Yar	ds):	NA		
COLORS C									
SITE SKETCH	BGT Located: off on si	te PLOT PLA	N circle: attache	d OVM (CALIB. READ. = NA	A ppm	RF =0.52		
CONTAINMENT RING TO P & A MARKER NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	PROD. PBGTL TANK T.B. ~ 5' B.G.	SEPA SEPA	OMPRESSOR RATOR X - S.P.I. FAPPROX.; W.H. = WELL HEA	WW REPH PJ Pe OC Tani	MISCELL. O: EF: P-116 C: ZBEEBS J#: X7-0064 Prinit date(s): CD Appr. date(s): CD Appr. date(s): BGT Sidewalls Visit BGT Sidewalls Visit	NOT 60SJS H-E 06/03/ 09/07/ Vapor Meter million ole: Y / Note: Y / No	10 11 11 11		
APPLICABLE OR NOT AVAILABLE; SW - SINGLE	E WALL; DW - DOUBLE WALL; SB - SINGLE BO	TTOM; DB - DOUBLE BOTTON	1.	IVI	agnetic declination	on. 10	E		

revised: 11/26/13 BEI1005E-6.SKF

Analytical Report

Lab Order 1505469

Date Reported: 5/14/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB@5'(95)

Project: GCU #265

Collection Date: 5/11/2015 9:10:00 AM

Lab ID: 1505469-001

Matrix: MEOH (SOIL) Received Date: 5/12/2015 7:00:00 AM

Analyses	Result	RL Q	ual Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS				Analyst	KJH
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	5/12/2015 10:37:00 AM	19174
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	5/12/2015 10:37:00 AM	19174
Surr: DNOP	99.8	57.9-140	%REC	1	5/12/2015 10:37:00 AM	19174
EPA METHOD 8015D: GASOLINE RA	NGE				Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	5/14/2015 12:58:36 AM	R26157
Surr: BFB	94.5	80-120	%REC	1	5/14/2015 12:58:36 AM	R26157
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.046	mg/Kg	1	5/14/2015 12:58:36 AM	R26157
Toluene	ND	0.046	mg/Kg	1	5/14/2015 12:58:36 AM	R26157
Ethylbenzene	ND	0.046	mg/Kg	1	5/14/2015 12:58:36 AM	R26157
Xylenes, Total	ND	0.093	mg/Kg	1	5/14/2015 12:58:36 AM	R26157
Surr: 4-Bromofluorobenzene	106	80-120	%REC	1	5/14/2015 12:58:36 AM	R26157
EPA METHOD 300.0: ANIONS					Analyst	LGT
Chloride	ND	30	mg/Kg	20	5/12/2015 11:10:21 AM	19183

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1505469

14-May-15

Client:

Blagg Engineering

Project:

GCU #265

Sample ID MB-19183

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID: **PBS**

Batch ID: 19183

RunNo: 26148

Prep Date: 5/12/2015

Analysis Date: 5/12/2015

Units: mg/Kg

HighLimit

PQL SPK value SPK Ref Val %REC LowLimit

SeqNo: 775789

RPDLimit Qual

Analyte Chloride

ND 1.5

Sample ID LCS-19183

Prep Date: 5/12/2015

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 19183

RunNo: 26148

SeqNo: 775790

Units: mg/Kg

Qual

Analyte

Analysis Date: 5/12/2015

SPK value SPK Ref Val %REC LowLimit

HighLimit

1.5

%RPD

Page 2 of 5

Chloride

15.00

93.7

%RPD

RPDLimit

Qualifiers:

E

Value exceeds Maximum Contaminant Level.

Analyte detected below quantitation limits

R RPD outside accepted recovery limits

Value above quantitation range

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н ND Not Detected at the Reporting Limit

P

Reporting Detection Limit

Sample pH Not In Range

0 RSD is greater than RSDlimit

Spike Recovery outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

WO#: 1505469

14-May-15

Client:

Blagg Engineering

Project:

GCU #265

Project: GCU #26	5								
Sample ID MB-19174	SampType: MI	BLK	Tes	tCode: EF	PA Method	8015D: Dies	el Range (Organics	
Client ID: PBS	Batch ID: 19	174	F	RunNo: 26122					
Prep Date: 5/12/2015	Analysis Date: 5	/12/2015	S	SeqNo: 7	75008	Units: mg/F	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10								
Motor Oil Range Organics (MRO)	ND 50								
Surr: DNOP	9.8	10.00		98.3	57.9	140			
Sample ID LCS-19174 SampType: LCS TestCode: EPA Method 8015D: Diesel Range Organics									
Client ID: LCSS	Batch ID: 19	174	F	RunNo: 20	6122				
Prep Date: 5/12/2015	Analysis Date: 5	/12/2015	S	SeqNo: 7	75009	Units: mg/F	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	41 10	50.00	0	81.8	67.8	130			
Surr: DNOP	5.4	5.000		107	57.9	140			
Sample ID 1505469-001AMS	SampType: MS	S	Tes	tCode: EF	PA Method	8015D: Dies	el Range (Organics	
Client ID: 5PC-TB@5'(95)	Batch ID: 19	174	RunNo: 26122						
Prep Date: 5/12/2015	Analysis Date: 5	/12/2015	S	SeqNo: 7	75116	Units: mg/k	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	42 10	49.80	0	84.6	42.3	146			
Surr: DNOP	5.9	4.980		118	57.9	140			
Sample ID 1505469-001AMSI	SampType: MS	SD	Test	tCode: EF	PA Method	8015D: Dies	el Range (Organics	
Client ID: 5PC-TB@5'(95)	Batch ID: 19	174	R	RunNo: 20	6122				
Prep Date: 5/12/2015	Analysis Date: 5	12/2015	S	SeqNo: 7	75117	Units: mg/k	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	42 10	49.75	0	83.9	42.3	146	0.885	28.9	
Surr: DNOP	5.5	4.975		111	57.9	140	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#: 1505469

14-May-15

Client:

Blagg Engineering

Project:

GCU #265

Sample ID 5ML RB SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

LowLimit

LowLimit

80

Client ID:

PBS

Batch ID: R26157

PQL

5.0

RunNo: 26157

Prep Date:

Analysis Date: 5/13/2015

SeqNo: 776429

120

Analyte

%REC

Units: mg/Kg HighLimit

%RPD **RPDLimit**

Qual

Gasoline Range Organics (GRO) Surr: BFB

ND 960

Result

1000

SPK value SPK Ref Val

SPK value SPK Ref Val

95.5

Sample ID 2.5UG GRO LCS

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

LCSS

Batch ID: R26157

PQL

RunNo: 26157

Prep Date: Analyte

Analysis Date: 5/13/2015

SeqNo: 776430 %REC

Units: mg/Kg

%RPD HighLimit Qual

Gasoline Range Organics (GRO)

23 1000

Result

25.00 1000

92.5

64 80 130

RPDLimit

Surr: BFB

100

120

5.0

0

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range
- Analyte detected below quantitation limits I
- 0 RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded H
- Sample pH Not In Range Reporting Detection Limit
- Not Detected at the Reporting Limit Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#: 1505469

14-May-15

Client:

Blagg Engineering

Project:

GCU #265

Sample ID 5ML RB	SampType: MBLK			Tes	TestCode: EPA Method 8021B: Volatiles					
Client ID: PBS	Batch	n ID: R2	6157	F	RunNo: 2	6157				
Prep Date:	Analysis D	ate: 5/	13/2015	S	SeqNo: 7	76458	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.1		1.000		109	80	120			
Sample ID 100NG BTEX LCS	SampT	SampType: LCS			TestCode: EPA Method 8021B: Volatiles			iles		
01: 110 1000	Б	D. I. I. D. DOGATE			D 11 00155					

Sample ID TOUNG BIEX LCS	5 Samp Type: LCS TestCode: EPA Method 8021B: Volatiles													
Client ID: LCSS	Batch ID: R26157 RunNo: 26157													
Prep Date:	Analysis Date: 5/13/2015			S	SeqNo: 7	76459	Units: mg/K	: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	1.0	0.050	1.000	0	101	76.6	128							
Toluene	1.0	0.050	1.000	0	101	75	124							
Ethylbenzene	1.0	0.050	1.000	0	103	79.5	126							
Xylenes, Total	3.1	0.10	3.000	0	102	78.8	124							
Surr: 4-Bromofluorobenzene	1.1		1.000		113	80	120							

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE

Sample Log-In Check List Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Client Name:	BLAGG	Work Order Number:	1505469		RcptNo: 1								
Received by/date	e:	05/12/15		e sere u sue									
Logged By:	Lindsay Mangin	5/12/2015 7:00:00 AM		James Harry									
Completed By:	Lindsay Mangin	5/12/2015 7:39:18 AM		Simulay Herper									
Reviewed By:	Ca	05/12/15											
Chain of Cus	tody	0)[[1]				Α							
	als intact on sample bottles?		Yes 🗌	No 🗌	Not Present								
	Custody complete?		Yes 🏕	No 🗌	Not Present								
	e sample delivered?		Courier										
Log In													
4. Was an atte	empt made to cool the sample	s?	Yes 🕜	No 🗌	NA 🗆								
5. Were all san	mples received at a temperatu	re of >0° C to 6.0°C	Yes 🗹	No 🗌	NA 🗆								
6. Sample(s) in	n proper container(s)?	Yes 🖈	No 🗌										
7. Sufficient sa	ample volume for indicated tes	t(s)?	Yes 🖈	No 🗌									
8. Are samples	s (except VOA and ONG) prop	Yes 🖝	No 🗌	-									
9. Was preserv	vative added to bottles?		Yes	No 🖈	NA 🗆								
10.VOA vials ha	ave zero headspace?		Yes	No 🗌	No VOA Vials								
11. Were any sa	ample containers received bro	ken?	Yes 🗌	No 🐼	# of preserved								
	work match bottle labels?		Yes 🖈	No 🗆	bottles checked for pH:	7							
	pancies on chain of custody)	of Ourstands O	V 🔼	No 🗆	(<2 or > Adjusted?	12 unless noted)							
	s correctly identified on Chain nat analyses were requested?	of Custody?	Yes 🐼	No 🗆		A 2000 X							
	ding times able to be met?		Yes 🖈	No 🗆	Checked by:								
	customer for authorization.)		100 12	,,, _	6 . N. M. & M. P.								
Special Hand	lling (if applicable)												
16. Was client n	notified of all discrepancies wit	h this order?	Yes	No 🗌	NA 🖈								
Persor	n Notified:	Date:											
By Wh	nom:	Via: [eMail	Phone Fax	☐ In Person								
Regard	ding:		VI VIII Abra grapher error. Consta February	AND BURELLES TO AN AMAN LOUN AND MANAGEMENT									
Client	Instructions:				mentantika kina menuantan kana kanapangan dan pangan dan dan bandan dan dan dan dan dan dan dan dan da								
17. Additional re	emarks:		6 40.9004490.0000	1 2 4 5 4 5 5 E									
18. Cooler Info	lo Temp °C Condition	Seal Intact Seal No Se	Seal Date	Signed By									
		The state of the s											

Chain-of-Custody Record		Turn-Around Time:						ŀ	Δŀ		F	N	/T	3O	NI	ME	NT	ГА	L		
Client: BLAGG ENGR. / BP AMERICA			☐ Standard	Rush _	DAY)		10-40-														
			Project Name:				ANALYSIS LABORATORY www.hallenvironmental.com														
Mailing A	ddress:	P.O. BO	X 87	5	CU # 2	65	4901 Hawkins NE - Albuquerque, NM 87109														
		BLOOM	FIELD, NM 87413	Project #:				Tel. 505-345-3975 Fax 505-345-4107													
Phone #: (505) 632-1199		1				Analysis Request															
email or Fax#:		Project Manager:																			
QA/QC Package: Standard Level 4 (Full Validation)		NELSON VELEZ			wB's (8021B)	only)	MRO)			(S)		04,504	PCB's			er - 300.1)			0		
Accreditat	ion:			Sampler: NELSON VELEZ 977			3 (80	Gas	RO/	1)	1)	SIM		O ₂ ,F	8082			water			mple
□ NELAP □ Other		Ondce: X Yes 🖽 No			1	TPH	0/D	418.	504.	3270		N,EC	-		(A)	0.00			e sa		
□ EDD (Type)		Sample Temp	érature: Z i		1	3E + .	(GR(pou	pou	or 8	etals	Š,	cide	(A)	i-VC	il - 3(e	osit		
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO. 1505419	BTEX +-NATBE	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. composite sample
5/11/15	OPIO	SOIL	5PC-TB @ 5 (95)	402 1	CooL	-001	1		1									7			1
	72																				
																			\neg		
																		+	\neg	-	_
		1																	\neg		\dashv
														-				_	\dashv	_	\dashv
-																			-	1	+
																			\dashv	-	\dashv
																		$\overline{}$	\dashv	-	\dashv
							-								-				-		\dashv
																			-	\dashv	\dashv
							-									32			\dashv		\dashv
Date:	Time:	Relinquish	ed bv:	Received by:		Date Time	Ren	nark	ç.												
5/11/15	1545			Christie Warles 5/1/15 1545			Remarks: BILL DIRECTLY TO BP: Jeff Peace, 200 Energy Court, Farmington, NM 87401														
Date: Time: Relinquished by: U		Received by: Date Time				Reference #: P-116 Paykey: \$8558569JS															

.



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 27, 2015

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: GALLEGOS CANYON UNIT 265

API#: 3004520655

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 30, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

Jerry Van Riper

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

May 6, 2015

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 265 API 30-045-20655 (P) Section 25 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around May 8, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



