<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or 12976 Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Oll CONS. DIV DIST. 3 45-23369 Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778 Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Gartner 2
API Number:3004523369OCD Permit Number:
U/L or Qtr/QtrGSection29Township30NRange8WCounty:San Juan
Center of Proposed Design: Latitude36.78566 Longitude107.69550 NAD: □1927 ⋈ 1983
Surface Owner: X Federal X State Private Tribal Trust or Indian Allotment
2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
■ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Attended. Trease specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Signed in compliance with 15.15.16.6 ravite	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 No Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	nments are NMAC 5.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documentation and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	documents are
Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Find Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 9/17 Title: Compliance OCD Permit Number:	12815
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date:11/23/2010_	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-logo) If different from approved plan, please explain.	oop systems only)
21. <u>Closure Report Attachment Checklist</u> : <u>Instructions</u> : Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached.	adicate, by a check

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Posse	Date:June 16, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

Page 6 of 6

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gartner 2 API No. 3004523369 Unit Letter G, Section 29, T30N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and has been reclaimed since the well was plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP has seeded the area as part of final reclamation since the well was plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

				56	illia I C	5, INIVI 0/J	03					
			Rele	ease Notific	eatior	and Co	rrective A	ction				
						OPERA	ΓOR		Initia	l Report	\boxtimes	Final Report
Name of Co	mpany: B	P				Contact: Jef	f Peace					
		Court, Farmi	ington, N	M 87401		Telephone N	No.: 505-326-94	79				
Facility Nar			0)				e: Natural gas v					
							8					
Surface Ow	ner: Feder	al		Mineral C)wner:]	Federal		AF	'I No.	30045233	69	
				LOCA	ATIO	OF REI	LEASE					
Unit Letter G	Section 29	Township 30N	Range 8W	Feet from the 1,450	North/ North	South Line	Feet from the 1,520	East/West L East	ine	County: Sa	ın Juan	
		Lat	itude3	6.78566		_ Longitud	e107.69550_					
				NAT	URE	OF REL	EASE					
Type of Release: none						Volume of	Release: N/A	Volu	ime R	ecovered: N	J/A	
Source of Release: below grade tank – 95 bbl					Date and F	lour of Occurrence	e: Date	and F	Hour of Disc	covery:	7 41	
Was Immedia	ate Notice (Yes [] No 🛛 Not Re	equired	If YES, To	Whom?					
By Whom?						Date and H	lour					
Was a Water	course Read	ched?					olume Impacting t	he Watercour	se.			
Yes No						1 0						
If a Watercou	ırse was Im	pacted, Descr	ibe Fully.	k								
				n Taken.* Sampli					oval to	o ensure no	soil im	pacts from
the BGT. So	il analysis ı	resulted in TP	H, BTEX	and chloride belo	w standa	rds. Analys	is results are attac	ched.				
Describe Are	a Affected	and Cleanup	Action Tal	en.* BGT was re	moved a	and the area u	nderneath the DC	T was cample	d Th	e area unde	r the D	GT was
				d since the well w				i was sampic	u. III	c area unde	i tile B	O1 was
backimed an	d compacte	d and has been	ii icciaiiiic	d since the wen v	vas prag	ged and aban	doned.					
I hereby certi	fy that the	information gi	ven above	is true and comp	lete to th	ne best of my	knowledge and u	nderstand that	t pursu	ant to NM(OCD ru	iles and
				nd/or file certain r								
				ce of a C-141 repo								
				investigate and r								
				tance of a C-141	report de	oes not reliev	e the operator of	responsibility	for co	mpliance w	ith any	other
federal, state,	or local la	ws and/or regu	ilations.				OH GON	anner i me	0371	DIVINO		
0	0	0					OIL CON	SERVAII	ON I	DIVISIO	N	
Signature:	ORK I	200										
oignature.	ALL I						F					
Printed Name	e: Jeff Peac	e				Approved by	Environmental S	pecialist:				
mid nitra		.10 "						т.				
Title: Field E	nvironmen	tal Coordinate	or		-	Approval Dat	e:	Expira	ttion L	pate:		
E-mail Address: peace.jeffrey@bp.com						Conditions of	Approval:			Attached		

Date: June 16, 2015

Phone: 505-326-9479

^{*} Attach Additional Sheets If Necessary

	BLAGG ENGINEERING, INC. BOX 87, BLOOMFIELD, NM 8741: (505) 632-1199	3004523	369
FIELD REPORT: BGT CC (other)	ONFIRMATION TEMP. PIT CLOSURE / RELEASE INVESTIGATION	PAGE No: 1 of	1
SITE INFORMATION: S	ITE NAME: GARTNER # 2	DATE STARTED: 11/03	/10
	RNG: 8W PM: NM CNTY: SJ ST: NM	DATE FINISHED:	
	SW/NE LEASE TYPE: FEDERAL STATE / FEE /		
LEASE #: SF079511A PROD. FOR	RMATION: PC CONTRACTOR: MBF - J. WILLBO	SPECIALIST: NJ\	
	WELL HEAD (W.H.) GPS COORD.: 36.78551		190'
1) 95 BGT (DW/DB) GPS COO	RD.: 36.78566 X 107.69550	DISTANCE/BEARING FROM W.H.: 99', N6	3W
2) GPS COO	RD.:	DISTANCE/BEARING FROM W.H.:	
3) GPS COO	RD.:	DISTANCE/BEARING FROM W.H.:	
4) GPS COO	RD.:	DISTANCE/BEARING FROM W.H.:	
LAB INFORMATION: 0	CHAIN OF CUSTODY RECORD(S): HALL	F	OVM READING
1) SAMPLE ID: 5PC - TB @ 6' - 95 BBL BGT SA	MPLE DATE: 11/03/10 SAMPLETIME: 1533 LAB AN	418.1/8015B/8021B/300.0 (CI)	(ppm)
1	MPLE DATE: SAMPLE TIME: LAB ANA		
3) SAMPLE ID: SA	MPLE DATE: SAMPLE TIME: LAB ANA	LYSIS:	
4) SAMPLE ID: SA	MPLE DATE: SAMPLE TIME: LAB ANA	LYSIS:	
SOIL DESCRIPTION: SO	OIL TYPE: SAND SILTY SAND / SILT / SILTY CLAY / CLAY /	CPAVEL OTHER PERPOCK (condetons	-1
SOIL COLOR: GRAYISH OR/		BEDROCK (Salidstone	=)
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY COHESIVE / C		LIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLAST	ПС
CONSISTENCY (NON COHESIVE SOILS): LOOSE FIRM		SILTS): SOFT / FIRM / STIFF / VERY STIFF / HAR	D
MOISTURE: DRY SLIGHTLY MOIST MOIST / WET / SATURAT SAMPLE TYPE: GRAB COMPOSITE # OF PTS.	ED / SUPER SATURATED HC ODOR DETECTED: YE	S NO EXPLANATION -	
DISCOLORATION/STAINING OBSERVED: YES NO			
DISCOLORATION'S TAINING OBSERVED. 125 INC	EXPLANATION-		
ANY AREAS DISPLAYING WETNESS: YES NO EXPLANATION	ON -		
	CE OF A RELEASE OBSERVED FROM BGT. BGT EXCA	ATION CONSIST OF SANDSTONE. SAMP	LE
COLLECTED FROM SANDSTONE SURFACE. BE	DROCK - VERY HARD, COMPETENT.		
EXCAVATION DIMENSIONS (if applicable):	A ft. X NA ft. X NA ft.	cubic yards excavated (if applicable):	4
SITE SKETCH BERM	PLOT PLAN circle: att	ached OVM CALIB READ. = / ppm	- /-
		OVM CALIB. GAS = ppm	RF = 0.52
*		TILVE: am/pm _DATE:	/
	PROD.	MISCELL. NOTE	
	TANK		S
FENCE	TANK	WO: N1120378	S
			S
	PBGTL −T.B. ~ 6'	WO: N1120378	S
FENCE $(x \times x)$	PBGTL	WO: N1120378 PAYKEY: ZEGJ01RIGS	
	PBGTL −T.B. ~ 6'	WO: N1120378 PAYKEY: ZEGJ01RIGS BGT SIDEWALLS NOT VISIB	
	PBGTL -T.B. ~ 6' B.G.	WO: N1120378 PAYKEY: ZEGJ01RIGS BGT SIDEWALLS NOT VISIB DW - DOUBLE WALLED	
	PBGTL −T.B. ~ 6'	WO: N1120378 PAYKEY: ZEGJ01RIGS BGT SIDEWALLS NOT VISIB	
	PBGTL -T.B. ~ 6' B.G. - SEPARATOR WELL	WO: N1120378 PAYKEY: ZEGJ01RIGS BGT SIDEWALLS NOT VISIB DW - DOUBLE WALLED	LE
	PBGTL -T.B. ~ 6' B.G.	WO: N1120378 PAYKEY: ZEGJ01RIGS BGT SIDEWALLS NOT VISIB DW - DOUBLE WALLED DB - DOUBLE BOTTOM	LE
	PBGTL T.B. ~ 6' B.G. SEPARATOR WELL HEAD HEAD	WO: N1120378 PAYKEY: ZEGJ01RIGS BGT SIDEWALLS NOT VISIB DW - DOUBLE WALLED DB - DOUBLE BOTTOM NA = NOT APPLICABLE OR NOT AVAILA	BLE
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION DEPRESSI	PBGTL −T.B. ~ 6' B.G. - SEPARATOR WELL HEAD ⊕	WO: N1120378 PAYKEY: ZEGJ01RIGS BGT SIDEWALLS NOT VISIB DW - DOUBLE WALLED DB - DOUBLE BOTTOM NA=NOT APPLICABLE OR NOT AVAILA	BLE

revised: 10/02/10 BEI1005E-2.SKF

Hall Environmental Analysis Laboratory, Inc.

Date: 23-Nov-10

CLIENT:

Blagg Engineering

1011357

Lab Order: Project:

Gartner #2

Lab ID:

1011357-01

Client Sample ID: 5 PC-TB@6'- 95 BBL BGT

Collection Date: 11/3/2010 3:30:00 PM

Date Received: 11/9/2010

Matrix: SOIL

Analyses	Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS		-			Analyst: SCC
Diesel Range Organics (DRO)	ND	10		mg/Kg	1	11/10/2010 6:14:43 PM
Surr: DNOP	102	61.7-135		%REC	1	11/10/2010 6:14:43 PM
EPA METHOD 8015B: GASOLINE RA	NGE					Analyst: NSB
Gasoline Range Organics (GRO)	ND	5.0		mg/Kg	1	11/13/2010 12:40:54 AM
Surr: BFB	101	89.7-125		%REC	1	11/13/2010 12:40:54 AM
EPA METHOD 300.0: ANIONS						Analyst: LJB
Chloride	ND	7.5		mg/Kg	5	11/20/2010 7:28:27 PM
EPA METHOD 8260B: VOLATILES SI	HORT LIST					Analyst: MMS
Benzene	ND	0.050		mg/Kg	1	11/12/2010 5:03:13 AM
Toluene	ND	0.050		mg/Kg	1	11/12/2010 5:03:13 AM
Ethylbenzene	ND	0.050		mg/Kg	1	11/12/2010 5:03:13 AM
Xylenes, Total	ND	0.10		mg/Kg	1	11/12/2010 5:03:13 AM
Surr: 1,2-Dichloroethane-d4	98.9	77.8-97.5	S	%REC	1	11/12/2010 5:03:13 AM
Surr: 4-Bromofluorobenzene	91.6	82.2-105		%REC	1	11/12/2010 5:03:13 AM
Surr: Dibromofluoromethane	98.2	63.7-133		%REC	1	11/12/2010 5:03:13 AM
Surr: Toluene-d8	95.8	87.2-105		%REC	1	11/12/2010 5:03:13 AM
EPA METHOD 418.1: TPH						Analyst: LRW
Petroleum Hydrocarbons, TR	ND	20		mg/Kg	1	11/11/2010

Qualiflers:

- Value exceeds Maximum Contaminant Level
- Estimated value E
- Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- MCL Maximum Contaminant Level
- ND Not Detected at the Reporting Limit
- Spike recovery outside accepted recovery limits

Page 1 of 1

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project: Gartner #2

Work Order:

1011357

•								****		1011557
Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec L	owLimit H	ighLimit %RP	D RPDLimi	t Qual
Method: EPA Method 300.0: A	nions					***************************************	, ,			
Sample ID: 1011357-01AMSD		MSD				Batch ID:	24597	Analysis Date	11/20/2010	8:03:17 P
Chloride	15.69	mg/Kg	7.5	15	2.847	85.7	53.9	146 1.23	2 20	
Sample ID: MB-24597		MBLK				Batch ID:	24597	Analysis Date	11/20/2010	2:49:51 P
Chloride	ND	mg/Kg	1.5							
Sample ID: LCS-24597		LCS				Batch ID:	24597	Analysis Date:	11/20/2010	3:07:16 P
Chloride	13.88	mg/Kg	1.5	15	0	92.6	90	110		
Sample ID: 1011357-01AMS		MS				Batch ID:	24597	Analysis Date:	11/20/2010	7:45:52 P
Chloride	15.89	mg/Kg	7.5	15	2.847	86.9	53.9	146		
Method: EPA Method 418.1: TF	PH									
Sample ID: MB-24481		MBLK				Batch ID:	24481	Analysis Date:		11/11/201
Petroleum Hydrocarbons, TR	ND	mg/Kg	20							
Sample ID: LCS-24481		LCS				Batch ID:	24481	Analysis Date:		11/11/201
Petroleum Hydrocarbons, TR	107.3	mg/Kg	20	100	0	107	86.8	116		
Sample ID: LCSD-24481		LCSD				Batch ID:	24481	Analysis Date:		11/11/201
Petroleum Hydrocarbons, TR	105.9	mg/Kg	20	100	0	106	86.8	116 1.29	16.2	
Method: EPA Method 8015B: D	iesel Range	Organics			1					
Sample ID: MB-24448	reser range	MBLK				Batch ID:	24448	Analysis Date:	11/10/2010	0:51:39 A
Diesel Range Organics (DRO)	ND	mg/Kg	10							
Sample ID: LCS-24448		LCS				Batch ID:	24448	Analysis Date:	11/10/2010 1	1:25:48 Al
Diesel Range Organics (DRO)	52.23	mg/Kg	10	50	0	104	64.6	116		
Sample ID: LCSD-24448		LCSD				Batch ID:	24448	Analysis Date:	11/10/2010 1	1:59:56 AM
Diesel Range Organics (DRO)	43.93	mg/Kg	10	50	0	87.9	64.6	116 17.3	17.4	
Wethod: EPA Method 8015B: G	asoline Ran	ne							the shade or a six are about	
Sample ID: MB-24432	addinio rian	MBLK				Batch ID:	24432	Analysis Date:	11/13/2010	3:34:27 AN
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0					,		
Sample ID: LCS-24432	.,,,	LCS	0.0			Batch ID:	24432	Analysis Date:	11/13/2010	3:05:33 AN
Gasoline Range Organics (GRO)	24.89	mg/Kg	5.0	25	0	99.6	95.7	120		
Method: EPA Method 8260B: Ve	olatiles Sho	rt List		* * ***					1/	
Sample ID: mb-24432		MBLK				Batch ID:	24432	Analysis Date:	11/12/2010 1	2:20:46 AN
Benzene	ND	mg/Kg	0.050							
oluene	ND	mg/Kg	0.050							
thylbenzene	ND	mg/Kg	0.050							
	ND	mg/Kg	0.10							
ylenes, Total	7.12									
	,,_	LCS				Batch ID:	24432	Analysis Date:	11/11/2010 1	1:52:39 PN
(ylenes, Total sample ID: Ics-24432 senzene	0.9228	LCS mg/Kg	0.050	1	0	Batch ID: 92.3	24432 73.3	Analysis Date: 116	11/11/2010 1	1:52:39 PM

			-	-	-	_	-	
0	119	11	fi	n	r	Q		

ND

R RPD outside accepted recovery limits Page 1

E Estimated value

J Not Detected at the Reporting Limit

Analyte detected below quantitation limits

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

Hall Environmental Analysis Laboratory, Inc.

Sample Receipt Checklist

Client Name BLAGG		Date Received: 11/9/2010										
Work Order Number 1011357			Received by	AMG								
Checklist completed by: Carrie Signature		Date	Sample ID la	bels checked	b y :	Initials						
Matrix: Carrier name:	Grey	hound										
Shipping container/cooler in good condition?	Yes	V	No.	Not Present			9					
Custody seals intact on shipping container/cooler?	Yes	\checkmark	No 🗀	Not Present		Not Shipped						
Custody seals intact on sample bottles?	Yes		No 🗌	N/A	V							
Chain of custody present?	Yes	Y	No 🗌									
Chain of custody signed when relinquished and received?	Yes	~	No 🗔									
Chain of custody agrees with sample labels?	Yes	\checkmark	No 🗔									
Samples in proper container/bottle?	Yes	\checkmark	No 🗔									
Sample containers intact?	Yes	Y	No 🗔									
Sufficient sample volume for indicated test?	Yes	V	No 🗔									
All samples received within holding time?	Yes	Y	No 🗌			Number of bottles che						
Water - VOA vials have zero headspace? No VOA vials subr	nitted	V	Yes	No 🗌		pH:	cked (U)					
Water - Preservation labels on bottle and cap match?	Yes		No 🗌	N/A								
Water - pH acceptable upon receipt?	Yes		No 🗌	N/A		<2 >12 unleadelow.	ss noted					
Container/Temp Blank temperature?	5.	3°	<6° C Acceptable			2010111						
COMMENTS:			If given sufficient	time to cool.								
						*						
Client contacted Date contacted:			Doros	n controlled								
Chefit contacted.		Person contacted										
Contacted by: Regarding:												
Comments:												
Corrective Action						A. A. Santa Sa						

Chain-of-Custody Record			Turn-Around	Time:		· .							_								•	
Client: 2	BLAKE	ENZ.	R. BP AMERICA	Standard	□ Rush															NT		,
		Project Name:					ANALYSIS LABORATORY															
Mailing Address: 0 0 Ptv 9-7		GARTNER # 2				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109																
7. U. B × X 8 1			Project #:												-							
			FD., Nm 87413	- 10,000					Te	el. 50)5-34	45-39	DUBLIS	No.	SECTION S	-		410	7			
Phone #	#: (505)	632-1199			-							A	naiy		Req	uesi					
email or	Fax#:			Project Mana	iger:		925	18	Jn.	se					04)	S						
QA/QC F	_			NELS	on the	EZ		802	as c	(Gas/Diesel)) ₄ ,S	PCB's			0			
X Stan			☐ Level 4 (Full Validation)	Sampler: /	1			3,2	9	Gas					2,PC							
Accredi		□ Othe	PF	Sampler: /	VELSON Yes	VELEZ		+ TIMB'S (80218)	- TPH (Gas only)	15B (418.1)	504.1)	√H)		3,NO	/ 808		2	300		1	- S
□ EDD				Sample Tem	perature: 4	< 2				80	141	d 50	r P	als	SN,	des		101			00	\ \ \
Date	Time	Matrix	Sample Request ID		Preservative Type			BTEX -WTBE	BTEX + MTBE	TPH Method 8015B	TPH (Method	EDB (Method	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE		S Pr. Composite	-2.
11/3/10	1530	501L	5 PC-TB @ 6' - 95 BBL BGT	4021	Cool	_	1	V		1	V								1		/	1
		100																				
								T													\top	\top
														_				_		\vdash	+	+
		1		and the second s				-	-	-						_			-		+	+
				titi and the second sec				-	-	-								_			+	+
								_	_													\perp
						- Andrews																
								\top														\top
								\top	\vdash												+	+
-								+	-										\vdash	\vdash		+
						-		+	-	-					_			-		\vdash	+	+
Date: ,	Time:	Pelinguich	and hv.	Received.by:		Date	e Time	Do	mark													\perp
11/5/10	1133			Whathe Walter 1/5/10 1133						Remarks: 6RO + DRO ON BOIS												
Date:	Time:	Relinquish	, , , , , ,	Received by:	A	Date																
1/8/10	1000	1	0.00	CA	1	1911	0100								AP.							
1	f necessary,	samples sub	mitted to Hall Environmental may be sub	ocontracted to other a	ccledited laboratori	es. Thistse	ves as notice of thi	is poss	ibility.	Any s	ub-cor	tracte	d data	will be	e clear	rly nota	ated o	n the a	nalytic	al report	-	



