District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.District IV 1220 S. St. Francis Dr., Santa Fe, NM 875051220 South St. Francis Dr. Santa Fe, NM 87505For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
Pit, Below-Grade Tank, or         12978       Proposed Alternative Method Permit or Closure Plan Application         Type of action:       Below grade tank registration       Oll CONS. DIV DIST. 3         Permit of a pit or proposed alternative method       JUN 17 2015         4/5-26960       Closure of a pit, below-grade tank, or proposed alternative method       JUN 17 2015         Modification to an existing permit/or registration       JUN 17 2015         Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request         Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
I.       Operator: BP America Production CompanyOGRID #:778         Address:200 Energy Court, Farmington, NM 87401         Facility or well name:Hughes C 2R         API Number:3004526960OCD Permit Number:         U/L or Qtr/QtrBSection27Township29NRange8WCounty:San Juan         Center of Proposed Design: Latitude36.70055Longitude107.86158107.46158 NAD: [_1927 X] 1983         Surface Owner: X Federal [] State [] Private [] Tribal Trust or Indian Allotment
<ul> <li>2.</li> <li>Pit: Subsection F, G or J of 19.15.17.11 NMAC</li> <li>Temporary: Drilling Workover</li> <li>Permanent Emergency Cavitation P&amp;A Multi-Well Fluid Managen Low Chloride Drilling Fluid yes no</li> <li>Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other</li> <li>String-Reinforced</li> <li>Liner Seams: Welded Factory Other Other Volume: bbl Dimensions: L x W x D</li> </ul>
3.         Below-grade tank:       Subsection I of 19.15.17.11 NMAC       Tank A         Volume:95.0bbl       Type of fluid:Produced water         Tank Construction material:Steel

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

6

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting							
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> - ☐ NM Office of the State Engineer - iWATERS database search; ☐ USGS; ☐ Data obtained from nearby wells							
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells							
<ul> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul>							
<ul> <li>Within the area overlying a subsurface mine. (Does not apply to below grade tanks)</li> <li>Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division</li> </ul>	🗌 Yes 🗌 No						
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	🗌 Yes 🗌 No						
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No						
Below Grade Tanks							
<ul> <li>Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No						
<ul> <li>Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.</li> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No						
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
<ul> <li>Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No						

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No								
<ul> <li>application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>									
- visual inspection (certification) of the proposed site, Aerial photo, saterine image									
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site									
<ul> <li>Within 100 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No								
Temporary Pit Non-low chloride drilling fluid									
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,									
or playa lake (measured from the ordinary high-water mark).									
- Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No								
<ul> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	🗌 Yes 🗌 No								
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;									
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No								
<ul> <li>Within 300 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No								
Permanent Pit or Multi-Well Fluid Management Pit									
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa									
<ul> <li>lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No								
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	_								
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No								
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.									
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No								
<ul> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	Yes No								
<sup>10.</sup> Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N	MAC								
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc									
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC									
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	NMAC								
<ul> <li>Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> <li>Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> </ul>									
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC									
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC								
Previously Approved Design (attach copy of design) API Number: or Permit Number:									
11.									
<u>Multi-Well Fluid Management Pit Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the down of the second seco	anna ants ana								
attached.	uments ure								
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC									
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC									
☐ A List of wells with approved application for permit to drill associated with the pit.									
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19	.15.17.9 NMAC								
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	.15.17.9 NMAC								
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19	.15.17.9 NMAC								

.

<ul> <li>Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC</li> <li>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.</li> <li>Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC</li> <li>Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> <li>Climatological Factors Assessment</li> <li>Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Quality Control/Quality Assurance Construction and Installation Plan</li> <li>Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Nuisance or Hazardous Odors, including H<sub>2</sub>S, Prevention Plan</li> <li>Emergency Response Plan</li> <li>Oil Field Waste Stream Characterization</li> <li>Monitoring and Inspection Plan</li> <li>Erosion Control Plan</li> <li>Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC</li> </ul>	documents are					
<sup>13.</sup> Proposed Closure: 19.15.17.13 NMAC						
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.         Type:       Drilling       Workover       Emergency       Cavitation       P&A       Permanent Pit       Below-grade Tank       Multi-well F         Alternative       Proposed Closure Method:       Waste Excavation and Removal       Waste Removal (Closed-loop systems only)         On-site Closure Method (Only for temporary pits and closed-loop systems)       In-place Burial       On-site Trench Burial         Alternative Closure Method       Onesite Trench Burial       Onesite Trench Burial	luid Management Pit					
<ul> <li><sup>14.</sup> Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.</li> <li>Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC</li> <li>Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC</li> <li>Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)</li> <li>Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> <li>Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> <li>Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> </ul>						
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.						
<ul> <li>Ground water is less than 25 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul>	Yes No NA					
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA					
<ul> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul>	□ Yes □ No □ NA					
<ul> <li>Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No					
<ul> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	🗌 Yes 🗌 No					
<ul> <li>Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.</li> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No					
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No					
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance						
Form C-144 Oil Conservation Division Page 4 o	f 6					

•

- Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No						
<ul> <li>Within the area overlying a subsurface mine.</li> <li>Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division</li> </ul>	🗌 Yes 🗌 No						
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	🗌 Yes 🗌 No						
Within a 100-year floodplain. - FEMA map	Yes No						
16.         On-Site Closure Plan Checklist:       (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.         Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC         Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC         Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC         Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC         Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC         Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC         Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)         Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC         Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC         Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC         Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC         Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed to the best of my							
Name (Print): Title:							
Signature: Date:							
e-mail address: Telephone:							
e-mail address: Telephone: <u>OCD Approva</u> l: Permit Application (including closure plan) & Closure <del>Plan (onty)</del> OCD Conditions (see attachment) <u>OCD Representative Signature:</u>							
18.       OCD Approval:       Permit Application (including closure plan)       Closure Plan (onty)       OCD Conditions (see attachment)         OCD Representative Signature:       Ovalt       Kelly       Approval Date:       9/17/2000	the closure report.						
18.       OCD Approval:       Permit Application (including closure plan)       Closure Plan (onty)       OCD Conditions (see attachment)         OCD Representative Signature:       Ovalt       Kelly       Approval Date:       117/         Title:       OcD Permit Number:       OcD Permit Number:       19.         Closure Report (required within 60 days of closure completion):       19.15.17.13 NMAC       Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this						

•

### **Operator Closure Certification:**

۰.

22.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.							
Name (Print):Jeff Peace	Title: Field Environmental Coordinator						
Signature: Off Proce	Date:June 16, 2015						
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479						

### BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

#### Hughes C 2R API No. 3004526960 Unit Letter B, Section 27, T29N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### **General Closure Plan**

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was made due to misunderstanding of the BGT notice requirements at that time.
- BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
   No notice was made due to misunderstanding of the BGT notice requirements at

No notice was made due to misunderstanding of the BGT notice requirements at that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
   All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	7.6
TPH	US EPA Method SW-846 418.1	100	6,200
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX and chloride levels were below the stated limits. TPH was 6,200 ppm by Method 418.1 and was 4,600 ppm by Method 8015B. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
   Sampling results indicate a release occurred. The release was addressed through the spill and release guidelines.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

# The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

.

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Fran	ncis Dr., Santa	Fe, NM 87505		Sec. Sec.		e, NM 875						
			Dale		and of solid sectors	CONTRACTOR OF THE OWNER OWNE	orrective A	etion				
			Refe	ease noting	catio			ction		1 Derest		Einel Demen
Name of Co	ompany: BD	)				OPERA' Contact: Jef			🖂 Initia	al Report		Final Report
Name of Company: BP Address: 200 Energy Court, Farmington, NM 87401							No.: 505-326-94	170				
Facility Nat			ngton, N	WI 07401		1	e: Natural gas v					
							e. Matural gas v	WOII	1			
Surface Ow	vner: Federa	1		Mineral C	)wner:	Federal			API No	. 3004526	960	
				LOCA	ATIO	N OF RE	LEASE					
Unit Letter B	Section 27	Township 29N	Range 8W	Feet from the 1,125	North North	/South Line	Feet from the 1,828	East/V East	West Line	County: S	an Juar	1
		Lati	tude_3	6.70055		Longitud	e107.86158_					
				NAT	URE	OF REL	EASE					
	ease: oil/cond						Release: unknow			Recovered: 1		
Source of Re	elease: below	grade tank –	95 bbl			1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.	lour of Occurrenc	ce:			covery	: October 17,
Was Imma !!	ate Notice G	wan?				unknown	Whom?		2011; 3:4	8 PM		
was Immedi	late Notice G		Yes 🛛	No 🗌 Not R	equired	If YES, To	wnom?					
By Whom?						Date and H	Iour					
	course Reach	ned?					olume Impacting t	the Wate	ercourse.			
			Yes 🛛	No								
If a Waterco	urse was Imp	acted, Descri	be Fully.*	k								
Analysis resu Describe Are release occur backfilled an I hereby cert regulations a	ults are attach ea Affected ar rred. The rele ad compacted ify that the in all operators a	nd Cleanup A ase was addr and is still w formation gi re required to	Action Tak essed thro vithin the a ven above	ten.* BGT was re bugh the spill and active well area. this true and comp ad/or file certain r	moved release	and the area u guidelines an he best of my lotifications a	00 ppm by Metho nderneath the BG d a final C-141 wi knowledge and u nd perform correc arked as "Final R	T was s ill be su inderstar	ampled. Sa bmitted. Th nd that purs	ampling rest he area unde suant to NM eases which	ults ind er the B OCD re may er	icate a BGT was ules and ndanger
should their or the enviro	operations ha	we failed to a	dequately CD accep	investigate and r	emediat	e contaminati	on that pose a three the operator of the operator ope	reat to gr	ound water ibility for co	, surface wa ompliance v	iter, hu vith any	man health
Signature: Jeff Peace						OIL CON	SERV	ATION	DIVISIC	DN		
Printed Name: Jeff Peace						Approved by	Environmental S	pecialis	t:			
Title: Field E	Environmenta	al Coordinato	r			Approval Da	te:	]	Expiration Date:			
E-mail Addr	ess: peace.jef	ffrey@bp.com	n			Conditions of Approval: Attached						
Date: June 1	6, 2015		Phone: 50	5-326-9479								
	the second second											

\* Attach Additional Sheets If Necessary

·							
CLIENTE BP		API #: 3004526960					
CLIENT:	P.O. BOX 87, BLOOMFIELD, NM 87	7413					
	(505) 632-1199		(if applicble): A				
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:		PAGE #:1 of1				
SITE INFORMATION	SITE NAME: HUGHES C # 2R		DATE STARTED: 10/17/11				
QUAD/UNIT: B SEC: 27 TWP:	29N RNG: 8W PM: NM CNTY: SJ ST	т: <b>NM</b>	DATE FINISHED:				
	<b>18'10' NW/NE</b> LEASE TYPE: FEDERAL/ STATE / FEE PROD. FORMATION: MV CONTRACTOR: ELKHORN	/ INDIAN	ENVIRONMENTAL SPECIALIST(S): JCB				
REFERENCE POINT	_	V 407 CC4					
	WELL HEAD (W.H.) GPS COORD.: 36.70080 GPS COORD.: 36.70055 X 107.66158		ARING FROM W.H.: 147', S50W				
	GPS COORD.:						
	GPS COORD.:		ARING FROM W.H.:				
	GPS COORD.:		ARING FROM W.H.:				
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL		OVM READING				
	: @ 6' SAMPLE DATE: 10/17/11 SAMPLE TIME: 1548 LAB AN	ALVER 418 1/8	(ppm)				
	SAMPLE DATE:		. ,				
	SAMPLE DATE:						
	SAMPLE DATE:						
SOIL COLOR: DARK YELL	SOIL TYPE: SAND / SILTY SAND / SILT / SILTY CLAY / CLAY /	GRAVEL	HERI BEDROCK (sandstone)				
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTL		SLIGHTLY PLASTIC / C	OHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC				
CONSISTENCY (NON COHESIVE SOILS):			/ FIRM / STIFF / VERY STIFF / HARD				
MOISTURE: DRY SLIGHTLY MOIST / W SAMPLE TYPE: GRAB (COMPOSITE # OF PTS.	THE OD OT DETECTED.	ES NO EXPL	ANATION - MINOR				
	YES NO EXPLANATION - GRAY STAIN ON TOP OF SANDSTON	E @ TANK A					
		0					
ANY AREAS DISPLAYING WETNESS: YES / NO ADDITIONAL COMMENTS:	EXPLANATION -						
ADDITIONAL COMMENTS.							
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: _>100'_ N			IMATION (Cubic Yards) : <u>NA</u> D TPH CLOSURE STD: <u>5,000</u> ppm				
SITE SKETCH	PLOT PLAN circle: a	attached 0VM	CALIB. READ. = PPM RF = 0.52				
PROD.	•	A OVM	CALIB. GAS =ppm				
	Well HEAD	N TIME:	am/pm DATE:				
	FENCE		MISCELL. NOTES				
95-B BGT			NO - N1420426				
	BERM		PK - ZSCHWLLBGT				
	$\sim$	_					
	FENCE						
	5-A) BGTL		ermit Date: 06/14/10				
T.E	3.~6' X	Tan	CD Appr. Date: 08/09/11				
	BERM		BGT Sidewalls Visible: Y /(N)/ NA				
	ATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~ = APPRO	S.P.D.	BGT Sidewalls Visible: Y / N / NA				
T.B. = TANK BOTTOM; PBGTL = PREVIOUS	BELOW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAIN	ING WALL;	agnetic declination: <b>10</b> ° E				
TDAVEL NOTEO	; SW- SINGLE WALL; DW- DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTO ONSITE: 10/17/11	JM.					
TRAVEL NOTES: CALLOUT:	ONSITE: 10/1/11						

.

Date: 31-Oct-11

#### Analytical Report

### Hall Environmental Analysis Laboratory, Inc.

CLIENT:	Blagg Engineering			Clier	t Sample ID:	95 BGT-A	5-Point@6'
Lab Order:	1110A26			Co	llection Date:	10/17/2011	3:48:00 PM
Project:	Hughes C 2R			D	ate Received:	10/20/2011	
Lab ID:	1110A26-01				Matrix:	SOIL	
Analyses		Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD 8	015B: DIESEL RANGE	ORGANICS					Analyst: JB
Diesel Range O	rganics (DRO)	4000	100		mg/Kg	10	10/25/2011 1:02:29 PM
Surr: DNOP		0	73.4-123	S	%REC	10	10/25/2011 1:02:29 PM
EPA METHOD 8	015B: GASOLINE RANG	GE					Analyst: RAA
Gasoline Range	Organics (GRO)	600	24		mg/Kg	5	10/24/2011 1:51:17 PM
Surr: BFB		560	75.2-136	S	%REC	5	10/24/2011 1:51:17 PM
EPA METHOD 8	021B: VOLATILES						Analyst: RAA
Benzene		ND	0.24		mg/Kg	5	10/24/2011 1:51:17 PM
Toluene		ND	0.24		mg/Kg	5	10/24/2011 1:51:17 PM
Ethylbenzene		ND	0.24		mg/Kg	5	10/24/2011 1:51:17 PM
Xylenes, Total		7.6	0.47		mg/Kg	5	10/24/2011 1:51:17 PM
Surr: 4-Bromo	fluorobenzene	107	80-120		%REC	5	10/24/2011 1:51:17 PM
EPA METHOD 3	00.0: ANIONS						Analyst: SRM
Chloride		ND	7.5		mg/Kg	5	10/27/2011 11:03:51 AM
EPA METHOD 4	18.1: TPH						Analyst: JB
Petroleum Hydro	carbons, TR	6200	200		mg/Kg	10	10/26/2011

Qualifiers:

\* Value exceeds Maximum Contaminant Level

E Estimated value

J Analyte detected below quantitation limits

NC Non-Chlorinated

PQL Practical Quantitation Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded

MCL Maximum Contaminant Level

- ND Not Detected at the Reporting Limit
- S Spike recovery outside accepted recovery limits

## **QA/QC SUMMARY REPORT**

Client:Blagg EngProject:Hughes C	•								Worł	c Order:	1110A26
Analyte	Result	Units	PQL	SPK V	a SPK ref	%Rec L	owLimit Hi	ghLimit	%RPD	RPDLim	it Qual
Method: EPA Method 300.0:	Anions								-		
Sample ID: MB-29065		MBLK				Batch ID:	29065	Analysi	s Date:	10/27/2011	10:29:00 AM
Chloride	ND	mg/Kg	1.5								
Sample ID: LCS-29065		LCS				Batch ID:	29065	Analysis	s Date:	10/27/2011	10:46:25 AM
Chloride	14.31	mg/Kg	1.5	15	0	95.4	90	110			
Method: EPA Method 418.1:	ТРН	1									
Sample ID: MB-29058		MBLK				Batch ID:	29058	Analysis	s Date:		10/26/2011
Petroleum Hydrocarbons, TR	ND	mg/Kg	20								
Sample ID: LCS-29058		LCS				Batch ID:	29058	Analysis	s Date:		10/26/2011
Petroleum Hydrocarbons, TR	103.6	mg/Kg	20	100	0	104	87.8	115			
Sample ID: LCSD-29058		LCSD				Batch ID:	29058	Analysis	s Date:		10/26/2011
Petroleum Hydrocarbons, TR	108.8	mg/Kg	20	100	0	109	87.8	115	4.90	8.04	
Method: EPA Method 8015B:	Diesel Range	Organics									
Sample ID: MB-29027	Dieser Mange	MBLK				Batch ID:	29027	Analysis	a Date:	10/24/201	1 9:23:33 AM
Diesel Range Organics (DRO)	ND	mg/Kg	10								
Sample ID: LCS-29027		LCS	, 0			Batch ID:	29027	Analysis	a Date:	10/24/201	1 9:57:57 AM
Diesel Range Organics (DRO)	42.78	mg/Kg	10	50	0	85.6	66.7	119			
	Canalina Day										······································
Method: EPA Method 8015B: Sample ID: MB-29020	Gasonne Rar	MBLK				Batch ID:	29020	Analysia	Date:	10/24/2011	12:53:38 PM
	ND		5.0			Daton 1D.	25020	/ mary sie	Date.		12.00.00110
Gasoline Range Organics (GRO) Sample ID: LCS-29020	ND	mg/Kg LCS	5.0			Batch ID:	29020	Analysis	Date	10/24/2011	11:27:03 AM
Gasoline Range Organics (GRO)	28.79	mg/Kg	5.0	25	0	115	86.4	132	Duto.	10/2 1/2011	11121.00711
		mg/rtg	0.0			110	00.4	102			
Method: EPA Method 8021B:	Volatiles					Datab ID	-	A I (	Data	10/04/0044	10.50.00 DM
Sample ID: MB-29020		MBLK				Batch ID:	29020	Analysis	Date:	10/24/2011	12:53:38 PM
Benzene	ND	mg/Kg	0.050								
Toluene	ND	mg/Kg	0.050								
Ethylbenzene Xulenen Totel	ND	mg/Kg	0.050								
Xylenes, Total Sample ID: LCS-29020	ND	mg/Kg LCS	0.10			Batch ID:	29020	Analysis	Date:	10/24/2011	12:24:44 PM
Benzene	0.9362		0.050	к	0.0147	92.2	83.3	107	Dato.	I U/L TILU	1 B. AT. TT ( ) YI
Benzene Toluene	0.9362	mg/Kg	0.050		0.0147	92.2 91.2	74.3	107			
Ethylbenzene	0.9245	mg/Kg mg/Kg	0.050		0.0129	91.2	74.3 80.9	122			
Xylenes, Total	2.760	mg/Kg	0.000		0.0140	90.5	85.2	123			
Ayrones, rotar	2.700	ing/itg	0.10	5	0,0440	00.0	00.L	120			

Qualifiers:

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

- H Holding times for preparation or analysis exceeded
- NC Non-Chlorinated
- R RPD outside accepted recovery limits

### Hall Environmental Analysis Laboratory, Inc.

	Sample	Rec	eipt Ch	necklist			
Client Name BLAGG				Date Received	1:		10/20/2011
Work Order Number 1110A26				Received by:	MMG		
Checklist completed by:		10	Date	Sample ID Ia	bels checked	by:	TO
Matrix:	) Carrier name:	Cour	rier				
Shipping container/cooler in good condition?		Yes	$\checkmark$	No 🗌	Not Present		
Custody seals intact on shipping container/coo	ler?	Yes	$\checkmark$	No 🗌	Not Present		Not Shipped
Custody seals intact on sample bottles?		Yes		No	N/A	$\checkmark$	
Chain of custody present?		Yes	$\checkmark$	No 🗌			
Chain of custody signed when relinquished and	received?	Yes	$\checkmark$	No			
Chain of custody agrees with sample labels?		Yes	$\checkmark$	No 🗌			
Samples in proper container/bottle?		Yes	$\checkmark$	No 🗌			
Sample containers intact?		Yes	$\checkmark$	No 🗌			
Sufficient sample volume for indicated test?		Yes	$\checkmark$	No 🗌			
All samples received within holding time?		Yes	$\checkmark$	No 🗌			Number of preserved
Water - VOA vials have zero headspace?	No VOA vials subm	nitted	$\checkmark$	Yes	No 🗌		bottles checked for pH:
Water - Preservation labels on bottle and cap n	natch?	Yes		No 🗌	N/A		
Water - pH acceptable upon receipt?		Yes		No	N/A		<2 >12 unless noted below.
Container/Temp Blank temperature?		1.0	0°	<6° C Acceptable			Delow.
COMMENTS:				If given sufficient	time to cool.		
Client contacted	Date contacted:			Perso	n contacted	· · · · · · · · · · · · · · · · · · ·	
Contacted by:	Regarding:						
Comments:							
		_					
3		9. 365 PR / 3					
				6/2. L			
Corrective Action							
				417 Mar an			

С	hain-	of-Cu	stody Record	Turn-Around Time:							н			E	v	TR	20	NR	4F	NT	14	
Client: BLAGG ENGINEERING INC				i≷ Standard □ Rush				ANALYSIS LABORATORY														
BP AMERICA				Project Name:				www.hallenvironmental.com														
Mailing Address: P.O. Box 87				HUGHES C 2R				4901 Hawkins NE - Albuquerque, NM 87109														
BLOOMFIED, NM 87413				Project #:							5-34							4107				
Phone #: 505-632-1199				-					10								uest					
email or Fax#:				Project Manager:				_	(yl	sel)					04)							
QA/QC Package: X Standard □ Level 4 (Full Validation)				J. BLAGG				s (8021)	TPH (Gas only)	(Gas/Diesel)					PO4,SC	PCB's						
Accreditation				Sampler: J_BLALL On Ice. Strate Kes Scientification Strategy				+ TMB's	+ TPH	5B	418.1)	504.1)	(HAH)		03,NO2	s / 8082		(A)				or N)
EDD (Type)				Sample Temperature: ///					BE	d 8(	od 4	g po	orF	etals	CI'N	cide	A)	N-I	ليا			Z
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL	State In the second second	BTEX + WITBE + 3	BTEX + MTBE	TPH Method 801	TPH (Method	EDB (Method	8310 (PNA or	RCRA 8 Metals	Anions (F,Cl,NO <sub>3</sub> ,NO <sub>2</sub> ,PO <sub>4</sub> ,SO <sub>4</sub> )	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			Air Bubbles (Y or N)
10/17/11	1548	SUIL	95B&T-A C-6'	40z×1	COOL		- }	X		X	X								X			
[																						
							-											-				
Data	Time	Polinquich	od by:	Received by:		Date 10/19/2011	Time								~							
Date: Time: Relinquished by: 10/19/2011 1242 Juff Blagg			Monte	Remarks: GRO + DRO ON BOISB WORKDROER: N 1420426 PATKET: ZPEACJDEND																		
Date: Time: Relinquished by:				Received by: Date Time					NTA													
	f necessary,	samples sub	mitted to Hall Environmental may be sub	contracted to other a	ccredited laboratorio	es. This serves a	as notice of this	s possi	bility.	Any si	ub-con	tracte	d data	will b	e clear	rly not	ated o	n the a	inalytic	al repo	irt.	



