<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.								
	Pit, Below-Grade Tank, or									
13003 Proposed Alterr	native Method Permit or Closure P	Plan Application								
	rade tank registration	OIL CONS. DIV DIST. 3								
45-27812 Image: Delow grade tank registration Image: Delow grade tank registregistration <										
or proposed alternative metho		non-permitted pit, below-grade tank,								
Instructions: Please submit one	application (Form C-144) per individual pit, below-	grade tank or alternative request								
Please be advised that approval of this request does not r environment. Nor does approval relieve the operator of i										
	OGRID #:7	778								
	NM 87401									
	OCD Permit Number:									
	Township31N Range11W Co									
	733Longitude108.016672									
Surface Owner: \boxtimes Federal \square State \square Private \square		NAD. [1927] 1965								
□ <u>Pit</u> : Subsection F, G or J of 19.15.17.11 NMA	C									
Temporary: Drilling Workover										
Permanent Emergency Cavitation P&	A 🗌 Multi-Well Fluid Management Le	ow Chloride Drilling Fluid 🗌 yes 🗌 no								
Lined Unlined Liner type: Thickness	mil LLDPE HDPE PVC Ot	her								
String-Reinforced										
Liner Seams: Welded Factory Other	Volume:bbl	Dimensions: Lx Wx D								
3.										
Below-grade tank: Subsection I of 19.15.17.1	1 NMAC Tank B									
Volume:95.0bbl Type of	of fluid:Produced water									
Tank Construction material:Steel										
$\hfill\square$ Secondary containment with leak detection $\hfill\square$	Visible sidewalls, liner, 6-inch lift and automatic ov	verflow shut-off								
\Box Visible sidewalls and liner \boxtimes Visible sidewal	ls only 🗌 Other _Single walled/double botto	omed								
Liner type: Thicknessmil	HDPE PVC Other									
4.										

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify_

6

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	□ Yes □ No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
10. <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached.	cuments are
 Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	NMAC
 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. 	15.17.9 NMAC
and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
^{11.} <u>Multi-Well Fluid Management Pit Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the down the back that the back that the back that the down the back that that the back that that the back that that that that the back that that that that that that that tha</i>	cuments are
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
 A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC 	.15.17.9 NMAC
 Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

٠

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the o	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC	
 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Associated upon the appropriate requirements of 19.15.17.11 NMAC 	
 Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC 	
 Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan 	
 Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan 	
 Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	
13.	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl	uid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems)	
In-place Burial On-site Trench Burial Alternative Closure Method	
 <i>closure plan. Please indicate, by a check mark in the box, that the documents are attached.</i> Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
is. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Pl 19.15.17.10 NMAC for guidance.	ce material are lease refer to
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa ake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No

- Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No									
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No									
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No									
Within a 100-year floodplain. - FEMA map	Yes No									
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 										
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.									
Name (Print): Title:										
Signature: Date:										
e-mail address:										
18. <u>OCD Approval</u> : Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	-1									
	5/15									
OCD Approval: Permit Application (including closure plan) X Closure Plan (only) OCD Conditions (see attachment)	5/15									
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:										
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:										
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	complete this									

Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): Jeff Peace

Title: Field Environmental Coordinator

Signature:

.

22.

.

ff Peace

Date: June 2, 2015

e-mail address: __peace.jeffrey@bp.com_

______ Telephone: ___(505) 326-9479_

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Case A 18 – Tank B (95 bbl)</u> <u>API No. 3004527812</u> <u>Unit Letter N, Section 5, T31N, R11W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

No notice was made due to misunderstanding of the BGT notice requirements at that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)

- c. Basin Disposal, Permit NM-01-0005 (Liquids)
- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids) All liquids and sludge in the BGT were removed and sent to one of the

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

BP BGT Closure Plan 04-01-2010

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

•

.

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

1000 Rio Brazos Road Aztec NM 8/410	220 South	nservation Division outh St. Francis Dr. ta Fe, NM 87505							
Release No	the state of the second se	Contractory of the local division of the loc	A REAL PROPERTY AND A REAL	ction					
		OPERAT	FOR	🗌 In	itial Report	\boxtimes	Final Repor		
Name of Company: BP		Contact: Jef	f Peace						
Address: 200 Energy Court, Farmington, NM 87401		Telephone N	No.: 505-326-94	79					
Facility Name: Case A 18		Facility Typ	e: Natural gas w	vell					
Surface Owner: Federal Mine	eral Owner:	Federal		API	No. 3004527	812			
L	OCATIO	N OF REI	EASE						
Unit LetterSectionTownshipRangeFeet fromN531N11W1,270		/South Line	Feet from the 1,625	East/West Lin West	e County: S	an Juan	1		
Latitude 36.923733		Longitude	e_108.016672						
	NATURE	OF RELI	EASE						
Type of Release: none			Release: N/A	Volum	e Recovered: 1	V/A			
Source of Release: below grade tank – 95 bbl, Tank B			our of Occurrenc		nd Hour of Dis		:		
Was Immediate Notice Given?	Not Required	If YES, To	Whom?						
By Whom?		Date and H							
Was a Watercourse Reached?		If YES, Vo	lume Impacting t	he Watercourse					
Describe Cause of Problem and Remedial Action Taken.* S the BGT. Soil analysis resulted in TPH, BTEX and chloride					al to ensure no	soil in	pacts from		
Describe Area Affected and Cleanup Action Taken.* BGT we backfilled and compacted and is still within the active well a	area.								
I hereby certify that the information given above is true and regulations all operators are required to report and/or file cer public health or the environment. The acceptance of a C-14 should their operations have failed to adequately investigate or the environment. In addition, NMOCD acceptance of a C federal, state, or local laws and/or regulations.	rtain release n 1 report by th and remediat	otifications ar e NMOCD ma e contaminati	nd perform correct arked as "Final Ro on that pose a thre	tive actions for eport" does not eat to ground wa	eleases which elieve the ope ter, surface wa	may er rator of ater, hu	ndanger f liability man health		
0.000			OIL CONS	SERVATIO	N DIVISIO)N			
Signature: off Veree									
Printed Name: Jeff Peace		Approved by	Environmental Sp	pecialist:					
Title: Field Environmental Coordinator		Approval Dat	e:	Expiratio	on Date:				
E-mail Address: peace.jeffrey@bp.com		Conditions of	Approval:	Attached					
Date: June 2, 2015 Phone: 505-326-9479									
* Attach Additional Sheets If Necessary									

CLIENTE BP		API# 3004527812								
CLIENT:	13									
	(505) (circle one): BGT CONFIRMATION / REL	632-1199		(if applicble):	¥В					
FIELD REPORT:		PAGE #: 1	of							
SITE INFORMATION	I: SITE NAME: CASE A #	±18		DATE STARTED: 09	/20/11					
QUAD/UNIT: N SEC: 5 TWP:	31N RNG: 11W PM: N	M CNTY: SJ ST:	NM	DATE FINISHED:						
1/4 -1/4/FOOTAGE: 1,270'S / 1,62		FEDERAL / STATE / FEE / IN	NDIAN	ENVIRONMENTAL	1.0.7					
LEASE #: SF078095 PROD. FORMATION: FT CONTRACTOR: MBF - C. MCINNES SPECIALIST(S): NJV										
REFERENCE POINT: well head (w.h.) GPS COORD.: 36.92359 X 108.01639 GL ELEV.: 6,197' 1) -95-BCT (SW/DB) - A GPS COORD.: 36.923346 X 108.016384 DISTANCE/BEARING FROM WH.: 87', S4W'										
1)		722 V 400 046672		105						
					, N58W					
3)	GPS COORD.:									
			DISTANCE/BEA		OVM					
SAMPLING DATA:			440.4/0		READING (ppm)					
 SAMPLE ID: <u>5PC - TB @ 5' (9</u> SAMPLE ID: 5PC - TB @ 5' (9) 		SAMPLE TIME: 1630 LAB ANALYSI SAMPLE TIME: 1620 LAB ANALYSI		015B/8021/B/300.0 (C 015B/8021/B/300.0 (C						
				0150/0021/0/500.0 (0	CI) NA					
 3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:LAB ANALYSI SAMPLE TIME: LAB ANALYSI								
,										
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAN	ID SILT / SILTY CLAY / CLAY / GF	RAVEL / OTH	HER						
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY		PLASTICITY (CLAYS): NON PLASTIC / SLIG	-TTLY PLASTIC / C	COHESIME / MEDILIM PLASTIC / HIGHL)	PLASTIC					
CONSISTENCY (NON COHESIVE SOILS): LC		DENSITY (COHESIVE CLAYS & S								
MOISTURE: DRY SLIGHTLY MOIST MOIST WE		HC ODOR DETECTED: YES	NO EXPLA	ANATION -						
SAMPLE TYPE: GRAB COMPOSITE # OF PTS.										
DISCOLORATION/STAINING OBSERVED:	YES NO EXPLANATION -									
ANY AREAS DISPLAYING WETNESS: YES NO	EXPLANATION -									
ADDITIONAL COMMENTS: NO APPARE		RVED FROM EITHER BGT.								
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA ft.	X NA ft. EXCAV	ATION EST	IMATION (Cubic Yards) :	NA					
DEPTH TO GROUNDWATER: >100' N	EAREST WATER SOURCE: >1,000' NE	AREST SURFACE WATER: <20	0' NMOCI	D TPH CLOSURE STD: 10	0 ppm					
SITE SKETCH		PLOT PLAN circle: attac	ched OVM (Calib. Read. = NA	opm PE - 0.52					
	FENCE				$\frac{\text{RF} = 0.52}{\text{ppm}}$					
				NA am/pm DATE:	NA					
(95-B)				MISCELL. NO	TES					
PBGTL T.B. ~ 5'	BERM				ILO					
B.G.	WELL			NO - N1435257						
	\oplus			PO - 55397 PK - ZANDECALSL						
				N-ZANDLOALSL						
			_							
			P	ermit Date: 06	/08/10					
				CD Appr. Date: 03	/01/12					
			Tanl	~						
		X - S.	P.D.	RGT Sidewalle Visible:						
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAV		BELOW; T.H. = TEST HOLE; ~ = APPROX.;	B	BGT Sidewalls Visible:(Y)						
	BELOW-GRADE TANK LOCATION; SPD = SAMPLE <u>SW - SINGLE WALL; DW - DOUBLE WALL; SB - SI</u>		WALL; M	agnetic declination: 1	0 E					
TRAVEL NOTES: CALLOUT:		ONSITE: 09/20/11 - Af	ter.							

.

Hall Environmental Analysis Laboratory, Inc.

Date: 04-Oct-11 Analytical Report

CLIENT:	Blagg Engineering			Clier	nt Sample ID:	5PC-TB (@5' (95 BGT-B)
Lab Order:	1109910			Co	llection Date:	9/20/2011	4:20:00 PM
Project:	Case A #18			D	ate Received:	9/23/2011	
Lab ID:	1109910-02				Matrix:	SOIL	
Analyses		Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD	8015B: DIESEL RANGE	ORGANICS					Analyst: JB
Diesel Range O	rganics (DRO)	ND	10		mg/Kg	1	9/28/2011 12:12:37 PM
Surr: DNOP		135	73.4-123	S	%REC	1	9/28/2011 12:12:37 PM
EPA METHOD	8015B: GASOLINE RANG	GE					Analyst: RAA
Gasoline Range	e Organics (GRO)	ND	4.7		mg/Kg	1	9/30/2011 3:36:29 AM
Surr: BFB		93.7	75.2-136		%REC	1	9/30/2011 3:36:29 AM
EPA METHOD	8021B: VOLATILES						Analyst: RAA
Benzene		ND	0.047		mg/Kg	1	9/30/2011 3:36:29 AM
Toluene		ND	0.047		mg/Kg	1	9/30/2011 3:36:29 AM
Ethylbenzene		ND	0.047		mg/Kg	1	9/30/2011 3:36:29 AM
Xylenes, Total		ND	0.095		mg/Kg	1	9/30/2011 3:36:29 AM
Surr: 4-Brom	ofluorobenzene	102	80-120		%REC	1	9/30/2011 3:36:29 AM
EPA METHOD	300.0: ANIONS						Analyst: SRM
Chloride		ND	1.5		mg/Kg	1	9/29/2011 6:27:45 PM
EPA METHOD	418.1: TPH						Analyst: JB
Petroleum Hydro	ocarbons, TR	ND	19		mg/Kg	1	9/29/2011

Qualifiers:

* Value exceeds Maximum Contaminant Level

E Estimated value

J Analyte detected below quantitation limits

NC Non-Chlorinated

PQL Practical Quantitation Limit

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

MCL Maximum Contaminant Level

ND Not Detected at the Reporting Limit

S Spike recovery outside accepted recovery limits

QA/QC SUMMARY REPORT

Client:	Blagg Engine	eering										
Project:	Case A #18									Work	Order:	1109910
Analyte		Result	Units	PQL	SPK V	a SPK ref	%Rec L	owLimit Hi	ghLimit	%RPD	RPDLimit	Qual
	thod 300.0: An	ions										
Sample ID: MB-28	618		MBLK				Batch ID:	28618	Analysi	s Date:	9/29/2011	1:14:20 PN
Chloride		ND	mg/Kg	1.5								
Sample ID: LCS-2	8618		LCS				Batch ID:	28618	Analysi	s Date:	9/29/2011	1:31:45 PN
Chloride		13.91	mg/Kg	1.5	15	0	92.7	90	110			
Method: EPA Me	thod 418.1: TP	н										
Sample ID: MB-28	601		MBLK				Batch ID:	28601	Analysi	s Date:		9/29/2011
Petroleum Hydrocart	bons, TR	ND	mg/Kg	20								
Sample ID: LCS-28	3601		LCS				Batch ID:	28601	Analysi	s Date:		9/29/2011
Petroleum Hydrocart	oons, TR	100.5	mg/Kg	20	100	0	101	87.8	115			
Sample ID: LCSD-			LCSD				Batch ID:	28601	Analysi	s Date:		9/29/2011
Petroleum Hydrocart	oons, TR	103.2	mg/Kg	20	100	0	103	87.8	115	2.61	8.04	
Method: EPA Me Sample ID: MB-28	thod 8015B: Di 603	esel Range	Organics MBLK				Batch ID:	28603	Analysi	s Date:	9/28/2011	9:54:16 AM
Diesel Range Organi	ics (DRO)	ND	mg/Kg	10								
Sample ID: LCS-28	3603		LCS				Batch ID:	28603	Analysis	s Date:	9/28/2011 1	0:28:40 AM
Diesel Range Organi	ics (DRO)	55.22	mg/Kg	10	50	4.175	102	66.7	119			
Method: EPA Met	thod 8015B: Ga	asoline Ran	ge									
Sample ID: 110991	0-01AMSD		MSD				Batch ID:	28595	Analysis	s Date:	9/30/2011 1	1:21:12 PM
Gasoline Range Orga	anics (GRO)	26.71	mg/Kg	4.7	23.26	0	115	72.4	149	3.20	19.2	
Sample ID: MB-28			MBLK				Batch ID:	28595	Analysis	s Date:	9/29/2011 1	1:45:48 PM
Gasoline Range Orga	anics (GRO)	ND	mg/Kg	5.0								
Sample ID: LCS-28	1595		LCS				Batch ID:	28595	Analysis	s Date:	9/29/2011 1	0:48:10 PM
Gasoline Range Orga	anics (GRO)	28.48	mg/Kg	5.0	25	0	114	86.4	132			
Sample ID: 110991	and the second second		MS				Batch ID:	28595	Analysis	s Date:	9/30/2011 1	0:52:22 PM
Gasoline Range Orga	anics (GRO)	25.87	mg/Kg	4.8	23.76	0	109	72.4	149			
Method: EPA Met	thod 8021B: Vo	latiles							100			
Sample ID: MB-285		nacios	MBLK				Batch ID:	28595	Analysis	a Date:	9/29/2011 1	1:45:48 PM
Benzene		ND	mg/Kg	0.050								
Toluene		ND	mg/Kg	0.050								
Ethylbenzene		ND	mg/Kg	0.050								
Xylenes, Total		ND	mg/Kg	0.10								
Sample ID: LCS-28	595		LCS				Batch ID:	28595	Analysis	a Date:	9/29/2011 1	1:16:59 PM
Benzene		1.019	mg/Kg	0.050	1	0.0141	100	83.3	107			
Toluene		1.002	mg/Kg	0.050		0.0129	98.9	74.3	115			
Ethylbenzene		1.023	mg/Kg	0.050		0.0136	101	80.9	122			

Qualifiers:

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

R RPD outside accepted recovery limits

Page 1

Hall Environmental Analysis Laboratory, Inc.

2

	Sample	Receipt	Checklist		
Client Name BLAGG			Date Receive	d:	9/23/2011
Work Order Number 1109910			Received by	DAM	
Checklist completed by:)	1	Sample ID la Date 9/26/11	abels checked by:	Initials WMS
Matrix:	Carrier name:	<u>Greyhou</u>	nd		
Shipping container/cooler in good condition?		Yes 🗸	No	Not Present	
Custody seals intact on shipping container/cooler?		Yes 🗸	No	Not Present	Not Shipped
Custody seals intact on sample bottles?		Yes	No	N/A ✓	
Chain of custody present?		Yes 🗸	No		
Chain of custody signed when relinquished and red	ceived?	Yes 🗸	No		
Chain of custody agrees with sample labels?		Yes 🗸	No		
Samples in proper container/bottle?		Yes 🗸	No		
Sample containers intact?		Yes 🗸	No		
Sufficient sample volume for indicated test?		Yes 🗸	No		
All samples received within holding time?		Yes 🗸	No		Number of preserved
Water - VOA vials have zero headspace?	No VOA vials subm	nitted 🔽	Yes	No	bottles checked for pH:
Water - Preservation labels on bottle and cap mate	h?	Yes	No	N/A 🗸	
Water - pH acceptable upon receipt?		Yes	No	N/A 🗸	<2 >12 unless noted below.
Container/Temp Blank temperature?		3.3°	<6° C Acceptabl		DOIOW.
COMMENTS:			If given sufficient	time to cool.	~

Client contacted

Date contacted:

Regarding:

Person contacted

Contacted by:

Comments:

Corrective Action


Chain-of-Custody Record			Turn-Around Time:									E			20	NI.		NT	- 41			
Client:	BLAG	G ENGR.	/ BP AMERICA	Standard	Rush														ATC			
				Project Name:																		
Mailing /	Address:	P.O. BO	X 87	CASE A # 18					www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109													
			FIELD, NM 87413	Project #:						Tel. 505-345-3975 Fax 505-345-4107												
Phone #:	· · · · · · · · · · · · · · · · · · ·	(505) 63					12.11	Te	1. 50	5-54	+3-3	a data	1 1 1 1 1 1 1	100000	A STATE	jues	Contraction of the	/				
email or	and the second design of the s	(303) 03		Project Manag	er:				-												-	
QAVQC P	-		Level 4 (Full Validation)		NELSON VE	LEZ	TMB13 (8021B)	TPH (Gas only)	(Gas/Diesel)						PCB's						PLE	
Accredita				Sampler:	NELSON VE	LEZ 920	T	4 (G	3 (G	1)	1)			ance	8082						SAM	
	P	Other		On lice:	≫ Yes	🗆 No	I	+ TPI	0151	118.	504.	AH)		Bala	-		(A)	(0)			ITE	or N
	(Туре)	1		Sample Temp	rature: 3.3		#		od 8	7 pot	pol	orF	etals	nion	cide	A)	i-VO	(30(IPLE	POS	s (V
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX + MTDE	BTEX + MTBE	TPH Method 8015B	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Cation / Anion Balance	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE (300.0)		GRAB SAMPLE	5 PT. COMPOSITE SAMPLE	Air Bubbles (Y or N)
	1630	SOIL	5PO-TB @ 5' (95 BOT-A)	4 02 2	Cool	1109-110-1	V	-	V	¥					~			V	\square		V	-
							1			_												
9/20/11	1620	SOIL	5PC-TB @ 5' (95 BGT-B)	4 oz 2	Cool	-2	٧		٧	٧								٧		1	٧	
												-										
												İ										
							1															
											1		1				1					
							1	1				<u> </u>		-		1	1	1				
Date:	Time:	Relinquish	ed by:	Received by:		Date Time	Rer	nark	s:	TPI	H (8	015	B) -	GRO	2 &	DRO		NLY.	<u></u>			
9/22/11	1530	91	um of	Christ	Welter	9/22/11/530	Remarks: TPH (8015B) - GRO & DRO ONLY. BILL DIRECTLY TO BP: Jeff Peace, 200 Energy Court, Farmington, NM 87401															
Date:	Time:	Relinquish	ed by: A to black	Received by:		Date Time 9/23/11	E													SL	~	
123/11	1810	1/1	Usture Valent	Auro		12911	Work Order: <u>N1435257</u> Paykey: <u>ZANDECRLSL</u>															

C

•







State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office. For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

\mathbf{P}	t, Closed-L	oop System	, Below-G	rade Tank.	, or
Proposed	Alternative	Method Per	rmit or Clos	sure Plan	Application

Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit

Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system,

below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

Operator: BP AMERICA PRODUCTION COMPANY OGRID #:778				
Address: 200 Energy Court, Farmington, NM 87401				
Facility or well name: CASE A 018				
API Number: 3004527812 OCD Permit Number:				
U/L or Qtr/Qtr N Section 5.0 Township 31.0N Range 11W County: San Juan County				
Center of Proposed Design: Latitude 36.922346 Longitude -108.014135 NAD: 1927 × 1983				
Surface Owner: X Federal State Private Tribal Trust or Indian Allotment				
2 ☐ Pit [·] Subsection F or G of 19.15.17.11 NMAC				
Temporary: Drilling Workover				
Permanent Emergency Cavitation P&A				
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other				
String-Reinforced				
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D				
3 Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other Liner Seams: Welded Factory Other				
4 Image: Subsection 1 of 19.15.17.11 NMAC Tank ID: A Volume: 95.0 bbl Type of fluid: Produced Water Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Single WALLED DOUBLE BOTTOMED Liner type: mil HDPE PVC				
 <u>Alternative Method</u> Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 				

District I 1625 N French Dr , Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S St Francis Dr , Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office. For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or	
Proposed Alternative Method Permit or Closure Plan Application	

Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit

Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system,

below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

Operator BP AMERICA PRODUCTION COMPANY OGRID #:778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: CASE A 018
API Number: 3004527812 OCD Permit Number.
U/L or Qtr/Qtr N Section 5.0 Township 31.0N Range 11W County: San Juan County
Center of Proposed Design: Latitude 36.922738 37 33 Longitude -108.014428 01667 NAD: [1927 Ⅰ 1983
Surface Owner: 🗷 Federal 🗌 State 🗌 Private 🗋 Tribal Trust or Indian Allotment
2
Pit Subsection F or G of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A
Lined Unlined Liner type Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L,x W x D
3
Closed-loop System Subsection H of 19.15.17.11 NMAC
Type of Operation: 🗌 P&A 🗌 Drilling a new well 🗋 Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent)
Drying Pad 🔲 Above Ground Steel Tanks 🗌 Haul-off Bins 🗌 Other
Lined Unlined Liner type [.] Thickness mil LLDPE HDPE PVC Other
Liner Seams' Welded Factory Other
4
Elow-grade tank. Subsection I of 19.15.17.11 NMAC Tank ID. B
Volume: 95.0 bbl Type of fluid: Produced Water
Tank Construction material: Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
Usible sidewalls and liner X Visible sidewalls only Other Other
Liner type. Thickness mil HDPE PVC Other
5
Alternative Method
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval