District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

13002

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or	
Proposed Alternative Method Permit or Closure Plan A	pplication

Santa Fe, NM 87505

Type of action: Below grade tank registration	OIL CONS. DIV DIST. 3
Permit of a pit or proposed alternative method ☐ Closure of a pit, below-grade tank, or proposed alternative method	JUL 08 2015
☐ Modification to an existing permit/or registration☐ Closure plan only submitted for an existing permitted or non-perm	itted nit below-grade tank
or proposed alternative method	atted pit, below grade talk,
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank	or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental	of surface water, ground water or the authority's rules, regulations or ordinances.
Operator: RP America Production Company	
Operator: BP America Production Company OGRID #:778	
Address:200 Energy Court, Farmington, NM 87401	
Facility or well name:Case A 18	
API Number:3004527812 OCD Permit Number:	
U/L or Qtr/Qtr	_San Juan
Center of Proposed Design: Latitude36.923346 Longitude108.016384	NAD: □1927 ⊠ 1983
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment	
2.	
Pit: Subsection F, G or J of 19.15.17.11 NMAC	
Temporary: Drilling Workover	
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management ☐ Low Chloride	
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other	
String-Reinforced	
Liner Seams: Welded Factory Other Volume: bbl Dimensio	ns: L x W x D
3.	
■ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A	
Volume:95.0bbl Type of fluid:Produced water	
Tank Construction material:Steel	
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut	-off
☐ Visible sidewalls and liner ☒ Visible sidewalls only ☐ Other _Single walled/double bottomed	
Liner type: Thicknessmil	
4.	
Alternative Method:	
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau	- CC C

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church)	, hospital,					
Four foot height, four strands of barbed wire evenly spaced between one and four feet						
Alternate. Please specify						
6.						
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)						
Screen Netting Other						
Monthly inspections (If netting or screening is not physically feasible)						
Worlding inspections (if netting of screening is not physically feasible)						
7.						
Signs: Subsection C of 19.15.17.11 NMAC						
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers						
☐ Signed in compliance with 19.15.16.8 NMAC						
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.						
Please check a box if one or more of the following is requested, if not leave blank:						
 □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 						
Exception(s). Requests must be submitted to the Santa re Environmental Bureau office for consideration of approval.						
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source					
General siting						
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No					
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No					
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No					
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map						
Below Grade Tanks						
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)						
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are
attached. □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached.	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18. OCD Approval: ☐ Permit Application (including closure plan) ☑ Closure Plan (only) ☐ OCD Conditions (see attachment)	-/,-
OCD Representative Signature: Approval Date: Approval Date:	2//5
Title: KNUSTO Spee. OCD Permit Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
⊠ Closure Completion Date:10/4/2011_	
Closure Method: ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please into mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude36.923346	dicate, by a check 927 ⊠ 1983

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure in	
belief. I also certify that the closure complies with all applicable closure requiren	nents and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Name (Print):Jeff Peace	Date:June 2, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Case A 18 – Tank A (95 bbl)</u> <u>API No. 3004527812</u> Unit Letter N, Section 5, T31N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)

- c. Basin Disposal, Permit NM-01-0005 (Liquids)
- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	23
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011
Submit 1 Copy to appropriate District Office in

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ase Notific	cation	n and Co	orrective A	ction				
						OPERA'	ΓOR		Initia	al Report		Report
Name of Co	I					Contact: Jef	f Peace			1		1
			ngton, NI	M 87401		Telephone 1	No.: 505-326-94	179				
						Facility Typ	e: Natural gas v	well				
Surface Ow	ner: Feder	al		Mineral ()wner:	Federal			API No	. 3004527812	2	
				LOCA	ATIO	N OF RE	LEASE		,			
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	East/W	Vest Line	County: San	Juan	
	200 000-000-000				South		1,625	West				
		Latit	ude 36.	923346		Longitud	e 108.016384					
		Latit	uuc50.									
Tyma of Dala	0001 0000			NAI	UKE	OF REL			M-1 D) 1 - NT//	A	
Type of Rele		v grade tank –	05 bbl. Te	nk A			Release: N/A Iour of Occurrence	20:		Recovered: N/A Hour of Disco		
Was Immedia			95 001, 17	шкл		If YES, To			Date and	Hour of Disco	very.	
Yes No Not Required						11 120, 10	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
By Whom?						Date and F	lour					
Was a Water	course Read	ched?					lume Impacting t	the Wate	rcourse.			
			Yes 🛚	No			,					
If a Watercou	irse was Im	pacted, Descri	be Fully.*									
D !! C	20 11	1.0										
							the BGT was do		g removal t	o ensure no so	il impacts fi	rom
the BG1. So.	ii alialysis i	esuited iii 111	I, DIEA a	ind cinoride belo	w Stanua	arus. Amarys	is results are attac	iled.				
					moved a	and the area u	nderneath the BG	T was sa	ampled. Th	ne area under t	he BGT was	S
backfilled and	a compacte	a and is still w	itnin the a	ctive well area.								
							knowledge and u					
							nd perform correct arked as "Final R					
							on that pose a thr					
							e the operator of					
		vs and/or regu										
0	0.0	0					OIL CON	SERV	ATION	DIVISION	1	
Signature:	all h	0002										
Signature.	100					Annroyad by	Environmental S	nagialist				
Printed Name	: Jeff Peace					Approved by	Environmental S	pecialist.	•			
T'41 P' 11 P		-1.01				A				2-4		
Title: Field E	nvironment	al Coordinator	ā			Approval Dat	e:	E	Expiration I	Jate:		
E-mail Addre	ess: peace.ie	ffrey@bp.com	1			Conditions of	Approval:				_	
li .							. 1			Attached	_	
Date: June 2,	, 2015	P	hone: 505-	-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		ENGINEERING, INC BLOOMFIELD, NM		API #: 300452	27812
	· ·	05) 632-1199		TANK ID (if applicble):	& B
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTH	ER:	PAGE #: 1	of
SITE INFORMATION	I: SITE NAME: CASE	A #18		DATE STARTED: 09	9/20/11
QUAD/UNIT: N SEC: 5 TWP:	31N RNG: 11W PM	M: NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,270'S / 1,62 LEASE #: SF078095		ETYPE: FEDERAL STATE / FE ELKHORN CONTRACTOR: MBF - C. McII		ENVIRONMENTAL SPECIALIST(S):	NJV
REFERENCE POINT	: WELL HEAD (W.H.) GF	PS COORD.: 36.923	59 X 108.016	39 GL ELEV.:	6,197'
95 BGT (SW/DB) - A		6.923346 X 108.016384	DISTANCE/BE/		7', S4W
2) - 95 BGT (SW/DB) - B		6.923733 X 108.016672			5', N58W
3)	GPS COORD.:			ARING FROM W.H.:	
CAMPLING DATA:	GPS COORD.:	AODIADUSED.	DISTANCE/BEA	ARING FROM W.H.:	OVM
SAMPLING DATA: 1) SAMPLE ID: 5PC - TB @ 5' (9	CHAIN OF CUSTODY RECORD(S) # 5-A) SAMPLE DATE: 09/20/			015B/8021/B/300.0 (READING (ppm)
2) SAMPLE ID: 5PC - TB @ 5' (9		4620		015B/8021/B/300.0 (CI) NA
3) SAMPLE ID:	0.411 22 0.112	O'III EE IIIIE.		, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAE			
SOIL DESCRIPTION	SOIL TYPE: SAND SIL	TY SAND (SILT / SILTY CLAY / CLA	AY / GRAVEL / OTI	HER	
SOIL COLOR: DARK YEL	LOWISH BROWN				
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL				COHESIVE / MEDIUM PLASTIC / HIGH	
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST W		HC ODOR DETECTED:		/ FIRM / STIFF / VERY STIFF ANATION -	· / HARD
SAMPLE TYPE: GRAB (COMPOSITE) # OF PTS.	5	TIO OBOIT BETEGTED.	TLO [NO] EXI D	AIVATION -	
DISCOLORATION/STAINING OBSERVED	YES NO EXPLANATION -	***			
ANY AREAS DISPLAYING WETNESS: YES NO	EXPLANATION -				
ADDITIONAL COMMENTS: NO APPARE	NT EVIDENCE OF A RELEASE	OBSERVED FROM EITHER BGT.			
	NA ft. X NA EAREST WATER SOURCE: >1,00			IMATION (Cubic Yards) : D TPH CLOSURE STD:1	NA 00 ppm
SITE SKETCH		PLOT PLAN circle:	attached	CALIB. READ. = NA	ppm RF = 0.52
			♦ OVM	CALIB. GAS = NA	ppm Til 0.02
			TIME:	: NA am/pm DATE:	NA
			' [MISCELL. NO	OTES
		VELL		NO - N1435257	
	r	HEAD ⊕		PO - 55397	
			-	PK - ZANDECALSL	•
	BER	M FENCE			
					6/08/10
	(95-A)	SEPARATOR	C Tan	OCD Appr. Date: 03	3/01/12
	PBGTL T.B. ~ 5'		_ID)/ N / NA
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAV	B.G. B.G.		- S.P.D.	BGT Sidewalls Visible.	/ N / NA
T.B. = TANK BOTTOM; PBGTL = PREVIOUS NA-NOT APPLICABLE OR NOT AVAILABLE	BELOW-GRADE TANK LOCATION; SPD = 3	SAMPLE POINT DESIGNATION; R.W. = RETA	AINING WALL;	lagnetic declination:	_
TRAVEL NOTES: CALLOUT:		ONSITE: 09/20/11	- After.		

Hall Environmental Analysis Laboratory, Inc.

Date: 04-Oct-11 Analytical Report

CLIENT:

Blagg Engineering

Client Sample ID: 5PC-TB @5' (95 BGT-A)

Lab Order:

1109910

Project:

Case A #18

Collection Date: 9/20/2011 4:30:00 PM

Lab ID:

1109910-01

Date Received: 9/23/2011 Matrix: SOIL

Analyses	Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS					Analyst: JB
Diesel Range Organics (DRO)	23	10		mg/Kg	1	9/28/2011 11:37:58 AM
Surr: DNOP	150	73.4-123	S	%REC	1	9/28/2011 11:37:58 AM
EPA METHOD 8015B: GASOLINE RA	NGE					Analyst: RAA
Gasoline Range Organics (GRO)	· ND	4.6		mg/Kg	1	9/30/2011 3:07:41 AM
Surr: BFB	92.6	75.2-136		%REC	1	9/30/2011 3:07:41 AM
EPA METHOD 8021B: VOLATILES						Analyst: RAA
Benzene	ND	0.046		mg/Kg	1	9/30/2011 3:07:41 AM
Toluene	ND	0.046		mg/Kg	1	9/30/2011 3:07:41 AM
Ethylbenzene	ND	0.046		mg/Kg	1	9/30/2011 3:07:41 AM
Xylenes, Total	ND	0.093		mg/Kg	1	9/30/2011 3:07:41 AM
Surr: 4-Bromofluorobenzene	99.0	80-120		%REC	1	9/30/2011 3:07:41 AM
EPA METHOD 300.0: ANIONS						Analyst: SRM
Chloride	ND	1.5		mg/Kg	1	9/29/2011 5:52:55 PM
EPA METHOD 418.1: TPH						Analyst: JB
Petroleum Hydrocarbons, TR	ND	20		mg/Kg	1	9/29/2011

Qualifiers:

- Value exceeds Maximum Contaminant Level
- E Estimated value
- Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- MCL Maximum Contaminant Level
- ND Not Detected at the Reporting Limit
- Spike recovery outside accepted recovery limits

Date: 04-Oct-11

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project: Case A #18

Work Order:

1109910

rioject. Case A #16									WOLK	Order:	1109910
Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec L	owLimit Hi	ghLimit	%RPD	RPDLimit	Qual
Method: EPA Method 300.0: A	nions										
Sample ID: MB-28618		MBLK				Batch ID:	28618	Analys	is Date:	9/29/2011	1:14:20 PN
Chloride	ND	mg/Kg	1.5								
Sample ID: LCS-28618		LCS				Batch ID:	28618	Analys	is Date:	9/29/2011	1:31:45 PN
Chloride	13.91	mg/Kg	1.5	15	0	92.7	90	110			
Method: EPA Method 418.1: Ti	PH										
Sample ID: MB-28601		MBLK				Batch ID:	28601	Analys	is Date:		9/29/2011
Petroleum Hydrocarbons, TR	ND	mg/Kg	20								
Sample ID: LCS-28601		LCS				Batch ID:	28601	Analys	is Date:		9/29/201
Petroleum Hydrocarbons, TR	100.5	mg/Kg	20	100	0	101	87.8	115			
Sample ID: LCSD-28601		LCSD				Batch ID:	28601	Analys	is Date:		9/29/2011
Petroleum Hydrocarbons, TR	103.2	mg/Kg	20	100	0	103	87.8	115	2.61	8.04	
Method: EPA Method 8015B: D Sample ID: MB-28603	iesel Range	Organics MBLK				Batch ID:	28603	Analys	is Date:	9/28/2011	9:54:16 AN
Diesel Range Organics (DRO)	ND	mg/Kg	10								
Sample ID: LCS-28603		LCS				Batch ID:	28603	Analys	is Date:	9/28/2011 10	0:28:40 AN
Diesel Range Organics (DRO)	55.22	mg/Kg	10	50	4.175	102	66.7	119			
Method: EPA Method 8015B: G	asoline Rar							1		***	
Sample ID: 1109910-01AMSD	addinio mai	MSD				Batch ID:	28595	Analys	is Date:	9/30/2011 1	1:21:12 PN
Gasoline Range Organics (GRO)	26.71	mg/Kg	4.7	23.26	0	115	72.4	149	3.20	19.2	
Sample ID: MB-28595		MBLK				Batch ID:	28595		is Date:	9/29/2011 1	1:45:48 PN
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0								
Sample ID: LCS-28595		LCS				Batch ID:	28595	Analys	is Date:	9/29/2011 10	0:48:10 PN
Gasoline Range Organics (GRO)	28.48	mg/Kg	5.0	25	0	114	86.4	132			
Sample ID: 1109910-01AMS		MS				Batch ID:	28595	Analysi	is Date:	9/30/2011 10	0:52:22 PN
Gasoline Range Organics (GRO)	25.87	mg/Kg	4.8	23.76	0	109	72.4	149			
Method: EPA Method 8021B: V	olatiles						-				
Sample ID: MB-28595	o i a i i i i i i i i i i i i i i i i i	MBLK				Batch ID:	28595	Analysi	s Date:	9/29/2011 1	1:45:48 PN
Benzene	ND	mg/Kg	0.050								
Toluene	ND	mg/Kg	0.050								
Ethylbenzene	ND	mg/Kg	0.050								
Kylenes, Total	ND	mg/Kg	0.10								
Sample ID: LCS-28595		LCS				Batch ID:	28595	Analysi	s Date:	9/29/2011 1	1:16:59 PN
Benzene	1.019	mg/Kg	0.050	1	0.0141	100	83.3	107			
						98.9	74.3	115			
Toluene	1.002	mg/Kg	0.050	1	0.0129	30.3	17.0	115			
Toluene Ethylbenzene	1.002 1.023	mg/Kg mg/Kg	0.050		0.0129	101	80.9	122			

Oı	10	1: 1	r	^	*	e
VI	131	ш.	u	u	J	a

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

R RPD outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

Sample Receipt Checklist

Client Name BLAGG			Date	Received			9/23/2011						
Work Order Number 1109910				Rec	eived by:	DA	M						
Checklist completed by: Signature	9	!	Date	9/26/	iple ID lat	oels check	ed by:	Initials (MS)					
Matrix:	Carrier name:	Grey	hound										
Shipping container/cooler in good condition?		Yes	V	No		Not Prese	ent						
Custody seals intact on shipping container/coole	r?	Yes	V	No		Not Prese	ent	Not Shipped					
Custody seals intact on sample bottles?		Yes	i !	No		N/A	~						
Chain of custody present?		Yes	V	No	t								
Chain of custody signed when relinquished and r	eceived?	Yes	V	No		,							
Chain of custody agrees with sample labels?		Yes	~	No ·									
Samples in proper container/bottle?		Yes	v	No									
Sample containers intact?		Yes	V	No	(8)								
Sufficient sample volume for indicated test?		Yes	V	No -									
All samples received within holding time?		Yes	V	No				Number of preserved					
Water - VOA vials have zero headspace?	No VOA vials subm	itted		Yes	1	No		bottles checked for pH:					
Water - Preservation labels on bottle and cap ma	itch?	Yes	1 1	No		N/A	V						
Water - pH acceptable upon receipt?		Yes		No:		N/A	V	<2 >12 unless noted below.					
Container/Temp Blank temperature?		3.	3°		cceptable			201011.					
COMMENTS:			If given s	sufficient t	time to cod	oł.	*						
			*										
Client contacted I	Date contacted:				Perso	n contacte	ed						
Contacted by:	Regarding:												
Comments:													

Chain-of-Custody Record		Turn-Around Time:						H	IAI		F	MV	TE	20	M	WE	INIT	CA				
Client: BLAGG ENGR. / BP AMERICA		☑ Standard ☐ Rush			HALL ENVIRONMENTAL ANALYSIS LABORATORY																	
			Project Name:				www.hallenvironmental.com															
Mailing Address: P.O. BOX 87			CASE A # 1	18		49	01 H	awki	ns N	IE -	Alb	uqu	erqu	ue, N	IM 8	7109	9					
		BLOOM	FIELD, NM 87413	Project #:			4901 Hawkins NE - Albuquerque, NM 87109 Tel. 505-345-3975 Fax 505-345-4107															
Phone #	:	(505) 63	2-1199									A	naly	/sis	Rec	ques	t					
email or Fax#:		Project Manager:			<u>~</u>		(le															
QA/QC P	_		Level 4 (Full Validation)	NELSON VELEZ			MB3 (8021B)	+ TPH (Gas only)	(Gas/Diesel)					ФJ	PCB's						COMPOSITE SAMPLE	
Accredit	ation:			Sampler: NELSON VELEZ 920			4	9) H	B (G	1)	1)			ance	8082						SAN	9
□ NELA		☐ Other		On lice: ➤ Yes □ No			f	4 TP	3015	418	504	PAH	S	Ba ı	-		(AC	0.0)			SITE	or
□ EDD	(Type)	T		Sample Temp	erature: 33		革	TBE	po	hod	hod	1 or	etal	nior	icide	(AC	nj-V((30		APLE	1PO	λ) se
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX + MTB	BTEX + MTBE	TPH Method 8015B	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Cation / Anion Balance	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE (300.0)		GRAB SAMPLE	5 PT. CON	Air Bubbles (Y or N)
9/20/11	1630	SOIL	5PC-TB @ 5' (95 BGT-A)	4 oz 2	Cool	1109910-	-		٧	٧								٧			٧	
9/20/11	1620	SOIL	SPC-TB @ 5' (95 BCT-B)	4 02 2	Cool	5	V		٧	٧								V			٧	
Date:	Time: 1530	Relinquish	ed by:	Received by: Date Time			Remarks: TPH (8015B) - GRO & DRO ONLY. BILL DIRECTLY TO BP:															
Date:	Date: Time: Relinquished by:		Received by: Date Time		Jeff Peace, 200 Energy Court, Farmington, NM 87401 Work Order: N1435257 Paykey: ZANDECRUSL																	
if necessary, samples submitted to Hall Environmental may be subconfacted to other accredited laboratories. This serves as notice of				of this	possibi	ility. A	ny sub	-contra	acted	data v	will be	dear	ly nota	ted or	the a	nalytic	al repr	ort.				



