District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	Pit, Below-Grade Tank, or	
12994 Prope	osed Alternative Method Permit or Closure Plan Applie	cation
Type of action:	☐ Below grade tank registration	OIL CONS. DIV DIST. 3
45-28331	Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration	JUL 07 2015

Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request

environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1.
Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Gallegos Canyon Unit 507
API Number:3004528331OCD Permit Number:12693
U/L or Qtr/Qtr
Center of Proposed Design: Latitude36.717270 Longitude108.128090 NAD: ☐1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
⊠ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptant are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□ Vas □ Na
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	NMAC 15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
□ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	.15.17.9 NMAC
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the description is the subsection of the following items must be attached to the application.	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Flank Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	uid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P. 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	7.0.5

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed to the best of my	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18. OCD Approval: ☐ Permit Application (including closure plan) ☐ Closure Plan (only) ☐ OCD Conditions (see attachment)	/-
OCD Representative Signature: Approval Date: 4/15	7/15
Title: LNV: ron Mental Spel OCD Permit Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 5/21/2015	
20.	
Closure Method: ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-logical of the formal of the following of the fol	pop systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached.	edicate, by a check

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this clo	
belief. I also certify that the closure complies with all applicable closure red	quirements and conditions specified in the approved closure plan.
N (B') I-CC D	mid Field Feeders and I Complianted
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Off Page	
Signature: Off Pale	Date:July 6, 2015
000	
e-mail address: peace.jeffrey@bp.com	Telephone: (505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 507 API No. 3004528331 Unit Letter D, Section 20, T29N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	120

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	catio	n and Co	orrective A	ction				
						OPERA	ΓOR	_ In	tial Report		Final Report	
Name of Co						Contact: Jef						
		Court, Farm		M 87401		Telephone No.: 505-326-9479						
Facility Na	me: Galleg	gos Canyon I	Jnit 507			Facility Typ	e: Natural gas	well				
Surface Ow	ner: Priva	te		Mineral ()wner:	Federal		API	No. 3004528	331		
				LOCA	ATIO	N OF REI	LEASE					
Unit Letter D	Section 20	Township 29N	Range 12W	Feet from the 840	North	n/South Line	Feet from the 815	East/West Line West	County: S	San Juan		
		Latit	ude36	.717270		Longitud	e108.128090		_			
				NAT	TURE	OF REL	EASE					
Type of Rele							Release: N/A		Recovered:		27/1	
Source of Re	lease: belov	w grade tank -	- 95 bbl			Date and H N/A	lour of Occurrence	ce: Date ar	d Hour of Di	scovery:	N/A	
Was Immedi	ate Notice (Yes [No Not R	equired	If YES, To	Whom?					
By Whom?						Date and H						
Was a Water	Was a Watercourse Reached? ☐ Yes ☒ No						If YES, Volume Impacting the Watercourse.					
If a Watercon	urse was Im	pacted, Descr	ibe Fully.	*								
				n Taken.* Sampli and chlorides bel					al to ensure no	o soil im	pacts from	
				cen.* BGT was reactive well area.	emoved	and the area u	nderneath the BC	T was sampled.	The area und	er the B	GT was	
regulations a public health should their or the enviro	Il operators or the envi operations l nment. In a	are required to ronment. The nave failed to	o report and acceptant adequately OCD acceptant	e is true and comp nd/or file certain to ce of a C-141 report investigate and obtained of a C-141	release ort by the remedia	notifications and the NMOCD matter contamination	nd perform correct arked as "Final R on that pose a thr	etive actions for report" does not reat to ground wa	eleases which elieve the ope ter, surface w	n may en erator of eater, hu	danger liability man health	
	1 00	0					OIL CON	SERVATIO	N DIVISIO	NC		
Signature:	yff	Sace				Approved by	Environmental S	necialist:				
Printed Nam	e: Jeff Peac	e				- Approved by		F				
Title: Field F	invironmen	tal Coordinate	or			Approval Da	e:	Expiration	n Date:			
		effrey@bp.com				Conditions of	Approval:		Attached	d 🗌		
Date: July 6	. 2015		Phone: 50.	5-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		NGINEERING, INC LOOMFIELD, NM		API#: 3004528	331
	(50	5) 632-1199		TANK ID (if applicble):	
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OT	THER:	PAGE #: 1 of	_1
SITE INFORMATION	I: SITE NAME: GCU #	507		DATE STARTED: 05/1	9/15
QUAD/UNIT: D SEC: 20 TWP:	29N RNG: 12W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 840'N / 815"		TYPE: FEDERAL / STATE /		ENVIRONMENTAL	
LEASE #: SF080723	PROD. FORMATION: PC C	ONTRACTOR: MBF - D. F	IELDSTED	SPECIALIST(S):	JV
REFERENCE POINT	· · · · · · · · · · · · · · · · · · ·				
95 BGT (DW/DB)	GPS COORD.: 36.	717270 X 108.128090	DISTANCE/BEA	RING FROM W.H.: 45', N8	88E
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)				RING FROM W.H.:	
	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	OVM
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # (-D/2004D/2000 0 (OI)	READING (ppm)
1) SAMPLE ID: 5PC-TB @ 5'				5B/8021B/300.0 (CI)	NA
2) SAMPLE ID:					
SAMPLE ID: SAMPLE ID:	SAMPLE DATE:				
SOIL DESCRIPTION					
SOIL COLOR: DARK YELLOW COHESION (ALL OTHERS): NON COHESIVE SLIGHTLE CONSISTENCY (NON COHESIVE SOILS): LE MOISTURE: DRY/SLIGHTLY MOIST MOIST W SAMPLE TYPE: GRAB COMPOSITE F DISCOLORATION/STAINING OBSERVED: YES NO SITE OBSERVATION	Y COHESIVE / COHESIVE / HIGHLY COHESIVE DOSE FIRM / DENSE / VERY DENSE ET / SATURATED SUPER SATURATED OF PTS. 5 OEXPLANATION -	HC ODOR DETECTED: YES NO IS ANY AREAS DISPLAYING WETNESS TATION ONLY.	SILTS): SOFT/FIRM/ EXPLANATION -	STIFF / VERY STIFF / HARD	
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER:		Anation:			
SOIL IMPACT DIMENSION ESTIMATION	101	ft. X NA ft.		TIMATION (Cubic Yards):	NA
	EAREST WATER SOURCE: >1,000		<200' NMOC	D TPH CLOSURE STD:100) ppm
SITE SKETCH PUMP JACK	BGT Located : off on sit	PLOT PLAN circl PERIMETER SECURITY FENCE	QVM	CALIB. READ. = NA ppm CALIB. GAS = NA ppm E: NA am/pm DATE: MISCELL. NOT	NA
w.H.	FENCE (XXX)	-43'	R	/O: EF: P-44 K: ZEVH01BGT2 J#: Z2-006Q0	
TO ME GCU #263 W.H.	ARATOR STER UN	EPHEMERAL WASH	O Tar IL A		115 er
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATI T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGL	OW-GRADE TANK LOCATION; SPD = SAMPLE	POINT DESIGNATION; R.W. = RETAINING \	V.H. = WELL HEAD; L NALL; NA - NOT N	Magnetic declination: 10	
NOTES: GOOGLE EARTH IMAGE	ERY DATE: 03/15/2015.	ONSITE: 05/19/1	5		

Analytical Report

Lab Order 1505876

Date Reported: 5/21/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB@5' (95)

Project: GCU #507

Collection Date: 5/19/2015 9:57:00 AM

Lab ID: 1505876-001

Matrix: MEOH (SOIL)

Received Date: 5/20/2015 8:15:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	LGT
Chloride	120	30	mg/Kg	20	5/20/2015 11:12:05 AM	19314
EPA METHOD 8015D: DIESEL RANGE (ORGANICS				Analyst	KJH
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	5/20/2015 10:38:07 AM	19312
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	5/20/2015 10:38:07 AM	19312
Surr: DNOP	104	57.9-140	%REC	1	5/20/2015 10:38:07 AM	19312
EPA METHOD 8015D: GASOLINE RANG	BE .				Analyst:	RAA
Gasoline Range Organics (GRO)	ND	3.9	mg/Kg	1	5/20/2015 10:02:14 AM	R26308
Surr: BFB	90.2	80-120	%REC	1	5/20/2015 10:02:14 AM	R26308
EPA METHOD 8021B: VOLATILES					Analyst:	RAA
Benzene	ND	0.039	mg/Kg	1	5/20/2015 10:02:14 AM	R26308
Toluene	ND	0.039	mg/Kg	1	5/20/2015 10:02:14 AM	R26308
Ethylbenzene	ND	0.039	mg/Kg	1	5/20/2015 10:02:14 AM	R26308
Xylenes, Total	ND	0.079	mg/Kg	1	5/20/2015 10:02:14 AM	R26308
Surr: 4-Bromofluorobenzene	109	80-120	%REC	1	5/20/2015 10:02:14 AM	R26308

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDImit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH Not In Range
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1505876

21-May-15

Client:

Blagg Engineering

Project:

GCU #507

Sample ID MB-19314

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 19314

PQL

RunNo: 26327

Prep Date:

HighLimit

5/20/2015

Analysis Date: 5/20/2015

SeqNo: 782398

Units: mg/Kg

%RPD

RPDLimit

Qual

Analyte Chloride

ND 1.5

Sample ID LCS-19314

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Result

Batch ID: 19314

RunNo: 26327

Prep Date: 5/20/2015

SeqNo: 782399

Units: mg/Kg

Analyte

Analysis Date: 5/20/2015

%RPD **RPDLimit**

SPK value SPK Ref Val

15.00

%REC 92.6

Chloride

1.5

0

SPK value SPK Ref Val %REC LowLimit

90

110

Qual

14

HighLimit

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0

- RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits

- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- Not Detected at the Reporting Limit P
- Sample pH Not In Range Reporting Detection Limit

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 21-May-15

1505876

Client:

Blagg Engineering

Project:	GCU #50)7									
Sample ID	MB-19293	SampTy	pe: N	IBLK	Tes	tCode: E	PA Method	8015D: Dies	el Range (Organics	
Client ID:	PBS	Batch	ID: 1	9293	F	RunNo: 2	26304				
Prep Date:	5/19/2015	Analysis Da	ite: 5	5/20/2015		SeqNo: 7	781491	Units: %RE	С		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		10		10.00		104	57.9	140			
Sample ID	LCS-19293	SampTy	pe: L	cs	Tes	tCode: E	PA Method	8015D: Dies	el Range (Organics	
Client ID:	LCSS	Batch	ID: 1	9293	F	RunNo: 2	26304				
Prep Date:	5/19/2015	Analysis Da	ite: 5	5/20/2015	5	SeqNo: 7	81492	Units: %RE	С		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		5.1		5.000		101	57.9	140			
Sample ID	MB-19312	SampTy	pe: M	BLK	Tes	tCode: E	PA Method	8015D: Diese	el Range (Organics	
Client ID:	PBS	Batch	ID: 19	9312		RunNo: 2					
Prep Date:	5/20/2015	Analysis Da	te: 5	5/20/2015	5	SeqNo: 7	81584	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
_	Organics (DRO)	ND	10								
Motor Oil Rang Surr: DNOP	e Organics (MRO)	ND 10	50	10.00		101	57.9	140			
						101	57.9	140			
	LCS-19312	SampTy						8015D: Diese	el Range (Organics	
Client ID:		Batch	ID: 19	9312		RunNo: 2					
Prep Date:	5/20/2015	Analysis Da	te: 5	/20/2015	8	SeqNo: 7	81593	Units: mg/K	g		
Analyte	(550)	Result	PQL		SPK Ref Val		LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP	Organics (DRO)	50 5.1	10	50.00 5.000	0	99.2	67.8 57.9	130 140			
Ouil. Divol		3.1		3.000		101	57.5	140			
	1505876-001AMS	SampTy						8015D: Diese	el Range (Organics	
	5PC-TB@5' (95)	Batch				RunNo: 2					
Prep Date:	5/20/2015	Analysis Da	te: 5	/20/2015	S	SeqNo: 7	81637	Units: mg/K	g		
Analyte		Result	PQL		SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
	Organics (DRO)	50	10		0	99.6	42.3	146			
Surr: DNOP		5.4		4.975		108	57.9	140			
Cample ID	1505876-001AMSE	SampTy	ре: М	SD	Tes	tCode: E	PA Method	8015D: Diese	el Range C	Organics	
Sample ID						RunNo: 2	6303				
	5PC-TB@5' (95)	Batch	ID: 19	9312	F	MITINO. Z	.0000				
Client ID:	5PC-TB@5' (95) 5/20/2015	Batch Analysis Da				SeqNo: 7		Units: mg/K	g		
				/20/2015				Units: mg/K	g %RPD	RPDLimit	Qual

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- Reporting Detection Limit

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1505876

21-May-15

Qual

Client:

Blagg Engineering

Project:

GCU #507

Sample ID 1505876-001AMSD

SampType: MSD

TestCode: EPA Method 8015D: Diesel Range Organics

Client ID: 5PC-TB@5' (95) Batch ID: 19312

RunNo: 26303

5/20/2015

Analysis Date: 5/20/2015

Analyte

Result

PQL SPK value SPK Ref Val

SeqNo: 781651

Units: mg/Kg

Prep Date:

%REC

LowLimit

HighLimit

%RPD **RPDLimit**

Surr: DNOP

5.2

4.970

105

57.9

140

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded H

ND Not Detected at the Reporting Limit

Sample pH Not In Range P

Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1505876

21-May-15

Client:

Blagg Engineering

Project:

GCU #507

Project:	GCU #50) /												
Sample ID	2.5UG GRO LCS	SampT	ype: LC	s	PA Method	8015D: Gas	oline Rang	e						
Client ID:	LCSS	Batch	ID: R2	26308	F	RunNo: 2	6308							
Prep Date:		Analysis D	ate: 5 /	20/2015	5	SeqNo: 7	81587	Units: mg/l	≺g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Rang	e Organics (GRO)	22	5.0	25.00	0	86.9	64	130						
Surr: BFB		970		1000		96.7	80	120						
Sample ID 5ML-RB SampType: MBLK TestCode: I								8015D: Gase	oline Rang	е				
Client ID: PBS Batch ID: R26308					RunNo: 26308									
Prep Date:		Analysis Da	ate: 5/	20/2015	5	SeqNo: 7	81588	Units: mg/l	≺g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Rang	e Organics (GRO)	ND	5.0											
Surr: BFB		910		1000		90.5	80	120						
Sample ID	1505876-001A MS	SampT	уре: М	3	Tes	tCode: El	PA Method	8015D: Gase	oline Rang	е				
Client ID:	5PC-TB@5' (95)	Batch	ID: R2	6308	F	RunNo: 2	6308							
Prep Date:		Analysis Da	ate: 5/	20/2015	5	SeqNo: 7	82071	Units: mg/l	K g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Rang	e Organics (GRO)	18	3.9	19.70	0	91.6	47.9	144						
Surr: BFB		780		788.0		99.0	80	120						
Sample ID	1505876-001A MS	D SampTy	уре: М	SD	Tes	tCode: El	PA Method	8015D: Gaso	oline Rang	е				
Client ID:	5PC-TB@5' (95)	Batch	ID: R2	6308	F	RunNo: 2	6308							
Prep Date:		Analysis Da	ate: 5/	20/2015	SeqNo: 782072			Units: mg/l	(g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Rang	e Organics (GRO)	17	3.9	19.70	0	86.6	47.9	144	5.61	29.9				
Surr: BFB		770		788.0		97.6	80	120	0	0				

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 15

1505876 21-May-15

Client:

Blagg Engineering

Project:

GCU #507

Project:														
Sample ID	100NG BTEX LCS	SampT	ype: LC	S	Tes	TestCode: EPA Method 8021B: Volatiles								
Client ID:	LCSS	Batch	6308	F										
Prep Date:		Analysis D	ate: 5/20/2015		S	SeqNo: 7	81590	Units: mg/K	(g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene		1.1	0.050	1.000	0	111	76.6	128						
Toluene		1.1	0.050	1.000	0	113	75	124						
Ethylbenzene		1.1	0.050	1.000	0	111	79.5	126						
Xylenes, Total		3.3	0.10	3.000	0	111	78.8	124						
Surr: 4-Brom	nofluorobenzene	1.1		1.000		113	80	120						
Sample ID	5ML-RB	SampT	уре: МЕ	BLK	Tes	tCode: E	PA Method	8021B: Volat	tiles					
Client ID:	PBS	Batch ID: R26308			F									
Prep Date:		Analysis D	ate: 5/	20/2015	8	SeqNo: 7	81592	Units: mg/K	(g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene		ND	0.050											
Toluene		ND	0.050											
Ethylbenzene		ND	0.050											
.,														
,		ND	0.10											
Xylenes, Total	nofluorobenzene	ND 1.1	0.10	1.000		109	80	120						
Xylenes, Total Surr: 4-Brom	nofluorobenzene 1505876-001A MS	1.1	0.10 Type: M \$		Tes			120 8021B: Vola t	tiles					
Xylenes, Total Surr: 4-Brom Sample ID		1.1 SampT		3			PA Method		tiles					
Xylenes, Total Surr: 4-Brom Sample ID	1505876-001A MS	1.1 SampT	ype: MS	6308	F	tCode: E	PA Method 6308							
Xylenes, Total Surr: 4-Brom Sample ID Client ID:	1505876-001A MS	1.1 SampT Batch	ype: MS	6308 20/2015	F	tCode: E	PA Method 6308	8021B: Volat		RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte	1505876-001A MS	SampT Batch Analysis D	ype: MS	6308 20/2015	F	tCode: E RunNo: 2 SeqNo: 7	PA Method 6308 82097	8021B: Volat	(g	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene	1505876-001A MS	SampT Batch Analysis D Result	Type: MS ID: R2 Tate: 5/	6308 20/2015 SPK value	SPK Ref Val	tCode: E RunNo: 2 SeqNo: 7 %REC	PA Method 6308 82097 LowLimit	8021B: Volat Units: mg/K HighLimit	(g	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date:	1505876-001A MS	1.1 SampT Batch Analysis D Result 0.95	Type: MS n ID: R2 pate: 5/ PQL 0.039	6308 20/2015 SPK value 0.7880	SPK Ref Val	tCode: E RunNo: 2 SeqNo: 7 %REC 120	PA Method 6308 82097 LowLimit 69.2	8021B: Volate Units: mg/K HighLimit 126	(g	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene	1505876-001A MS	1.1 SampT Batch Analysis D Result 0.95 0.91	Type: MS n ID: R2 nate: 5/ PQL 0.039 0.039	6308 20/2015 SPK value 0.7880 0.7880	SPK Ref Val	tCode: E RunNo: 2 SeqNo: 7 %REC 120 115	PA Method 6308 82097 LowLimit 69.2 65.6	8021B: Volate Units: mg/K HighLimit 126 128	(g	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total	1505876-001A MS	1.1 SampT Batch Analysis D Result 0.95 0.91 0.93	PQL 0.039 0.039	6308 20/2015 SPK value 0.7880 0.7880 0.7880	SPK Ref Val 0 0 0	tCode: E RunNo: 2 SeqNo: 7 %REC 120 115 118	PA Method 6308 82097 LowLimit 69.2 65.6 65.5	8021B: Volate Units: mg/K HighLimit 126 128 138	(g	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom	1505876-001A MS 5PC-TB@5' (95)	1.1 SampT Batch Analysis D Result 0.95 0.91 0.93 2.8 0.93	PQL 0.039 0.039	6308 20/2015 SPK value 0.7880 0.7880 2.364 0.7880	SPK Ref Val 0 0 0 0	tCode: E RunNo: 2 SeqNo: 7 %REC 120 115 118 118 118	PA Method 6308 82097 LowLimit 69.2 65.6 65.5 63 80	8021B: Volat Units: mg/K HighLimit 126 128 138 139	%RPD	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID	1505876-001A MS 5PC-TB@5' (95)	Analysis D Result 0.95 0.91 0.93 2.8 0.93 D SampT	rype: MS n ID: R2 nate: 5/ PQL 0.039 0.039 0.039 0.079	6308 20/2015 SPK value 0.7880 0.7880 0.7880 2.364 0.7880	SPK Ref Val 0 0 0 0 Tes	tCode: E RunNo: 2 SeqNo: 7 %REC 120 115 118 118 118	PA Method 6308 82097 LowLimit 69.2 65.6 65.5 63 80	8021B: Volate Units: mg/K HighLimit 126 128 138 139 120	%RPD	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID	1505876-001A MS 5PC-TB@5' (95)	Analysis D Result 0.95 0.91 0.93 2.8 0.93 D SampT	PQL 0.039 0.039 0.079 0.079 MS ID: R2	6308 20/2015 SPK value 0.7880 0.7880 2.364 0.7880 650 6308	SPK Ref Val 0 0 0 0 Tes	tCode: E RunNo: 2 ReqNo: 7 %REC 120 115 118 118 118 tCode: E	PA Method 6308 82097 LowLimit 69.2 65.6 65.5 63 80 PA Method 6308	8021B: Volate Units: mg/K HighLimit 126 128 138 139 120	%RPD	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID Client ID:	1505876-001A MS 5PC-TB@5' (95)	Analysis D Result 0.95 0.91 0.93 2.8 0.93 D SampT Batch	PQL 0.039 0.039 0.079 0.079 MS ID: R2	6308 20/2015 SPK value 0.7880 0.7880 0.7880 2.364 0.7880 6308 20/2015 SPK value	SPK Ref Val 0 0 0 0 Tes	tCode: E RunNo: 2 ReqNo: 7 %REC 120 115 118 118 118 2tCode: E RunNo: 2 SeqNo: 7 %REC	PA Method 6308 82097 LowLimit 69.2 65.6 63.8 80 PA Method 6308 82098 LowLimit	8021B: Volate Units: mg/K HighLimit 126 128 138 139 120 8021B: Volate	%RPD tiles %RPD	RPDLimit	Qual			
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date:	1505876-001A MS 5PC-TB@5' (95)	Analysis D Result 0.95 0.91 0.93 2.8 0.93 D SampT Batch Analysis D	PQL 0.039 0.079 0.079 0.079 0.079 PQL 0.039	6308 20/2015 SPK value 0.7880 0.7880 2.364 0.7880 6308 20/2015 SPK value 0.7880	SPK Ref Val 0 0 0 0 Tes	tCode: E RunNo: 2 ReqNo: 7 %REC 120 115 118 118 118 2tCode: E RunNo: 2 SeqNo: 7 %REC 121	PA Method 6308 82097 LowLimit 69.2 65.6 65.5 63 80 PA Method 6308 82098 LowLimit 69.2	8021B: Volate Units: mg/K HighLimit 126 128 138 139 120 8021B: Volate Units: mg/K HighLimit 126	%RPD tiles %RPD 0.738	RPDLimit 18.5				
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene	1505876-001A MS 5PC-TB@5' (95)	Analysis D Result 0.95 0.91 0.93 2.8 0.93 D SampT Batch Analysis D	PQL 0.039 0.039 0.079 0.079 PQL 0.079 PQL 0.079	6308 20/2015 SPK value 0.7880 0.7880 0.7880 2.364 0.7880 6308 20/2015 SPK value	SPK Ref Val 0 0 0 0 Tes F SPK Ref Val	tCode: E RunNo: 2 ReqNo: 7 %REC 120 115 118 118 118 2tCode: E RunNo: 2 SeqNo: 7 %REC	PA Method 6308 82097 LowLimit 69.2 65.6 63.8 80 PA Method 6308 82098 LowLimit	8021B: Volate Units: mg/K HighLimit 126 128 138 139 120 8021B: Volate Units: mg/K HighLimit	%RPD tiles %RPD	RPDLimit 18.5 20.6				
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte	1505876-001A MS 5PC-TB@5' (95)	Analysis D Result 0.95 0.91 0.93 2.8 0.93 D SampT Batch Analysis D Result 0.96	PQL 0.039 0.079 0.079 0.079 0.079 PQL 0.039	6308 20/2015 SPK value 0.7880 0.7880 2.364 0.7880 6308 20/2015 SPK value 0.7880 0.7880 0.7880 0.7880	SPK Ref Val 0 0 0 0 Tes SPK Ref Val 0	tCode: E RunNo: 2 ReqNo: 7 %REC 120 115 118 118 118 2tCode: E RunNo: 2 SeqNo: 7 %REC 121	PA Method 6308 82097 LowLimit 69.2 65.6 65.5 63 80 PA Method 6308 82098 LowLimit 69.2	8021B: Volate Units: mg/K HighLimit 126 128 138 139 120 8021B: Volate Units: mg/K HighLimit 126	%RPD %RPD 0.738 0.540 1.41	RPDLimit 18.5 20.6 20.1				
Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene Toluene	1505876-001A MS 5PC-TB@5' (95)	Analysis D Result 0.95 0.91 0.93 2.8 0.93 D SampT Batch Analysis D Result 0.96 0.90	rype: MS a ID: R2 ate: 5/ PQL 0.039 0.039 0.079 rype: MS a ID: R2 pate: 5/ PQL 0.039 0.039	6308 20/2015 SPK value 0.7880 0.7880 2.364 0.7880 6308 20/2015 SPK value 0.7880 0.7880 0.7880	SPK Ref Val 0 0 0 0 Tes SPK Ref Val 0 0	tCode: E RunNo: 2 SeqNo: 7 %REC 120 115 118 118 118 118 CCode: E RunNo: 2 %REC 121 114	PA Method 6308 82097 LowLimit 69.2 65.6 65.5 63 80 PA Method 6308 82098 LowLimit 69.2 65.6	8021B: Volati Units: mg/K HighLimit 126 128 138 139 120 8021B: Volati Units: mg/K HighLimit 126 128	%RPD %RPD 0.738 0.540	RPDLimit 18.5 20.6				

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 6 of 6



Hull Environmental Arkhysis Laberatory 1901 Hawkiis NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Order Number: 1505876 RcotNo: 1 Received by/date: Logged By 5/20/2015 8-15:00 AM Ashley Gallegos Completed By: Ashley Gallegos 5/20/2015 8:21 07 AM Reviewed By Chain of Custody No . Not Present V 1. Guslody scals intact on sample bottles? No Yes V Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In 4. Was an attempt made to cool the samples? No NA NA 🗌 5. Were all samples received at a temperature of >0° C to 6.0°C Yes V No No 6. Sample(s) in proper container(s)? Yes V No 7. Sufficient sample volume for indicated test(s)? Yes No 8. Are samples (except VOA and ONG) properly preserved? No V NA 9. Was preservative added to bottles? Yes No No VOA Vials 10. VOA vials have zero headspace? Yes No V 11. Were any sample containers received broken? Yes # of preserved bottles checked No for pH: 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 13. Are matrices correctly identified on Chain of Custody? YES V Yes V No 14 Is it clear what analyses were requested? Yes V No 🗌 Checked by: 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) Yes 16. Was client notified of all discrepancies with this order? NA V Person Notified: Date By Whom Via: Phone Fax In Person eMail Regarding: Client Instructions 17. Additional remarks: 18 Cooler Information Cooler No Temp °C Condition | Seal Intact | Seal No Seal Date Signed By Good Yes

Chain-of-Custody Record Client: BLAGG ENGR. / BP AMERICA			Turn-Around Time: SAME Rush DAY				HALL ENVIRONMENTAL ANALYSIS LABORATORY														
			Project Name			-				www	w.ha	illen	viro	nme	ntal	.con	1				
Mailing Address: P.O. BOX 87 BLOOMFIELD, NM 87413 Phone #: (505) 632-1199			GCU # 507					4901 Hawkins NE - Albuquerque, NM 87109													
			Project #:			Tel. 505-345-3975 Fax 505-345-4107															
			1								А	hnah	ysis	Rec	lues	st					
email or F	ax#:			Project Manag	jer:									-				1)		T	T
QA/QC Pa	7		Level 4 (Full Validation)	1	JEM204	VELEZ	(80218)	(Aluo	/ DRO / MRO)			(S)		04,504	PCB's			er - 300.1)			es
Accredita				Sampler: N	ELSOY ,	VELEZ AN	-88	Gas	30/	1	=	SIN		102,F	3082			water			sample
□ NELAP □ Other		On Ice: Yes □ No			1	TPH (Gas	0/0	418.	504.	3270		N,80	3/8		(AC	000			e Sa		
□ EDD (Type)			Sample Temp	erature:	1.0		+	(GRC	po	po	0.0	tals	N.I.	cide	A	i-VC	11 - 3(01	osit
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX +-MFB	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. composite
5/19/15	0957	SOIL	SPC-T8@5'(95)	402-1	COOL	-001	V											V		٦	/
								-													<u>+</u> +
																					-
Date:	Time	Relinquish	ed by:	Received by:		Date Time	Rem	narks	S:												\perp
5/19/15 Date: 5/19/15	1535 Time: 1727	Relinquish	1/1/1	Received by:	Loete 1		Jef	f Pea	ice, 2	LY TO 200 E	nerg	y Co		Farm					018	ST.	2



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

May 13, 2015

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: GALLEGOS CANYON UNIT 507

API#: 3004528331

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 18, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

Jerry Van Riper

Surface Land Negotiator

90 Vaker

BP America Production Company

Peace, Jeffrey

From:

Railsback, Farrah (CH2M HILL)

Sent:

Tuesday, May 12, 2015 2:40 PM

To:

Smith, Cory, EMNRD (Cory.Smith@state.nm.us)

Cc:

Peace, Jeffrey

Subject:

BP Pit Close Notification - GALLEGOS CANYON UNTI 507

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

May 12, 2015

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE:

Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 507 API 30-045-28331 (D) Section 20 – T29N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around May 18, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor



