

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB No. 1004-0136
Expires November 30, 2000

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM84809
1b. Type of Well: <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other: CBM <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator CONOCOPHILLIPS COMPANY		7. If Unit or CA Agreement, Name and No. 31330
3a. Address 5525 HWY. 64 FARMINGTON, NM 87401		8. Lease Name and Well No. SAN JUAN 32-8 UNIT 202A
3b. Phone No. (include area code) Ph: 505.599.3454 Fx: 505-599-3442		9. API Well No. 30045 31702
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface SENW 1600FNL 1300FWL 36.95750 N Lat, 107.66640 W Lon At proposed prod. zone		10. Field and Pool, or Exploratory BASIN FRUITLAND COAL
14. Distance in miles and direction from nearest town or post office* 36.3 MILES FROM BLOOMFIELD, NM		11. Sec., T., R., M., or Blk. and Survey or Area F Sec 27 T32N R8W Mer NMP SME: BLM
15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 1300	16. No. of Acres in Lease 893.14	12. County or Parish SAN JUAN
18. Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft.		13. State NM
19. Proposed Depth 3850 MD 3850 TVD		17. Spacing Unit dedicated to this well 320.00 W/2
21. Elevations (Show whether DF, KB, RT, GL, etc.) 6742 GL		20. BLM/BIA Bond No. on file ES0085
22. Approximate date work will start 06/05/2003		23. Estimated duration 30 DAYS

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature (Electronic Submission)	Name (Printed/Typed) PATSY CLUGSTON	Date 05/19/2003
Title AUTHORIZED REPRESENTATIVE		
Approved by (Signature) /s/ David J. Mankiewicz	Name (Printed/Typed)	JUN 10 2003
Title	Office	

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional Operator Remarks (see next page)

Electronic Submission #22046 verified by the BLM Well Information System
For CONOCOPHILLIPS COMPANY, sent to the FarmingtonThis action is subject to technical and
procedural review pursuant to 43 CFR 3165.3
and appeal pursuant to 43 CFR 3165.4DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS".

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

NMOCDD

DISTRICT I
P.O. Box 1980, Hobbs, N.M. 88241-1980

DISTRICT II
811 South First, Artesia, N.M. 88210

DISTRICT III
1000 Rio Brazos Rd., Artesia, N.M. 87410

DISTRICT IV
2040 South Pacheco, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, NM 87504-2088

Form C-102
Revised February 21, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

*API Number 30-045-31702		*Pool Code 71629	*Pool Name Basin Fruitland Coal
*Property Code 009261	*Property Name SAN JUAN 32-8 UNIT		*Well Number 202A
*OGRID No. 017654	*Operator Name PHILLIPS PETROLEUM COMPANY		*Elevation 6742

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
F	27	32N	8W		1600	NORTH	1300	WEST	SAN JUAN

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
F									

¹² Dedicated Acres 320.0 W/2	¹³ Joint or Infill Y	¹⁴ Consolidation Code U	¹⁵ Order No.
--	------------------------------------	---------------------------------------	-------------------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	<p>¹⁷ OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.</p> <p><i>Patsy Clugston</i> Signature Patsy Clugston Printed Name Sr. Regulatory CCle+k Title October 8, 2002 Date</p>
	<p>¹⁸ SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>08/28/02 Date of Survey Signature and Seal of Registered Surveyor: Certificate Number</p>

San Juan 32-8 #202A

SURFACE CASING :

Drill Bit Diameter	12.25"	
Casing Outside Diameter	9.625"	8.989
Casing Weight	32.3	ppf
Casing Grade	H-40	
Shoe Depth	200'	40'
Cement Yield	118	cuft/sk
Excess Cement	100	%

Casing Capacity	0.0785 bbl/ft	0.4407 cuft/ft
Hole / Casing Annulus Capacity	0.0558 bbl/ft	0.3132 cuft/ft

Cement Required 123.2 sx

SHOE 200', 9.625", 32.3 ppf, H-40

INTERMEDIATE CASING :

Drill Bit Diameter	7.875"	
Casing Outside Diameter	5.5"	4.901
Casing Weight	17	ppf
Casing Grade	J-55	
Shoe Depth	3850'	
Lead Cement Yield	261	cuft/sk
Lead Cement Excess	150	%
Tail Cement Length	500'	90'
Tail Cement Yield	127	cuft/sk
Tail Cement Excess	150	%

Casing Capacity	0.0233 bbl/ft	0.1310 cuft/ft
Casing / Casing Annulus Capacity	0.0491 bbl/ft	0.2757 cuft/ft
Hole / Casing Annulus Capacity	0.0309 bbl/ft	0.1733 cuft/ft

Lead Cement Required 543.8 sx

Tail Cement Required 179.8 sx

SHOE 3850', 5.5", 17 ppf, J-55

PHILLIPS PETROLEUM COMPANY

WELL NAME: San Juan 32-8 Unit #202A

DRILLING PROGNOSIS

1. Location of Proposed Well: Unit F, 1600' FNL & 1300' FWL
Section 27, T32N, R8W
2. Unprepared Ground Elevation: @ 6742'
3. The geological name of the surface formation is San Jose.
4. Type of drilling tools will be rotary.
5. Proposed drilling depth is 3850'.
6. The estimated tops of important geologic markers are as follows:

<u>Nacimiento - 905'</u>	<u>Base Coal Interval - 3650'</u>
<u>Ojo Alamo - 2380'</u>	<u>Pictured Cliffs - 3650'</u>
<u>Kirtland - 2425'</u>	<u>Interm Casing - n/a</u>
<u>Fruitland - 3230'</u>	<u>T. D. - 3850'</u>

TD includes 200' of sump/rathole & COPC will comply with the BLM/OCD's Conditions of Approval for the proposed sump/rathole in this non-producing Pictured Cliffs Formation.

7. The estimated depths at which anticipated water, oil, gas or other mineral bearing formations are expected to be encountered are as follows:

Water:	<u>Ojo Alamo - 2380' - 2425'</u>
Oil:	<u>none</u>
Gas:	<u>Fruitland Coal - 3230' - 3650'</u>
Gas & Water:	<u>Fruitland Coal - 3230' - 3650'</u>

8. The proposed casing program is as follows:

Surface String: 9-5/8", 32.3#, H-40 @ 200' *
Production String: 5-1/2", 17#, J-55 STC @ 3850'

* The surface casing will be set at a minimum of 200', but could be set deeper if required to maintain hole stability.

9. Cement Program: *Circulate Cement*
Surface String: 123.2 sx - 15.8 ppg Class G cement + 2% bwoc CaC12 & 0.25
#/sx Cello-flake. Yield = 1.16 ft³/sx Volume from 235 feet to
surface with 100% excess = 143 cf - 25.45 bbls

9. Cement program: (continued from Page 1)

Production String: Lead - 543.8 sx - 11.7 ppg, Class G cement + 0.25#/sx D029 (lost circulation), 3% D0079 (extender), 0.2% D046 (anti-foam), Yield - 2.61 ft³/sx, Mix water = 15.79 gal/sx. Volume from 2925' to surface with 150% excess in open hole = 1419.31 cf.

TOC at least 100' above base of surface CS9

Tail - 179.8 sx - 13.5 ppg, 50/50 Class G/POZ + 0.25#/sx D029 (lost circulation), 5#/sx D024 (lost circulation), 5#/sx D024 (extender), 2% D020 (extender), 2% S001 (accelerator), 0.1% D046 (anti-foam). Yield - 1.27 ft³/sx, Mix water = 6.33 gal/sx. Volume from 3695' to 2925' with 150% excess - 228.34 cf.

Note: ConocoPhillips Company continually works to improve the cement slurries on our wells. Our Cementing Service Companies are currently trying to improve what we are using now and before we would use a new cement program it would have to have stronger properties than we are currently using.

Centralizer Program:

Surface: Total four (4) - 10' above shoe and top of 2nd, 3rd, & 4th jts.

Production: Total seven (7) - 10' above shoe and top of 1st, 2nd, 4th, 6th, 8th, & 1st jt. into shoe.


Turbulators: Total three (3) - one at 1st jt below Ojo Alamo and next 2 jts up.

The well will be completed by fracture stimulation.


10. The minimum specifications for pressure control equipment which are to be used, a schematic diagram thereof showing sizes, pressure ratings (or) API series and the testing procedure and testing frequency are enclosed within the APD packet.
11. Drilling Mud Prognosis: Surface - spud mud on surface casing.
Production - fresh water w/polymer sweeps. Bentonite as required for viscosity w/LCM for lost circulation.
12. The testing, logging, and coring programs are as follows:
D.S.T.s or cores:
Logs: GR/CCL/CBL & GSL over zones of interest
13. Anticipated no abnormal pressures or temperatures to be encountered or any other potential hazards such as Hydrogen Sulfide Gas. Low risk H₂S equipment will be used.

Estimated Bottomhole pressures: Fruitland Coal - +/- 970 psi
14. The anticipated starting date is sometime around June 5, 2003 with duration of drilling/ completion operations for approximately 30 days thereafter.

BLOWOUT PREVENTER HOOKUP



1. Rotating Head
2. Fill-up Line & valve
3. Flowline
4. Blowout Preventer (3000 psi)
5. Pipe Rams
6. Blind Rams
7. Kill Line
8. Kill Line Check Valve
9. Kill Line Valve
10. Inner Choke Line Valve (3")
11. Outer Choke Line Valve (3")
12. Choke Line (3")
13. Variable Choke
14. Choke Line Valve (2")
15. Panic Line Valve (3")
16. Choke Manifold Pressure Gauge
17. Choke Line (2")
18. Spacer Spool
19. Casing Spool "B" Section
20. Casing Spool "B" Section 2" Valve
21. Casing Head "A" Section
22. Casing Head "A" Section 2" Valve
23. 9 5/8" Casing Collar



Drilling contractors used in the San Juan Basin supply 3000 psi equipment, but cannot provide annular preventors because of sub-structure limitations. Maximum anticipated surface pressures for this well will not exceed the working pressure of the proposed BOP system. The above diagram of the BOP system details 2000 psi equipment according to Onshore Order No. 2 even though the equipment will test to 3000 psi. The 2000 psi system allows deletion of the annular preventor and fulfills your requirements.

In addition to the equipment in the above diagram the following equipment will comprise the BOP system:

1. Upper Kelly cock Valve with handle
2. Stab-in TIW valve for all drillstrings in use

The BOPs will be pressure tested according to Onshore Order #2III, A1 and 30% Safety factor.

**San Juan 32-8 Unit #202A
NMNM084809; Unit F, 1600' FNL & 1300' FWL
Section 27, T32N, R8W; San Juan County, NM**

Cathodic Protection

ConocoPhillips proposes to drill a cathodic protection deep well groundbed for the subject well. Will drill a 6-7/8" hole to an anticipated minimum depth of 300' (maximum depth of 500'). Cement plugs will not be used unless more than one water zone is encountered. Prior drilling history for the area indicates only one zone to that depth. If more than one water zone is encountered, notification will be made and details of cement and casing will be provided.

All drilling activity will remain on existing well pad and a Farmington based company will be doing the drilling for ConocoPhillips.