Form 3160-5 (April 2004)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CHMDDA	NOTICES	AND	REPORTS	ON	WELL	c
SUNURY	NUTICES	ANIJ	REPURIS	UN	VVELL	. 3

Do not use this form for proposals to drill or to re-enter an

FORM APPROVED
ØMB NO. 1004-0137
Expires March 31, 2007

MSF	080	091	7

6. If Indian, Allottee or Tribe Name

abandoned well. Use Form 3	3160-3 (APD) for such	proposals.		om 9 29	
SUBMIT IN TRIPLICATE - Ot	her instructions on re	verse side (UU0		7. If Unit or CA/As	greement, Name and/or No
1. Type of Well Oil Well X Gas Well Other 2. Name of Operator	100 M	E 63	REGE 070 FARMI	8. Well Name and 1 Hart Canyon 4	
Energen Resources Corporation 3a. Address	36/ER	IN 2008 Some New York of the Control		9. API Well No. 30-045-29081	
2198 Bloomfield Highway, Farmington, 4. Location of Well (Footage, Sec., T., R., M., or Survey Des Sec.04, T30N, R10W 970' FSL, 1 SE/SW		X505)D325-6806 ST. 8		10. Field and Pool Basin Fruitla 11. County or Part San Juan	
12. CHECK APPROPRIATE B	OX(ES) TO INDICAT	E NATURE OF N	IOTICE, REP	ORT, OR OTHER	R DATA
TYPE OF SUBMISSION		TYP	E OF ACTION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production Reclamatio	(Start/Resume)	Water Shut-Off
X Subsequent Report Final Abandonment Notice	Casing Repair Change Plans Convert to Injection	New Construction Plug and Abandon Plug Back	Recomplet Temporarii Water Disp	y Abandon	Other <u>refrac</u>
Attach the Bond under which the work will be perfor following completion of the involved operations. If it testing has been completed. Final Abandonment Not determined that the final site is ready for final inspectic 07/19/05 MIRU. Kill well and TOH with TIH and set 5-1/2" packer @ 2780'. 07/20/05 Pressure test casing to 2 from 3014-24' with 60 holes - 0.43' 2885-89', 2891-93', 2899-2901', 291 07/21/05 Set 5-1/2" frac liner acc 07/22/05 Spearhead 1000 gals 15% If foam 20# Linear gel, 10,000# 40/70 wellhead isolation tool. Flow back 07/25/05 Retrieve frac liner and 1 tool. 07/26/05 Spearhead 2000 gals 15% If foam 20# Linear gel, 10,000# 40/70 wellhead isolation tool. Flow back 07/26/05 Spearhead 2000 gals 15% If foam 20# Linear gel, 10,000# 40/70 wellhead isolation tool. Flow back 07/27-08/02/05 Flow back frac & CO 08/03/05 Land 2-3/8" tubing @ 2905	he operation results in a multices shall be filed only after on.) 1/2-3/8" tubing. TI 2000 psi-ok. Releas 1. Re-perforate Upp 14-16' & 2922-26' w 15-16' & 2922-26' w 15-16' & 35,000# 20/ 15-1	tiple completion or reall requirements, incide the w/5-1/2" case a packer & TOH er Fruitland Coith 108 holes d Coal perfs. Truitland Coal 40 sand @ a maddge plug @ 296 cruitland Coal 40 brady sand cill out BP and	completion in a ruding reclamation in graphed in Re-perform 28 - 0.43". RU stinger from 3014-2 eximum concerns 2851-2 @ a maximum cut	new interval, a Form n, have been completed and bit to the cate Lower Fru 151-57', 2863-wellhead isolation of 3 ager wellhead 1926' with 141 n concentration	3160-4 shall be filed once ted, and the operator has 3080'. TOH. itland Coal 66', 2877-81', ation tool. 0 gals 70Q .4 ppg. RD isolation ,000 gals 70Q n of 5 ppg. RD
14 I hereby certify that the foregoing is true and correct		Title			
Name (Printed Typed) Vicki Donaghey			tory Analys	t ACCEPTE	D FOR RECORD
Mch Donaghly		Date 01/06/06		JAN	17 200s
Approved by	SPACE FOR FEDERAL	Title	ICE USE	PARMINGTOI	V FIELD OFFICE
Conditions of approval, if any, are attached. Approval of t	his notice does not warrent			87	FICE
conditions of approval, it any, are attached. Approval of the certify that the applicant holds legal or equitable title to the which would entitle the applicant to conduct operations there.	ose rights in the subject lea	or Office se			July 1