submitted in lieu of Form 3160-5

UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

۵				50 cm/c	\sim \sim	
	duldry Nocices	and Reports	COUNTY WEALS	20 PM 3	23	
Type of Well GAS				ECENVED	5.	Lease Number NMSF-047020-B If Indian, All. or Tribe Name
Name of Operator				28 29 30 3777 A	. پرک رکن	Unit Agreement Nam
BURLINGTON RESOURCES	OIL & GAS CO	MPANY	1223 100 1100 1100 1100 1100 1100 1100 1	JAN 2006 .ン	756	
Address & Phone No.	of Operator			Nor a DIV.	8	Well Name & Number Calvin #1F
PO Box 4289, Farmi		499 (505) 32	6-9700	· • • • • • • • • • • • • • • • • • • •	(9)	API Well No.
Location of Well, F	lootogo God	7 D W		5/6/5/2/	10.	30-045-33093 Field and Pool
Unit J 1635'FSL, 21			1W, NMPM	CAPTACIAL		Basin Dakota County and State
						San Juan, NM
CHECK APPROPRIATE Type of Submission	BOX TO INDICA		'NOTICE, e of Acti		THER	DATA
Notice of I	intent	Abandonmen		On Change o	f Pla	ns
X Subsequent	Report	Recompleti Plugging B Casing Rep	ack	New Cons Non-Rout	truct ine F	ion racturing
Final Aband		Casing Rep Altering C Other - Co	asing	Water Sh Conversi		Injection
13.Describe Propose	d or Complete	d Operations	}			
13.Describe Propose	d or Complete	ed Operations				
13.Describe Propose	d or Complete	d Operations	,			
/31/05 RU Wireline. Ra	n gauge ring to 6	- 5496'. PBTD (@ 6497'. R			-
/31/05 RU Wireline. Ra CL from 5800' to 4550'. /L.	n gauge ring to 6 Run CBL-GR-	6496'. PBTD @ CCL from 4550	② 6497'. R	e. TOC @ 1		
/31/05 RU Wireline. Ra CL from 5800' to 4550'. /L.	n gauge ring to 6 Run CBL-GR-	6496'. PBTD @ CCL from 4550	② 6497'. R	e. TOC @ 1		
/31/05 RU Wireline. RaCL from 5800' to 4550'. /L. /1/05 RU frac valve. PT	n gauge ring to 6 Run CBL-GR-6 Valve & csg to	5496'. PBTD @ CCL from 4550 4100 psi/15 mi	2) 6497'. R O' to surface nutes. Goo	e. TOC @ 1		
/31/05 RU Wireline. RaCL from 5800' to 4550'. /L. /1/05 RU frac valve. PT	n gauge ring to 6 Run CBL-GR-6 Valve & csg to	5496'. PBTD (CCL from 4550 4100 psi/15 mi	2) 6497'. R.)' to surface nutes. Goo	d test.	40'.	Surface set @ 364'. RD
/31/05 RU Wireline. RacL from 5800' to 4550'. /L. /1/05 RU frac valve. PT . I hereby certify gned	n gauge ring to 6 Run CBL-GR-6 valve & csg to	6496'. PBTD @CCL from 4550 4100 psi/15 mi	2) 6497'. R.)' to surface nutes. Goo	d test.	t Dat	Surface set @ 364'. RD
/31/05 RU Wireline. Ra CL from 5800' to 4550'. /L. /1/05 RU frac valve. PT	n gauge ring to 6 Run CBL-GR- valve & csg to that the for al or State Of if any: it a crime for any per	5496'. PBTD @CCL from 4550 4100 psi/15 mi regoing is tr Title Refice use) Title	2) 6497'. R)' to surface nutes. Goo	d test. rrect. Specialis Dat	t Dat	e 1/19/06 CCEPTED FOR RECO