

OCT 14 2015

**GCU 157**

Dakota

API # 30-045-07067

Sec. 35, T28N, R13W

San Juan County, New Mexico

History

Drill date 2/1964

1/25/08: Cleaned out approx. 67' of fill to 6380'.

Removed bull nose at end of tubing and lowered ~ 100'.

6/11 Wireline: Sand in the lubricator. Retrieved

lunger at 6310', retrieved slip stop at 6312'

Tag at 6350' with no tight spots. Reset same slip stop

at 6315'.

Formation Tops

Oil and shale	0
Fractured Cliffs	1620'
Lawis Shale	1825'
Lesaverde	2535'
Lawcos Shale	4387'
Fullup	5286'
Base Gallup	5796'
Greenhorn	6126'
Laweros Shale	6184'
Laweros Dakota	6248'
Lawin Dakota	6306'

6067 RDB

12-1/4" Hole
8-5/8", 24#, @ 357'
Cmt w/ 225 sks

2-3/8" EOT @ 6342'

Dakota Perforations

6258' - 6266' @ 4 spf } Frac'd w/ 24,900 gal water &
6248' - 6254' @ 4 spf } 660,000 lbs sand

6323' - 6330' @ 6 spf } Frac'd w/ 39,700 gal water &
440,000 lbs sand

Fill at 6380'

7-7/8" Hole
4-1/2", 10.5# @ 6435'
Cmt: w/ 1350 sxs

PBTD: 6398'
TD: 6435'

Amy Adkison (3/31/11)