District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
Permit of a pit or proposed alternative method
 ✓ 15-09188 ✓ Closure of a pit, below-grade tank, or proposed alternative method ✓ Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: E. E. Elliott B #6
API Number: 3004509188 OCD Permit Number:
U/L or Qtr/Qtr F Section 27 Township 30N Range 9W County: San Juan
Center of Proposed Design: Latitude <u>36.78445</u> Longitude <u>-107.77071</u> NAD: □1927 ☑ 1983
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume: 95.0 bbl Type of fluid: Produced water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other <u>Single walled/double bottomed; side walls not visible</u>
Liner type: Thicknessmil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	hognital			
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church)	, поѕриаі,			
Four foot height, four strands of barbed wire evenly spaced between one and four feet				
Alternate. Please specify				
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)				
Screen Netting Other				
Monthly inspections (If netting or screening is not physically feasible)				
Signs: Subsection C of 19.15.17.11 NMAC				
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers				
☐ Signed in compliance with 19.15.16.8 NMAC				
8.	To Mark the second			
<u>Variances and Exceptions</u> : Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.				
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.				
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	eptable source			
General siting				
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA			
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No			
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No			
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No			
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map				
Below Grade Tanks				
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)				
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No				
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 					
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site					
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Temporary Pit Non-low chloride drilling fluid					
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,					
or playa lake (measured from the ordinary high-water mark).	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No				
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock					
watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Permanent Pit or Multi-Well Fluid Management Pit					
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa					
lake (measured from the ordinary high-water mark).					
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No				
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of					
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.					
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.1 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19					
and 19.15.17.13 NMAC	.13.17.9 NWAC				
Previously Approved Design (attach copy of design) API Number: or Permit Number:					
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC					
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	ocuments are				
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC					
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC					
☐ A List of wells with approved application for permit to drill associated with the pit. ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19	9.15.17.9 NMAC				
and 19.15.17.13 NMAC					
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC					
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	44.74.16.1				

and the state of t	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	'luid Management Pit
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable south provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	□ Vas □ Na
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 10/30	0/8015
Title: Comptience Office OCD Permit Number:	
Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 8/13/2009	the closure report.
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with t	his closure report is true, accurate and complete to the best of my knowledge and ure requirements and conditions specified in the approved closure plan.
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Allo Mulo	Date:July 29, 2015
e-mail address: <u>steven.moskal@bp.com</u>	Telephone:(505) 326-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

E. E. Elliott B #6 API No. 3004509188 Unit Letter F, Section 27, T30N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

- 5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 - All equipment associated with the BGT has been removed.
- 6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method 95 bbl BGT	Release Verification (mg/Kg)	Sample results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	0.0033
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	0.0195
TPH	US EPA Method SW-846 418.1	100	37.6
Chlorides	US EPA Method 300.0 or 4500B	250 or background	20

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was submitted for laboratory analysis of TPH, BTEX and chloride. Laboratory results were below the stated limits. The laboratory results are attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no significant release has occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and has been reclaimed since the well was plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT was backfilled with clean soil and has been reclaimed since the well was plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT was backfilled with clean soil and has been reclaimed since the well was plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT was backfilled with clean soil and has been reclaimed since the well was plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP has seeded the area as part of final reclamation since the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011
Conv to appropriate District Office in

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

						OPERA	ГOR	☐ In	itial Report
Name of Company: BP			Contact: Ste	eve Moskal					
Address: 20				Telephone 1	No.: 505-326-94	497			
Facility Na	me: E. E.	Elliott B #6				Facility Typ	e: Natural gas	well	A STATE OF THE STA
Surface Ow	e Owner: Federal Mineral Owner:			Owner:	Federal	Lesinis	API	No. 3004509188	
				LOC	ATIO	N OF RE	LEASE		
Unit Letter	Section	Township	Range	Feet from the		South Line			e County: San Juan
F	27	30N	9W	1,837	North		1,830	West	
		Lati	tude 36	5.78445		Longitude	e <u>-107.77071</u>		
					TIDE	OF REL	The last of the la		
Type of Rele	ase: none		8	INA	TURE		Release: N/A	Volum	e Recovered: N/A
		w grade tank -	95 bbl				Hour of Occurrence		nd Hour of Discovery:
Was Immedi			75 001		14	If YES, To		ce. Date ti	id Hour of Discovery.
			Yes [No Not I	Required				
By Whom?						Date and F	Iour		
Was a Water	course Rea	ched?			6	If YES, Vo	olume Impacting	the Watercourse.	
			Yes 🛚	No					
If a Watercon	ırse was In	npacted, Descr	ibe Fully.*						
							be I have		
									al to ensure no soil impacts from
the BGT. So	il analysis	resulted in TP.	H, BTEX	and chloride bel	ow standa	ırds. Analysi	s results are attac	hed.	
Describe Are	a Affected	and Cleanup	Action Tak	en.* BGT was r	emoved a	and the area u	nderneath the BC	T was sampled.	The area under the BGT was
				active well area.	J110 / Cu 0			or was samplear	
71 1 1	C 1 1 1				1	1		10000	NR (000 1
									ursuant to NMOCD rules and releases which may endanger
									elieve the operator of liability
									ter, surface water, human health
									compliance with any other
		ws and/or regu							
							OIL CON	SERVATIO	N DIVISION
Ciamatuma.	1919	3 Mi							
Signature:	LX00	s in	4						
Printed Name	e: Steve Mo	oskal				Approved by	Environmental S	pecialist:	
Tido: Pi-13 P		4-1 0 1				1.0		Б	D
Title: Field E	nvironmen	tal Coordinato	r		-	Approval Dat	e:	Expiration	n Date:
E-mail Addre	ess: steven.	moskal@bp.co	om			Conditions of	Approval:		
		(J-F.00)							Attached
Date: July 29	2015		Phone: 50	5-326-9497					

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	API#: 3004509188
FIELD REPORT:	BGT CONFIRMATION TEMP. PIT CLOSURE / RELEASE INVESTIGATION (other)	PAGE No:1 of1_
QTR-QTR/FOOTAGE: 1,837'N/	SITE NAME: E.E. ELLIOTT B # 6 P: 30N RNG: 9W PM: NM CNTY: SJ ST: NM 1,830'W SE/NW LEASE TYPE: FEDERAL STATE / FEE / INITERPROD. FORMATION: PC CONTRACTOR: ELKHORN	DIAN DATE STARTED: 08/03/09 DATE FINISHED: DIAN ENVIRONMENTAL SPECIALIST: JCB
1) 95 BGT (SW/DB) 2) 3) 4)	GPS COORD.: GPS COORD.: GPS COORD.:	DISTANCE/BEARING FROM W.H.: DISTANCE/BEARING FROM W.H.:
SAMPLE ID: SAMPLE ID: SAMPLE ID:	CHAIN OF COSTOD I RECORD(S).	ABANALYSIS:
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL CONSISTENCY (NON COHESIVE SOILS): LO PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / DENSITY (COHESIVE CLAYS & SILTS): SOFT MOISTURE: DRY SLIGHTLY MOIST MOIST / MOIST / MO	COHESIVE COHESIVE / HIGHLY COHESIVE DOSE FIRM / DENSE / VERY DENSE COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC T/ FIRM / STIFF / VERY STIFF / HARD	IPOSITE # OF PTS. 5
SITE SKETCH BERM	PROD. TANK FENCE SEPARATOR WOODEN R.W. PBGTL T.B. @ 5' B.G. X - S.	MISCELL. NOTES SW - SINGLE WALLED DW - DOUBLE BOTTOM SIDEWALLS VISIBLE
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXO T.B. = TANK BOTTOM; PBGTL = PREVIOU TRAVEL NOTES: CALLOUT:	AVATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~= APPROX. IS BELOW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING ONSITE: 08/03/09	MAGNETIC DECLINATION @ 13.5°E

EPA METHOD 418.1 TOTAL PETROLEUM **HYDROCARBONS**

Client:	Blagg / BP	Project #:	94034-0010
Sample ID:	95 BGT 5-pt @ 5'	Date Reported:	08-13-09
Laboratory Number:	51153	Date Sampled:	08-03-09
Chain of Custody No:	7670	Date Received:	08-07-09
Sample Matrix:	Soil	Date Extracted:	08-10-09
Preservative:	Cool	Date Analyzed:	08-10-09
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

37.6

16.5

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

EE Elliott B #6.

Review



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics **Total Petroleum Hydrocarbons**

Client:	Blagg/BP	Project #:	94034-0010
Sample ID:	95 BGT 5-pt @ - 5'	Date Reported:	08-12-09
Laboratory Number:	51153	Date Sampled:	08-03-09
Chain of Custody No:	7670	Date Received:	08-07-09
Sample Matrix:	Soil	Date Extracted:	08-10-09
Preservative:	Cool	Date Analyzed:	08-11-09
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

EE Elliott B#6

Analyst

Mustly on Warden



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg/BP	Project #:	94034-0010
Sample ID:	95 BGT 5-pt @ - 5'	Date Reported:	08-12-09
Laboratory Number:	51153	Date Sampled:	08-03-09
Chain of Custody:	7670	Date Received:	08-07-09
Sample Matrix:	Soil	Date Analyzed:	08-11-09
Preservative:	Cool	Date Extracted:	08-10-09
Condition:	Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	0.9
Toluene	3.3	1.0
Ethylbenzene	1.2	1.0
p,m-Xylene	10.1	1.2
o-Xylene	4.9	0.9
Total BTEX	19.5	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

EE Elliott B#6

Analyst

Mustly Maeters Review



Chloride

Client: Sample ID: Lab ID#: Sample Matrix: Preservative:

Condition:

Blagg/BP 95 BGT 5-pt @ 5' 51153 Soil Cool Intact

Project #:
Date Reported:
Date Sampled:
Date Received:
Date Analyzed:
Chain of Custody:

08-12-09 08-03-09 08-07-09 08-11-09 7670

94034-0010

Parameter

Concentration (mg/Kg)

Total Chloride

20

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

EE Elliott B #6.

Analyst

Muster m Weelers Review

CHAIN OF CUSTODY RECORD

7670

	Sample Cool	Sample Intact
		Sample Intact
		Sampl
	V	1
		1-
8/7/3	99	Time 8:28
	Date 8/7/	



5796 US Highway 64 • Farmington, NM 87401 • 505-632-0615 • lab@envirotech-inc.com



EPA METHOD 418.1 TOTAL PETROLEUM HYROCARBONS QUALITY ASSURANCE REPORT

Client:		QA/QC		Project #:		N/A
Sample ID:		QA/QC		Date Reported		08-11-09
Laboratory Numbe	r:	08-10-TPH.QA/	QC 51135	Date Sampled:		N/A
Sample Matrix:		Freon-113		Date Analyzed		08-10-09
Preservative:		N/A		Date Extracted	:	08-10-09
Condition:		N/A		Analysis Need	ed:	TPH
Calibration	I-Cal Date 08-03-09	C-Cal Date 08-10-09	I-Cal RF: 1,380	C-Cal RF: 1,270	% Difference 8.0%	Accept. Range +/- 10%
Blank Conc. (m	ig/Kg)		Concentration ND		Detection Lim	it
Duplicate Cond	c. (mg/Kg)		Sample 386	Duplicate 386	% Difference 0.0%	Accept. Range
Spike Conc. (m	ng/Kg)	Sample 386	Spike Added 2,000	Spike Result 2,320	% Recovery 97.2%	Accept Range 80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 51135 - 51136, 51153 - 51159.

Analyst Analyst

Review



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

0 - 30%

99.2%

104%

Mustu m Wellen Review

Recovery

Accept. Range

75 - 125%

75 - 125%

Client:	QA/QC		Project #:		N/A
Sample ID:	08-11-09 QA/	QC	Date Reported:		08-12-09
Laboratory Number:	51139		Date Sampled:		N/A
Sample Matrix:	Methylene Chlo	ride	Date Received:		N/A
Preservative:	N/A		Date Analyzed:		08-11-09
Condition:	N/A		Analysis Reque	sted:	TPH
	I-Cal Date	I-Cal RF.	C-Cal RF:	% Difference	Accept Range
Gasoline Range C5 - C10	05-07-07	1.0285E+003	1.0289E+003	0.04%	0 - 15%
Diesel Range C10 - C28	05-07-07	1.0946E+003	1.0950E+003	0.04%	0 - 15%
Blank Conc. (mg/L - mg/Kg)		Concentration		Detection Limit	
Gasoline Range C5 - C10		ND		0.2	
Diesel Range C10 - C28		ND		0.1	
Total Petroleum Hydrocarbons		ND		0.2	
Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Difference	Accept Range	
Gasoline Range C5 - C10	ND	ND	0.0%	0 - 30%	

18.8

Spike Added

250

250

6.2%

Spike Result

248

279

ND - Parameter not detected at the stated detection limit.

References:

Diesel Range C10 - C28

Spike Conc. (mg/Kg)

Gasoline Range C5 - C10

Diesel Range C10 - C28

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

17.7

Sample

ND

17.7

Comments:

QA/QC for Samples 51139 - 51141 and 51153 - 51159.

Analyst



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client	N/A	Project #	N/A
Sample ID	08-11-BT QA/QC	Date Reported	08-12-09
Laboratory Number:	51139	Date Sampled	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	08-11-09
Condition:	N/A	Analysis:	BTEX

Calibration and Extention Limits (ug/L)	I-Cal RF	C-Cal RF:	%Dift	Blank	Detect.
Centection Elitits (ogic)		Accept. Rang	je u - 1574	Conc	Limit
Benzene	4.9421E+006	4.9520E+006	0.2%	ND	0.1
Toluane	4.5512E+006	4.5603E+006	0.2%	ND	0.1
Ethylbenzene	3.9553E+006	3 9632E+006	0.2%	ND	0.1
p,m-Xylene	1.0157E+007	1 0177E+007	0.2%	ND	0.1
o-Xylene	3.7742E+006	3.7817E+006	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample	Duplicate	_ %Dift	Accept Range	Detect Limit	- Villege
Benzene	10.1	10.2	1.0%	0 - 30%	0.9	
Toluene	16.1	16.6	3.1%	0 - 30%	1.0	
Ethylbenzene	21.6	22.2	2.3%	0 - 30%	1.0	
p.m-Xylene	44.7	45.5	1.8%	0 - 30%	1.2	
o-Xylene	25.2	25.4	0.8%	0 - 30%	0.9	

Spike Conc. (ug/Kg)	Sample Amo	ount Spiked Spil	ked Jample	% Recovery	Accept Range
Benzene	10.1	50.0	53.0	98.2%	39 - 150
Toluene	16.1	50.0	63.9	96.7%	46 - 148
Ethy/benzene	21.6	50.0	58.4	95.5%	32 - 160
p,m-Xylene	44.7	100	150	103%	46 - 148
o-Xylene	25.2	50.0	70.6	93.9%	46 - 148

ND - Parameter not detected at the stated detection limit,

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Washer LIV-846, USEPA,

December 1996

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996

Comments:

QA/QC for Samples 51139 - 51141 and 51153 - 51159.

Analyst



