<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method
Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration OCT 1 4 2015
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: Johnson 001
API Number: 3004509862 OCD Permit Number:
U/L or Qtr/Qtr J Section 2 Township 30N Range 11W County: San Juan
Center of Proposed Design: Latitude 36.837942 Longitude -107.956297 NAD: □1927 ⋈ 1983
Surface Owner: A Federal A State Private Tribal Trust or Indian Allotment
Surface Owner: Federal State Private Tribal Trust or Indian Allotment Description Descripti
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
☐ String-Reinforced Liner Seams: ☐ Welded ☐ Factory ☐ Other
3. ☐ Below-grade tank: Subsection I of 19.15.17.11 NMAC ☐ Auk 4
Volume: 21.0 bbl Type of fluid: Produced water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other <u>Single walled/double bottomed</u> ; side walls visible
Liner type: Thicknessmil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church)	, hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6. Next in Coloration F of 10.15.17.11 NIMAC (April to the property of the pro	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:	
 □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accer material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	eptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	T. S. A.
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	57.5
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19 15 17 9 NMAC	The Section
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Page 3 of 6

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment	
☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC	
Quality Control/Quality Assurance Construction and Installation Plan	
☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
☐ Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan ☐ Emergency Response Plan	
Oil Field Waste Stream Characterization	
☐ Monitoring and Inspection Plan ☐ Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	Fluid Management Pit
Proposed Closure Method: Waste Excavation and Removal	
 ☐ Waste Removal (Closed-loop systems only) ☐ On-site Closure Method (Only for temporary pits and closed-loop systems) 	
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sou provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written a	pproval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-M	lining and Mineral Division	☐ Yes ☐ No
Within an unstable area.	LOCAL DE LOCAL DE LA COLONIA D	
 Engineering measures incorporated into the design; NM Bureau of Go Society; Topographic map 	eology & Mineral Resources; USGS; NM Geological	☐ Yes ☐ No
Within a 100-year floodplain FEMA map		☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate Proof of Surface Owner Notice - based upon the appropriate requiremed Construction/Design Plan of Burial Trench (if applicable) based upon Construction/Design Plan of Temporary Pit (for in-place burial of a dry Protocols and Procedures - based upon the appropriate requirements of Confirmation Sampling Plan (if applicable) - based upon the appropriate Waste Material Sampling Plan - based upon the appropriate requirement Disposal Facility Name and Permit Number (for liquids, drilling fluids Soil Cover Design - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subse	the requirements of 19.15.17.10 NMAC into the appropriate requirements of Subsection K of 19.15.17. The appropriate requirements of Subsection K of 19.15.17. The appropriate requirements of 19.15. The appropriate requirements of 19.15. The appropriate requirements of 19.15. The app	.11 NMAC 15.17.11 NMAC
17.		
Operator Application Certification: I hereby certify that the information submitted with this application is true, as	ccurate and complete to the best of my knowledge and beli	ief.
Name (Print):		
Name (Fint).	Title.	
Signature:	Date:	
e-mail address:	Telephone:	
OCD Approval: Perr OCD Representative Sign	Plan (only) OCD Conditions (see attachment)	
OCD Representative Sign ULIVILU	Approval Date:	
Title:	OCD Permit Number:	
19. Closure Report (required within 60 days of closure completion): 19.15.17 Instructions: Operators are required to obtain an approved closure plan pri The closure report is required to be submitted to the division within 60 days section of the form until an approved closure plan has been obtained and th	or to implementing any closure activities and submitting of the completion of the closure activities. Please do not e closure activities have been completed.	
	☑ Closure Completion Date: 8/7/2015	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alter ☐ If different from approved plan, please explain.	ernative Closure Method Waste Removal (Closed-lo	oop systems only)
Closure Report Attachment Checklist: Instructions: Each of the following mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closured Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude 36.837942 Long		

22.	
Operator Closure Certification:	
	th this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicable c	closure requirements and conditions specified in the approved closure plan.
	THE CONTRACTOR OF THE CONTRACT
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Alley Wind	
Signature: Stelly Mind	Date: October 12, 2015
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497
o man address. See to man address of the man	

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Johnson 001 API No. 3004509862 Unit Letter J, Section 2, T30N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method 21 bbl BGT	Release Verification (mg/Kg)	Sample results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.040
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.080
TPH	US EPA Method SW-846 418.1	100	<48
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for laboratory analysis of TPH, BTEX and chloride with results below the stated limits.

7. BP shall notify the division District III office of its results on form C-141.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 - Laboratory results indicate no significant release has occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and the well is scheduled for plugging and abandonment.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area under the BGT was backfilled with clean soil and the well is scheduled for plugging and abandonment.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area under the BGT was backfilled with clean soil and the well is scheduled for plugging and abandonment. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rele	ease Notifi	catio	n and C	orrective A	ction				
						OPERA	TOR		Initi	al Report	\boxtimes	Final Report
Name of Co	ompany: B	P				Contact: St	eve Moskal					
Address: 20	00 Energy	Court, Farmi	ngton, N	M 87401		Telephone	No.: 505-326-94	197				
Facility Na	me: Johnso	on 001					pe: Natural gas v	well	W.			
Surface Ow	mer: Feder	Sm)		Mineral (Owner	Fee (m)			API No	. 30045098	362	
							LEACE					
Unit Letter	Section	Township	Range	Feet from the		N OF RE	Feet from the	Fast/W	est Line	County: Sa	an Iuan	
J	2	30N	11W	1,650	South		1,550	East	est Effic	County. 5	an suan	
		Latitu	ide 36.	837942		Longitud	e -107.956297					
				NAT	TURE	OF REL	EASE					
Type of Rele	ase: N/A	4 15 17		1112			f Release: none		Volume	Recovered:	none	
Source of Re				4 - 4 - 4			Hour of Occurrence	ce: N/A	Date and	Hour of Di	scovery	: N/A
Was Immedi	ate Notice (Yes [No ⊠ Not R	eauired	If YES, To	Whom?		HISK			
By Whom?				, , , ,		Date and I	Jones					
Was a Water	course Reac	ched?			-		olume Impacting t	the Water	course.			
			Yes 🛛	No		12.0,	oranie impaeting i		Course			
If a Watercon	urse was Im	pacted, Descri	be Fully.*				14 W. 11 11 11 11 11 11 11 11 11 11 11 11 11			1 4 5	M	
		em and Remed							113			
		ow grade tank and Cleanup A		soil was sampled	with no	significant ir	npacts noted.					
Describe Are	a Affected a	and Cleanup P	iction rak	en.								
	location of						curred. The attach pad area. Reclam					
regulations a public health should their of or the environment	Il operators or the envir operations h nment. In a	are required to ronment. The ave failed to a	report an acceptance dequately CD accep	nd/or file certain in the of a C-141 report investigate and in	release of ort by the remedia	notifications a ne NMOCD m te contaminat	knowledge and u nd perform correct tarked as "Final Roion that pose a through the operator of the	etive action eport" do eat to gro responsib	ons for rele es not reli und water ility for co	eases which eve the oper s, surface was compliance w	may end ator of l ter, hum ith any	danger liability nan health
	11	2					OIL CONS	SERVA	ATION	DIVISIO	N	
Signature:	elle	Men)										7 7 1
Printed Name		skal				Approved by	Environmental Sp	pecialist:	this s			
Title: Field E	nvironment	al Coordinator	r			Approval Da	te:	E	xpiration l	Date:		
E-mail Addre	ess: steven.n	noskal@bp.co	m			Conditions o	f Approval:			Attached		
Date: Octobe	er 12, 2015		Phone	: 505-326-9497					40	- Andriod		X 2 1 1 1

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	API #:3004509862 TANK IDA
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE#: 1 of 1
1/4 -1/4/FOOTAGE: 1,650'S / 1,5	SITE NAME: JOHNSON # 1 30N RNG: 11W PM: NM CNTY: SJ ST: NM 50'E NW/SE LEASE TYPE: FEDERAL / STATE FEE INDIAN PROD. FORMATION: PC CONTRACTOR: MBF - C. PARKS	DATE STARTED: 08/06/15 DATE FINISHED: ENVIRONMENTAL SPECIALIST(S): NJV
REFERENCE POINT 1) 21 BGT (SW/DB) 2) 3)	WELL HEAD (W.H.) GPS COORD.: 36.83803 X 107.95634 GPS COORD.: 36.837942 X 107.956297 DISTANCE/BEAL GPS COORD.: DISTANCE/BEAL GPS COORD.: DISTANCE/BEAL	GL ELEV.: 5,827' RING FROM W.H.: 34.5', S11E RING FROM W.H.: RING FROM W.H.:
2) SAMPLE ID:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	
	SAMPLE DATE:SAMPLE TIME:LAB ANALYSIS: SOIL TYPE: SAND/ SILT/ SILT/ SILTY CLAY / CLAY / GRAVEL / OTHER	
	COHESIVE / COHESIVE / HIGHLY COHESIVE OSE FIRM DENSE / VERY DENSE HC ODOR DETECTED: YES NO EXPLANATION - OF PTS	STIFF / VERY STIFF / HARD
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: >100' N		TIMATION (Cubic Yards) : NA ED TPH CLOSURE STD: 1,000 ppm
SITE SKETCH TO METER RUN NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	BGT Located: off on site PLOT PLAN circle: attached OWN W.H. PERIMETER SECURITY FENCE PRODUCT SURFACE DRAINAGE DIRECTION N DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~= APPROX; W.H. = WELL HEAD;	CALIB. READ. = NA ppm RF = 0.52 CALIB. GAS = NA ppm MISCELL. NOTES /O: EF #: P-225 K: ZDCS01DRL1 J #: ermit date(s): 06/14/10 CD Appr. date(s): 08/03/15 OVM = Organic Vapor Meter ppm = parts per million BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELI	DW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT WALL; DW-DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM.	lagnetic declination: 10° E



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

OrderNo.: 1508275

October 12, 2015

Nelson Velez
Blagg Engineering
P. O. Box 87
Bloomfield, NM 87413

TEL: (505) 320-3489 FAX (505) 632-3903

RE: Johnson #1

Dear Nelson Velez:

Hall Environmental Analysis Laboratory received 1 sample(s) on 8/7/2015 for the analyses presented in the following report.

This report is a revised report and it replaces the original report issued August 11, 2015.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to www.hallenvironmental.com or the state specific web sites. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. All samples are reported as received unless otherwise indicated.

Please don't hesitate to contact HEAL for any additional information or clarifications.

Sincerely,

Andy Freeman

Laboratory Manager

4901 Hawkins NE

Albuquerque, NM 87109

Analytical Report

Lab Order 1508275

Date Reported: 10/12/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB@7' (21)

Collection Date: 8/6/2015 9:20:00 AM

Project: Johnson #1 Lab ID:

1508275-001

Matrix: MEOH (SOIL)

Received Date: 8/7/2015 8:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS			Targeto.		Analyst:	LGT
Chloride	ND	30	mg/Kg	20	8/7/2015 12:03:02 PM	20668
EPA METHOD 8015M/D: DIESEL RANGE	ORGANIC	S			Analyst:	KJH
Diesel Range Organics (DRO)	ND	9.5	mg/Kg	1	8/7/2015 11:15:23 AM	20664
Motor Oil Range Organics (MRO)	ND	48	mg/Kg	1	8/7/2015 11:15:23 AM	20664
Surr: DNOP	83.8	57.9-140	%REC	1	8/7/2015 11:15:23 AM	20664
EPA METHOD 8015D: GASOLINE RANGE					Analyst:	RAA
Gasoline Range Organics (GRO)	ND	4.0	mg/Kg	1	8/7/2015 10:54:06 AM	20637
Surr: BFB	86.7	75.4-113	%REC	1	8/7/2015 10:54:06 AM	20637
EPA METHOD 8021B: VOLATILES					Analyst:	RAA
Benzene	ND	0.040	mg/Kg	1	8/7/2015 10:54:06 AM	20637
Toluene	ND	0.040	mg/Kg	1	8/7/2015 10:54:06 AM	20637
Ethylbenzene	ND	0.040	mg/Kg	1	8/7/2015 10:54:06 AM	20637
Xylenes, Total	ND	0.080	mg/Kg	1	8/7/2015 10:54:06 AM	20637
Surr: 4-Bromofluorobenzene	92.5	80-120	%REC	1	8/7/2015 10:54:06 AM	20637

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- Value above quantitation range E
- Analyte detected below quantitation limits Page 1 of 5
- Sample pH Not In Range P
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1508275

12-Oct-15

Client:

Blagg Engineering

Project:

Johnson #1

Sample ID MB-20668

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 20668

RunNo: 28069

Prep Date: 8/7/2015

Analysis Date: 8/7/2015

SeqNo: 845462

Units: mg/Kg

Qual

Analyte Chloride

Result

PQL SPK value SPK Ref Val %REC LowLimit

%RPD HighLimit

RPDLimit

ND 1.5

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Sample ID LCS-20668

Prep Date: 8/7/2015

Batch ID: 20668

RunNo: 28069 SeqNo: 845463

Units: mg/Kg

%RPD

Analyte

Analysis Date: 8/7/2015 PQL

SPK value SPK Ref Val

%REC

HighLimit

RPDLimit

Qual

110

Chloride

15

1.5

15.00

0

100

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- Value above quantitation range
- Analyte detected below quantitation limits
- Sample pH Not In Range
- Reporting Detection Limit

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

PQL

10

Result

48

4.8

WO#: 1508275

12-Oct-15

Client:

Blagg Engineering

Project:

Analyte

Surr: DNOP

Diesel Range Organics (DRO)

Johnson #1

Sample ID MB-20664 Client ID: PBS Prep Date: 8/7/2015	SampType: MBLK Batch ID: 20664 Analysis Date: 8/7/2015		F	tCode: El RunNo: 2 SeqNo: 8	8026	I 8015M/D: Diesel Range Organics Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10	1.74			1			No.	
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.8		10.00		98.5	57.9	140			
Sample ID LCS-20664	SampT	ype: LC	s	Tes	Code: El	PA Method	8015M/D: Die	esel Range	e Organics	
Client ID: LCSS	Batcl	ID: 20	664	F	unNo: 2	8026				
Prep Date: 8/7/2015	Analysis D	ate: 8	7/2015	c	egNo: 8	13786	Units: mg/K	a		

HighLimit

139

140

LowLimit

95.7

57.4

57.9

%RPD

RPDLimit

SPK value SPK Ref Val %REC

50.00

5.000

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#: 1508275

12-Oct-15

Client:

Blagg Engineering

Project:

Johnson #1

Sample ID LCS-20637 SampType: LCS TestCode: EPA Method 8015D: Gasoline Range Client ID: LCSS Batch ID: 20637 RunNo: 28035 Prep Date: 8/6/2015 Analysis Date: 8/7/2015 SeqNo: 844373 Units: mg/Kg Result PQL SPK value SPK Ref Val %REC %RPD **RPDLimit** Analyte LowLimit HighLimit Qual Gasoline Range Organics (GRO) 21 5.0 25.00 84.9 79.6 122

Surr: BFB 920 1000 92.2 75.4 113

Sample ID MB-20637 SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range Client ID: PBS Batch ID: 20637 RunNo: 28035

Prep Date: 8/6/2015 Analysis Date: 8/7/2015 SeqNo: 844374 Units: mg/Kg

Analyte Result PQL SPK value SPK Ref Val %REC HighLimit %RPD **RPDLimit** Qual LowLimit

Gasoline Range Organics (GRO) 5.0 ND

Surr: BFB 880 1000 87.8 113 75.4

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R
- S % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits
- Sample pH Not In Range
- Reporting Detection Limit

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1508275

12-Oct-15

Client:

Blagg Engineering

Project:

Johnson #1

Sample ID LCS-20637	ple ID LCS-20637 SampType: LCS				TestCode: EPA Method 8021B: Volatiles						
Client ID: LCSS Batch ID: 20637				F	RunNo: 28035						
Prep Date: 8/6/2015 Analysis Date: 8/7/2015			8	SeqNo: 8	44420	Units: mg/k	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	0.94	0.050	1.000	0	94.4	76.6	128			Tolland.	
Toluene	0.94	0.050	1.000	0	93.5	75	124				
Ethylbenzene	0.90	0.050	1.000	0	90.5	79.5	126				
Xylenes, Total	2.9	0.10	3.000	0	98.1	78.8	124				
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120				

Sample ID MB-20637	SampType: MBLK Batch ID: 20637 Analysis Date: 8/7/2015			TestCode: EPA Method 8021B: Volatiles										
Client ID: PBS				F	RunNo: 2	8035								
Prep Date: 8/6/2015				SeqNo: 844423			Units: mg/l							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	ND	0.050		***										
Toluene	ND	0.050												
Ethylbenzene	ND	0.050												
Xylenes, Total	ND	0.10												
Surr: 4-Bromofluorobenzene	0.97		1.000		96.6	80	120							

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client	Name: B	LAGG		Work Order Num	ber: 1508275		RcptNo: 1	
Recei	ved by/date:	Ja		08 07/15				T-Earl
Logge	d By	Ashley Gal	egos	8/7/2015 8:00:00 A	М	A		
the state of the s	ON THE REAL PROPERTY.	Ashley Gall		8/7/2015 8:48:38 A		A		
E-13/12	wed By:	Charles de la constitución de	05	08/07/15		- ' 0		1
240	of Custo	-		9-412				
	And the same of the same of		mple bottles?		Yes 🗆	No 🗆	Not Present 🗹	
15 3000	Chain of Cu:				Yes 🗹	No 🗆	Not Present	
3. H	ow was the s	ample delive	ered?		Courier			
Log	<u>In</u>							
4. W	as an attem	pt made to	cool the samp	les?	Yes 🗹	No L	NA 🗆	
5. W	ere all samp	les received	at a tempera	ture of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
6. s	ample(s) in p	roper conta	iner(s)?		Yes 🗸	No 🗆		
7. Si	ufficient samp	ple volume f	or Indicated t	est(s)?	Yes 🗹	No 🗆		
8. Ar	e samples (e	except VOA	and ONG) pr	operly preserved?	Yes 🗹	No 🗆		
9. W	as preservat	ive added to	bottles?		Yes 🗆	No 🗹	NA 🗆	
10.vo	DA vials have	e zero heads	space?		Yes 🗆	No 🗆	No VOA Vials	
11. W	ere any sam	ple containe	ers received t	roken?	Yes 🗆	No 🗸	# of preserved	
12 D	oes paperwo	ek mutek ko	Selected att		Yes 🗸	No 🗆	bottles checked for pH:	
			ain of custody)	169 (3)	110	(<2 or >12 unless no	oted)
13. Ar	e matrices c	orrectly iden	tified on Cha	n of Custody?	Yes 🗸	No L	Adjusted?	-
14. Is it clear what analyses were requested?					Yes 🗸	No 🗆	25 W. N.	
	ere all holding no, notify cu		to be met? authorization.		Yes 🗸	No L	Checked by:	
-	ial Handli		AND PROPERTY.	vith this order?	Yes 🗌	No 🗆	NA 🗹	
10. **			sciepaticies (
- 4	Person N	STATE OF		Dat	AND THE PERSON NAMED IN	Phone Fax	☐ In Person	
	By Whor Regardin			Via	eMail	Phone Fax	L] III F GISOII	
	THE PARTY OF THE P	structions		The state of the s	Company of the last			
17. A	dditional rem							
-11146								
18. <u>C</u>	Cooler No	Temp °C	Condition	Seal Intact Seal No	Seal Date	Signed By		
	1	2.7	Good	Yes	310.000			

Chain-of-Custody Record Client: BLAGG ENGR. / BP AMERICA Mailing Address: P.O. BOX 87 BLOOMFIELD, NM 87413 Phone #: (505) 632-1199 email or Fax#:			Turn-Around Time: SAME Standard Rush DAY Project Name: TOHASON # Project #:				HALL ENVIRONMENTAL ANALYSIS LABORATORY www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109 Tel. 505-345-3975 Fax 505-345-4107														
												Allai	ysis	Nec	lues		1)				
QA/QC Package: Standard Level 4 (Full Validation)			NEUSON VELEZ			(80218)	(Aluo	MRO)			(S)		05,400	8081 Pesticides / 8082 PCB's	A)	i-voa)	er - 300.1)		9		
Accreditation: NELAP			Sampler: NELSON VELEZ On Ice: De Yes □ No Sample Temperature: 2.7			TMB/s (80	TPH (Gas	/ DRO /	118.1)	504.1)	32705IN		03,NO2,				il - 300.0 / water		e sampl		
						I T	+ 3	GRC	700	po	or	tals	N.	cide				9	osit		
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX + MTBE	BTEX + MTBE + TPH (Gas only)	TPH 80158 (GRO / DRO / MRO)	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 82705IMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesti	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil	Grab sample	5 pt. composite sample	
इ/6/15	0920	SOIL	596-TBC7'(21)	4021	Cool	-001	×		X									×		×	- A - A - A - A - A - A - A - A - A - A
		•																			
Date: 8/6/15 Date: 8/in/ir	Time:	Relinquist	Man y	Received by: Chustle Received by: Amga	u Walters ellijos	Date Time 8/4/15 1009 Date Time 08/07/15 0800	Remarks: BILL DIRECTLY TO BP: Jeff Peace, 200 Energy Court, Farmington, NM 87401 Reference #: P-225 Paykey: Z0C391.						1.DR	<u>'</u>	L						



