

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED  
OMB No. 1004-0137  
Expires: October 31, 2014

**SUNDRY NOTICES AND REPORTS ON WELLS**  
**Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.**

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		5. Lease Serial No. Fee & Fed (NMSF-081332/081332-B)
2. Name of Operator Anschutz Exploration Corporation		6. If Indian, Allottee or Tribe Name
3a. Address 555 17th Street, Suite 2400, Denver, CO 80202	3b. Phone No. (include area code) (303) 298-1000	7. If Unit of CA/Agreement, Name and/or No.
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) SHL Unit B, 1070' FNL & 2382' FEL of Section 14, T25N, R2W BHL Unit B, 865' FNL & 1825' FEL of Section 15, T25N, R2W		8. Well Name and No. Regina Com 25-2-14-15 #1H
		9. API Well No. 30-039-31203
		10. Field and Pool or Exploratory Area Gavilan Mancos
		11. County or Parish, State Rio Arriba, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input checked="" type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recomplate in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

TD 12-1/4" hole at 3795' at 09:00 hrs on 12/23/14. Circulate hole & run wiper trip to prep hole for 9-5/8" casing. Run 39 jts of 9-5/8", 40#, J55, LT&C and 54 jts of 9-5/8", 36#, J55, LT&C casing. Land casing at 3795', annular csg packer at 1478' & DV tool at 1475'. RU Baker & hold safety meeting. Mix and pump 1st stage as follows: 25 bbls FW, 20 bbls Seal Bond Spacer, 510 sx (1132 cf) of Class G w/ CSEII, LW6, CD32, FL 52, FP6L & 1/4# celloflake. 201 bbls of slurry at 12.0 ppg. Displace w/284 bbls of FW & mud. Bump plug at 860 psi. Check floats - holding OK. Inflate ACP at 2200 psi. Drop bomb & open DV tool at 800 psi. Circulated 52 bbls of cement to surface. Pump 2nd state as follows: 25 bbls FW, 20 bbls of Seal Bond spacer, 336 sx (746 cf) of Class G w/ CSEII, LW6, CD32, FL52, FP6L & 1/4# celloflake. Displace w/ 114 bbls of mud. Bump plug to 2050 psi. Floats held OK. Circulate 40 bbls of cement to surface, WOC, ND BOP, set slips & cut off casing. NU 11" BOPE equipment. 3rd party pressure test annular preventor 250 psi (low) for 5 min & 2000 psi (high) for 10 min. BOPE & related equipment surface equipment 250 psi (low) for 5 min & 3000 psi (high) for 10 min. Test casing to 2000 psi for 30 min. All tests good.

OIL CONS. DIV DIST. 3

NOV 18 2015

ACCEPTED FOR RECORD

OCT 28 2015

FARMINGTON FIELD OFFICE  
BY: William Tamblekou

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Randall W. Maxey	AMENDED ORIGINALSUBMISSION OF 1/5/2015
Signature <i>Randy M. Maxey</i>	Title Permitting and Regulatory Manager
	Date 10/23/2015

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

AV