Current Schematic ConocoPhillips Well Name: WHAN JONES #1 API/UWI 3004505660 Well Configuration Type urface Legal Local **NEW MEXICO** 030-026N-008W-K BALLARD PC (GAS #0060 Ground Elevation (ft) Original KB/RT Elevation (ft) KB-Casing Flange Distance (ft) KB-Tubing Hanger Distance (ft) 6,264.00 6,272.00 8.00 Original Hole, 9/28/2015 3:37:30 PM MD Formation Tops (ftKB) Vertical schematic (actual) 7.9 1; Surface; 8 5/8 in; 8.097 in; 8.0 ftKB; 90.9 92.0 ftKB Surface Casing Cement; 8.0-92.0; 2/12/1955; Cemented w/ 75 sx cement. TOC @ surface w/ 75% eff. Tubing; 2 1/16 in; 3.25 lb/ft; J-55; 7.9 OJO ALAMO 1,131.9 ftKB; 1,899.9 ftKB **KIRTLAND** 1,227.0 OIL CONS. DIV DIST. 3 1,390.1 SEP 3 0 2015 1,681.1 **网** Hydraulic Fracture; 9/30/2004; Frac'd 据 器 FRUITLAND 1,733.9 w/ 26,000 gals 20# linear gel w/ 75Q Fruitland Coal; 1,681.0-1,840.0; **33 88** foam; 80,000# 20/40 AZ sand; 831 1/1/2004 **网络** Mscf N2. 1,839.9 1,897.0 100 日 1,899.9 M M 田瀬 THE RES MA WA Intermediate Casing Cement; 1,390.0-Pup Joint; 2 1/16 in; 3.25 lb/ft; J-55; 1,900.9 SE SEC 1,901.0; 3/17/1955; Cemented w/ 100 PICTURED CLIFFS in page 1,899.9 ftKB; 1,902.0 ftKB sx cement. TOC @ 1390' w/ 75% eff. 0680 1,901,9 880 BOH 幅 凝解 磁 颛 1,905.8 **100** 88 2; Intermediate; 5 1/2 in; 5.012 in; 8.0 C. STA 8 1,907.2 ftKB; 1,907.0 ftKB Tubing; 2 1/16 in; 3.25 lb/ft; J-55; MAR 1,902.0 ftKB; 1,933.5 ftKB 144 Market . 1.933.4 2000 Seat Nipple; 2 1/16 in; 3.25 lb/ft; J-55; 1 1,933.5 ftKB; 1,934.2 ftKB 1,934.1 WAST. Expendable Check; 2 1/16 in; 3.25 lb/ft; **新教室** J-55; 1,934.2 ftKB; 1,935.0 ftKB 1.935.0 (B) (B) **BASS Septe MAGE** Hydraulic Fracture; 5/23/1996; Frac'd 190999 20750 w/ 24,000 gals 30# linear gel w/ 70Q Pictured Cliffs; 1,897.0-2,045.0; foam; 80,000# 20/40 AZ sand; 877,775 1 5/23/1996 300 scf N2. 266 2.044.9 2.053. PBTD; 2,053.0 3; Production; 3 1/2 in; 2.992 in; 8.0 ftKB; Adjusted set depth for an 8' KB from a 10' KB.; 2,056.3 ftKB 2.053.8 Auto cement plug; 2,053.0-2,063.0; 5/20/1996; Automatically created 2.055.8 cement plug from the casing cement because it had a tagged depth. Production Casing Cement; 8.0-2,056.4 2,063.0; 5/20/1996; Cemented w/ 200 sx Class A 50/50 poz. Circulated 5 2,063,0 bbls good cement. CBLS shows cement to surface. Report Printed: 9/28/2015 Page 1/1