District I v 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

P. er State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
13687 Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
45-30687 Closure of a pit, below-grade tank, or proposed alternative method DEC 15 2015 Modification to an existing permit/or registration DEC 15 2015
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
ease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the avironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
L. Operatory ConcernPhilling Company, OCPID #: 217817
Operator: ConocoPhillips Company OGRID #: 217817 Address: PO BOX 4289, Farmington, NM 87499
Facility or well name: <u>Newsom 18E</u>
API Number: 30-045-30687 OCD Permit Number: U/L or Qtr/Qtr F (SENW) Section 20 Township 26N Range 8W County: San Juan
Center of Proposed Design: Latitude <u>36.4755889</u> <u>•N</u> Longitude <u>-107.7085944</u> <u>•W</u> NAD: □1927 ⊠ 1983
Surface Owner: X Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3,
Below-grade tank: Subsection I of 19.15.17.11 NMAC
Volume: <u>120</u> bbl Type of fluid: <u>Produced Water</u>
Tank Construction material: Metal
Secondary containment with leak detection 🛛 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
□ Visible sidewalls and liner □ Visible sidewalls only □ Other
Liner type: Thickness mil HDPE PVC Other Unspecified
4.
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)
Four foot height, four strands of barbed wire evenly spaced between one and four feet
Alternate. Please specify
Form C-144 Oil Conservation Division Page 1 of 6

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

7.

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

- Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.
 Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	17.36.1
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank	□ Yes □ No ⊠ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ⊠ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	- / .
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🛛 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🛛 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No

Within 100 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes 🗌 No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	Yes No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMA Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docum attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	ments are IMAC .17.9 NMAC
11.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docum attached.	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	documents are
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method Onesite Trench Burial	luid Management Pit
 Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC More that the comments of the plane of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. More that the procedures - based upon the appropriate requirements of 19.15.17.13 NMAC More that the procedures - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC More that the procedure of the plane of the pl	
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. If 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste	□ Yes □ No □ NA □ Yes □ No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	
Form C-144 Oil Conservation Division Page 4 of	6

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No
Within an unstable area.	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain.	
- FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure p by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Maste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cand Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	7.11 NMAC 9.15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and be	lief.
Name (Print): Title:	
Signature: Date:	101
e-mail address: Telephone:	1 States
18.	
OCD Approval: Permit Application (including closure plan) Closure Plan (only). OCD Conditions (see attachment)	
OCD Representative Signature: Date: 1212 Approval Date: 1212	112015
Title: Environmental Speedist OCD Permit Number:	225 C 1924
19.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do no section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 10/20/2014	
20.	
Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.	oop systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in	ndicate, by a check

Oil Conservation Division

22. Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

 Name (Print):
 Crystal Walker
 Title:
 Regulatory Coordinator

 Signature:
 Signature:
 Date:
 12/11/2015

 e-mail address:
 crystal.walker@cop.com
 Telephone:
 (505) 326-9837

ConocoPhillips Company San Juan Basin Below Grade Tank Closure Report

Lease Name: Newsom 18E API No.: 30-045-30687

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure of the below-grade tank referenced above. All proper documentation regarding closure activities is being included with the C-144.

General Plan:

 COPC shall close a below-grade tank within 60 days of cessation of operations per Subsection G.4 of 19.15.17.13 NMAC. This will include a) below-grade tanks that do not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC; b) an earlier date that the division requires because of imminent danger to fresh water, public health or the environment. For any closure, COPC will file the C144 Closure Report as required.

The below-grade tank referenced above was permitted and closed within 60 days of cessation of the below-grade tanks operation.

 COPC shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall dispose of the liquids and sludge in a division-approved facility. The facilities to be used will be Basin Disposal (Permit #NM-01-005), JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) and Envirotech Land Farm (Permit #NM-01-011). The liner after being cleaned well (Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC) will be disposed of at the San Juan County Regional Landfill located on CR 3100.

All recovered liquids were disposed of at Basin Disposal (Permit #NM-01-005) and any sludge or soil required to be removed to facilitate closure was hauled to Envirotech Land Farm (Permit #NM-01-011) and JFJ Landfarm % IEI (Permit #NM-01-0010B). The liner was cleaned per Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC was disposed of at the San Juan County Regional Landfill located on CR 3100.

3. COPC will receive prior approval to remove the below-grade tank and dispose of it in a division-approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves.

The below-grade tank was disposed of in a division-approved manner.

4. If there is any on-site equipment associated with a below-grade tank, then COPC shall remove the equipment, unless the equipment is required for some other purpose.

All on-site equipment associated with the below-grade tank was removed.

5. COPC will test the soils beneath the below-grade tank to determine whether a release has occurred. COPC shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyzed for the constituents listed in Table I of 19.15.17.13 NMAC. COPC shall notify the division of its results on form C-141.

A five point composite sample was taken of the below-grade tank using sampling tools and all samples tested per Subsection B of 19.15.17.1 3(B)(1)(b). (Sample results attached). Form C-141 is attached.

Components	Tests Method	Limit (mg/kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	100
Chlorides	EPA 300.0	250

 If COPC or the division determines that a release has occurred, then COPC shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.

A release was determined for the above referenced well.

7. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Table I of 19.15.17.13 NMAC, then COPC shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the site.

The below-grade tank area passed all requirements of Paragraph (4) of Subsection E of 19.15.17.13 NMAC and was backfilled with compacted, non-waste containing, earthen material.

- 8. Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email or verbally. The notification of closure will include the following:
 - i. Operator's name
 - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.

Notification is missing.

9. The surface owner shall be notified of COPC's closing of the below-grade tank 72 hours, but not more than one week, prior to closure as per the approved closure plan via certified mail, return receipt requested.

The closure process notification to the landowner was not found.

10. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.

The below-grade tank area was re-contoured to match fit, shape, line, form and texture of the surrounding area. Re-shaping including drainage control, to prevent ponding and erosion. Natural drainages were unimpeded and water bars and/or silt traps were placed in areas where needed to prevent erosion on a large scale. Final recontour has a uniform appearance with smooth surface, fitting the natural landscape.

11. COPC shall seed the disturbed areas the first favorable growing season following closure of a below-grade tank. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM stipulated seed mixes will used on federally regulated lands and division-approved seed mixtures (administratively approved if required) will be utilized on all State or private lands. A uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre- disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds. If alternate seed mix is required by the state, private owner or tribe, it will be implemented with administrative approval if needed. COPC will repeat seeding or planting will be continued until successful vegetative growth occurs. Provision 13 was accomplished through complying with BLM seeding requirements as allowed by the BLM/OCD MOU.

12. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material, with chloride concentrations less than 600 mg/kg as analyzed by EPA Method 300.0, to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.

The below-grade tank area was backfilled and more than four feet of cover was achieved and the cover included one foot of suitable material to establish vegetation at the site.

- 13. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on C-144 and incorporate the following:
 - Soil Backfilling and Cover Installation (See Report)
 - Re-vegetation application rates and seeding techniques (See Report)
 - Photo documentation of the site reclamation (Included as an attachment)
 - Confirmation Sampling Results (Included as an attachment)
 - Proof of closure notice (Missing)

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office to accordance with 19.15.29 NMAC.

						OPERA '	TOR		Initia	al Report 🛛 Final Repo
Name of Co	mpany C	onocoPhillip	s Compan	y	(Contact Lis	sa Hunter			
Address 3401 East 30th St, Farmington, NM						Telephone 1	No. (505) 258-1	1607	a state	State The West and
Facility Nar	ne: News	om 18E			1	Facility Typ	be: Gas Well (I	P&A)	and the second	
Surface Ow	ner Fede	ral		Mineral C	Owner	Federal (S	F-078433)		API No	o. 3004530687
				LOCA	ATION	OF RE	LEASE			
Unit Letter Section Township Range Feet from					a second s	h/South Line Feet from the E		East/West Line West		County
Type of Rele	ase Proc	luced Water			75849 TURE	Longit	Release Unk	7 nown	Volume I	San Juan Recovered None
F	20	26N	08W	Latitude <u>36.47</u>	5849	_ Longit	ude - <u>107.70925</u>		Vest	San Juan
Type of Rele	ase Proc	luced Water		Latitude <u>36.47</u>	75849 TURE	Longit	ude - <u>107.70925</u> EASE FRelease Unkn Hour of Occurrence	7 nown	Volume I	Recovered None Hour of Discovery
Type of Rele Source of Re	ase Proc lease Belo	luced Water ow Grade Ta Biven?	nk (BGT)	Latitude <u>36.47</u> NAT	75849 TURE	Longit OF REL Volume of Date and H	ude - <u>107.70925</u> EASE FRelease Unki Hour of Occurrence	7 nown	Volume I Date and	Recovered None Hour of Discovery
Type of Rele Source of Re Was Immedia	ase Proc lease Belo	luced Water ow Grade Ta Biven?	nk (BGT)	Latitude <u>36.47</u> NAT Closure Resam	75849 TURE	Longit OF REL Volume of Date and F Unknown If YES, To	ude - <u>107.70925</u> EASE Release Unk Hour of Occurrence Whom?	7 nown	Volume I Date and	Recovered None Hour of Discovery
F Type of Relea Source of Re Was Immedia By Whom? Was a Watero	ase Proc lease Belo ate Notice C N/A	luced Water ow Grade Ta diven?	nk (BGT)	Latitude <u>36.47</u> NAT Closure Resam No 🛛 Not Re	75849 TURE	Longitu OF REL. Volume of Date and H Unknown If YES, To N/A Date and H	ude - <u>107.70925</u> EASE Release Unk Hour of Occurrence Whom?	7 nown ce	Volume F Date and 11/03/15	Recovered None Hour of Discovery

Describe Area Affected and Cleanup Action Taken.*

NMOCD action levels for releases are specified in NMOCD's Guidelines for Leaks, Spills and Releases and the release was assigned a ranking score of 0. Samples were collected and analytical results for methods 418.1, 8015 & 8021 are below applicable NMOCD action levels. Although Chloride levels were above Regulatory Standards at 440 mg/Kg, the chloride contaminates are below surface and COPC believes they will not pose an environmental threat, and that no further work will be required. The final lab report is attached for review. Samples were collected by third-party environmental using a geo-probe in the center of former BGT area to the extent of 8 feet.

I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.

E	OIL CONSERVATION DIVISION				
Signature: Julie H					
Printed Name: Lisa Hunter	Approved by Environmental Sp	pecialist:			
Title: Field Environmental Specialist	Approval Date:	Expiration	Date:		
E-mail Address: Lisa.Hunter@cop.com	Conditions of Approval:		Attached		
Date: December 4, 2015 Phone: (505) 258-1607					

* Attach Additional Sheets If Necessary



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: <u>www.hallenvironmental.com</u>

November 11, 2015

Emilee Skyles Animas Environmental 604 Pinon Street Farmington, NM 87401 TEL: (505) 564-2281 FAX

OrderNo.: 1511110

Dear Emilee Skyles:

RE: CoPC Newsom 18E

Hall Environmental Analysis Laboratory received 1 sample(s) on 11/4/2015 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to <u>www.hallenvironmental.com</u> or the state specific web sites. In order to properly interpret your results it is imperative that you review this report in its entirety. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. When necessary, data qualifers are provided on both the sample analysis report and the QC summary report, both sections should be reviewed. All samples are reported, as received, unless otherwise indicated. Lab measurement of analytes considered field parameters that require analysis within 15 minutes of sampling such as pH and residual chlorine are qualified as being analyzed outside of the recommended holding time.

Please don't hesitate to contact HEAL for any additional information or clarifications.

ADHS Cert #AZ0682 -- NMED-DWB Cert #NM9425 -- NMED-Micro Cert #NM0190

Sincerely,

andy

Andy Freeman Laboratory Manager 4901 Hawkins NE Albuquerque, NM 87109

Analytical Report Lab Order 1511110

Date Reported: 11/11/2015

Hall Environmental Analysis Laboratory, Inc.

Analyses	and the second second	Result	RL	Qual	Units	DF Date Analyzed	Batch
Lab ID:	1511110-001	Matrix: S	OIL		Received	Date: 11/4/2015 8:00:00 AM	
Project:	CoPC Newsom 18E				Collection	Date: 11/3/2015 11:22:00 AM	Λ
CLIENT:	Animas Environmental			C	lient Samp	le ID: BGT S-1	

EPA METHOD 418.1: TPH					Analyst:	том
Petroleum Hydrocarbons, TR	ND	19	mg/Kg	1	11/5/2015 12:00:00 PM	22177
EPA METHOD 300.0: ANIONS					Analyst:	LGT
Chloride	440	30	mg/Kg	20	11/9/2015 1:08:41 PM	22248
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANIC	S			Analyst:	KJH
Diesel Range Organics (DRO)	ND	9.4	mg/Kg	1	11/6/2015 4:37:34 PM	22193
Surr: DNOP	91.5	70-130	%REC	1	11/6/2015 4:37:34 PM	22193
EPA METHOD 8015D: GASOLINE RA	NGE				Analyst:	NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	11/6/2015 12:44:25 AM	22178
Surr: BFB	85.0	75.4-113	%REC	1	11/6/2015 12:44:25 AM	22178
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.048	mg/Kg	1	11/6/2015 12:44:25 AM	22178
Toluene	ND	0.048	mg/Kg	1	11/6/2015 12:44:25 AM	22178
Ethylbenzene	ND	0.048	mg/Kg	1	11/6/2015 12:44:25 AM	22178
Xylenes, Total	ND	0.095	mg/Kg	1	11/6/2015 12:44:25 AM	22178
Surr: 4-Bromofluorobenzene	106	80-120	%REC	1	11/6/2015 12:44:25 AM	22178

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	в	Analyte detected in the associated Method	Blank
	D	Sample Diluted Due to Matrix	E	Value above quantitation range	
	Н	Holding times for preparation or analysis exceeded	J	Analyte detected below quantitation limits	Page 1 of 6
	ND	Not Detected at the Reporting Limit	Р	Sample pH Not In Range	rage roro
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit	
	S	% Recovery outside of range due to dilution or matrix			

WO#: 1511110 11-Nov-15

Hall Environmental Analysis Laboratory, Inc.

Client: Project:		Environmer Newsom 18E			al						
Sample ID ME Client ID: PB Prep Date: 1		SampT Batch Analysis D	ID: 22	248	F	tCode: E RunNo: 3 SegNo: 9	0129	300.0: Anion Units: mg/F			
Analyte Chloride	119/2013	Result	PQL 1.5		SPK Ref Val	%REC		HighLimit	%RPD	RPDLimit	Qual
Sample ID LC Client ID: LC	S-22248	SampT	ype: LC			tCode: E RunNo: 3		300.0: Anion	IS		1
	1/9/2015	Analysis D Result		1/9/2015		SeqNo: 9 %REC		Units: mg/H	(g %RPD	RPDLimit	Qual
Chloride	1	14	1.5	15.00		90.7	90	110	, ci ti D		quui

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 2 of 6

WO#: 1511110 11-Nov-15

Hall Environmenta	l Analysis	Laboratory,	Inc.
-------------------	------------	-------------	------

	s Environmental Newsom 18E
Sample ID MB-22177	SampType: MBLK TestCode: EPA Method 418.1: TPH
Client ID: PBS	Batch ID: 22177 RunNo: 30033
Prep Date: 11/4/2015	Analysis Date: 11/5/2015 SeqNo: 914957 Units: mg/Kg
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20
Sample ID LCS-22177	SampType: LCS TestCode: EPA Method 418.1: TPH
Client ID: LCSS	Batch ID: 22177 RunNo: 30033
Prep Date: 11/4/2015	Analysis Date: 11/5/2015 SeqNo: 914958 Units: mg/Kg
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Petroleum Hydrocarbons, TR	110 20 100.0 0 114 83.6 116
Sample ID LCSD-22177	SampType: LCSD TestCode: EPA Method 418.1: TPH
Client ID: LCSS02	Batch ID: 22177 RunNo: 30033
Prep Date: 11/4/2015	Analysis Date: 11/5/2015 SeqNo: 914959 Units: mg/Kg
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Petroleum Hydrocarbons, TR	110 20 100.0 0 112 83.6 116 1.27 20

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 3 of 6

WO#: 1511110 11-Nov-15

Hall Environmental Analysis Laboratory, Inc.

	s Environmental Newsom 18E	a a star		
Sample ID MB-22193 Client ID: PBS Prep Date: 11/5/2015	SampType: MBLK Batch ID: 22193 Analysis Date: 11/6/2015	TestCode: EPA Method RunNo: 30056 SeqNo: 915927	8015M/D: Diesel Range Units: mg/Kg	Organics
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Diesel Range Organics (DRO) Surr: DNOP	ND 10 11 10.00	107 70	130	
Sample ID LCS-22193 Client ID: LCSS	SampType: LCS Batch ID: 22193	RunNo: 30056	8015M/D: Diesel Range	Organics
Prep Date: 11/5/2015	Analysis Date: 11/6/2015	SeqNo: 915928	Units: mg/Kg	
Analyte		SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Diesel Range Organics (DRO) Surr: DNOP	551050.004.85.000	0 109 57.4 95.6 70	139 130	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 4 of 6

WO#: 1511110 11-Nov-15

Hall Environmental Analysis Laboratory, Inc.

	s Environmental Newsom 18E			
Sample ID MB-22178 Client ID: PBS Prep Date: 11/4/2015	SampType: MBLK TestCode: EPA Method 8015D: Gasolin Batch ID: 22178 RunNo: 30022 Analysis Date: 11/5/2015 SeqNo: 915129 Units: mg/Kg	te Range		
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit	Qual	
Gasoline Range Organics (GRO) Surr: BFB	ND 5.0 850 1000 84.9 75.4 113		22	
Sample ID LCS-22178 Client ID: LCSS	SampType: LCS TestCode: EPA Method 8015D: Gasolin Batch ID: 22178 RunNo: 30022	te Range		
Prep Date: 11/4/2015	Analysis Date: 11/5/2015 SeqNo: 915130 Units: mg/Kg			
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit	Qual	
Gasoline Range Organics (GRO) Surr: BFB	25 5.0 25.00 0 98.3 79.6 122 930 1000 92.7 75.4 113			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 5 of 6

WO#: 1511110

H	lall	Env	ironment	al Ana	lysis	Labo	oratory	, Inc.
---	------	-----	----------	--------	-------	------	---------	--------

Animas Environmental

C	lient:
n	

CoPC Newsom 18E **Project:**

Sample ID MB-22178	ID MB-22178 SampType: MBLK TestCode: EPA Method 8021B: Vola						8021B: Vola	tiles	A. Cal	1
Client ID: PBS	PBS Batch ID: 22178 RunNo: 30022									
Prep Date: 11/4/2015	Analysis Date: 11/5/2015			5	SeqNo: 9	15186	Units: mg/h	٢g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050		- 10 C	1.0			10,247	5146.99	
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.1		1.000	the first	107	80	120	-	Sec. 2n	
Sample ID LCS-22178	Samp	Type: LC	s	Tes	tCode: E	PA Method	8021B: Vola	tiles	the second second	1 5
Client ID: LCSS	Batc	h ID: 22	178	F	RunNo: 3	0022				
Prep Date: 11/4/2015	Analysis [Date: 1	1/5/2015	5	SeqNo: 9	15187	Units: mg/h	٢g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.0	0.050	1.000	0	100	80	120	1.5	1.1.1.1	1.8
Toluene	0.98	0.050	1.000	0	97.7	80	120			
Ethylbenzene	1.0	0.050	1.000	0	101	80	120			
Xylenes, Total	3.0	0.10	3.000	0	101	80	120			
Surr: 4-Bromofluorobenzene	1.1		1.000		113	80	120			

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Sample Diluted Due to Matrix D
- Holding times for preparation or analysis exceeded Η
- Not Detected at the Reporting Limit ND
- R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix S
- Analyte detected in the associated Method Blank В
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Р Sample pH Not In Range
- RL Reporting Detection Limit

Page 6 of 6

¹¹⁻Nov-15

HALL ENVIRONMENTAL ANALYSIS LABORATORY	Hall Environmental Albu TEL: 505-345-3975 Website: www.hal	4901 querqui FAX: 5	Hawkins e, NM 871 05-345-41	NE 109 Samp	Sample Log-In Check List							
Client Name: Animas Environmental	Work Order Number:	15111	110		RcptNo: 1							
Received by/date:	11/04/15		•									
Logged By: Lindsay Mangin	11/4/2015 8:00:00 AM			Andy Hago		1						
Completed By: Lindsay Mangin	11/4/2015 8:57:20 AM			Andy Hago								
Reviewed By:	11/04/15			V								
Chain of Custody	11/07/12											
1. Custody seals intact on sample bottles?		Yes		No 🗆	Not Present							
2. Is Chain of Custody complete?		Yes		No 🗆	Not Present							
3. How was the sample delivered?		Cour	ier									
Log In												
4. Was an attempt made to cool the same	bles?	Yes		No 🗌								
5. Were all samples received at a temperative	ature of >0° C to 6.0°C	Yes		No 🗆								
6. Sample(s) in proper container(s)?		Yes		No 🗆								
7. Sufficient sample volume for indicated t	est(s)?	Yes		No 🗆								
8. Are samples (except VOA and ONG) pr	operly preserved?	Yes		No 🗆								
9. Was preservative added to bottles?		Yes		No 🛃								
10.VOA vials have zero headspace?		Yes		No 🗆	No VOA Vials							
11. Were any sample containers received	broken?	Yes		No 🛃	# of preserved							
12. Does paperwork match bottle labels? (Note discrepancies on chain of custod	y)	Yes		No 🗆	for pH: (<2 or >12 unlet	ss noted)						
13. Are matrices correctly identified on Cha		Yes		No 🗆	Adjusted?							
14. Is it clear what analyses were requested	d?	Yes		No 🗌								
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes		No 🗆	Checked by:							
Special Handling (if applicable)												
	The state of the O	Ver		No 🗖	NA A							

. W	as client notified of all discrepancie	with this order? Yes I No I	
	Person Notified:	Date:	
	By Whom:	Via: eMail Phone Fax In Person	n
	Regarding:		MANDALINANIN'
	Client Instructions:		and the local division of

17. Additional remarks:

1

18. Cooler Information

Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
1	1.7	Good	Yes			

Ch Client:			tody Record	S, LLC X Standard □ Rush Project Name:							ALL							
Mailing Ad	dress:	604 14	Pinon St.					www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109										
			gton, NM 87401	COPC Newsom 18E Project #:							5-3975		ax 50			09		
Phone #:	505-564	-2281									A	nalysi	s Req	uest				
eskyles@animasenvironmental.co		Project Manag	jer:															
			E. Skyles					(0)			A.							
Accreditati	on:	Other		Sampler:	n Glasse	3 No.				RO/DI								
	ype)			Samile Tenn	enerure /			-	0	5(0								N N
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO. 1	BTEX - 8021B	TPH - EPA 418.1	Chlorides - 300.0	TPH - EPA 8015 (GRO/DRO)		34.00	State 1					Air Bubbles (Y or N)
11-3-15	1122	SOIL	BGT S-1	2 - 4 oz.	cool	-001	x	x	х	X								
																+	T	
			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1													+	+	
	3															-		
										•				-				
14.8	1	1000		Sec. 14	13 1.2												-	
Dete: 11/3/15	Time:	Relinquish	-Why	Received by:	Jaeto	Date Time	WO Sup	# ervis		m Pe		Phillips	3					
Date: 1/3/15	Time: 1805	Relinquishe	+ Valter	Received by	5 11/0	Pate Time 415 0800	Area	: 21			ay Dum	as						

If nanacian estimate to Hall Environmental may be extended to dias Annalised in Annalised in Annalised Environmental may be extended an the analisial const

