OIL CONS. DIV DIST. 3

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

DEC 2 1 2015

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. 1. Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: Wilch A 003
API Number: 3004523342 OCD Permit Number:
U/L or Qtr/Qtr B Section 23 Township 29N Range 8W County: San Juan
Center of Proposed Design: Latitude 36.71520 Longitude 107.64284 NAD: □1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. □ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank Boundary
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other Single walled/single bottom
Liner type: Thicknessmil
4. Alternative Method:

Page 1 of 6

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) ☐ Screen ☐ Netting ☐ Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - ☑ NM Office of the State Engineer - iWATERS database search; ☐ USGS; ☐ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	1
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
	L les L No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	☐ Yes ☐ No
 NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. 	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan	
Oil Field Waste Stream Characterization Monitoring and Inspection Plan	
Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	HIST BALLER

adopted pursuant to NMSA 1978, Section 3-27-3 - Written confirmation or verification from		Written approva	obtained from the mur	nicipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or n	nap from the NM E	MNRD-Mining	and Mineral Division		☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into Society; Topographic map	the design; NM Bu	reau of Geology	& Mineral Resources; I	USGS; NM Geological	☐ Yes ☐ No
Within a 100-year floodplain FEMA map					Yes No
16.					
On-Site Closure Plan Checklist: (19.15.17.13 by a check mark in the box, that the documents Siting Criteria Compliance Demonstration Proof of Surface Owner Notice - based up Construction/Design Plan of Burial Trenc Construction/Design Plan of Temporary P Protocols and Procedures - based upon the Confirmation Sampling Plan (if applicable) Waste Material Sampling Plan - based upon Disposal Facility Name and Permit Numb Soil Cover Design - based upon the appro Re-vegetation Plan - based upon the appro Site Reclamation Plan - based upon the appro	are attached. as - based upon the conthe appropriate in the (if applicable) bath it (for in-place burity appropriate requires) - based upon the conthe appropriate requirements opriate requirements opriate requirements	appropriate requirequirements of Seed upon the appal of a drying palements of 19.15. appropriate requirements of 1 ing fluids and drof Subsection Head of Subsection Feed	rements of 19.15.17.10 Subsection E of 19.15.1 ropriate requirements of d) - based upon the app 17.13 NMAC frements of 19.15.17.13 9.15.17.13 NMAC Ill cuttings or in case on of 19.15.17.13 NMAC	NMAC 7.13 NMAC of Subsection K of 19.15.17 ropriate requirements of 19 NMAC street closure standards can	7.11 NMAC 9.15.17.11 NMAC
17. Operator Application Certification: I hereby certify that the information submitted w	with this application	is true accurate	and complete to the he	st of my knowledge and be	lief
Name (Print):				st of my knowledge and be	
Signature:	el el		Date:		
e-mail address:			Telephone:		
OCD Approval: Permit Application included the Company of the Compa	alist		OCD Permit Number:	Approval Date:	2819018
Closure Report (required within 60 days of clo Instructions: Operators are required to obtain a The closure report is required to be submitted to section of the form until an approved closure pl	an approved closur the division within	e plan prior to i n 60 days of the	mplementing any closu completion of the closu	ire activities. Please do no	
			Closure Completion	on Date: 11/2/2015	
20. Closure Method: Waste Excavation and Removal ☐ On-Si ☐ If different from approved plan, please expla		☐ Alternativ	e Closure Method	Waste Removal (Closed-l	oop systems only)
Closure Report Attachment Checklist: Instruction Mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and Proof of Deed Notice (required for on-site Plot Plan (for on-site closures and temporal Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seed Site Reclamation (Photo Documentation) On-site Closure Location: Latitude	ed. d division) closure for private ary pits) s (if applicable) lts (required for on- er	land only)	s must be attached to th	ne closure report. Please i	

Operator Closus	re Certification:	
I hereby certify the	hat the information and attachments submitted v	with this closure report is true, accurate and complete to the best of my knowledge and closure requirements and conditions specified in the approved closure plan.
Name (Print):	Steve Moskal	Title: Field Environmental Coordinator
Signature:	Plannud	Date: December 15, 2015
e-mail address:	steven.moskal@bp.com	Telephone:(505) 326-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Wilcch A 003 API No. 3004523342 Unit Letter B, Section 23, T29N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice was made to the Bureau of Land Management Farmington Field Office.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice was made to the NMOCD District III Office.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method 21 bbl BGT	Release Verification (mg/Kg)	Sample results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.039
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.079
TPH	US EPA Method SW-846 418.1/8015 Extended Range	100	<48 (8015)
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride. BTEX and chloride concentrations were below the stated limits. THP determined by Method 8015 including GRO, DRO and MRO with results below the BGT closure standard. Laboratory data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate a release has not occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling demonstrates a release has not occurred. The BGT was backfilled and remains within the active well pad.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The BGT was backfilled and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The BGT was backfilled and is still within the active well area. This area will be reclaimed at a later date.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The BGT was backfilled and is still within the active well area and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

Waste material sent to IEI/JFJ Waste Management Facility; permit NM 01-0010B

From:

Railsback, Farrah (CH2M HILL)

To:

Smith, Cory, EMNRD (Cory, Smith@state.nm.us)

Cc:

Moskal, Steven; blagg niv@yahoo.com; jeffcblagg@aol.com

Subject: Date: BP Pit Close Notification - WILCH A 003 Thursday, October 29, 2015 10:31:12 AM

BP America Production Company

200 Energy Court

Farmington, NM 87401

Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

October 29, 2015

New Mexico Oil Conservation Division

1000 Rio Brazos Road

Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

WILCH A 003

API 30-045-23342

(B) Section 23 - T29N - R08W

San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl BGT that will no longer be operational at

this well site. We anticipate this work to start on or around November 2, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal

BP Field Environmental Coordinator

(505) 326-9497

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

October 29, 2015

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: WILCH A 003

API#: 3004523342

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about November 2, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

Charlie Davis

BP America Production Company

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

						OPERA'	ГOR		Initi	al Report Final Repor		
Name of C						Contact: Ste	eve Moskal					
Address: 2	00 Energy	Court, Farm	ington, N	IM 87401			No.: 505-326-94			C- THEALT IN		
Facility Na	me: Wilch	A 003			Facility Type: Natural gas well							
Surface Ov	vner: Fede	ral		Mineral (Owner:	Federal			API No	o. 3004523342		
			· F	LOC	ATIO	N OF RE	LEASE					
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/We	st Line	County: San Juan		
В	23	29N	8W	920	North		1,800	East				
		Lati	tude 3	6.71520		Longitude	-107.64284					
				NAT	TURE	OF REL	EASE					
Type of Rel	ease: none	Mr -		300,000,000		Volume of	Release: unknov	wn V	/olume l	Recovered: N/A		
		w grade tank -	- 21 bbl			Date and I unknown	Iour of Occurrence		Date and 2008	Hour of Discovery: October 20,		
Was Immed	iate Notice		Yes 🛭	No □ Not R	equired	If YES, To	Whom?					
By Whom?				1 = 12 1 - 1		Date and H			701			
Was a Wate	rcourse Rea		Yes 🛭	No		If YES, Vo	olume Impacting	the Waterc	ourse.			
	hloride belo									Soil analysis resulted for TPH, sure standards. Analysis results		
		and Cleanup A		ken.* BGT was re	emoved a	and backfilled	. The area is stil	ll within the	e active	well area and will be reclaimed		
regulations a public health should their or the enviro	all operators of the envi- operations lonment. In a	are required to ronment. The nave failed to	o report a acceptan adequately OCD accep	nd/or file certain ce of a C-141 rep y investigate and	release n ort by th remediat	otifications a e NMOCD m e contaminati	nd perform correctarked as "Final Roon that pose a three the operator of	ctive action Report" doe reat to grou responsibil	ns for rel es not rel and wate lity for c	suant to NMOCD rules and eases which may endanger ieve the operator of liability r, surface water, human health ompliance with any other		
Signature:	Hus	Mure					OIL CON	ISERVA	TION	DIVISION		
Printed Nam						Approved by	Environmental S	Specialist:				
Title: Field	Environmen	tal Coordinate	or			Approval Da	e:	Ex	piration	Date:		
E-mail Addı	E-mail Address: steven.moskal@bp.com					Conditions of Approval:			Attached			
Date: Dece	mber 15, 20	15	Pho	one: 505-326-949	7							

CLIENT: BP		GINEERING, INC. OOMFIELD, NM 87413	API#: 3004523342
		6) 632-1199	TANK ID (if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / OTHER:	PAGE#: 1 of 1
SITE INFORMATION		2.00	DATE STARTED: 11/02/15
	29N RNG: 8W PM:	NM CNTY: SJ ST: N	DATE I INIOI IED.
1/4 - 1/4/FOOTAGE: 920'N / 1,800 LEASE #: SF078416A		PE: FEDERAL STATE / FEE / INDIAN STRIKE NTRACTOR: MBF - S. GLYNN	ENVIRONMENTAL SPECIALIST(S): NJV
REFERENCE POINT		COORD.: 36.71553 X 107.642	279 GL ELEV.: 5,712'
1) 21 BGT (SW/SB)	GPS COORD.: 36.7		CE/BEARING FROM WH.: 115', S4W
2)	GPS COORD.:	DISTANC	CE/BEARING FROM W.H.:
3)	GPS COORD.:	DISTANC	CE/BEARING FROM W.H.:
4)	GPS COORD.:	DISTANC	CE/BEARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR		OVM READING (ppm)
1) SAMPLE ID: 5 PC-TB@6'	(21) SAMPLE DATE: 11/02/1	5 SAMPLETIME: 1020 LAB ANALYSIS:	8015B/8021B/300.0 (CI) NA
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:	
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:	
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:	
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND SIL	T/SILTY CLAY/CLAY/GRAVEL/OTHER	
SOIL COLOR: DARK YELLON COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY / SLIGHTLY MOIST / WOIST / W SAMPLE TYPE: GRAB (COMPOSITE) + DISCOLORATION/STAINING OBSERVED: YES / M	COHESIVE / COHESIVE / HIGHLY COHESIVE DOSE / FIRM DENSE / VERY DENSE HET / SATURATED SOF PTS.	PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC PLASTIC / SLIGHTLY PLASTIC PLASTIC / SLIGHTLY PLASTIC PLASTIC / SLIGHTLY PLASTIC PL	
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	DAND/OR OCCURRED : YES NO EXPLAN		
SOIL IMPACT DIMENSION ESTIMATION:		AND THE RESERVE AND ADDRESS OF THE PARTY OF	N ESTIMATION (Cubic Yards) : NA
	EAREST WATER SOURCE: >1,000'	NEAREST SURFACE WATER: >1,000	NMOCD TPH CLOSURE STD: 5,000 ppm
SITE SKETCH FENCE BERM	BGT Located : off on site	PLOT PLAN circle: attached TO W.H.	OVM CALIB. READ. = NA ppm RF = 0.52 OVM CALIB. GAS = NA ppm TIME: NA am/pm DATE: NA MISCELL. NOTES WO:
FENCE	95 BGT (TANK A)	BERM	REF #: P - 159 VID: VHIXONEVB2 PJ#:
PROD. TANK	21 BBL PBGTL T.B. ~ 6' B.G. (TANK B)	FENCE X - S.P.D.	Permit date(s): NONE, BUT SIGNED OCD Appr. date(s): 10/21/15 Tank OVM = Organic Vapor Meter ID ppm = parts per million B BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE POI E WALL; DW- DOUBLE WALL; SB - SINGLE BOTTO	OW, T.H. = TEST HOLE; ~ = APPROX; W.H. = WELL HEAD; NT DESIGNATION; R.W. = RETAINING WALL; NA - NOT M; DB - DOUBLE BOTTOM.	Magnetic declination: 10° E

Analytical Report

Lab Order 1511041

Date Reported: 11/4/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC - TB @ 6' (21)

Project: WILCH A # 3

Collection Date: 11/2/2015 10:20:00 AM

Lab ID: 1511041-001

Matrix: MEOH (SOIL)

Received Date: 11/3/2015 7:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS			hi go o		Analyst:	LGT
Chloride	ND	30	mg/Kg	20	11/3/2015 2:47:29 PM	22155
EPA METHOD 8015M/D: DIESEL RANGE	ORGANIC	S			Analyst:	KJH
Diesel Range Organics (DRO)	ND	9.7	mg/Kg	1	11/3/2015 11:05:35 AM	22137
Motor Oil Range Organics (MRO)	ND	48	mg/Kg	1	11/3/2015 11:05:35 AM	22137
Surr: DNOP	92.8	70-130	%REC	1	11/3/2015 11:05:35 AM	22137
EPA METHOD 8015D: GASOLINE RANG	E				Analyst:	NSB
Gasoline Range Organics (GRO)	ND	3.9	mg/Kg	1	11/3/2015 10:32:37 AM	22126
Surr: BFB	90.4	75.4-113	%REC	1	11/3/2015 10:32:37 AM	22126
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.039	mg/Kg	1	11/3/2015 10:32:37 AM	22126
Toluene	ND	0.039	mg/Kg	1	11/3/2015 10:32:37 AM	22126
Ethylbenzene	ND	0.039	mg/Kg	1	11/3/2015 10:32:37 AM	22126
Xylenes, Total	ND	0.079	mg/Kg	1	11/3/2015 10:32:37 AM	22126
Surr: 4-Bromofluorobenzene	109	80-120	%REC	1	11/3/2015 10:32:37 AM	22126

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit

Client:			tody Record / BP AMERICA	Turn-Around Standard Project Name	☑ Rush _	SAME DAY													NTA		
Mailing A	ddress:	P.O. BO	X 87	Project Name	WILCH A #	13		49	01 H			w.ha						n 3710:	9		
		BLOOM	FIELD, NM 87413	Project #:		legizmen.		Te	1. 50	5-3	45-3	975	1	Fax	505	-345	-410	7			
Phone #:		(505) 63	2-1199									F	hnal	ysis	Red	ques	t				
email or F	ax#:			Project Manag	jer:									4				1)		T	T
QA/QC Pa			Level 4 (Full Validation)		NELSON VI	ELEZ	WB's (8021B)	only)	(MRO)			(S)		05'70	PCB's			er - 300.1)		9	,
Accreditat	tion:			Sampler:	NELSON VI	ELEZ ny	8) G	(Gas	RO/	1)	1	SIIV	4	102	8082			/ wat		sample	
□ NELAF	•	□ Other		On ice:	∕d Yes	i⊒ No.	*	TPH	0/0	418.	504	827(ıs	03,1	-		(A)	0.00	20 1	e sa	IN .
□ EDD (ype)			Sample Temp	erature: 2,6	1997	1	3E +	(GR	pou	por	or	etak	S	cide	(A)	i-VC	- Jil	a	osit	2
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO. /	BTEX ←MFE	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO /	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 / water	Grab sample	5 pt. composite	Air Dishhlar
11/2/15	1020	SOIL	5PC - TB @ 6' (21)	4 oz 1	Cool	-001	٧		٧									٧		V	_
																					T
											7										土
																			+	+	+
														1							T
· · · · · · · · · · · · · · · · · · ·																					
						AUTO SE SERVE													20 2		I
			****		5 1															+	+
Date:	Time:	Relinquishe	n.Vf	Received by:	. Warte	Date Time 11/2/15 1541 Date Time	BI		RECT				ourt,	Farn	ningt	on, M	I 8	7401			
1/2/15	1920	1 Chris	the Waller	10	11/02/	15 OFFOO	Re	fere	nce #	!: _		P-15	9		Pa	ykey	:\	/HIXC	ONEVB2		

Hall Environmental Analysis Laboratory, Inc.

WO#: 1511041

04-Nov-15

Client:

Blagg Engineering

Project:

WILCH A#3

Sample ID MB-22155

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 22155

RunNo: 29992

Prep Date: 11/3/2015

Analysis Date: 11/3/2015

SeqNo: 913743

Units: mg/Kg

Client ID:

HighLimit

RPDLimit

Qual

Analyte Chloride

Result PQL ND 1.5

SampType: LCS

TestCode: EPA Method 300.0: Anions

SPK value SPK Ref Val %REC LowLimit

RunNo: 29992

Sample ID LCS-22155

LCSS

Batch ID: 22155

Units: mg/Kg

Prep Date: 11/3/2015

Analysis Date: 11/3/2015

PQL

SeqNo: 913744

Analyte

1.5

0

SPK value SPK Ref Val %REC

92.9

HighLimit

RPDLimit

Qual

Chloride

14

15.00

LowLimit

110

%RPD

%RPD

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Holding times for preparation or analysis exceeded H

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH Not In Range

Reporting Detection Limit

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1511041

04-Nov-15

Client:

Blagg Engineering

Sample ID MB-22137	SampType: MBLK	TestCode: EPA Method 8	015M/D: Diesel Range Organics
Client ID: PBS	Batch ID: 22137	RunNo: 29954	
Prep Date: 11/3/2015	Analysis Date: 11/3/2015	SeqNo: 912449	Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	ND 10		
Motor Oil Range Organics (MRO)	ND 50		
Surr: DNOP	9.7 10.00	97.2 70	130
Sample ID LCS-22137	SampType: LCS	TestCode: EPA Method 8	015M/D: Diesel Range Organics
Client ID: LCSS	Batch ID: 22137	RunNo: 29954	
Prep Date: 11/3/2015	Analysis Date: 11/3/2015	SeqNo: 912452	Jnits: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	46 10 50.00	0 91.4 57.4	139
Surr: DNOP	5.1 5.000	102 70	130
Sample ID MB-22117	SampType: MBLK	TestCode: EPA Method 80	015M/D: Diesel Range Organics
Client ID: PBS	Batch ID: 22117	RunNo: 29954	
Prep Date: 11/2/2015	Analysis Date: 11/3/2015	SeqNo: 912719	Jnits: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: DNOP	12 10.00	125 70	130
Sample ID LCS-22117	SampType: LCS	TestCode: EPA Method 86	015M/D: Diesel Range Organics
Client ID: LCSS	Batch ID: 22117	RunNo: 29954	
Prep Date: 11/2/2015	Analysis Date: 11/3/2015	SeqNo: 912857	Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: DNOP	6.4 5.000	129 70	130

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1511041

04-Nov-15

Client:

Blagg Engineering

Project:

WILCH A #3

Sample ID MB-22126

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: 22126

RunNo: 29970

Prep Date: 11/2/2015

Analysis Date: 11/3/2015

880

SeqNo: 913194

Units: mg/Kg

Analyte

%REC

113

HighLimit

Gasoline Range Organics (GRO)

PQL Result 5.0 ND

SPK value SPK Ref Val 1000

LowLimit 75.4 %RPD **RPDLimit**

Qual

Surr: BFB

Sample ID LCS-22126

SampType: LCS

88.0

TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS

Batch ID: 22126

RunNo: 29970 SeqNo: 913195

Units: mg/Kg

Prep Date: 11/2/2015

Analysis Date: 11/3/2015

%REC LowLimit HighLimit %RPD

RPDLimit

Qual

Analyte Gasoline Range Organics (GRO) Surr: BFB

Result PQL 26 5.0 960

SPK value SPK Ref Val 0 25.00 1000

79.6 105 96.2 75.4 122 113

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- H Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1511041

04-Nov-15

Client:

Blagg Engineering

Project:

WILCH A#3

Sample ID MB-22126	SampType: MBLK		TestCode: EPA Method 8021B: Volatiles							
Client ID: PBS Batch ID: 22126		F								
Prep Date: 11/2/2015	Analysis [Analysis Date: 11/3/2015			SeqNo: 913277			Units: mg/Kg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050			THE					
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
(ylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120			

Sample ID LCS-22126 SampType: LCS		TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS	Batch ID: 22126			F	RunNo: 2	9970				
Prep Date: 11/2/2015	Analysis Date: 11/3/2015		SeqNo: 913278			Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	113	80	120		x	
Toluene	1.0	0.050	1.000	0	100	80	120			
Ethylbenzene	1.0	0.050	1.000	0	101	80	120			
Xylenes, Total	3.0	0.10	3.000	0	100	80	120			
Surr: 4-Bromofluorobenzene	1.1		1.000		113	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 5 of 5



Hall Environmental Analysis Laboratory
4901 Hawkins NE
Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG	Work Order Number:	1511041		RcptNo:	1
Received by/date	· Ad	11/03/15				
Logged By:	Lindsay Mangin	11/3/2015 7:00:00 AM		Simulay Hospige		The later
Completed By:	Lindsay Mangin	11/3/2015 7:35:05 AM		January Harpy D		Die glein
Reviewed By:	Da	11/03/15				
Chain of Cust	tody	110 110				
1. Custody seal	ls intact on sample bottles?		Yes 🗌	No 🗆	Not Present	
2. Is Chain of C	custody complete?		Yes	No 🗆	Not Present	
3. How was the	sample delivered?		Courier			
Log In						
4. Was an atter	mpt made to cool the samp	oles?	Yes 🐼	No 🗆	NA 🗆	
5. Were all sam	nples received at a tempera	Yes 🐼	No 🗆	NA 🗆		
6. Sample(s) in	proper container(s)?	Yes 🗹	No 🗆			
7. Sufficient sar	mple volume for indicated to	est(s)?	Yes 🐼	No 🗆		
8. Are samples	(except VOA and ONG) pr	Yes 🐼	No 🗆			
9. Was preserv	ative added to bottles?		Yes 🗌	No 🗪	NA 🗆	
10.VOA vials ha	ive zero headspace?		Yes 🗌	No 🗆	No VOA Vials	
11. Were any sa	ample containers received b	proken?	Yes 🗆	No 🗹	# of preserved	
					bottles checked	
	work match bottle labels? cancies on chain of custody	0	Yes 🖈	No 🗆	for pH: (<2 d	or >12 unless noted)
	correctly identified on Cha	Yes 🐼	No 🗆	Adjusted?		
	at analyses were requested	Yes 🐼	No 🗆			
	ding times able to be met? customer for authorization.)		Yes 🐼	No □	Checked by:	
Special Hand	ling (if applicable)					
	otified of all discrepancies v	with this order?	Yes	No 🗆	NA 🗹	
Person	Notified:	Date:	MARK WARRANT WARRANT CORE	NOTICE THE PROPERTY OF THE PRO	9 KW 9 94 40]
By Wh	TATION THE PARTY OF THE PARTY O	Via:	eMail	Phone Fax	☐ In Person	
Regard	San Transport Control of the Control			3.110110		
	Instructions:				-	
17. Additional re	emarks:		Do 10 3		** ** ** ***	
18. Cooler Info	rmation					
Cooler No	o Temp °C Condition		Seal Date	Signed By		
1	2.6 Good	Yes	and the state of t			



