

State of New Mexico  
Energy, Minerals and Natural Resources Department

Susana Martinez  
Governor

David Martin  
Cabinet Secretary

Brett F. Woods, Ph.D.  
Deputy Cabinet Secretary

David R. Catanach Division Director  
Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following 3160-3 APD form.

Operator Signature Date: 3/25/15

Well information;

Operator Encana, Well Name and Number Lybrook P24A-2206 #1H


API# 30-043-21270, Section 24, Township 22 N/S, Range 6 E/W

Conditions of Approval:

(See the below checked and handwritten conditions)

- ☒ Notify Aztec OCD 24hrs prior to casing & cement.
- ☒ Hold C-104 for directional survey & "As Drilled" Plat
- ☒ Hold C-104 for NSL, NSP, DHC
- ☐ Spacing rule violation. Operator must follow up with change of status notification on other well to be shut in or abandoned
- ☐ Regarding the use of a pit, closed loop system or below grade tank, the operator must comply with the following as applicable:
  - A pit requires a complete C-144 be submitted and approved prior to the construction or use of the pit, pursuant to 19.15.17.8.A
  - A closed loop system requires notification prior to use, pursuant to 19.15.17.9.A
  - A below grade tank requires a registration be filed prior to the construction or use of the below grade tank, pursuant to 19.15.17.8.C
- ☐ Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
- ☒ Regarding Hydraulic Fracturing, review EPA Underground Injection Control Guidance 84
- ☒ Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
- ☒ Well-bore communication is regulated under 19.15.29 NMAC. This requires well-bore Communication to be reported in accordance with 19.15.29.8.

APD Held for corrected C-102 rec'd on 1-27-16

  
NMOCD Approved by Signature

2-4-2016  
Date RY



RECEIVED

OIL CONS. DIV DIST. 3

DEC 16 2015

FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT


## APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> <b>Drill</b> <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM 117563
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name N/A
2. Name of Operator Encana Oil & Gas (USA) Inc.		7. If Unit or CA Agreement, Name and No. N/A
3a. Address 370 17th Street, Suite 1700 Denver, CO 80202	3b. Phone No. (include area code) 720-876-5994	8. Lease Name and Well No. Lybrook P24A-2206 01H
4. Location of Well (Report location clearly and in accordance with any State requirements *) At surface 626' FSL and 731' FEL Section 24, T22N, R6W At proposed prod. zone 330' FSL and 1780' FEL Section 25, T22N, R6W		9. API Well No. 30-043-21270
14. Distance in miles and direction from nearest town or post office* +/- 62.5 miles South from the intersection of HWY 64 and HWY 550 in Bloomfield, NM		10. Field and Pool, or Exploratory Wildcat Gallup
15. Distance from proposed* location to nearest property or lease line, ft. BHL is 330' FSL Section 25, T22N, R6W (Also to nearest drig. unit line, if any)	16. No. of acres in lease NMNM 117563 - 1,120 acres	11. Sec., T. R. M. or Blk. and Survey or Area Section 24, T22N, R6W NMPM
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. SHL +/-30' N Lybrook P24A-2206 02H	19. Proposed Depth 5,283' TVD; 10,652' MD	12. County or Parish Sandoval
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 7,207' GL 7,223' KB	22. Approximate date work will start* 11/05/2015	13. State NM
17. Spacing Unit dedicated to this well 160.0 acres- W2E2 Section 25, T22N, R6W		
20. BLM/BIA Bond No. on file COB-000235		
23. Estimated duration 20 Days		


## 24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the BLM.

25. Signature 	Name (Printed/Typed) Shawn Turk	Date 3/25/15
--	------------------------------------	-----------------

Title Regulatory Analyst	
-----------------------------	--

Approved by (Signature) 	Name (Printed/Typed) B. Meeker	Date 12/19/15
--	-----------------------------------	------------------

Title AFM	Office FFO
--------------	---------------

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

BLM'S APPROVAL OR ACCEPTANCE OF THIS ACTION DOES NOT RELIEVE THE LESSEE AND OPERATOR FROM OBTAINING ANY OTHER AUTHORIZATION REQUIRED FOR OPERATIONS ON FEDERAL AND INDIAN LANDS

NMOCD AV

DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHED "GENERAL REQUIREMENTS"

This action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4

CONFIDENTIAL



DEC 16 2015

Form C-102

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone (505) 748-1283 Fax: (505) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S St. Francis Dr., Santa Fe, NM 87505  
Phone (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Revised August 1, 2011  
Submit one copy to appropriate  
District Office

☐ AMENDED REPORT

## WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number 30-043-21270	<sup>2</sup> Pool Code 97981	<sup>3</sup> Pool Name WILDCAT WC 22N6W22E Gallyup
<sup>4</sup> Property Code	<sup>5</sup> Property Name LYBROOK P24A-2206	<sup>6</sup> Well Number 01H
<sup>7</sup> OGRID No. 282327	<sup>8</sup> Operator Name ENCANA OIL & GAS (USA) INC.	<sup>9</sup> Elevation 7207.3'

<sup>10</sup> Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West Line	County
P	24	22N	06W		626	SOUTH	731	EAST	SANDOVAL

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West Line	County
O	25	22N	06W		330	SOUTH	1780	EAST	SANDOVAL

<sup>12</sup> Dedicated Acres (RECORD) 160.00 ACRES	PROJECT AREA W/2 E/2 SECTION 25	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No.
--	------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

<sup>17</sup> OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature: *Shawn Turk* Date: 3/25/15

Printed Name: Shawn Turk

E-mail Address: shawn.turk@encana.com

E-mail Address

<sup>18</sup> SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

September 8, 2014

Date of Survey

Signature and Seal of Professional Surveyor:



RICHARD L. MULLIKEN

Certificate Number

16873



Lybrook P24A-2206 01H  
SHL: 626' FSL, 731' FEL Sec 24, T22N, R6W  
BHL: 330' FSL, 1780' FEL Sec 25, T22N, R6W  
Sandoval, New Mexico  
Lease Number: NMNM 117563

**Encana Oil & Gas (USA) Inc.  
Drilling Plan**

**1. ESTIMATED TOPS OF GEOLOGICAL MARKERS (TVD)**

The estimated tops of important geologic markers are as follows:

Formation	Depth (TVD) units = feet
San Jose Fn.	n/a
Nacimiento Fn.	surface
Ojo Alamo Ss.	1,318
Kirtland Shale	1,524
Fruitland Coal	1,656
Pictured Cliffs Ss.	1,874
Lewis Shale	2,011
Cliffhouse Ss.	2,669
Menefee Fn.	3,378
Point Lookout Ss.	4,135
Mancos Shale	4,351
Mancos Silt	4,900
Gallup Fn.	5,168
Base Gallup	5,454

The referenced surface elevation is 7207', KB 7223'

**2. ESTIMATED DEPTH OF POTENTIAL WATER, OIL, GAS,  
& OTHER MINERAL BEARING FORMATIONS**

Substance	Formation	Depth (TVD) units = feet
Water/Gas	Fruitland Coal	1,656
Oil/Gas	Pictured Cliffs Ss.	1,874
Oil/Gas	Cliffhouse Ss.	2,669
Gas	Menefee Fn.	3,378
Oil/Gas	Point Lookout Ss.	4,135
Oil/Gas	Mancos Shale	4,351
Oil/Gas	Mancos Silt	4,900
Oil/Gas	Gallup Fn.	5,168

All shows of fresh water and minerals will be reported and protected.



Lybrook P24A-2206 01H

SHL: 626' FSL, 731' FEL Sec 24, T22N, R6W

BHL: 330' FSL, 1780' FEL Sec 25, T22N, R6W

Sandoval, New Mexico

Lease Number: NMNM 117563

### 3. PRESSURE CONTROL

- a) Pressure control equipment and configuration will be designed to meet 2M standards.
- b) Working pressure on rams and BOPE will be 3,000 psi.
- c) Function test and visual inspection of the BOP will be conducted daily and noted in the IADC Daily Drilling Report.
- d) The Annular BOP will be pressure tested to a minimum of 50 percent of its rated working pressure.
- e) Blind and Pipe Rams/BOP will be tested against a test plug to 100 percent of rated working pressure.
- f) Pressure tests are required before drilling out from under all casing strings set and cemented in place.
- g) BOP controls must be installed prior to drilling the surface casing plug and will remain in use until the well is completed or abandoned.
- h) BOP testing procedures and testing frequency will conform to Onshore Order No. 2.
- i) BOP remote controls shall be located on the rig floor at a location readily accessible to the driller. Master controls shall be on the ground at the accumulator and shall have the capability to function all preventers.
- j) The kill line shall be 2-inch minimum and contain two kill line valves, one of which shall be a check valve.
- k) The choke line shall be a 2-inch minimum and contain two choke line valves (2-inch minimum).
- l) The choke and manifold shall contain two adjustable chokes.
- m) Hand wheels shall be installed on all ram preventers.
- n) Safety valves and wrenches (with subs for drill string connections) shall be available on the rig floor at all times.
- o) Inside BOP or float sub shall also be available on the rig floor at all times.

Proposed BOP and choke manifold arrangements are attached.

### 4. CASING & CEMENTING PROGRAM

The proposed casing and cementing program has been designed to protect and/or isolate all usable water zones, potentially productive zones, lost circulation zones, abnormally pressured zones, and any prospectively valuable deposits of minerals. Any isolating medium other than cement shall receive approval prior to use. The casing setting depth shall be calculated to position the casing seat opposite a competent formation which will contain the maximum pressure to which it will be exposed during normal drilling operations. All indications of useable water shall be reported.

- a) The proposed casing design is as follows:

Casing	Depth (MD)	Hole Size	Csg Size	Weight	Grade
Conductor	0'-60'	26"	16"	42.09#	
Surface	0'-500'	12 1/4"	9 5/8"	36#	J55, STC New
Intermediate	0'-5529'	8 3/4"	7"	26#	J55, LTC New
Production Liner	5429'-10652'	6 1/8"	4 1/2"	11.6#	B80*, LTC New

Casing String				Casing Strength Properties			Minimum Design Factors		
Size	Weight (ppf)	Grade	Connection	Collapse (psi)	Burst (psi)	Tensile (1000lbs)	Collapse	Burst	Tension
9 5/8"	36	J55	STC	2020	3520	394	1.125	1.1	1.5
7"	26	J55	LTC	4320	4980	367	1.125	1.1	1.5
4.5"	11.6	B80	LTC	6350	7780	201	1.125	1.1	1.5

\*B80 pipe specifications are attached.

Casing design is subject to revision based on geologic conditions encountered.



Lybrook P24A-2206 01H

SHL: 626' FSL, 731' FEL Sec 24, T22N, R6W

BHL: 330' FSL, 1780' FEL Sec 25, T22N, R6W

Sandoval, New Mexico

Lease Number: NMNM 117563

All casing strings below the conductor shall be pressure tested to 0.22 psi per foot of casing string length or 1,500 psi, whichever is greater, but not to exceed 70 percent of the minimum internal yield. If pressure declines more than 10 percent in 30 minutes, corrective action shall be taken.

b) The proposed cementing program is as follows:

Casing	Depth (MD)	Cement Volume (sacks)	Cement Type & Yield	Designed TOC	Centralizers
Conductor	0'-60'	100 sks	Type I Neat 16 ppg	Surface	None
Surface	0'-500'	228 sks	Type III Cement + 1% bwoc Calcium Chloride + 0.25 lbs/sack Cello Flake + 0.2% bwoc FL-52A + 58.9% Fresh Water	Surface	1 per joint on bottom 3 joints
Intermediate	0'-5529'	100% open hole excess Stage 1 Lead: 515 sks Stage 1 Tail: 392 sks	Lead: PremLite + 3% CaCl + 0.25lb/sk CelloFlake + 5lb/sk LCM, 12.1ppg 2.13cuft/sk Tail: Type III Cmt + 1% CaCl + 0.25lb/sk Cello Flake 14.5ppg 1.38cuft/sk	Surface	1 every 3 joints through water bearing zones
Production Liner	5429'- 10652'	50% OH excess Stage 1 Blend Total: 295sks	Blend: Premium Lite High Strength FM + 0.7% bwoc R-3 + 3% bwoc Potassium Chloride + 0.25lbs/sack Cello Flake + 0.5% bwoc CD-32 + 1.15% bwoc FL- 52A + 60 lbs/sack Calcium Carbonate + 124.4% Fresh Water. Yield 2.63 cuft/sk	Liner Hanger	N/A

Actual volumes will be calculated and determined by conditions onsite. All cement slurries will meet or exceed minimum BLM and New Mexico Oil Conservation Division requirements. Slurries used will be the slurries listed above or equivalent slurries depending on service provider selected. Cement yields may change depending on slurries selected.

All waiting on cement times shall be a minimum of 8 hours or adequate to achieve minimum of 500 psi compressive strength at the casing shoe prior to drilling out.

## 5. WELL PLAN & DIRECTIONAL DRILLING PROGRAM

The proposed horizontal well will have a kick off point of 500'. Directional plans are attached.

Description	Proposed Depth (TVD/MD)	Formation
Horizontal Lateral TD	5283'/10652'	Gallup



Lybrook P24A-2206 01H  
SHL: 626' FSL, 731' FEL Sec 24, T22N, R6W  
BHL: 330' FSL, 1780' FEL Sec 25, T22N, R6W  
Sandoval, New Mexico  
Lease Number: NMNM 117563

## 6. DRILLING FLUIDS PROGRAM

### a) Surface through Intermediate Casing Point:

Hole Size (in)	Depth (TVD/MD)	Mud Type	Density (ppg)	Viscosity (sec/qt)	Fluid Loss (cc)
30"	0-60'/60'	Fresh Water	8.3-9.2	38-100	4-28
12 1/4"	0'-500'/500'	Fresh Water	8.3-10	60-70	NC
8 3/4"	500'/500'-5267'/5529'	Fresh Water LSND	8.3-10	40-50	8-10

### b) Intermediate Casing Point to TD:

Hole Size (in)	Depth (TVD/MD)	Mud Type	Density (ppg)	Viscosity (sec/qt)	Fluid Loss (cc)
6 1/8"	5267'/5529'- 5283'/10652'	Fresh Water LSND	8.3-10	15-25	<15

c) There will be sufficient mud on location to control a blowout should one occur. Mud flow and volume will be monitored both visually and with electronic pit volume totalizers. Mud tests shall be performed every 24 hours after mudding up to determine, as applicable: density, viscosity, gel strength, filtration, and pH.

✓ d) A closed-loop system will be used to recover drilling fluid and dry cuttings in both phases of the well and on all hole intervals. Above-ground tanks will be utilized to hold cuttings and fluids for rig operations. A frac tank will be on location to store fresh water. Waste will be disposed of properly at an EPA-approved hazardous waste facility. Fresh water cuttings will be disposed of at Basin Disposal, Inc. and/or Industrial Ecosystems, Inc. The location will be lined in accordance with the Surface Use Plan of Operations.

## 7. TESTING, CORING, & LOGGING

- a) Drill Stem Testing - None anticipated.
- b) Coring - None anticipated.
- c) Mudd Logging - Mud loggers will be on location from kick off point to TD.
- d) Logging - See below.

Cased Hole:

CBL/CCL/GR/VDL will be run as needed for perforating control.

## 8. ABNORMAL PRESSURES & HYDROGEN SULFIDE

The anticipated bottom hole pressure is +/- 2528 psi based on a 9.0 ppg at 5402' TVD of the horizontal lateral target. No abnormal pressure or temperatures are anticipated.

No hydrogen sulfide gas is anticipated, however, if H<sub>2</sub>S is encountered, the guidelines in Onshore Order No. 6 will be followed.

## 9. ANTICIPATED START DATE AND DURATION OF OPERATIONS

Drilling is estimated to commence on November 5, 2015. It is anticipated that completion operations will begin within 30 days after the well has been drilled depending on fracture treatment schedules with various pumping service companies.

It is anticipated that the drilling of this well will take approximately 20 days.



LOC: 626' FSL, 731' FEL Sec 24, T22N, R6W County: Sandoval WELL: Lybrook P24A-2206 01H			Encana Oil & Gas (USA) Inc.  WELL SUMMARY				ENG: David Scadden 3-24-15 RIG: Unassigned GLE: 7207 RKBE: 7223			
MWD LWD	OPEN HOLE LOGGING	FORM	DEPTH			HOLE SIZE	CASING SPECS	MW MUD TYPE	DEVIATION INFORMATION	
			TVD	MD						
			60	60'		26	16" 42.09# 100sx Type I Neat 16.0ppg cmt	Fresh wtr 8.3-9.2		
		San Jose Fn.	0							
Multi-Well pad take survey every stand and run anti-collision report prior to spud	None					12 1/4	9 5/8" 36ppf J55 LTC  TOC Surface with 100% OH Excess: 228 sks Type III Cement + 1% bwoc Calcium Chloride + 0.25 lbs/sack Cello Flake + 0.2% bwoc FL-52A + 58.9% Fresh Water.	Fresh wtr  8.3-10	Vertical <1°	
		Nacimiento Fn. 9 5/8" Csg	surface 500	500.00						
Survey Every 60'-120', updating anticollision report after surveys. Stop operations and contact drilling engineer if separation factor approaches 1.5	No OH logs	Ojo Alamo Ss.	1,318			8 3/4	7" 26ppf J55 LTC  TOC @ surface (100% OH excess - 70% Lead 30% Tail) Stage 1 Total: 908sks  Stage 1 Lead: 515 sks Premium Lite FM + 3% CaCl2 + 0.25/sk Cello Flake + 5#/sk LCM-1 + 8% Bentonite + 0.4% FL-52A + 0.4% Sodium Metasilicate. Mixed at 12.1 ppg. Yield 2.13 cuft/sk.  Stage 1 Tail: 392 sks Type III Cement + 1% CaCl2 + 0.25#/sk Cello Flake + 0.2% FL-52A. Mixed at 14.6 ppg. Yield 1.38 cuft/sk.	Fresh Wtr  8.3-10	Vertical <1°	
		Kirtland Shale	1,524							
		Fruitland Coal	1,656							
		Pictured Cliffs Ss. Lewis Shale	1,874 2,011							
		Cliffhouse Ss. Menefee Fn.	2,669 3,378							
Surveys every 30' through the curve	Mud logger onsite	Point Lookout Ss.	4,135							
		Mancos Shale	4,351							
		KOP	500							500
		Mancos Silt	4,900							
		Gallup Fn.	5,168							
		7" Csg	5,267	5,529'						
Surveys every stand to TD unless directed otherwise by Geologist	No OH Logs	Horizontal Target TD	5,402 5,283	10,652		6 1/8	100' overlap at liner top		Horz Inc/TVD 91.2deg/5402ft	
		Base Gallup	5,454				5123' Drilled Lateral			TD = 10652.3 MD
MWD Gamma Directional							4 1/2" 11.6ppf SB80 LTC  TOC @ hanger (50% OH excess) Stage 1 Total: 295sks  Stage 1 Blend: 295 sks Premium Lite High Strength FM + 0.7% bwoc R-3 + 3% bwow Potassium Chloride + 0.25lbs/sack Cello Flake + 0.5% bwoc CD-32 + 1.15% bwoc FL-52A + 60 lbs/sack Calcium Carbonate + 124.4% Fresh Water. Yield 2.63 cuft/sk.	WBM 8.3-10		

**NOTES:**

- 1) Drill with 26" bit to 60', set 16" 42.09ppf conductor pipe
- 2) Drill surface to 500', R&C 9 5/8" casing
- 3) N/U BOP and surface equipment
- 4) Drill to KOP of 500', 8 3/4 inch holesize
- 5) Start curve at 10deg/100' build rate
- 6) Drill to csg point of 5529' MD
- 7) R&C 7" csg, circ cmt to surface
- 8) Land at ~55 deg, drill lateral to 10652' run 4 1/2 inch cemented liner






Project: Sandoval County, NM  
Site: S24-T22N-R6W  
Well: Lybrook P24A-2206 01H  
Wellbore: HZ  
Design: Plan #1



OIL CONS. DIV DIST. 3

DEC 16 2015

SECTION DETAILS										
Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	Vsect	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	500.0	0.00	0.00	500.0	0.0	0.0	0.00	0.00	0.0	
3	1505.5	20.11	254.68	1485.0	-46.1	-168.5	2.00	254.68	48.9	
4	3667.3	20.11	254.68	3515.0	-242.5	-885.3	0.00	0.00	257.1	
5	4672.8	0.00	0.00	4500.0	-288.6	-1053.8	2.00	180.00	306.0	
6	4918.3	0.00	0.00	4745.5	-288.6	-1053.8	0.00	0.00	306.0	
7	5931.7	91.20	180.95	5382.0	-938.5	-1064.6	9.00	180.95	956.0	
8	10652.3	91.20	180.95	5283.1	-5657.4	-1143.1	0.00	0.00	5675.6	Lybrook P24A-2206 01H PBHL





DEC 16 2015

<b>Database:</b>	USA EDM 5000 Multi Users DB	<b>Local Co-ordinate Reference:</b>	Well Lybrook P24A-2206 01H
<b>Company:</b>	EnCana Oil & Gas (USA) Inc	<b>TVD Reference:</b>	16' KB @ 7223.0ft
<b>Project:</b>	Sandoval County, NM	<b>MD Reference:</b>	16' KB @ 7223.0ft
<b>Site:</b>	S24-T22N-R6W	<b>North Reference:</b>	True
<b>Well:</b>	Lybrook P24A-2206 01H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	HZ		
<b>Design:</b>	Plan #1		

<b>Project</b>	Sandoval County, NM		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Central Zone		

<b>Site</b>	S24-T22N-R6W			
<b>Site Position:</b>		<b>Northing:</b>	1,863,955.62 ft	<b>Latitude:</b> 36.117104
<b>From:</b>	Lat/Long	<b>Easting:</b>	1,296,422.70 ft	<b>Longitude:</b> -107.414705
<b>Position Uncertainty:</b>	0.0 ft	<b>Slot Radius:</b>	13.200 in	<b>Grid Convergence:</b> -0.69 °

<b>Well</b>	Lybrook P24A-2206 01H			
<b>Well Position</b>	+N/-S	0.0 ft	<b>Northing:</b>	1,863,955.62 ft
	+E/-W	0.0 ft	<b>Easting:</b>	1,296,422.70 ft
<b>Position Uncertainty</b>	0.0 ft		<b>Wellhead Elevation:</b>	0.0 ft
			<b>Ground Level:</b>	7,207.0 ft

<b>Wellbore</b>	HZ				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	HDGM	3/10/2015	9.12	62.93	49,673

<b>Design</b>	Plan #1			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	0.0
<b>Vertical Section:</b>	<b>Depth From (TVD)</b>	<b>+N/-S</b>	<b>+E/-W</b>	<b>Direction</b>
	(ft)	(ft)	(ft)	(°)
	0.0	0.0	0.0	180.95

<b>Plan Sections</b>										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,505.5	20.11	254.68	1,485.0	-46.1	-168.5	2.00	2.00	0.00	254.68	
3,667.3	20.11	254.68	3,515.0	-242.5	-885.3	0.00	0.00	0.00	0.00	
4,672.8	0.00	0.00	4,500.0	-288.6	-1,053.8	2.00	-2.00	0.00	180.00	
4,918.3	0.00	0.00	4,745.5	-288.6	-1,053.8	0.00	0.00	0.00	0.00	
5,931.7	91.20	180.95	5,382.0	-938.5	-1,064.6	9.00	9.00	0.00	180.95	
10,652.3	91.20	180.95	5,283.1	-5,657.4	-1,143.1	0.00	0.00	0.00	0.00	Lybrook P24A-2206 0



# Planning Report

Database: USA EDM 5000 Multi Users DB  
 Company: EnCana Oil & Gas (USA) Inc  
 Project: Sandoval County, NM  
 Site: S24-T22N-R6W  
 Well: Lybrook P24A-2206 01H  
 Wellbore: HZ  
 Design: Plan #1

Local Co-ordinate Reference: Well Lybrook P24A-2206 01H  
 TVD Reference: 16' KB @ 7223.0ft  
 MD Reference: 16' KB @ 7223.0ft  
 North Reference: True  
 Survey Calculation Method: Minimum Curvature

## Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Comments / Formations
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	KOP @ 500' - 9 5/8"
600.0	2.00	254.68	600.0	-0.5	-1.7	0.5	2.00	2.00	
700.0	4.00	254.68	699.8	-1.8	-6.7	2.0	2.00	2.00	
800.0	6.00	254.68	799.5	-4.1	-15.1	4.4	2.00	2.00	
900.0	8.00	254.68	898.7	-7.4	-26.9	7.8	2.00	2.00	
1,000.0	10.00	254.68	997.5	-11.5	-42.0	12.2	2.00	2.00	
1,100.0	12.00	254.68	1,095.6	-16.5	-60.4	17.5	2.00	2.00	
1,200.0	14.00	254.68	1,193.1	-22.5	-82.1	23.8	2.00	2.00	
1,300.0	16.00	254.68	1,289.6	-29.3	-107.0	31.1	2.00	2.00	
1,328.8	16.58	254.68	1,317.3	-31.4	-114.8	33.3	2.00	2.00	Ojo Alamo Ss.
1,400.0	18.00	254.68	1,385.3	-37.0	-135.2	39.3	2.00	2.00	
1,500.0	20.00	254.68	1,479.8	-45.6	-166.6	48.4	2.00	2.00	
1,505.5	20.11	254.68	1,485.0	-46.1	-168.5	48.9	2.00	2.00	EOB; INC=20.11°
1,545.9	20.11	254.68	1,522.9	-49.8	-181.8	52.8	0.00	0.00	Kirtland Shale
1,600.0	20.11	254.68	1,573.7	-54.7	-199.8	58.0	0.00	0.00	
1,686.1	20.11	254.68	1,654.6	-62.5	-228.4	66.3	0.00	0.00	Fruitland Coal
1,700.0	20.11	254.68	1,667.6	-63.8	-233.0	67.7	0.00	0.00	
1,800.0	20.11	254.68	1,761.5	-72.9	-266.1	77.3	0.00	0.00	
1,900.0	20.11	254.68	1,855.4	-82.0	-299.3	86.9	0.00	0.00	
1,917.8	20.11	254.68	1,872.1	-83.6	-305.2	88.6	0.00	0.00	Pictured Cliffs Ss.
2,000.0	20.11	254.68	1,949.3	-91.0	-332.4	96.5	0.00	0.00	
2,063.4	20.11	254.68	2,008.8	-96.8	-353.5	102.6	0.00	0.00	Lewis Shale
2,100.0	20.11	254.68	2,043.2	-100.1	-365.6	106.2	0.00	0.00	
2,200.0	20.11	254.68	2,137.1	-109.2	-398.8	115.8	0.00	0.00	
2,300.0	20.11	254.68	2,231.0	-118.3	-431.9	125.4	0.00	0.00	
2,400.0	20.11	254.68	2,324.9	-127.4	-465.1	135.1	0.00	0.00	
2,500.0	20.11	254.68	2,418.9	-136.5	-498.2	144.7	0.00	0.00	
2,600.0	20.11	254.68	2,512.8	-145.5	-531.4	154.3	0.00	0.00	
2,700.0	20.11	254.68	2,606.7	-154.6	-564.6	164.0	0.00	0.00	
2,762.6	20.11	254.68	2,665.4	-160.3	-585.3	170.0	0.00	0.00	Cliffhouse Ss.
2,800.0	20.11	254.68	2,700.6	-163.7	-597.7	173.6	0.00	0.00	
2,900.0	20.11	254.68	2,794.5	-172.8	-630.9	183.2	0.00	0.00	
3,000.0	20.11	254.68	2,888.4	-181.9	-664.1	192.8	0.00	0.00	
3,100.0	20.11	254.68	2,982.3	-190.9	-697.2	202.5	0.00	0.00	
3,200.0	20.11	254.68	3,076.2	-200.0	-730.4	212.1	0.00	0.00	
3,300.0	20.11	254.68	3,170.1	-209.1	-763.5	221.7	0.00	0.00	
3,400.0	20.11	254.68	3,264.0	-218.2	-796.7	231.4	0.00	0.00	
3,500.0	20.11	254.68	3,357.9	-227.3	-829.9	241.0	0.00	0.00	
3,516.0	20.11	254.68	3,372.9	-228.7	-835.2	242.5	0.00	0.00	Menefee Fn.
3,600.0	20.11	254.68	3,451.8	-236.4	-863.0	250.6	0.00	0.00	
3,667.3	20.11	254.68	3,515.0	-242.5	-885.3	257.1	0.00	0.00	Start Drop -2.00
3,700.0	19.46	254.68	3,545.8	-245.4	-896.0	260.2	2.00	-2.00	
3,800.0	17.46	254.68	3,640.6	-253.7	-926.5	269.1	2.00	-2.00	
3,900.0	15.46	254.68	3,736.5	-261.2	-953.9	277.0	2.00	-2.00	
4,000.0	13.46	254.68	3,833.3	-267.8	-977.9	284.0	2.00	-2.00	
4,100.0	11.46	254.68	3,931.0	-273.5	-998.7	290.0	2.00	-2.00	
4,200.0	9.46	254.68	4,029.3	-278.3	-1,016.3	295.1	2.00	-2.00	



# Planning Report

Database: USA EDM 5000 Multi Users DB  
 Company: EnCana Oil & Gas (USA) Inc  
 Project: Sandoval County, NM  
 Site: S24-T22N-R6W  
 Well: Lybrook P24A-2206 01H  
 Wellbore: HZ  
 Design: Plan #1

Local Co-ordinate Reference: Well Lybrook P24A-2206 01H  
 TVD Reference: 16' KB @ 7223.0ft  
 MD Reference: 16' KB @ 7223.0ft  
 North Reference: True  
 Survey Calculation Method: Minimum Curvature

## Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Comments / Formations
4,300.0	7.46	254.68	4,128.2	-282.2	-1,030.4	299.2	2.00	-2.00	
4,300.5	7.45	254.68	4,128.7	-282.2	-1,030.5	299.3	2.00	-2.00	Point Lookout Ss.
4,400.0	5.46	254.68	4,227.6	-285.2	-1,041.3	302.4	2.00	-2.00	
4,500.0	3.46	254.68	4,327.3	-287.2	-1,048.8	304.6	2.00	-2.00	
4,517.4	3.11	254.68	4,344.6	-287.5	-1,049.7	304.9	2.00	-2.00	Mancos Shale
4,600.0	1.46	254.68	4,427.2	-288.4	-1,052.9	305.8	2.00	-2.00	
4,672.8	0.00	0.00	4,500.0	-288.6	-1,053.8	306.0	2.00	-2.00	EOD; INC=0°
4,700.0	0.00	0.00	4,527.2	-288.6	-1,053.8	306.0	0.00	0.00	
4,800.0	0.00	0.00	4,627.2	-288.6	-1,053.8	306.0	0.00	0.00	
4,900.0	0.00	0.00	4,727.2	-288.6	-1,053.8	306.0	0.00	0.00	
4,918.3	0.00	0.00	4,745.5	-288.6	-1,053.8	306.0	0.00	0.00	Start Build 9.00
5,000.0	7.35	180.95	4,826.9	-293.8	-1,053.9	311.3	9.00	9.00	
5,067.4	13.42	180.95	4,893.2	-306.0	-1,054.1	323.4	9.00	9.00	Mancos Silt
5,100.0	16.35	180.95	4,924.7	-314.3	-1,054.2	331.8	9.00	9.00	
5,200.0	25.35	180.95	5,018.1	-349.9	-1,054.8	367.3	9.00	9.00	
5,300.0	34.35	180.95	5,104.7	-399.6	-1,055.6	417.1	9.00	9.00	
5,367.6	40.44	180.95	5,158.4	-440.7	-1,056.3	458.1	9.00	9.00	Gallup Fn.
5,400.0	43.35	180.95	5,182.5	-462.3	-1,056.7	479.7	9.00	9.00	
5,500.0	52.35	180.95	5,249.5	-536.3	-1,057.9	553.8	9.00	9.00	
5,529.4	55.00	180.95	5,267.0	-560.0	-1,058.3	577.5	9.00	9.00	ICP @ 55°
5,600.0	61.35	180.95	5,304.2	-620.0	-1,059.3	637.4	9.00	9.00	
5,700.0	70.35	180.95	5,345.0	-711.1	-1,060.8	728.6	9.00	9.00	
5,800.0	79.35	180.95	5,371.1	-807.5	-1,062.4	825.0	9.00	9.00	
5,900.0	88.35	180.95	5,381.8	-906.8	-1,064.1	924.3	9.00	9.00	
5,931.7	91.20	180.95	5,382.0	-938.5	-1,064.6	956.0	9.00	9.00	LP @ 5382' TVD; 91.2°
5,931.7	91.20	180.95	5,382.0	-938.5	-1,064.6	956.0	0.00	0.00	Lybrook P24A-2206 01H POE
6,000.0	91.20	180.95	5,380.5	-1,006.8	-1,065.7	1,024.3	0.00	0.00	
6,100.0	91.20	180.95	5,378.4	-1,106.8	-1,067.4	1,124.3	0.00	0.00	
6,200.0	91.20	180.95	5,376.3	-1,206.7	-1,069.1	1,224.3	0.00	0.00	
6,300.0	91.20	180.95	5,374.2	-1,306.7	-1,070.7	1,324.3	0.00	0.00	
6,400.0	91.20	180.95	5,372.2	-1,406.6	-1,072.4	1,424.2	0.00	0.00	
6,500.0	91.20	180.95	5,370.1	-1,506.6	-1,074.0	1,524.2	0.00	0.00	
6,600.0	91.20	180.95	5,368.0	-1,606.6	-1,075.7	1,624.2	0.00	0.00	
6,700.0	91.20	180.95	5,365.9	-1,706.5	-1,077.4	1,724.2	0.00	0.00	
6,800.0	91.20	180.95	5,363.8	-1,806.5	-1,079.0	1,824.1	0.00	0.00	
6,900.0	91.20	180.95	5,361.7	-1,906.5	-1,080.7	1,924.1	0.00	0.00	
7,000.0	91.20	180.95	5,359.6	-2,006.4	-1,082.4	2,024.1	0.00	0.00	
7,100.0	91.20	180.95	5,357.5	-2,106.4	-1,084.0	2,124.1	0.00	0.00	
7,200.0	91.20	180.95	5,355.4	-2,206.4	-1,085.7	2,224.1	0.00	0.00	
7,300.0	91.20	180.95	5,353.3	-2,306.3	-1,087.3	2,324.0	0.00	0.00	
7,400.0	91.20	180.95	5,351.2	-2,406.3	-1,089.0	2,424.0	0.00	0.00	
7,500.0	91.20	180.95	5,349.1	-2,506.3	-1,090.7	2,524.0	0.00	0.00	
7,600.0	91.20	180.95	5,347.0	-2,606.2	-1,092.3	2,624.0	0.00	0.00	
7,700.0	91.20	180.95	5,344.9	-2,706.2	-1,094.0	2,723.9	0.00	0.00	
7,800.0	91.20	180.95	5,342.8	-2,806.1	-1,095.7	2,823.9	0.00	0.00	
7,900.0	91.20	180.95	5,340.7	-2,906.1	-1,097.3	2,923.9	0.00	0.00	
8,000.0	91.20	180.95	5,338.6	-3,006.1	-1,099.0	3,023.9	0.00	0.00	
8,100.0	91.20	180.95	5,336.6	-3,106.0	-1,100.6	3,123.9	0.00	0.00	
8,200.0	91.20	180.95	5,334.5	-3,206.0	-1,102.3	3,223.8	0.00	0.00	
8,300.0	91.20	180.95	5,332.4	-3,306.0	-1,104.0	3,323.8	0.00	0.00	
8,400.0	91.20	180.95	5,330.3	-3,405.9	-1,105.6	3,423.8	0.00	0.00	
8,500.0	91.20	180.95	5,328.2	-3,505.9	-1,107.3	3,523.8	0.00	0.00	



# Planning Report

<b>Database:</b>	USA EDM 5000 Multi Users DB	<b>Local Co-ordinate Reference:</b>	Well Lybrook P24A-2206 01H
<b>Company:</b>	EnCana Oil & Gas (USA) Inc	<b>TVD Reference:</b>	16' KB @ 7223.0ft
<b>Project:</b>	Sandoval County, NM	<b>MD Reference:</b>	16' KB @ 7223.0ft
<b>Site:</b>	S24-T22N-R6W	<b>North Reference:</b>	True
<b>Well:</b>	Lybrook P24A-2206 01H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	HZ		
<b>Design:</b>	Plan #1		

## Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Comments / Formations
8,600.0	91.20	180.95	5,326.1	-3,605.9	-1,108.9	3,623.7	0.00	0.00	
8,700.0	91.20	180.95	5,324.0	-3,705.8	-1,110.6	3,723.7	0.00	0.00	
8,800.0	91.20	180.95	5,321.9	-3,805.8	-1,112.3	3,823.7	0.00	0.00	
8,900.0	91.20	180.95	5,319.8	-3,905.7	-1,113.9	3,923.7	0.00	0.00	
9,000.0	91.20	180.95	5,317.7	-4,005.7	-1,115.6	4,023.7	0.00	0.00	
9,100.0	91.20	180.95	5,315.6	-4,105.7	-1,117.3	4,123.6	0.00	0.00	
9,200.0	91.20	180.95	5,313.5	-4,205.6	-1,118.9	4,223.6	0.00	0.00	
9,300.0	91.20	180.95	5,311.4	-4,305.6	-1,120.6	4,323.6	0.00	0.00	
9,400.0	91.20	180.95	5,309.3	-4,405.6	-1,122.2	4,423.6	0.00	0.00	
9,500.0	91.20	180.95	5,307.2	-4,505.5	-1,123.9	4,523.6	0.00	0.00	
9,600.0	91.20	180.95	5,305.1	-4,605.5	-1,125.6	4,623.5	0.00	0.00	
9,700.0	91.20	180.95	5,303.0	-4,705.5	-1,127.2	4,723.5	0.00	0.00	
9,800.0	91.20	180.95	5,300.9	-4,805.4	-1,128.9	4,823.5	0.00	0.00	
9,900.0	91.20	180.95	5,298.9	-4,905.4	-1,130.6	4,923.5	0.00	0.00	
10,000.0	91.20	180.95	5,296.8	-5,005.4	-1,132.2	5,023.4	0.00	0.00	
10,100.0	91.20	180.95	5,294.7	-5,105.3	-1,133.9	5,123.4	0.00	0.00	
10,200.0	91.20	180.95	5,292.6	-5,205.3	-1,135.5	5,223.4	0.00	0.00	
10,300.0	91.20	180.95	5,290.5	-5,305.2	-1,137.2	5,323.4	0.00	0.00	
10,400.0	91.20	180.95	5,288.4	-5,405.2	-1,138.9	5,423.4	0.00	0.00	
10,500.0	91.20	180.95	5,286.3	-5,505.2	-1,140.5	5,523.3	0.00	0.00	
10,600.0	91.20	180.95	5,284.2	-5,605.1	-1,142.2	5,623.3	0.00	0.00	
10,652.3	91.20	180.95	5,283.1	-5,657.4	-1,143.1	5,675.6	0.00	0.00	TD at 10652.3 - Lybrook P24A-2206 01H PBHL

## Targets

Target Name	- hit/miss target	Dip Angle (°)	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (ft)	Easting (ft)	Latitude	Longitude
Lybrook P24A-2206 01H	- plan misses target center by 0.1ft at 5931.7ft MD (5382.0 TVD, -938.5 N, -1064.6 E)	0.00	0.00	5,381.9	-938.5	-1,064.6	1,863,029.92	1,295,346.93	36.114526	-107.418309
Lybrook P24A-2206 01H	- plan hits target center	0.00	0.00	5,283.1	-5,657.4	-1,143.1	1,858,312.27	1,295,211.93	36.101564	-107.418574

## Casing Points

Measured Depth (ft)	Vertical Depth (ft)	Name	Casing Diameter (in)	Hole Diameter (in)
500.0	500.0	9 5/8"	0.000	0.000
5,529.4	5,267.0	ICP @ 55°	0.000	0.000



# Planning Report

**Database:** USA EDM 5000 Multi Users DB  
**Company:** EnCana Oil & Gas (USA) Inc  
**Project:** Sandoval County, NM  
**Site:** S24-T22N-R6W  
**Well:** Lybrook P24A-2206 01H  
**Wellbore:** HZ  
**Design:** Plan #1

**Local Co-ordinate Reference:** Well Lybrook P24A-2206 01H  
**TVD Reference:** 16' KB @ 7223.0ft  
**MD Reference:** 16' KB @ 7223.0ft  
**North Reference:** True  
**Survey Calculation Method:** Minimum Curvature

Formations						
Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)	
1,328.8	1,318.0	Ojo Alamo Ss.		-1.20	180.95	
1,545.9	1,524.0	Kirtland Shale		-1.20	180.95	
1,686.1	1,656.0	Fruitland Coal		-1.20	180.95	
1,917.8	1,874.0	Pictured Cliffs Ss.		-1.20	180.95	
2,063.4	2,011.0	Lewis Shale		-1.20	180.95	
2,762.6	2,669.0	Cliffhouse Ss.		-1.20	180.95	
3,516.0	3,378.0	Menefee Fn.		-1.20	180.95	
4,300.5	4,135.0	Point Lookout Ss.		-1.20	180.95	
4,517.4	4,351.0	Mancos Shale		-1.20	180.95	
5,067.4	4,900.0	Mancos Silt		-1.20	180.95	
5,367.6	5,168.0	Gallup Fn.		-1.20	180.95	

Plan Annotations					
Measured Depth (ft)	Vertical Depth (ft)	Local Coordinates			
		+N/-S (ft)	+E/-W (ft)	Comment	
500.0	500.0	0.0	0.0	KOP @ 500'	
1,505.5	1,485.0	-46.1	-168.5	EOB; INC=20.11°	
3,667.3	3,515.0	-242.5	-885.3	Start Drop -2.00	
4,672.8	4,500.0	-288.6	-1,053.8	EOD; INC=0°	
4,918.3	4,745.5	-288.6	-1,053.8	Start Build 9.00	
5,931.7	5,382.0	-938.5	-1,064.6	LP @ 5382' TVD; 91.2°	
10,652.3	5,283.1	-5,657.4	-1,143.1	TD at 10652.3	



# **EnCana Oil & Gas (USA) Inc**

**Sandoval County, NM**

**S24-T22N-R6W**

**Lybrook P24A-2206 01H**

**HZ**

**Plan #1**

## **Anticollision Report**

**25 March, 2015**



# Anticollision Report

<b>Company:</b>	EnCana Oil & Gas (USA) Inc	<b>Local Co-ordinate Reference:</b>	Well Lybrook P24A-2206 01H
<b>Project:</b>	Sandoval County, NM	<b>TVD Reference:</b>	16' KB @ 7223.0ft
<b>Reference Site:</b>	S24-T22N-R6W	<b>MD Reference:</b>	16' KB @ 7223.0ft
<b>Site Error:</b>	0.0ft	<b>North Reference:</b>	True
<b>Reference Well:</b>	Lybrook P24A-2206 01H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Well Error:</b>	0.0ft	<b>Output errors are at</b>	2.00 sigma
<b>Reference Wellbore</b>	HZ	<b>Database:</b>	USA EDM 5000 Multi Users DB
<b>Reference Design:</b>	Plan #1	<b>Offset TVD Reference:</b>	Offset Datum

<b>Reference</b>	Plan #1
<b>Filter type:</b>	NO GLOBAL FILTER: Using user defined selection & filtering criteria
<b>Interpolation Method:</b>	Stations
<b>Depth Range:</b>	Unlimited
<b>Results Limited by:</b>	Maximum center-center distance of 1,000.0ft
<b>Warning Levels Evaluated at:</b>	2.00 Sigma
<b>Error Model:</b>	Systematic Ellipse
<b>Scan Method:</b>	Closest Approach 3D
<b>Error Surface:</b>	Elliptical Conic

<b>Survey Tool Program</b>	<b>Date</b>	3/25/2015
<b>From (ft)</b>	<b>To (ft)</b>	<b>Survey (Wellbore)</b>
0.0	10,652.3	Plan #1 (HZ)
		<b>Tool Name</b>
		Geolink MWD
		<b>Description</b>
		Geolink MWD

Summary						
Site Name	Reference	Offset	Distance		Separation	Warning
	Measured	Measured	Between	Between		
Offset Well - Wellbore - Design	Depth	Depth	Centres	Ellipses	Factor	
	(ft)	(ft)	(ft)	(ft)		
S24-T22N-R6W						
Lybrook P24A-2206 02H - HZ - Plan #1	629.9	629.7	29.3	27.2	13.653	CC, ES
Lybrook P24A-2206 02H - HZ - Plan #1	700.0	699.0	30.2	27.8	12.592	SF



# Anticollision Report

**Company:** EnCana Oil & Gas (USA) Inc  
**Project:** Sandoval County, NM  
**Reference Site:** S24-T22N-R6W  
**Site Error:** 0.0ft  
**Reference Well:** Lybrook P24A-2206 01H  
**Well Error:** 0.0ft  
**Reference Wellbore:** HZ  
**Reference Design:** Plan #1

**Local Co-ordinate Reference:** Well Lybrook P24A-2206 01H  
**TVD Reference:** 16' KB @ 7223.0ft  
**MD Reference:** 16' KB @ 7223.0ft  
**North Reference:** True  
**Survey Calculation Method:** Minimum Curvature  
**Output errors are at** 2.00 sigma  
**Database:** USA EDM 5000 Multi Users DB  
**Offset TVD Reference:** Offset Datum

Offset Design S24-T22N-R6W - Lybrook P24A-2206 02H - HZ - Plan #1													Offset Site Error:	0.0 ft
Survey Program: 0-Geolink MWD													Offset Well Error:	0.0 ft
Reference	Offset	Semi Major Axis		Distance		Between Centres		Between Ellipses		Total Uncertainty	Separation Factor	Warning		
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Axis			
0.0	0.0	0.0	0.0	0.0	0.0	180.00	-29.9	0.0	29.9					
100.0	100.0	100.0	100.0	0.1	0.1	180.00	-29.9	0.0	29.9	29.6	0.29	101.812		
200.0	200.0	200.0	200.0	0.3	0.3	180.00	-29.9	0.0	29.9	29.2	0.64	46.479		
300.0	300.0	300.0	300.0	0.5	0.5	180.00	-29.9	0.0	29.9	28.9	0.99	30.113		
400.0	400.0	400.0	400.0	0.7	0.7	180.00	-29.9	0.0	29.9	28.5	1.34	22.271		
500.0	500.0	500.0	500.0	0.8	0.8	180.00	-29.9	0.0	29.9	28.2	1.69	17.670		
600.0	600.0	600.0	600.0	1.0	1.0	-77.97	-29.9	0.0	29.4	27.4	2.04	14.430		
629.9	629.9	629.7	629.7	1.1	1.1	-80.46	-30.0	0.1	29.3	27.2	2.15	13.653 CC, ES		
700.0	699.8	699.0	699.0	1.2	1.2	-89.98	-31.0	1.3	30.2	27.8	2.40	12.592 SF		
800.0	799.5	797.2	797.0	1.4	1.4	-108.14	-34.3	5.1	36.4	33.6	2.78	13.116		
900.0	898.7	894.1	893.5	1.7	1.6	-123.58	-39.7	11.4	50.4	47.2	3.15	15.992		
1,000.0	997.5	990.2	989.0	1.9	1.8	-133.55	-46.9	19.8	71.7	68.2	3.53	20.332		
1,100.0	1,095.6	1,086.3	1,084.5	2.3	2.0	-140.08	-54.5	28.6	97.3	93.4	3.91	24.875		
1,200.0	1,193.1	1,181.6	1,179.0	2.7	2.2	-144.67	-61.9	37.2	126.4	122.1	4.30	29.377		
1,300.0	1,289.6	1,275.7	1,272.5	3.2	2.5	-148.10	-69.3	45.8	158.9	154.2	4.70	33.812		
1,400.0	1,385.3	1,368.7	1,364.8	3.7	2.7	-150.76	-76.6	54.3	194.7	189.6	5.10	38.178		
1,505.5	1,485.0	1,465.4	1,460.8	4.3	3.0	-152.99	-84.2	63.1	235.9	230.3	5.52	42.714		
1,600.0	1,573.7	1,551.3	1,546.1	4.9	3.2	-154.85	-90.9	70.9	274.5	268.5	5.91	46.408		
1,700.0	1,667.6	1,642.2	1,636.3	5.5	3.4	-156.33	-98.0	79.1	315.5	309.2	6.33	49.842		
1,800.0	1,761.5	1,733.1	1,726.6	6.1	3.7	-157.47	-105.2	87.4	356.7	350.0	6.75	52.865		
1,900.0	1,855.4	1,824.0	1,816.9	6.8	3.9	-158.37	-112.3	95.7	398.0	390.8	7.17	55.544		
2,000.0	1,949.3	1,915.0	1,907.1	7.4	4.2	-159.11	-119.4	103.9	439.3	431.8	7.58	57.932		
2,100.0	2,043.2	2,005.9	1,997.4	8.1	4.4	-159.72	-126.5	112.2	480.7	472.7	8.00	60.072		
2,200.0	2,137.1	2,096.8	2,087.6	8.7	4.6	-160.23	-133.7	120.5	522.2	513.8	8.42	62.000		
2,300.0	2,231.0	2,187.7	2,177.9	9.3	4.9	-160.67	-140.8	128.8	563.6	554.8	8.84	63.745		
2,400.0	2,324.9	2,278.6	2,268.2	10.0	5.1	-161.04	-147.9	137.0	605.1	595.9	9.26	65.333		
2,500.0	2,418.9	2,369.6	2,358.4	10.6	5.4	-161.37	-155.0	145.3	646.6	637.0	9.68	66.783		
2,600.0	2,512.8	2,460.5	2,448.7	11.3	5.6	-161.66	-162.2	153.6	688.2	678.1	10.10	68.111		
2,700.0	2,606.7	2,551.4	2,538.9	11.9	5.9	-161.92	-169.3	161.8	729.7	719.2	10.52	69.333		
2,800.0	2,700.6	2,642.3	2,629.2	12.6	6.1	-162.15	-176.4	170.1	771.2	760.3	10.95	70.461		
2,900.0	2,794.5	2,733.2	2,719.5	13.2	6.4	-162.35	-183.5	178.4	812.8	801.4	11.37	71.505		
3,000.0	2,888.4	2,824.2	2,809.7	13.9	6.6	-162.54	-190.7	186.6	854.4	842.6	11.79	72.474		
3,100.0	2,982.3	2,915.1	2,900.0	14.5	6.8	-162.71	-197.8	194.9	895.9	883.7	12.21	73.375		
3,200.0	3,076.2	3,006.0	2,990.3	15.2	7.1	-162.86	-204.9	203.2	937.5	924.9	12.63	74.217		
3,300.0	3,170.1	3,096.9	3,080.5	15.8	7.3	-163.00	-212.0	211.5	979.1	966.0	13.05	75.003		



## Anticollision Report


**Company:** EnCana Oil & Gas (USA) Inc  
**Project:** Sandoval County, NM  
**Reference Site:** S24-T22N-R6W  
**Site Error:** 0.0ft  
**Reference Well:** Lybrook P24A-2206 01H  
**Well Error:** 0.0ft  
**Reference Wellbore:** HZ  
**Reference Design:** Plan #1

**Local Co-ordinate Reference:** Well Lybrook P24A-2206 01H  
**TVD Reference:** 16' KB @ 7223.0ft  
**MD Reference:** 16' KB @ 7223.0ft  
**North Reference:** True  
**Survey Calculation Method:** Minimum Curvature  
**Output errors are at** 2.00 sigma  
**Database:** USA EDM 5000 Multi Users DB  
**Offset TVD Reference:** Offset Datum

Reference Depths are relative to 16' KB @ 7223.0ft  
Offset Depths are relative to Offset Datum  
Central Meridian is -106.250000 °

Coordinates are relative to: Lybrook P24A-2206 01H  
Coordinate System is US State Plane 1983, New Mexico Central Zone  
Grid Convergence at Surface is: -0.69°

### Ladder Plot



### LEGEND

— Lybrook P24A-2206 02H, HZ, Plan #1 V0



Lybrook P24A-2206 01H

SHL: SESE Section 24, T22N, R6W  
626' FSL and 731' FEL

BHL: SWSE Section 25, T22N, R6W  
330' FSL and 1780' FEL

Sandoval County, New Mexico

Lease Number: NMNM 117563

inch outside diameter, buried steel well connect pipeline that was submitted to the BLM concurrently with this Application for Permit to Drill.

## 7. METHODS FOR HANDLING WASTE

### A. Cuttings

1. A closed-loop system will be used. Cuttings will be moved through a shaker system on the drill rig that separates drilling fluids from the cuttings. Cuttings will be stored onsite in above-ground storage tanks. Cuttings will be pulled from the storage tanks, mixed with saw dust or similar absorbent material, and disposed of at the Envirotech, Inc. and/or Industrial Ecosystem, Inc. waste disposal facilities.
2. The closed-loop system storage tanks will be adequately sized to ensure confinement of all fluids and will provide sufficient freeboard to prevent uncontrolled releases.
3. A 20-mil liner will be installed under tanks, pumps, ancillary facilities, and truck loading/unloading areas associated with the closed-loop system.

### B. Drilling Fluids

1. A closed-loop system will be used. Drilling fluids will be stored onsite in above-ground storage tanks. Upon termination of drilling operations, the drilling fluids will be recycled and transferred to other permitted closed-loop systems or returned to the vendor for reuse, as practical. Residual fluids will be vacuumed from the storage tanks and disposed of at Basin Disposal, Inc. and/or Industrial Ecosystem, Inc. waste disposal facilities.
2. The closed-loop system storage tanks will be adequately sized to ensure confinement of all fluids and will provide sufficient freeboard to prevent uncontrolled releases.
3. The closed-loop system storage tanks will be placed in bermed secondary containment sized to accommodate a minimum of 110 percent of the volume of the largest storage tank.
4. A 20-mil liner will be installed under tanks, pumps, ancillary facilities, and truck loading/unloading areas associated with the closed-loop system.

### C. Flowback Water

1. The water-based solution that flows back to the surface during and after completion operations will be placed in storage tanks on the location.
2. Flowback water will be confined to a storage tank for a period not to exceed 90 days after initial production and will be disposed of at Basin Disposal, Inc. and/or Industrial Ecosystem, Inc. waste disposal facilities.

### D. Spills – any spills of non-freshwater fluids will be immediately cleaned up and removed to an approved disposal site. Encana will also notify the BLM within 24 hours of any spill.

### E. Sewage – self-contained, chemical toilets will be provided for human waste disposal. The toilet holding tanks will be pumped, as needed, and the contents thereof disposed of in an approved sewage disposal facility. The toilets will be onsite during all operations.

### F. Garbage and other waste material – garbage, trash and other waste materials will be collected in a portable, self-contained and fully-enclosed trash container during drilling and completion operations. The accumulated trash will be removed, as needed, and will be disposed of at an authorized sanitary landfill. No trash will be buried or burned on location.



**ENCANA OIL & GAS (USA) INC.**  
LYBROOK P24A-2206 #01H  
626' FSL & 731' FEL  
LOCATED IN THE SE/4 SE/4 OF SECTION 24  
T22N, R06W, N.M.P.M.  
SANDOVAL COUNTY, NEW MEXICO  
1,100' +/- OF NEW ACCESS ACROSS BLM LANDS

### **DIRECTIONS**

- 1) FROM THE INTERSECTION OF HWY 64 & HWY 550 IN BLOOMFIELD, NEW MEXICO, TRAVEL SOUTH ON HWY 550 FOR 54.4 MILES TO COUNSELOR, NEW MEXICO, TO INDIAN SERVICE ROUTE 474.
- 2) TURN RIGHT (SOUTH) AND FOLLOW FOR 3.5 MILES TO AN INTERSECTION WITH AN OILFIELD SERVICE ROAD.
- 3) TURN LEFT (SOUTHEAST) AND FOLLOW 2.3 MILES TO A THREE WAY INTERSECTION. IT **MUST BE NOTED THAT AT THIS POINT YOU ARE ENTERING THE JICARILLA APACHE NATION AND PERMIT IS REQUIRED TO ENTER AND USE THIS ACCESS ROAD.**
- 4) TURN RIGHT (SOUTH) AND TRAVEL 2.1 MILES TO THE PROPOSED LYBROOK P24A-2206 ACCESS ROAD.
- 5) TURN RIGHT AND FOLLOW THE PROPOSED ACCESS ROAD SOUTHWEST FOR 0.2 MILES TO THE PROPOSED P24A-2206 LOCATION.
- 6) WELL FLAG LOCATED AT: LATITUDE: 36.117104° N, LONGITUDE: 107.414705° W ( NAD 83)



**encana**