Schematic - Current ConocoPhillips SCOTT #7 API / IIWI State/Province Field Name County SAN JUAN NORTH BLANCO MESAVERDE 3004511094 **NEW MEXICO** (PRORATED GAS East/West Distance (ft) East/West Reference North/South Distance (ft) North/South Reference **Original Spud Date** Surface Legal Location 825.00 FNL 5/30/1955 003-031N-010W-B FEL Original Hole, 3/23/2016 9:13:48 AM MD (ftKB) Vertical schematic (actual) Formation Tops OIL CONS. DIV DIST, 3 9.8 Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 10.0 ftKB; 41.7 ftKB 41.7 MAR 2 4 2016 Tubing Pup Joint; 2 3/8 in; 4.70 lb/ft; J-55; 41.7 ftKB; 60.2 ftKB 60.0 170.6 Surface Casing Cement; 10.0-171.7; 5/30/1955; Cemented with 125 sacks 1; Surface; 9 5/8 in; 0.000 in; 9.8 ftKB; cement; circulated to surface. 171.6 171.5 ftKB Cement Squeeze; 60.0-775.0; 3/4/1970: Squeezed with 150 sacks 185.0 Class C and 50 sacks Class C neat. TOC at 60' (Temp survey 3/4/1970). 774.9 SQUEEZE PERFS; 775.0; 3/4/1970 Re-squeezed with 215 sacks Class C. Cement Squeeze; 1,242.0-1,350.0; 1,242.1 3/3/1970; Squeezed with 50 sacks SQUEEZE PERFS; 1,350.0; 3/3/1970 Class C. TOC at 1242' (Temp survey) 1,350.1 Cement Squeeze; 1,413.0-2,476.0; 1,413.1 5/23/1967; Holes @ 2240' and 2320'. Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 60.2 Squeezed with 200 sacks Class A. FRUITLAND 2,305.1 ftKB; 5,244.0 ftKB TOC 1410' (Temp survey 5/24/67) 2,476.0 PICTURED CLIFFS 2,759.8 3,500.0 3,646.0 Cement Squeeze; 3,646.0-4,530.0; 3/3/1970; Squeezed with 100 sacks 4,198.2 Class C, followed with 50 sacks Class C. TOC at 3646' with 50% eff. 4,399.9 Intermediate Casing Cement; 3,500.0-4,530.0; 6/9/1955; Cemented with 125 4,529.9 sacks Regular, followed with 125 sacks Pozmix; TOC 3500' (Temp 4,530.8 2; Intermediate; 7 in; 6.336 in; 10.0 survey) ftKB: 4,532.0 ftKB 4,532.2 3; Production; 4 1/2 in; 4.052 in; 10.0 ftKB; 5,365.3 ftKB Production Casing Cement; 4,400.0-Hydraulic Fracture; 6/11/1955; 5,365.3; 3/10/1970; Cemented with 4,557.1 CLIFF HOUSE Fractured OH with 14,000 gallons of 125 sacks Class A. TOC 4400'. MENEFEE diesel and 12,500 # sand. 4,732.6 4.734.9 4,784.4 4,935.0 Cement Plug; 4,557.0-5,048.0; Hydraulic Fracture; 6/11/1955; 3/11/1970; Cemented with 150 sacks POINT LOOKOUT 5,047.9 Fractured OH with 12,500 gallons #2 Class C. diesel oil and 9,800 lbs #14 sand. MANCOS 5,210.0 5,244.1 5,365.2

Page 1/1

Report Printed: 3/23/2016