District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

Alternative Method:

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pt. P. I. G. I. W. I.
Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method
Closure of a pit, below-grade tank, or proposed alternative method MAR 0.4 2016
☐ Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: Gallegos Canyon Unit 186E
API Number: 3004525203 OCD Permit Number:
U/L or Qtr/Qtr N Section 33 Township 28N Range 12W County: San Juan
Center of Proposed Design: Latitude
Surface Owner: 🛮 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management ☐ Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined ☐ Liner type: Thickness ☐ mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ Drilling Fluid ☐ yes ☐ no
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A
Volume: 95 bbl Type of fluid: Produced water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _ Double walled/double bottom; no visible sidewalls
Liner type: Thicknessmil



Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

s. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Page 2 of 6

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	U Van U Va
	☐ Yes ☐ No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
11.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	
of Permeriamoti.	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan	documents are
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ 165 ☐ NO

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	LI TES LI NO
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) (Oct Oct Oct Oct Oct Oct Oct Oct Oct Oct	
OCD Representative Signature: Approval Date: 364	1110
The state of the s	
Title: Lovi rowned Spec OCD Permit Number:	
	the closure report. complete this
Title: Low rounted Spec OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

22. C	
Operator Closure Certification:	
	this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicable clo	osure requirements and conditions specified in the approved closure plan.
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
22	
Signature: Olas Sun	Date: March 2, 2016
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497
e-man address: steven.moskan@op.com	Telephone: (303) 320-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit #186E API No. 3004525203 Unit Letter N, Section 33, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT.
 Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided. NMOCD was on site during the removal of the BGT.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method 95 bbl BGT	Release Verification (mg/Kg)	Sample results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.076
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.038
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<46
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride. BTEX, TPH and chloride concentrations were below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no significant release has occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results determine no significant release has occurred. Area was backfilled with clean, earthen material. A low profile tank was placed in the location of the former BGT.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

 BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

						OPERA	ГOR		_ Initia	al Report	\bowtie	Final Repor
Name of Co	ompany: B	P			(Contact: Steve Moskal						
Address: 20	00 Energy	Court, Farm	ington, N	M 87401	-	Telephone 1	No.: 505-326-94	197				
Facility Na	me: Galleg	gos Canyon I	Jnit 186E	3]	Facility Typ	e: Natural gas	well	h Land			
Surface Ow	ner: Feder	al		Mineral O	wner: I	Federal			API No	. 30045252	203	
		2	9	LOCA	TION	OF RE	LEASE			The D		
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/V	Vest Line	County: Sa	an Juar	1
N	33	28N	12W	1,250	South	J. J	1,860	West				
		Lati	tude 3	5.61519		Longitude	-108.11950					
				NAT	URE	OF REL	EASE					
Type of Rele	ase: none	1.54			O L L		Release: unknow	vn	Volume F	Recovered: N	I/A	
		w grade tank -	- 95 bbl			Date and I	Iour of Occurrent	e:	Date and	Hour of Dis	covery	: none
Was Immedi	ate Notice		Yes 🗵	No □ Not Re	quired	If YES, To	Whom?					Lini
By Whom?						Date and H	Iour	1	-191-			
Was a Water	course Rea		Yes 🗵	No		If YES, Vo	olume Impacting	the Wate	ercourse.			
If a Watercon	urse was Im	pacted, Descr	ibe Fully.									
				n Taken.* Samplin ld reports and labo				ne durin	g removal.	Soil analys	is resul	ited for
Describe Are	ea Affected	and Cleanup	Action Tal	cen.* No action ne	cessary.	Final labora	tory analysis supp	ported cl	osure of th	e BGT locat	ion.	
regulations a public health should their of or the environment	Il operators or the envi operations h nment. In a	are required to ronment. The nave failed to	o report are acceptant adequately OCD accep	e is true and completed is true and completed is contained as the contained in the containe	lease no rt by the mediate	otifications as NMOCD m contaminati	nd perform correct arked as "Final R on that pose a thr	ctive acti eport" d eat to gr	ons for rele oes not reli ound water	eases which eve the oper , surface wa	may er rator of iter, hu	ndanger liability man health
Signature:	efo.	2					OIL CON	SERV	ATION	DIVISIO	N	
Printed Name					1	Approved by	Environmental S	pecialist	:			
Title: Field E	Environmen	tal Coordinate	or		F	Approval Dat	e:	I	Expiration Date:			
E-mail Addre	ess: steven.	moskal@bp.co	om			Conditions of	Approval:		Attached			
Date: March	2, 2016	4 / 5/16	Phone: 5	05-326-9497								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413	API#: 3004525203
CLENI.	(505) 632-1199	TANK ID (if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #: 1 of 1
SITE INFORMATION		DATE STARTED: 01/12/16
QUAD/UNIT: N SEC: 33 TWP:		DATE FINISHED:
1/4-1/4/FOOTAGE: 1,250'S / 1,8	STRIKE	
	PROD. FORMATION: DK CONTRACTOR: MBF - B. SCHUMAN	SPECIALIST(S): NJV
REFERENCE POINT	00.01-00 X 100.11	OOL NIGOT
95 BGT (DW/DB)		NCE/BEARING FROM W.H.: 83', N12E
2)		NCE/BEARING FROM W.H.:
3)		NCE/BEARING FROM W.H.: NCE/BEARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	OVM READING
1) SAMPLE ID: 5PC - TB @ 5	- Inch	8015B/8021B/300.0 (CI) NA
2) SAMPLE ID:		
3) SAMPLE ID:	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	
4) SAMPLE ID:	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	Strain and Miles Property
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND SILT / SILTY CLAY / CLAY / GRAVEL / OTHER	
SOIL COLOR: DARK YELLOV	TOU OR LUCE	STIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY		
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / W		The state of the s
SAMPLE TYPE: GRAB COMPOSITE - #		EXPLANATION -
DISCOLORATION/STAINING OBSERVED: YES	_	
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION -	
	DAND/OR OCCURRED: YES NO EXPLANATION: YES NO EXPLANATION - 105 BBL SHALLOW LOW PROFILE ABOVE-GRAI	DE TANK TO BE SET ATOP BGT LOCATION.
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA ft. X NA ft. EXCAVATIO	ON ESTIMATION (Cubic Yards) : NA
	EAREST WATER SOURCE: >1,000' NEAREST SURFACE WATER: >1,000'	NMOCD TPH CLOSURE STD: 100 ppm
SITE SKETCH	BGT Located : off on site PLOT PLAN circle: attached	OVM CALIB. READ. = NA ppm RF =0.52
		OVM CALIB. GAS = NA ppm
	→ FENCE N	TIME: NA am/pm DATE: NA
		MISCELL. NOTES
PRODTANK	→ SEPARATOR	WO:
	BERM	REF#: P - 263
		VID: VHIX0NEVB2
		PJ#:
TO	PBGTL T.B. ~5'	Permit date(s): 06/14/10
SURFACE DRAINAGE	B.G.	OCD Appr. date(s): 10/08/15 Tank OVM = Organic Vapor Meter
~ 140', N52.5W FROM CLOSEST		A BGT Sidewalls Visible: Y /(N)
EDGE OF BGT	TO Y CDD	DOT Cidentalla Visibles V / N
NOTES: BGT = BELOWAGRADE TANK: F.D. = EXCAVATION	√ W.H. X - S.P.D ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW GRADE;	DOTOLI- WALLEY WALLEY
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT	Magnetic declination: 10° E
NOTES: GOOGLE EARTH IMAG	EWALL; DW-DOUBLE WALL; SB-SINGLE BOTTOM; DB-DOUBLE BOTTOM. ERY DATE: 03/15/2015. ONSITE: 01/12/16	STORES AND DESCRIPTION



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

March 02, 2016

Nelson Velez

Blagg Engineering

P. O. Box 87

Bloomfield, NM 87413 TEL: (505) 320-3489

FAX

RE: GCU #186E

OrderNo.: 1601360

Dear Nelson Velez:

Hall Environmental Analysis Laboratory received 1 sample(s) on 1/13/2016 for the analyses presented in the following report.

This report is a revised report and it replaces the original report issued January 14, 2016.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to www.hallenvironmental.com or the state specific web sites. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. All samples are reported as received unless otherwise indicated.

Please don't hesitate to contact HEAL for any additional information or clarifications.

Sincerely,

Andy Freeman

Laboratory Manager

andyl

4901 Hawkins NE

Albuquerque, NM 87109

Analytical Report

Lab Order 1601360

Date Reported: 3/2/2016

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC - TB @ 5' (95)

Project: GCU #186E

Collection Date: 1/12/2016 9:15:00 AM

Lab ID: 1601360-001

Matrix: MEOH (SOIL)

Received Date: 1/13/2016 6:45:00 AM

Analyses	Result	PQL (Qual Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analys	LGT
Chloride	ND	30	mg/Kg	20	1/13/2016 10:52:23 AM	23193
EPA METHOD 8015M/D: DIESEL RAN	IGE ORGANIC	S			Analys	: KJH
Diesel Range Organics (DRO)	ND	9.3	mg/Kg	1	1/13/2016 10:49:32 AM	23185
Motor Oil Range Organics (MRO)	ND	46	mg/Kg	1	1/13/2016 10:49:32 AM	23185
Surr: DNOP	77.6	70-130	%Rec	1	1/13/2016 10:49:32 AM	23185
EPA METHOD 8015D: GASOLINE RA	NGE				Analys	: NSB
Gasoline Range Organics (GRO)	ND	3.8	mg/Kg	1	1/13/2016 10:11:21 AM	A31404
Surr: BFB	90.0	66.2-112	%Rec	1	1/13/2016 10:11:21 AM	A31404
EPA METHOD 8021B: VOLATILES					Analysi	: NSB
Benzene	ND	0.038	mg/Kg	1	1/13/2016 10:11:21 AM	C31404
Toluene	ND	0.038	mg/Kg	1	1/13/2016 10:11:21 AM	C31404
Ethylbenzene	ND	0.038	mg/Kg	1	1/13/2016 10:11:21 AM	C31404
Xylenes, Total	ND	0.076	mg/Kg	1	1/13/2016 10:11:21 AM	C31404
Surr: 4-Bromofluorobenzene	123	80-120	S %Rec	1	1/13/2016 10:11:21 AM	C31404

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

OC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1601360

02-Mar-16

Client:

Blagg Engineering

Project:

GCU #186E

Sample ID MB-23193

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID: PBS

Batch ID: 23193

RunNo: 31431

Prep Date: 1/13/2016 Analysis Date: 1/13/2016

SeqNo: 961994

SPK value SPK Ref Val %REC LowLimit

Units: mg/Kg

Analyte

Result PQL

HighLimit %RPD

RPDLimit Qual

Chloride

ND 1.5

Sample ID LCS-23193

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS Batch ID: 23193

RunNo: 31431

Prep Date: 1/13/2016 Analysis Date: 1/13/2016

SeqNo: 961995

Units: mg/Kg

Analyte

SPK value SPK Ref Val %REC LowLimit 15.00

RPDLimit

Chloride

PQL 1.5

HighLimit

%RPD

Qual

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded H

Not Detected at the Reporting Limit ND

R RPD outside accepted recovery limits

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

Value above quantitation range

Analyte detected below quantitation limits

Sample pH Not In Range

Reporting Detection Limit RL

Sample container temperature is out of limit as specified

Page 2 of 5

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1601360

02-Mar-16

Client:

Blagg Engineering

Project:

GCU #186E

Sample ID MB-23185	SampType: MBLK			TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS Batch ID: 23185		F	RunNo: 31396							
Prep Date: 1/13/2016	Analysis D	ate: 1/	13/2016	8	SeqNo: 9	61081	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								A T
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	7.8		10.00		77.8	70	130			

Sample ID LCS-23185	SampType: LCS			TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: LCSS	Batch	1D: 23	185	F	RunNo: 3	1396				
Prep Date: 1/13/2016	Analysis D	ate: 1/	13/2016	8	SeqNo: 9	61082	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	40	10	50.00	0	79.6	65.8	136			
Surr: DNOP	4.3		5.000		85.8	70	130			

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

RPD outside accepted recovery limits R

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

E Value above quantitation range

Analyte detected below quantitation limits

Sample pH Not In Range

Reporting Detection Limit RL

Sample container temperature is out of limit as specified

Page 3 of 5

OC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1601360

02-Mar-16

Client:

Blagg Engineering

Project:

GCU #186E

Sample ID	5ML RB	SampType:	MBLK	TestCode:	EPA Method	8015D: Gaso	line Rang	е
Client ID:	PBS	Batch ID:	A31404	RunNo:	31404			
Prep Date:		Analysis Date:	1/13/2016	SeqNo:	961494	Units: mg/K	g	
Analyte		Pesult PC	I SPK value	SPK Pef Val %PE	C Low imit	Highl imit	%PPD	PPDI in

1000

Gasoline Range Organics (GRO)

Sample ID 2.5UG GRO LCS

ND 5.0 Surr: BFB 880

TestCode: EPA Method 8015D: Gasoline Range

66.2

Client ID:

SampType: LCS Batch ID: A31404

Prep Date:

RunNo: 31404

87.6

%RPD

112

Analysis Date: 1/13/2016

SeqNo: 961495

Units: mg/Kg

Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit Gasoline Range Organics (GRO) 22 5.0 25.00 88.2 79.6 122 Surr: BFB 1000 1000 102 66.2 112

Sample ID 1601360-001AMS

SampType: MS

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

5PC - TB @ 5' (95)

Batch ID: A31404

RunNo: 31404

Prep Date:

Prep Date:

Analysis Date: 1/13/2016

SeqNo: 961496

Units: mg/Kg

143

112

HighLimit

%RPD **RPDLimit** Qual

RPDLimit

Qual

Qual

Analyte SPK value SPK Ref Val %REC Result PQL LowLimit 18 3.8 18.91 0 95.0 59.3 Gasoline Range Organics (GRO) Surr: BFB 780 756.4 103 66.2

Sample ID 1601360-001AMSD

SampType: MSD

TestCode: EPA Method 8015D: Gasoline Range

Client ID: 5PC - TB @ 5' (95)

Batch ID: A31404 Analysis Date: 1/13/2016 RunNo: 31404 SeqNo: 961497

Units: mg/Kg

HighLimit Result SPK value SPK Ref Val %REC %RPD **RPDLimit** Analyte POL LowLimit 3.8 18.91 94.3 59.3 0.718 20 Gasoline Range Organics (GRO) 18 0 143 Surr: BFB 760 756.4 101 66.2 112 0

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded H

Not Detected at the Reporting Limit ND

RPD outside accepted recovery limits R

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

E Value above quantitation range

Analyte detected below quantitation limits

Sample pH Not In Range

RL

Reporting Detection Limit Sample container temperature is out of limit as specified Page 4 of 5

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1601360

02-Mar-16

Client:

Blagg Engineering

Project:

GCU #186E

Sample ID 5ML RB	Samp	ype: ME	BLK	Tes							
Client ID: PBS	Batc	h ID: C3	1404	F	RunNo: 3	1404					
Prep Date:	Analysis Date: 1/13/2016			SeqNo: 961507			Units: mg/K	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	ND	0.050						77.73	1 1 1 1 1		
Toluene	ND	0.050									
Ethylbenzene	ND	0.050									
Xylenes, Total	ND	0.10									
Surr: 4-Bromofluorobenzene	1.2		1.000		118	80	120				

Sample ID 1601360-001AN	oainp	Samprype. MS									
Client ID: 5PC - TB @ 5' (95) Batcl) Batch ID: C31404 Analysis Date: 1/13/2016			RunNo: 31404						
Prep Date:	Analysis D				SeqNo: 961508			(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	0.68	0.038	0.7564	0	90.6	71.5	122	1138			
Toluene	0.73	0.038	0.7564	0	97.0	71.2	123				
Ethylbenzene	0.75	0.038	0.7564	0	98.6	75.2	130				
Xylenes, Total	2.4	0.076	2.269	0	105	72.4	131				
Surr: 4-Bromofluorobenzene	0.95		0.7564		126	80	120			S	

Sample ID 1601360-001AM	SD Samp	ype: MS	SD	Tes	tCode: E	PA Method	8021B: Vola	tiles			
Client ID: 5PC - TB @ 5' (9	95) Batc	Batch ID: C31404 Analysis Date: 1/13/2016			RunNo: 31404						
Prep Date:	Analysis [SeqNo: 961509			(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	0.69	0.038	0.7564	0	91.5	71.5	122	1.07	20		
Toluene	0.75	0.038	0.7564	0	99.0	71.2	123	2.04	20		
Ethylbenzene	0.77	0.038	0.7564	0	102	75.2	130	3.43	20		
Xylenes, Total	2.4	0.076	2.269	0	106	72.4	131	1.11	20		
Surr: 4-Bromofluorobenzene	1.0		0.7564		134	80	120	0	0	S	

Sample ID 100NG BTEX LC	S Samp	Type: LC	S	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID: LCSS	Batc	h ID: C3	1404	F	RunNo: 3					
Prep Date:	Analysis Date: 1/13/2016			SeqNo: 961916			Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.94	0.050	1.000	0	93.6	80	120		1,2(14)	
Toluene	0.98	0.050	1.000	0	98.0	80	120			
Ethylbenzene	1.0	0.050	1.000	0	101	80	120			
Xylenes, Total	3.2	0.10	3.000	0	108	80	120			
Surr: 4-Bromofluorobenzene	1.4		1.000		140	80	120			S

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RPD outside accepted recovery limits R

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

Value above quantitation range

Analyte detected below quantitation limits

Sample pH Not In Range

Reporting Detection Limit RL

Sample container temperature is out of limit as specified

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Howkins NE Albuquerque, NM 87169

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Order Numb	er: 1601360		RoptNo: 1
Received by/date: 01131LP			
Logged By: Lindsay Mangin 1/13/2016 6:45:00 A	M	of youngo	
Completed By: Lindsay Mangin 1/13/2016 7:00:05 A	M	And Allen	
		000	
Reviewed By: 01/13/16)		
1. Custody seals intact on sample bottles?	Yes 🗆	No 🗆	Not Present 🗹
2. Is Chain of Custody complete?	Yes 🗸	No 🗆	Not Present
How was the sample delivered?	Courier		
Log In			
4. Was an attempt made to cool the samples?	Yes 🗹	No 🗆	NA 🗆
5. Were all samples received at a temperature of >0° C to 6.0°C	Yes 🗸	No 🗆	NA 🗆
6. Sample(s) in proper container(s)?	Yes 🗹	No 🗆	
7. Sufficient sample volume for indicated test(s)?	Yes 🗹	No 🗆	
8. Are samples (except VOA and ONG) properly preserved?	Yes 🗸	No 🗆	
9. Was preservative added to bottles?	Yes 📙	No 🗸	NA 🗆
10.VOA vials have zero headspace?	Yes 🗆	No 🗆	No VOA Vials
11. Were any sample containers received broken?	Yes 🗆	No 🗸	# of preserved
12 0	Yes 🗹	No 🗆	bottles checked for pH:
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes W	NO L	(<2 or >12 unless not
13. Are matrices correctly identified on Chain of Custody?	Yes 🗹	No 🗆	Adjusted?
14. Is it clear what analyses were requested?	Yes 🗹	No 🗆	
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗸	No 🗔	Checked by:
Special Handling (if applicable) 16. Was client notified of all discrepancies with this order?	Yes 🗆	No 🗆	NA 🗹
Person Notified: Date	-	76/700/12/	
By Whom: Via:	eMail	Phone Fax	In Person
Regarding:			
Client Instructions:			THE THE REAL PROPERTY.
17. Additional remarks:			
18. Cooler Information Cooler No	Seal Date	Signed By	THE SHALL STREET
1 1.2 Good Yes	212.346		10 PH

CI	Chain-of-Custody Record			Turn-Around Tirne:						н	A	ш	E	NV	TE	20	NI	ME	NT	AL	
lient:			/ BP AMERICA	Project Name: GCU # 186E				HALL ENVIRONMENT ANALYSIS LABORATO www.hallenvironmental.com									ТО				
vialiting A	idui ess.	P.O. BO						4901 Hawkins NE - Albuquerque, NM 87109													
	A LONG TO SELECT THE PARTY OF T			Project #:				Tel. 505-345-3975 Fax 505-345-4107													
hone #:								Analysis Request													
mail or Fax#:		Project Mana	ger:				-					(%)	10			- 300.1)					
2A/QC Package: ☑ Standard			NELSON V	ELEZ	(8021B)	(yjuo si	/ MRO)			(SV		PO4,SC	2 PCB's					au au			
Accreditation:		Sampler:	NELSON V	ELEZ ny	£ 3	(Ga	ORC	(Method 418.1)	1	OSIN		102	808			300.0 / water		dun			
NELAP Other		On Ice:	Z Yes	□ No]#	TPH	1/0		504	827	10	03,	/ 5		(AC	0.00		e sa	N		
EDD (Type)		Sample Temp	erature: / ,	2	1	8E +	(GR	pou	pou	10	etal	CI,N	cide	A			e e	osit	3		
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX +-ME	BTEX + MTBE + TPH (Gas only)	TPH 80158 (GRO / DRO	TPH (Meth	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil -	Grab sample	5 pt. composite sample	Air Bubbles (Y or N)
1/12/16	0915	SOIL	5PC-TB@5'(95)	4 oz 1	Cool	-001	V		٧			7						٧		V	
late: 1/12/16 late:	Time: 1403 Time: 1924	Relinquishe Relinquishe	le Vo	Received by: Received by:	bet 1	Date Time 12 12 1403 Date Time 13 14 0445	BI St	eve l	RECT	rLY To al, 20	00 Er	nergy		irt, F		ingto	-	M 874 VHIXO	101 ONEVB	2	





Moskal, Steven

From: Sent: Railsback, Farrah (CH2M HILL) Tuesday, January 05, 2016 2:27 PM

To:

Smith, Cory, EMNRD (Cory.Smith@state.nm.us); Fields, Vanessa, EMNRD

Cc:

blagg_njv@yahoo.com; jeffcblagg@aol.com; Moskal, Steven

Subject:

BP Pit Close Notification - GALLEGOS CANYON UNIT 186E

BP America Production Company

200 Energy Court Farmington, NM 87401

Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

January 5, 2016

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 186E API 30-045-25203 (N) Section 33 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around January 8, 2016.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

January 5, 2016

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: GALLEGOS CANYON UNIT 186E

API#: 3004525203

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 8, 2016. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

Charlie Davis Surface Land Negotiator BP America Production Company