This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR			Lease	Name ARIZO	ONA JICARILL	A B	Well No. 8
ocation of W	ell: Unit L	etter C S	ec 09	Twp 026N	Rge	005W API	# 30-039-21501
	Na	ame of Reservoir or Poo	L	Type of Prod		Method of Prod	Prod Medium
Upper Completion			Gas		Flow		Tubing
Lower Completion	TO THE PROPERTY OF THE PROPERT				Artific	ial Lift	Tubing
			Pre-Flow S	hut-In Pressu	re Data		
Upper Completion	Hour, Date, Shut-In 4/15/2016		Length o	of Time Shut-In hours		ss. PSIG 152	Stabilized?(Yes or No) Yes
Lower Completion		Hour, Date, Shut-In 4/15/2016		of Time Shut-In ours	SI Pres	ss. PSIG 243	Stabilized?(Yes or No) Yes
			Flo	w Test No. 1			
Commenced	at:	4/18/2016			oducing (Upper	r or Lower): LC	OWER
Time Lapsed Time (date/time) Since*			PRESSURE Upper zone Lower zone		Prod Zone Temperature		Remarks
4/18/2016 11:00	0:00 AM	11	152	243			
4/19/2016 11:0	7:11 AM	35	153	243		opened high pres	ssured zone
4/20/2016 12:00	0:00 PM	60	153 53			Line pressure is 50psi. Well has 20% cros	
4/21/2016 2:00	4/21/2016 2:00:00 PM 86		153	51		finish test	
roduction rat	e during to	est					
il:	BPOD I	Based on:	Bbls. In	Hrs.		Grav.	GOR
as		MCFPD; Test th	nru (Orifice or M	leter)			
			Mid-Test S	hut-In Pressu	re Data		
Upper Completion	Hour, Da	te, Shut-In	ANALYSIS OF STATE OF	of Time Shut-In	the second secon	ss. PSIG	Stabilized?(Yes or No)
Lower Hour, Date, Shut-In Completion		Length o	of Time Shut-In	SI Pres	ss. PSIG	Stabilized?(Yes or No)	

OIL CONS. DIV DIST. 3

APR 26 2016

Flow Test No. 2

Commenced at:			Zone Pro	oducing (Upper	or Lower)	
Time	Lapsed Time	PRESSURE		Prod Zone		
(date/time)	Since*	Upper zone	Lower zone	Temperature		Remarks
- 1, 1111						
			5			
Production rate during						
Dil: BPOD	Based on:				Grav.	GOR
Dil: BPOD					Grav.	GOR
Dil: BPOD	Based on:				Grav.	GOR
Dil: BPOD	Based on:MCFPD; Test the	nru (Orifice or M	eter)			GOR
Dil:BPOD	Based on: MCFPD; Test the information herein of	nru (Orifice or M	eter)	to the best of r		GOR
Dil: BPOD Gas Remarks: hereby certify that the Approved: 28 Approve	Based on: MCFPD; Test the information herein of the information herein of the information between the	ontained is true	eter)	to the best of r	my knowledge.	GOR
Dil: BPOD Gas Remarks: hereby certify that the Approved: 28 A	Based on: MCFPD; Test the information herein of the information herein of the information between the	ontained is true	eter) and complete	to the best of r	my knowledge. or	GOR

15 T R I C T # 3
NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure
 for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall
 remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).