This form is not to be weed for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

				Name SAN			Well No. 93A
ocation of We	ell: Unit L	etter C S	ec 02	Twp 029N	Rge	007W API	# 30-039-25478
	Name of Reservoir or Pool			Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC		Gas	Gas		ial Lift	Tubing
Lower Completion	MV		Gas		Artific	ial Lift	Tubing
			Pre-Flow S	hut-In Pressu	ire Data		
Upper Completion	Hour, Date, Shut-In 4/14/2016			Length of Time Shut-In 180 hours		s. PSIG	Stabilized?(Yes or No) Yes
Lower Completion	Hour, Date, Shut-In 4/14/2016			Length of Time Shut-In 120 hours		s. PSIG	Stabilized?(Yes or No) Yes
			Flo	w Test No. 1			
Commenced	at:	4/19/2016		Zone Pro	oducing (Upper	or Lower): LO	WER
Time (date/time)		Lapsed Time Since*	PRES Upper zone	SURE Lower zone	Prod Zone Temperature	Remarks	
4/19/2016 1:30:00 PM 13		13	93 125			started flowing mv zone to get cross over pressure. Line pressure of 70 psi. flow Rate of 444mcf. Tbg 94 psi.	
4/20/2016 2:02:50 PM 38		93 84			line is 82 psi well has zero flow rate due to increase in lne pressure		
4/21/2016 12:46:06 PM		60	93	73			ed by Thomas Vermersch
roduction rat	e during te	est					
il: BPOD Based on: B			Bbls. In	ls. In Hrs.		Grav.	GOR
ias		MCFPD; Test th	nru (Orifice or M	leter)			
			Mid-Test S	hut-In Pressu	ire Data		
Upper Completion	Hour, Date, Shut-In			Length of Time Shut-In		s. PSIG	Stabilized?(Yes or No)
Lower Hour, Date, Shut-In Completion		Longth	Length of Time Shut-In		s. PSIG	Stabilized?(Yes or No)	

OIL CONS. DIV DIST. 3

APR 26 2016

Flow Test No. 2

Commenced at:			Zone Pro	oducing (Uppe	er or Lower)		
Time	Lapsed Time Since*	PRESSURE		Prod Zone			
(date/time)		Upper zone	Lower zone	Temperature	Remarks		
					764		
					-3462		
					15152		
Production rate during	D Based on:				Grav. GOR		
Gas	MCFPD; Test t	hru (Orifice or M	leter)				
Remarks:							
inal test pressures w	vitnessed by Thomas \	ermersch with	the NMOCD. F	Returned to no	ormal production.		
	ne information herein			to the best of	f my knowledge.		
Approved: 25	AAR	20 ZOK	Opera	tor: BR			
New Mexico Oil C	onservation Division		Ву:	By: Jeramy Hughes			
By: John C	Jullen		Title:	Title: Multi-Skilled Operator			
Title: DEPUTY OIL & GAS INSPECTOR				Date: Monday, April 25, 2016			

DISTRICT #3
NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure
 for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall
 remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 shows