

(USDOOT 179A)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

SUBMIT IN DUPLICATE*

(other in-
side on
re side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.
SF-079520

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ (Other _____)
2. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. CENVR. ☐ Other _____

2. NAME OF OPERATOR
Meridian Oil Inc.

3. ADDRESS AND TELEPHONE NO.
PO Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*
At surface 1065'FSL, 1190'FWL

At top prod. interval reported below

At total depth

14. PERMIT NO. DATE ISSUED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 28-5 Unit

8. FARM OR LEASE NAME, WELL NO.
San Juan 28-5 Unit 22

9. API WELL NO.
30-039-25271

10. FIELD AND POOL, OR WILDCAT
Basin Ft Coal/S. Blanco R

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec 27, T-28-N, R-5-W
NMPM

12. COUNTY OR
PARISH Rio Arriba

13. STATE
NM

15. DATE SPUNDED 06-15-93 16. DATE T.D. REACHED 06-19-93 17. DATE COMPL. (Ready to prod.) 09-22-93 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6771'GR 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 3774' 21. PLUG, BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY* 2 23. INTERVALS DRILLED BY 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* Pictured Cliffs (3628-3712') 25. WAS DIRECTIONAL SURVEY MADE commingled

26. TYPE ELECTRIC AND OTHER LOGS RUN
Ind., Dens, Neut, GR, ML

27. WAS WELL CORRED
NO

CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24.0#	245'	12 1/4"	277 cu.ft.	
4 1/2"	10.5#	3774'	7 7/8"	1508 cu.ft.	

LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)

TUBING RECORD

SIZE	DEPTH SET (MD)	PACKED SET (MD)
2 3/8"	3691'	

31. PERFORATION RECORD (Interval, size and number)

3628-96', 3706-12'

OIL CONS. DIV DIST. 3

MAY 11 2016

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3628-3712'	144.431# sand; 756 bbl fluid

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)			WELL STATUS (Producing or shut-in)		
		flowing, capable of commercial hydrocarbon production			shut in		
DATE OF TEST	HOURS TESTED	CHOKES SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
				2148 mcf/d	pitot gge		
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
SI 1029	SI 1019						

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

to be sold BHP @ 3670' 1139

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

none

ACCEPTED FOR REG.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED [Signature] TITLE Regulatory Representative

DATE OCT 2 2 1994

FARMINGTON DISTRICT OFFICE
OPERATOR

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38.

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2940'	3127'	White, cr-gr ss.	Ojo Alamo	2940'	
Kirtland	3127'	3432'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	3127'	
Fruitland	3432'	3628'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3432'	
Pictured Cliffs	3628'	3774'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3628'	