This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Well

No	101M	DK/MV	

Operator	WPX ENERG	Y					Lease N	Name_	Rosa Unit		No. 101M I
Location Of We	ll: Unit Letter	K	Sec	24	Twp	31N	Rge	06W	API # 30-0	3925577	

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	Mesa Verde	Gas	Flow	Tbg.
Lower Completion	Dakota	Gas	Flow	Tbg.

Pre-Flow Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	8:30 am 5-9-16	7 days	T-240 C-240	Yes
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	8:30 am 5-9-16	7 days	The - O	Yes

Flow Test No. 1

Commenced a	t (hour, date)* 8	130am 5-1	5-16	Zone producing (U	Jpper or Lower): upper
Time (Hour, Date)	Lapsed Time Since*		essure Lower Comp	Prod. Zone l. Temp.	Remarks
8130 am 5-17-16	24 br	Tb5 - 47	Tbg - (58°	178 Mcf
8:30 am 5-18-16	48 hr	They - 45 Csg - 230	Jbg- C) 48°	181 Me E
8:30 am 5-19-16	72 hr	Tbg - 50 Csg - 228	Tb9-C	55°	179 Met
8:30 am 5-20-16	96 hr	Tbg - 52 (sg - 230	Tbg-c	60°	177 Mcf
					OIL CONS. DIV DIST. 3
					JUN 0 3 2016

Production rate during test

Oil:	BO	PD based on	Bbls. In	Hrs	Grav	GOR	
Gas:	178	MCFPD; Test	thru (Orifice or Meter)	Orifice			

Mid-Test Shut-In Pressure Data

		Mid-I est Shut-in I ressure i	rata	
Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion				
Lower Completion	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)

(Continue on reverse side)

Flow Test No. 2

Commenced a	at (hour, date)**		Zon	Zone producing (Upper or Lower):			
Time (Hour, Date)	Lapsed Time Since**		Lower Compl.	Prod. Zone Temp.	Remarks		
L _k				-	. 5 -25	1 _ 2	
Production rate Oil: Gas:	BOPD based	d on D; Test thru (Ori	Bbls. In	Hrs	Grav	GOR	
Remarks:			ned is true and com				
		Division	20/6		UPX Energy		
	il Conservation I	714151011	20/6_	By Mart		TT	

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).