This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

OIL CONS. DIV DIST. 3

Northwest New Mexico Packer-Leakage Test

JUN 01 Revised June 10, 2003

Operator BR			Lease	Name DAVI	5		Well No. 7E
ocation of W	ell: Unit L	_etterL S	ec 11	Twp031N	Rge	012W API	# 30-045-23873
	Na	ame of Reservoir or Poo	ı	Type of Prod		Method of Prod	Prod Medium
Upper Completion	FRC		Gas	Gas			Tubing
Lower Completion	DK		Gas	Gas		ial Lift	Tubing
			Pre-Flow S	hut-In Pressu	ire Data		
Upper Completion	Hour, Date, Shut-In 5/12/2016			Length of Time Shut-In 327 hours		ss. PSIG 130	Stabilized?(Yes or No) Yes
Lower Completion	Hour, Date, Shut-In 5/12/2016			Length of Time Shut-In 264 hours		ss. PSIG 336.1	Stabilized?(Yes or No) Yes
			Flo	w Test No. 1			
Commenced	at:	5/23/2016		Zone Pro	oducing (Uppe	r or Lower): LO	WER
Time (date/time)		Lapsed Time Since*	PRES Upper zone	SURE Lower zone	Prod Zone Temperature	Remarks	
5/23/2016 2:55:00 AM		2	130.1	78.6		Achived 20% cros	
5/24/2016 2:52:55 PM		38	130.1	78.8		24 hr flow test	
5/25/2016 3:16:02 PM 63		130.3	68.9	cross over with u		st complete. Achived 20% oper zone holding pressure	
roduction rat		est Based on:	Bbls. In	Hrs.		at 130psi.	GOR
Bas		MCFPD; Test th	ru (Orifice or M	eter)			
			Mid-Toet S	hut-In Pressu	re Data		
Upper Completion	Hour, Date, Shut-In			Length of Time Shut-In		s. PSIG	Stabilized?(Yes or No)
Lower Completion			Length o	Length of Time Shut-In		s. PSIG	Stabilized?(Yes or No)

(Continue on reverse side)

Flow Test No. 2

Commenced at:			Zone Producing (Upper or Lower)								
Time	Lapsed Time Since*	PRESSURE		Prod Zone							
(date/time)		Upper zone	Lower zone	Temperature	Remarks	narks					
Production rate during Oil:BPOD	Based on:				Grav(GOR					
GasMCFPD; Test thru (Orifice or Meter)											
Remarks:											
I hereby certify that the information herein contained is true and complete to the best of my knowledge.											
Approved: 9Ju	NE	20 16	Operat	perator: BR							
New Mexico Oil Co	nservation Division		Ву:	By: Jeremy Horton							
By: John LA	Wan		Title:	Title: Multi-Skilled Operator							
	L & GAS INSPE	CTOR	Date:	Date: Tuesday, May 31, 2016							

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual oletion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the
- atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the
test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

^{5.} Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3