## This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NEW MEXICO OIL CONSERVATION DIVISION

Page 1

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Revised June 10, 2003

Well Lease Name Indian I No. 001 MV/PC Operator WPX ENERGY

Location Of Well: Unit Letter D Sec 27 Twp 28N Rge 03W API # 30-0 3907246

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	PC	Gas	Flow	Tha-
Lower Completion	my	Gas	Flow	tba.

**Pre-Flow Shut-In Pressure Data** 

Upper	Hour, Date, Shur	t-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	4-9-16 9:20a.m.		100 hrs	T. 850 C. 850	1/05
Lower	Hour, Date, Shur	t-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	6.9.16	9:00a.m.	laohrs	T-515	yes

Flow Test No. 1

			Flow 1	201 110	• 1	
Commenced a	t (hour, date)*	6-14-16	9:00am	Zone	producing (Up	oper or Lower): Upper
Time (Hour, Date)	Lapsed Time Since*	Upper Compl.	essure Lower Comp	4.4	Prod. Zone Temp.	Remarks
9:20a.m.	QYhr	T- 180 C- 315	T-514		20112	OIL CONS. DIV DIST, 3
9:20a.m.	48hr	T-142 C-295	T- 517			JUN 1 7 2016
=		k)			M 5 1	ISABMI BAD BOTUTTUYTU Ek Tolkiel

Production rate during test 160

Oil:	BC	OPD based on	Bbls. In	Hrs	Grav	GOR	
Gas:	0ما ا	MCFPD; Test	thru (Orifice or Mete	r): Ocifice			

Mid-Test Shut-In Pressure Data

		THE ACED CHIEF AND A COSTUTE A	*****	
Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion				
Lower Completion	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)

(Continue on reverse side)

Flow Test No. 2

Commenced a	t (hour, date)**	100	Zo		pper or Lower):								
Time (Hour, Date)	Lapsed Time Since**		essure Lower Compl.	Prod. Zone Temp.	Remarks								
-													
1-1													
roduction rate il:as:	BOPD base	d on D; Test thru (Ori	Bbls. In	Hrs.	Grav GOR								
emarks:			ned is true and com										
Approved 28 SCNE 20/6 New Mexico Oil Conservation Division  By John Human  Citle PUTY OIL & GAS INSPECTOR				Operator WPX  By Mike Cordova  Title Lease Operator II									
							ttle DISTRICT #3				E-mail Address Michael. Cordous @Wexangy.		
											Date 6-1	6.16	

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).