NEW MEXICO OIL CONSERVATION DIVISION

This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 Revised June 10, 2003

Operator WPX ENERGY

Lease Name Rosa Unit

Well No. 005A MV/PC

Location Of Well: Unit Letter P Sec 26 Twp 31N Rge 06W API # 30-0 3925407

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	Picture Cliffs	Gas	Flow	The
Lower Completion	Mesa Verde	Gas	How	Tbg

Pre-Flow Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	07:42 May 24,16	10 d z.5h (242.5h)	194/195	Ves
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	07:42 May 24,16	10d 25h (242.5hr)	172	yes

			Flow Te	est No. 1	
Commenced a	t (hour, date)*	0:10 Jun	3,16	Zone producing (Up	per or Lower): PC Upper
Time (Hour, Date)	Lapsed Time Since*		Lower Comp	Prod. Zone I. Temp.	Remarks
10:25 63	15 min	0/171	175	NA	blown to atmosphere.
10:40	30 min	0/171	175	/	achieved crossover
10:55	45 min	0/171	175	(= y [*] * 4	LAN PARSON (MARA)
11:10	60 min	0/171	175		OIL CONS. DIV DIST. 3
12:10	120 min	0/99	175		JUN 1 5 2016
13:10	180 mm	0/58	175	NA	

Production rate during test

Oil:	BOPD based on	Bbls. In	Hrs.	Grav.	GOR	14
			1 /.	1	\ \	

Gas: _____ MCFPD; Test thru (Orifice or Meter): _____ A (to atmosphere)

Mid-Test Shut-In Pressure Data

Upper Completion	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Lower Completion	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)

(Continue on reverse side)

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Commenced at (hour, date)**				Zone producing (Upper or Lower):		
Time	Lapsed Time		essure	Prod. Zone	Remarks	
(Hour, Date)	Since**	Upper Compl.	Lower Compl	. Temp.		
		+ 1-7+ - E+			$\frac{T}{T} \sigma T^{1}$	and the
pal				terfé	10.00	
Production rate d		N 451 .	1. 5	ALC: THE R	an Television I	- 10
	BOPD based			Hrs.	Grav.	GOR
Gas:	MCFP	D; Test thru (Orif	fice or Meter): _			12 12 15 15 15 15 15 15 15 15 15 15 15 15 15
Remarks:					1211 12 2 2	

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved 28 June 20 14	• Operator WIX
New Mexico Oil Conservation Division	By Amarda Vick
By John Durkm	Title Field Tech III
Title DEPUTY OIL & GAS INSPECTOR	E-mail Address amanda. Nick Eugevenergy. Om
DISTRICT #3	Date Thre 3.16
Northwest New Mexico Pac	ker Leakage Test Instructions

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.

4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Page 2