RECEIVED

Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR BURGALLOG LAND MANAGEMENT

JUL 0 8 2016

FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007

BUREAU OF LAND MANAGE	Farmington Field C	Office Lease Seria	I No.		
SUNDRY NOTICES AND REPORTS ON WELL So of Land Manager Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE – Other instru	7. If Unit of CA/Agreement, Name and/or No.				
1. Type of Well		NMNM 135	216X		
Oil Well Gas Well Other			8. Well Name and No. W. Lybrook UT # 707H		
Name of Operator WPX Energy Production, LLC	9. API Well No. 30-045-35739				
PO Box 640 Aztec, NM 87410 505-333-180	(include area code) 18	Field and Pool or Exploratory Area Lybrook Mancos W			
 Location of Well (Footage, Sec., T.,R.,M., or Survey Description) SHL: 877' FSL & 366' FEL, Sec 12, T23N, R9W BHL: 339' FNL & 2325' FWL, Sec 12 T23N, R9W 	11. Country or Parish, State San Juan, NM				
12. CHECK THE APPROPRIATE BOX(ES) TO II	NDICATE NATURE OF NOTICE	, REPORT OR OT	THER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION				
Subsequent Report	Treat Reclamation Instruction Recomplete I Abandon Temporarily I Ck Water Dispo Int details, including estimated start I plete horizontally, give subsurface I cork will be performed or provide to on of the involved operations. If the esting has been completed. Final Al	Abandon sal ing date of any pro locations and meas he Bond No. on file e operation results bandonment Notice	ured and true vertical depths of e with BLM/BIA. Required in a multiple completion or es must be filed only after all		
WPX Energy requests authorization to flare this well for 3 analysis report shows nitrogen at approximately 58.7%, w level of nitrogen will not be obtained by the date of expira 30 days to flare after expiration. The most recent gas meast NOTE: WPX received verbal approval from William (BL instead of the gas analysis report.	thich is higher than the Gas attion (7/24/16). WPX anticipus report is attached.	Systems allows pates that the words to attach the g	. It is anticipated that this ell will need an additional		
14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Lacey Granillo	Title Permit Tech III		JUL 1 4 2016		
Signature CHIS SPACE FOR FEI	Date 7/8/16 DERAL OR STATE OFFI	CELISE			
Approved by Tambekou Conditions of approval, if any, are attached. Approval of this notice does not certify that the applicant holds legal or equitable title to those rights in the sub which would entitle the applicant to conduct operations thereon.	Title Petroleum	- /	Date 7/11/2016		

(Instructions on page 2)



Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowinMCy and willfully to make to any department or agency of the

United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



GAS MEASUREMENT EMISSIONS TESTING

307.856.0866 www.precision-labs.com

Run File

Williams Mancos SGD 7.7 2pm.27-7-2016 2-04-23 PM.dat

Method

PrecisionC6.met

Operator

System

Analysis Date

7/7/2016

Client:

WIlliams

Date Sampled:

7/7/2016

Sample Identification:

Williams Mancos SGD 7.7 2pm.2

Purpose:

NI

Unique #:

NI

Pressure:

150

PSI

Sample Temperature:

89

DEG F

Type Sample:

SPOT

Sampled by:	Corey Rose			County:	San Juan
P					
Component	Mole %	BTU	GPM		
Hydrogen Sulfide (H2S)	0.0000	0.0000	0.0000		
Nitrogen (N2)	58.7420				
Carbon Dioxide	0.2390				
Methane (CH4)	30.4630	307.6763			
Ethane (C2)	4.3220	76.4864	1.1570		
Propane (C3)	3.8610	97.1466	1.0650		
iso-Butane (i-C4)	0.4900	15.9343	0.1610		
Butane (C4)	1.2020	39.2128	0.3790		
iso-Pentane (i-C5)	0.2440	9.7622	0.0890		
Pentane (C5)	0.2270	9.0997	0.0820		
Hexanes (C6+)	0.2100	10.7714	0.0920		

Totals

100.0000

566.0898

3.0250

Specific Gravity from Composition

0.8975

Ideal BTUs @ 14.730 Saturated 557.500 Ideal BTUs @ 14.730 Dry 567.400 Real BTUs @ 14.730 Saturated 558.500 Real BTUs @ 14.730 Dry 568.200

Ideal BTUs @ 14.650 Saturated 554.500 Ideal BTUs @ 14.650 Dry 564.300 Real BTUs @ 14.650 Saturated 555.500 Real BTUs @ 14.650 Dry 565.100

0.9986

Hydrogen Sulfide (H2S)

Compressibility

0ppm

Notes