Schematic - Current ConocoPhillips SCOTT #7 County SAN JUAN Field Name API / UWI State/Province BLANCO MESAVERDE NEW MEXICO NORTH 3004511094 (PRORATED GAS Original Spud Date Surface Legal Location East/West Distance (ft) East/West Reference North/South Distance (ft) North/South Reference 5/30/1955 003-031N-010W-B 825.00 FNL 1,700.00 FEL Original Hole, 3/31/2016 6:31:29 AM MD (ftKB) Vertical schematic (actual) Formation Tops 9.8 Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 10.0 ftKB; 41.7 ftKB 41.7 Tubing Pup Joint; 2 3/8 in; 4.70 lb/ft; J-55; 41.7 ftKB; 60.2 ftKB 60.0 Surface Casing Cement; 10.0-185.0; 170.6 5/30/1955; Cemented with 125 sacks 1; Surface; 9 5/8 in; 0.000 in; 9.8 ftKB; cement; circulated to surface. 171.6 171.5 ftKB Cement Squeeze: 60.0-775.0: 3/4/1970; Squeezed with 150 sacks 185.0 Class C and 50 sacks Class C neat. TOC at 60' (Temp survey 3/4/1970). SQUEEZE PERFS; 775.0; 3/4/1970 774.9 Re-squeezed with 215 sacks Class C. Cement Squeeze; 1,242.0-1,350.0; 1,242.1 3/3/1970; Squeezed with 50 sacks SQUEEZE PERFS; 1,350.0; 3/3/1970 1,350.1 Class C. TOC at 1242' (Temp survey) Cement Squeeze; 1,413.0-2,476.0; 1,413.1 5/23/1967; Holes @ 2240' and 2320'. 2,095.1 OJO ALAMO Squeezed with 200 sacks Class A. TOC 1410' (Temp survey 5/24/67) 2,107.0 **KIRTLAND** Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 60.2 2,305.1 FRUITLAND ftKB; 5,244.0 ftKB OIL CONS. DIV DIST. 2,476.0 2,757.9 PICTURED CLIFFS APR 0 1 2016 LEWIS 2,879.9 HUERFANITO BE 3,430.1 3,500.0 3,646.0 Cement Squeeze; 3,646.0-4,530.0; 3,867.1 CHACRA 3/3/1970; Squeezed with 100 sacks 4,198.2 Class C, followed with 50 sacks Class C. TOC at 3646' with 50% eff. 4,399.9 Intermediate Casing Cement; 3,500.0-4,529.9 4,532.0; 6/9/1955; Cemented with 125 2; Intermediate; 7 in; 6.336 in; 10.0 sacks Regular, followed with 125 4,530.8 ftKB; 4,532.0 ftKB sacks Pozmix; TOC 3500' (Temp 3; Production; 4 1/2 in; 4.052 in; 10.0 survey) 4,532.2 ftKB; 5,365.3 ftKB Production Casing Cement; 4,400.0-Hydraulic Fracture; 6/11/1955; 5,375.0; 3/10/1970; Cemented with 4,557.1 CLIFF HOUSE Fractured OH with 14,000 gallons of 125 sacks Class A. TOC 4400'. MENEFEE diesel and 12,500 # sand. 4,732.6 4,734.9 4,784.4 4,935.0 Cement Plug; 4,557.0-5,048.0; Hydraulic Fracture; 6/11/1955; POINT LOOKOUT 5.047.9 3/11/1970; Cemented with 150 sacks Fractured OH with 12,500 gallons #2 Class C. diesel oil and 9,800 lbs #14 sand. 5,210.0 MANCOS 5,244.1 5,375.0 Page 1/1 Report Printed: 3/31/2016