

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
1675' FNL, 405' FWL, Sec.27, T-30-N, R-7-W, NMPM

5. Lease Number  
NMSF-079074  
6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

San Juan 30-6 Unit  
8. Well Name & Number  
San Juan 30-6 U #422S  
9. API Well No.  
30-039-27306  
10. Field and Pool  
Basin Fruitland Coal  
11. County and State  
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

- |   |   |  |
|---|---|--|
| <input type="checkbox"/> Notice of Intent             | <input type="checkbox"/> Abandonment        | <input type="checkbox"/> Change of Plans         |
| <input checked="" type="checkbox"/> Subsequent Report | <input type="checkbox"/> Recompletion       | <input type="checkbox"/> New Construction        |
| <input type="checkbox"/> Final Abandonment            | <input type="checkbox"/> Plugging Back      | <input type="checkbox"/> Non-Routine Fracturing  |
|   | <input type="checkbox"/> Casing Repair      | <input type="checkbox"/> Water Shut off          |
|   | <input type="checkbox"/> Altering Casing    | <input type="checkbox"/> Conversion to Injection |
|   | <input checked="" type="checkbox"/> Other - |  |

13. Describe Proposed or Completed Operations

- 6-20-03 Drill to intermediate TD @ 3505'. Circ hole clean.
- 6-21-03 Circ hole clean. TOOH. TIH w/82 jts 7" 20# J-55 ST&C csg, set @ 3501'. Pump 10 bbl wtr, 10 bbl chemical wash, 10 bbl wtr ahead. Cmt'd w/436 sx Class "B" Premium Lite cmt w/3% calcium chloride, 0.25 pps Celloflake, 5 pps LCM-1, 0.4% fluid loss, 0.4% sodium metasilicate, 8% gel (929 cu.ft.). Tailed w/90 sx Class "B" Type III cmt w/1% calcium chloride, 0.25 pps Celloflake, 0.2% fluid loss (124 cu.ft.). Displaced w/wtr. Circ 65 bbl cmt to surface. WOC.
- 6-22-03 PT BOP & csg to 1500 psi/30 min, OK. TIH w/6 1/4" bit.
- 6-23-03 Drill from 3505 to TD @ 3865'. Circ hole clean. TOOH. TIH w/underreamer to 3505'. Underream @ 3505-3563'.
- 6-24-03 Underream @ 3563-3790'. Circ hole clean. TOOH w/underreamer.
- 6-25-03 TIH w/6 1/4" bit. Circ hole clean. TOOH w/bit. TIH, ran logs. TOOH. TIH, circ hole clean. TOOH.
- 6-26-03 TIH w/9 jts 5 1/2" 15.5# K-55 LT&C lnr, set @ 3865'. Top of lnr @ 3475'. Pre-perforated lnr @ 3566-3652', 3694-3779'. TOOH. TIH w/123 jts 2 3/8" 4.7# J-55 EUE tbq, landed @ 3836'. (SN @ 3798'). ND BOP. NU WH.
- 6-27-03 RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 7/2/03

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

