District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

## Oil Conservation Division OIL CONSERVATION 1220 South St. Francis Dr. ARTESIA DISTRICT

Santa Fe. NM 87505

		•	Santa 1 c, 14141 67505			SEP 1 3 2016	
Date: 9/9/2016	GAS CA	GAS CAPTURE PLAN			RECEIVED		
☐ Original ☐ Amended - Reason for A	Amendment:	-	& OGRID 1	No.: <u>Mewbo</u>	ume Oil Con	npany - 14744	
This Gas Capture Plan out new completion (new drill,				o reduce we	ll/production	facility flaring/venting fo	
Note: Form C-129 must be sub Well(s)/Production Facility The well(s) that will be loc	ty – Name of	f facility	. ,	·	,	4 of 19.15.18.12 NMAC).	
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments	
Devon 8 W2PM Fee #1H	30-015-43879	M-9-25S-28E	530'FSL & 185' FWL	0		Online after frac	
		_					
Gathering System and Pig Well(s) will be connected to place. The gas produced Crestwood low/hr 300 ' of pipeline to c (periodically) to Crestwo be drilled in the foreseeable conference calls to discuss Crestwood The actual flow of the gas with	o a production from production production pressure onnect the factor of	on facility after flation facility is de gathering system acility to low/high drilling, completion addition, Mewbord drilling and completed in Se	edicated to _ n located in n pressure ga n and estima ourne Oil Co upletion sche cc 29 _ , Tw	Crestw Eddy ( athering syst ted first prod ompany and dules. Gas n. 245, Rn	County, New em. Mewbo uction date for Crestwoo from these	and will be connected to Mexico. It will require urne Oil Company provide or wells that are scheduled to have periodic wells will be processed and County, New Mexico	
Flowback Strategy After the fracture treatment flared or vented. During flo sand, the wells will be turn production facilities, unless is Operator's belief the systematical strategies.	wback, the fled to product the toper. the	luids and sand contion facilities. Gastional issues on	ntent will be r s sales should Crestwood	nonitored. V d start as soo system at	When the procon as the wel	luced fluids contain minimalls start flowing through the	

## Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

- Power Generation On lease
  - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that

- NGL Removal On lease
  - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines