District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Proposed Alternative Method Permit or Closure Plan Application

or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request ase be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the fromment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. Poerator: BP America Production Company OGRID#: 778 OIL CONS. DIV DIST. 3 driess: 200 Energy Court, Farmington, NM 87401 SEP 1 9 2016 Bellity or well name: GALLEGOS CANYON UNIT #083E Pl Number: 3004526011 OCD Permit Number: The Or Qtr/Qtr C Section 26 Township 28N Range 12W County: San Juan methor of Proposed Design: Latitude 36.63786 Longitude -108.08398 NAD: 1927 1983 urface Owner: Federal State Private Tribal Trust or Indian Allotment Pit: Subsection F, G or J of 19.15.17.11 NMAC Important Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Interpretation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Demanded Factory Other Volume: bbl Dimensions: L x W x D Below-grade tank: Subsection 1 of 19.15.17.11 NMAC TANKA Submer: 95 bbl Type of fluid: Produced water Mc Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Double wall/ Double bottom; no visible sidewalls Alternative Method:	Froposed Alternative Method Fermit of Closure Flan Application
see be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the fromment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. Parator: BP America Production Company	Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
Detection Dete	Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
SEP 1.9 2016 SEP	ease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
ddress: 200 Energy Court, Farmington, NM 87401 SEP 1 9 2016	OCRID#: 778 OIL CONS. DIV DIST 3
Continued Cont	OGRID#: 178
PI Number: 3004526011 OCD Permit Number:	
Comparison of the control of the c	facility or well name: GALLEGOS CANYON UNIT #083E
enter of Proposed Design: Latitude 36.63786	API Number: 3004526011 OCD Permit Number:
Price Owner: Federal State Private Tribal Trust or Indian Allotment Price Subsection F, G or J of 19.15.17.11 NMAC Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no I Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Ner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A Dolume: 95 bbl Type of fluid: Produced water In Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Double wall/ Double bottom; no visible sidewalls Alternative Method:	J/L or Qtr/Qtr C Section 26 Township 28N Range 12W County: San Juan
Price Owner: Federal State Private Tribal Trust or Indian Allotment Price Subsection F, G or J of 19.15.17.11 NMAC Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no I Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Ner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A Dolume: 95 bbl Type of fluid: Produced water In Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Double wall/ Double bottom; no visible sidewalls Alternative Method:	Center of Proposed Design: Latitude 36.63786 Longitude -108.08398 NAD: □1927 ⋈ 1983
Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Nothing Fluid Produced Factory Other Volume: bbl Dimensions: L x W x D Dimensions: L	Surface Owner: X Federal X State Private Tribal Trust or Indian Allotment
Below-grade tank: Subsection I of 19.15.17.11 NMAC	Cemporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ PVC □ Other □ String-Reinforced
bll Type of fluid: Produced water mk Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Double wall/ Double bottom; no visible sidewalls mer type: Thickness mil HDPE PVC Other	
bll Type of fluid: Produced water mk Construction material: Steel Secondary containment with leak detection	Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Double wall/ Double bottom; no visible sidewalls ner type: Thickness mil HDPE PVC Other Alternative Method:	Volume: 95 bbl Type of fluid: Produced water
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Double wall/ Double bottom; no visible sidewalls ner type: Thickness mil HDPE PVC Other Alternative Method:	ank Construction material: Steel
Visible sidewalls and liner Visible sidewalls only Other Double wall/ Double bottom; no visible sidewalls Double wall/ Dou	Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
ner type: Thicknessmil	
	iner type: Thicknessmil
	Alternative Method: ubmittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church)	, hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers ☐ Signed in compliance with 19.15.16.8 NMAC	
Signed in compnance with 17.15.10.6 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
 □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	eptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
- Visual inspection (certification) of the proposed site, Aeriai photo, Saterite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock	
 watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Within 300 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
10.	
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the document of the following items must be attached to the application.	
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	15.17.9 NMAC
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	ruments are
attached. ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
☐ A List of wells with approved application for permit to drill associated with the pit.	
☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment	
 □ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC □ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization 	
 ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	3.1. T
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems)	
In-place Burial On-site Trench Burial Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	L les L No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date:	019916
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date:	0/2016 the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) Approval Date: 913 Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 7/14/2016	0/2016 the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) Approval Date: 918 Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 7/14/2016	the closure report.

22. Operator Closure Certification:	
	this closure report is true, accurate and complete to the best of my knowledge and sure requirements and conditions specified in the approved closure plan.
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Men	Date: September 16, 2016
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit #083E API No. 3004526011 Unit Letter C, Section 26, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT.
 Evidence of mailing of the notice to the address of the surface owner shown in the
 county tax records demonstrates compliance with this requirement.
 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method 95 bbl BGT	Release Verification (mg/Kg)	Sample results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.020
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.080
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<u><48</u>
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report, field report and C-141 has already been submitted for closure approval. The location will be reclaimed once the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

 Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Expiration Date:

Attached

Release Notification and Corrective Action **OPERATOR** Initial Report Final Report Name of Company: BP Contact: Steve Moskal Address: 200 Energy Court, Farmington, NM 87401 Telephone No.: 505-326-9497 Facility Name: Gallegos Canyon Unit #083E Facility Type: Natural gas well Surface Owner: Federal Mineral Owner: Federal API No. 3004526011 LOCATION OF RELEASE Unit Letter Section Township Feet from the North/South Line Feet from the East/West Line County: San Juan Range 26 28N 12W 1.120 1.850 C North East Latitude 36.63786° Longitude -108.08389° NATURE OF RELEASE Type of Release: none Volume of Release: unknown Volume Recovered: N/A Source of Release: below grade tank - 95 bbl Date and Hour of Occurrence: Date and Hour of Discovery: none none Was Immediate Notice Given? If YES, To Whom? ☐ Yes ☐ No ☐ Not Required By Whom? Date and Hour Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. ☐ Yes ☒ No If a Watercourse was Impacted, Describe Fully.* Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal. Soil analysis resulted for BTEX, TPH and chloride below standards. Field reports and laboratory results are attached. Describe Area Affected and Cleanup Action Taken.* No action necessary. Final laboratory analysis supported closure of the BGT location. I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Signature: Approved by Environmental Specialist: Printed Name: Steve Moskal

Approval Date:

Phone: 505-326-9497

Conditions of Approval:

Title: Field Environmental Coordinator

E-mail Address: steven.moskal@bp.com

Date: September 16, 2016

* Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

July 7, 2016

Bureau of Land Management Katherina Diemer 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 083E API #: 3004526011

Dear Mrs. Diemer,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about July 12, 2016. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Moskal, Steven

From:

Moskal, Steven

Sent:

Monday, July 11, 2016 4:00 PM

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us); kdiemer@blm.gov

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Salazar, Augustine T (Augie); Porter, Michael

Subject:

RE: BP Pit Close Notification - GALLEGOS CANYON UNIT 083E

The BGT is scheduled to be remove on July 13th, 2016 at 10:00 AM.

Thank you,

Steve Moskal

BP Lower 48 – San Juan – Farmington Field Environmental Coordinator Office: (505) 326-9497 Cell: (505) 330-9179



This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

From: Railsback, Farrah (CH2M HILL) Sent: Thursday, July 07, 2016 2:42 PM

To: Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc: jeffcblagg@aol.com; blagg_njv@yahoo.com; Moskal, Steven Subject: BP Pit Close Notification - GALLEGOS CANYON UNIT 083E

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

July 7, 2016

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 083E API 30-045-26011 (C) Section 26 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around July 12, 2016.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Railsback BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	BLAGG EN P.O. BOX 87, BI (50)		API#: 3004526 TANK ID (if applicble): A	011	
FIELD REPORT:	HER:	PAGE #:1 o	f _1		
SITE INFORMATION	: SITE NAME: GCU #	83E		DATE STARTED: 07/1	3/16
QUAD/UNIT: C SEC: 26 TWP:	28N RNG: 12W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,120'N / 1,8	50'W NE/NW LEASET	YPE: FEDERAL STATE / F	FEE / INDIAN	ENVIRONMENTAL	
LEASE #: SF078904	PROD. FORMATION: GLP CO			SPECIALIST(S): N	JV
REFERENCE POINT		COORD.: 36.63748		GLELEV.: 5	,807'
1) 95 BGT (DW/DB)	GPS COORD.: 36.			RING FROM W.H.: 135', S7	
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # O	R LAB USED: HALL			OVM READING (ppm)
1) SAMPLE ID: 5PC - TB @ 5'	(95) SAMPLE DATE: 07/13/	16 SAMPLETIME: 1130	AB ANALYSIS: 801	5B/8021B/300.0 (CI)	NA
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: L	AB ANALYSIS:		
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: L	AB ANALYSIS:		
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: L	AB ANALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND S	SILT / SILTY CLAY / CLAY / GRAVEL	OTHER		
	LOWISH ORANGE	PLASTICITY (CLAYS): NON PLASTIC			LY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY		DENSITY (COHESIVE CLAYS & SI			
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST/ MOIST/ W		HC ODOR DETECTED: YES NO	XPLANATION -		
SAMPLE TYPE: GRAB (COMPOSITE) #		ANY AREAS DISPLAYING WETNESS	S: YES NO EXPLAN	NATION -	
DISCOLORATION/STAINING OBSERVED: YES N					
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: [OTHER:	DAND/OR OCCURRED : YES NO EXPLA	ANATION:	BOVE-GRADE TAI	NK TO BE SET ATOP BGT L	OCATION.
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft.	EXCAVATION EST	TIMATION (Cubic Yards) :	NA
DEPTH TO GROUNDWATER: <50' N	EAREST WATER SOURCE: >1,000'	NEAREST SURFACE WATER:		D TPH CLOSURE STD: 10	0 ppm
SITE SKETCH	BGT Located: off on site	PLOT PLAN circle	e: attached OVM	CALIB. READ. = NA ppr	m RF =0.52
				CALIB. GAS = NA ppr	111 -0.02
W.H. ⊕ PUMP			N TIME		NA
JACK				MISCELL. NOT	TES
	PBGTL		l w	/O:	
	T.B. ~ 5' B.G.	FENCE		EF#: P-566	
	STEEL	FENCE	-	D: VHIXONEVB2	
	RING	(x x x)	P.	J #:	
	*	X DEKIN	Pe	ermit date(s): 04/20	0/09
	PROD.		O	CD Appr. date(s): 06/22	2/11
	TANK	1	IC	ppm = parts per million	
		SEPARATOR	Α		
			- S.P.D.	BGT Sidewalls Visible: Y /	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM: PBGTL = PREVIOUS BEL	ON DEPRESSION; B.G. = BELOW GRADE; B = BE OW-GRADE TANK LOCATION; SPD = SAMPLE PO		H. = WELL HEAD;	lagnetic declination: 10	
APPLICABLE OR NOT AVAILABLE; SW - SINGLE	E WALL; DW - DOUBLE WALL; SB - SINGLE BOTT	TOM; DB - DOUBLE BOTTOM.		agnetic declination: 10	
NOTES: GOOGLE EARTH IMAGE	ERY DATE: 3/15/2015.	ONSITE: 07/13/1	6		

Analytical Report

Lab Order 1607627

Date Reported: 7/15/2016

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Project: GCU #83E

Collection Date: 7/13/2016 11:30:00 AM

Lab ID: 1607627-001

Matrix: MEOH (SOIL) Received Date: 7/14/2016 8:15:00 AM

Analyses	Result	PQL Qua	Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst:	LGT
Chloride	ND	30	mg/Kg	20	7/14/2016 12:44:37 PM	26398
EPA METHOD 8015M/D: DIESEL RANG	SE ORGANICS				Analyst:	TOM
Diesel Range Organics (DRO)	ND	9.6	mg/Kg	1	7/14/2016 11:27:59 AM	26392
Motor Oil Range Organics (MRO)	ND	48	mg/Kg	1	7/14/2016 11:27:59 AM	26392
Surr: DNOP	91.7	70-130	%Rec	1	7/14/2016 11:27:59 AM	26392
EPA METHOD 8015D: GASOLINE RAN	GE				Analyst:	NSB
Gasoline Range Organics (GRO)	ND	4.0	mg/Kg	1	7/14/2016 11:07:52 AM	A35699
Surr: BFB	84.6	80-120	%Rec	1	7/14/2016 11:07:52 AM	A35699
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.020	mg/Kg	1	7/14/2016 11:07:52 AM	B35699
Toluene	ND	0.040	mg/Kg	1	7/14/2016 11:07:52 AM	B35699
Ethylbenzene	ND	0.040	mg/Kg	1	7/14/2016 11:07:52 AM	B35699
Xylenes, Total	ND	0.080	mg/Kg	1	7/14/2016 11:07:52 AM	B35699
Surr: 4-Bromofluorobenzene	93.9	80-120	%Rec	1	7/14/2016 11:07:52 AM	B35699

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 6
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Chain-of-Custody Record ent: BLAGG ENGR. / BP AMERICA ailling Address: P.O. BOX 87		BLAGG ENGR. / BP AMERICA Standard Rush DAY Project Name:						49	D1 H	HALL ENVIRONMENTAL ANALYSIS LABORATORY www.hallenvironmental.com Hawkins NE - Albuquerque, NM 87109										
	BLOOMFIELD, NM 87413		Project #:				Te	1.50	5-345	-397	5	Fax	505-	345	410	7				
none #:		(505) 63	32-1199	1				Analysis Request												
nail or l	Fax#:			Project Mana	ger:								4)				300.1)			
A/QC Pa		Level 4 (Full Validation)			NELSON VI	ELEZ	WB's (8021B)	+ TPH (Gas only)	/ MRO)		151		PO4,50	PCB's					0	
ccredita	tion:			Sampler:	NELSON VI	ELEZ 97V	38	(Ga	ORO	F	(I)		05	808			300.0 / water		ldwi	
	NELAP Other		On Ice:	T/Yes	□ No	1	TPH	1/0	418	827	l s	0,0	18		(AC	300.0		te sa	or N	
EDD (Type)			Sample Temp	perature: 1,9		1	BE +	(GR	pou	Dor lod	etal	CLN	icid	(A)	y-ir		ole	Sosi	S (7
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX +-MH	BTEX + MTBE	TPH 80158 [GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1) PAH (8310 or 82705 MS)	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil	Grab sample	5 pt. composite sample	Air Bubbles (Y or N)
7/13/16	1136	SOIL	5PC-TB@ 5 (95)	4 oz 1	Cool	-001	٧		٧								٧		٧	_
											+								- 1	
											+							†	+	
											+				7					
												-							1	
				Danie de la constante de la co		Date Time	Dan	n a sha		DIII C	DECTU	70.00	11533	7115	5155	FD		1111771		
ate: 7/13/16 ate:	133 I	Relinquishe	my	Meeting by		Received by: Dete Time Remarks: BILL DIRECTLY TO BP USING THE CIRCLES CORRESPONDING VID & REFERENCE # W Vance Hixon Steve Moska VID: VID:						Vance Hixon			WHEN APPLICABLE; kal John Ritchie					
1	1904	Onto	the Walter	h 17	A COLUMN ACCIONATORISM ACCIONATORISMA ACCIONATORI ACC	4/160815		eren	ce#		P - 56	5) .		illower.	_	_	RINKUV	_	

Hall Environmental Analysis Laboratory, Inc.

WO#: 1607627

15-Jul-16

Client:

Blagg Engineering

Project:

GCU #83E

Sample ID MB-26398

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 26398

RunNo: 35720

Prep Date: 7/14/2016

Analysis Date: 7/14/2016

SeqNo: 1105209

Units: mg/Kg

Analyte

Result PQL SPK value SPK Ref Val %REC LowLimit

RPDLimit %RPD

Qual

Chloride

ND

TestCode: EPA Method 300.0: Anions

HighLimit

Sample ID LCS-26398

SampType: LCS

RunNo: 35720

Client ID: LCSS

Batch ID: 26398

Units: mg/Kg

Prep Date: 7/14/2016

Analysis Date: 7/14/2016

SeqNo: 1105210

HighLimit LowLimit

%RPD

Analyte

0

92.2

90

Qual

15.00

14

%REC

Chloride

PQL 1.5

SPK value SPK Ref Val

110

RPDLimit

Qualifiers:

D

Value exceeds Maximum Contaminant Level. Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit RPD outside accepted recovery limits R

% Recovery outside of range due to dilution or matrix S

Value above quantitation range

Analyte detected below quantitation limits

P Sample pH Not In Range

RL Reporting Detection Limit

Sample container temperature is out of limit as specified

Analyte detected in the associated Method Blank В

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: **1607627**

15-Jul-16

Client:

Blagg Engineering

GCU #83E

Sample ID	LCS-26392	SampT	ype: LC	cs	Tes	tCode: E	PA Method	8015M/D: Di	esel Rang	e Organics	
Client ID:	LCSS	Batch	ID: 26	392	F	RunNo: 3	5684				
Prep Date:	7/14/2016	Analysis D	ate: 7	/14/2016	5	SeqNo: 1104052			⟨g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Surr: DNOP	Organics (DRO)	42 4.0	10	50.00 5.000	0	84.2 79.9	62.6 70	124 130			
Sample ID	MB-26392	SampT	ype: MI	BLK	Tes	tCode: E	PA Method	8015M/D: Di	esel Rang	e Organics	
Client ID:	PBS	Batch	ID: 26	392	F	RunNo: 3	5684				
Prep Date:	7/14/2016	Analysis D	ate: 7	/14/2016	5	SeqNo: 1	104053	Units: mg/l	S g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
	Organics (DRO)	ND	10								
	ge Organics (MRO)	ND	50								
Surr: DNOP		8.4		10.00		84.5	70	130			
Sample ID	LCS-26389	SampT	ype: LC	s	Tes	tCode: E	PA Method	8015M/D: Di	esel Rang	e Organics	
Client ID:	LCSS	Batch	ID: 26	389	F	RunNo: 3	5685				
Prep Date:	7/14/2016	Analysis Da	ate: 7	14/2016	5	SeqNo: 1	104054	Units: %Re	С		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP	3 9 5	4.9		5.000		97.3	70	130			
Sample ID	MB-26389	SampTy	ype: ME	BLK	Tes	tCode: El	PA Method	8015M/D: Di	esel Range	e Organics	
Client ID:	PBS	Batch	ID: 26	389		RunNo: 3					
Prep Date:	7/14/2016	Analysis Da	ate: 7/	14/2016	5	SeqNo: 1	104055	Units: %Re	С		
										DDDI imit	Ougl
Analyte Surr: DNOP		Result 9.6	PQL	10.00	SPK Ref Val	%REC 95.5	LowLimit 70	HighLimit 130	%RPD	RPDLimit	Qual
Can. DitOi		0.0		10.00		00.0	70	.50			
Sample ID	1607627-001AMS	SampTy	ype: MS	3	Tes	tCode: El	PA Method	8015M/D: Di	esel Range	e Organics	
Client ID:	5PC-TB @ 5' (95)	Batch	ID: 26	392	F	RunNo: 3	5683				
Prep Date:	7/14/2016	Analysis Da	ate: 7/	14/2016	5	SeqNo: 1	104580	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
rundiyio	Organics (DRO)	50	9.9	49.55	0	101	33.9	141			
Diesel Range (4.7		4.955		94.2	70	130			
				en.	Tes	tCode: El	PA Method	8015M/D: Di	esel Range	e Organics	11
Diesel Range (Surr: DNOP	1607627-001AMSI	SampTy	ype: MS	50							
Diesel Range (Surr: DNOP	1607627-001AMSI 5PC-TB @ 5' (95)		ype: MS		F	RunNo: 3	5683				
Surr: DNOP Sample ID Client ID:			ID: 26	392		RunNo: 3 SeqNo: 1		Units: mg/k	ζg		
Surr: DNOP Sample ID Client ID:	5PC-TB @ 5' (95)	Batch	ID: 26	392 14/2016		SeqNo: 1		Units: mg/F	(g %RPD	RPDLimit	Qual

Qualifiers:

 Value exceeds Maximum Contaminan 	Level.	
--	--------	--

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 3 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#: 10

RPDLimit

Qual

1607627 15-Jul-16

Client:

Blagg Engineering

Project:

GCU #83E

Sample ID 1607627-001AMSD SampType: MSD TestCode: EPA Method 8015M/D: Diesel Range Organics

Client ID: 5PC-TB @ 5' (95) Batch ID: 26392 RunNo: 35683

Prep Date: 7/14/2016 Analysis Date: 7/14/2016 SeqNo: 1104581 Units: mg/Kg

SPK value SPK Ref Val %REC %RPD **RPDLimit** Analyte Result PQL LowLimit HighLimit Qual 0 Surr: DNOP 4.7 4.970 95.2 70 130 0

Sample ID LCS-26377 SampType: LCS TestCode: EPA Method 8015M/D: Diesel Range Organics
Client ID: LCSS Batch ID: 26377 RunNo: 35683
Prep Date: 7/13/2016 Analysis Date: 7/14/2016 SeqNo: 1105643 Units: %Rec

 Analyte
 Result
 PQL
 SPK value
 SPK Ref Val
 %REC
 LowLimit
 HighLimit
 %RPD

 Surr: DNOP
 4.7
 5.000
 94.1
 70
 130

Sample ID MB-26377 SampType: MBLK TestCode: EPA Method 8015M/D: Diesel Range Organics

Client ID: PBS Batch ID: 26377 RunNo: 35683

Prep Date: 7/13/2016 Analysis Date: 7/14/2016 SeqNo: 1105644 Units: %Rec

Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual

Surr: DNOP 9.1 10.00 91.1 70 130

Qualifiers:

* Value exceeds Maximum Contaminant Level

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 4 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1607627

15-Jul-16

Client:

Blagg Engineering

Project:

GCU #83E

Sample ID 5ML RB Client ID: PBS

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

80

LowLimit

RunNo: 35699

Batch ID: A35699

Prep Date:

Surr: BFB

Analysis Date: 7/14/2016

SeqNo: 1105050

Analyte Gasoline Range Organics (GRO)

PQL Result ND 5.0 860

LowLimit

Units: mg/Kg

SPK value SPK Ref Val %REC HighLimit

120

RPDLimit

Qual

Sample ID 2.5UG GRO LCS

SampType: LCS

RunNo: 35699

%REC

0

86.5

TestCode: EPA Method 8015D: Gasoline Range

%RPD

%RPD

Client ID: LCSS Prep Date:

Batch ID: A35699 Analysis Date: 7/14/2016

5.0

SeqNo: 1105051

Units: mg/Kg

RPDLimit Qual

Analyte Gasoline Range Organics (GRO) Surr: BFB

Result PQL 25

870

SPK value SPK Ref Val 25.00 1000

1000

99.2 87.2

HighLimit 120

80 80 120

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded H

Not Detected at the Reporting Limit ND

R RPD outside accepted recovery limits

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

Value above quantitation range E

Analyte detected below quantitation limits

Page 5 of 6

Sample pH Not In Range

RL Reporting Detection Limit

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#: 1607627

15-Jul-16

Client:

Blagg Engineering

Project:

GCU #83E

Sample ID 5ML RB	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: B35699		RunNo: 35699							
Prep Date:	Analysis Date: 7/14/2016			SeqNo: 1105056			Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.96		1.000		96.2	80	120			

Sample ID 100NG BTEX L	.CS Samp	S SampType: LCS			TestCode: EPA Method 8021B: Volatiles							
Client ID: LCSS	Batc	Batch ID: B35699 Analysis Date: 7/14/2016			RunNo: 35699							
Prep Date:	Analysis [SeqNo: 1105057			Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	1.0	0.025	1.000	0	101	75.3	123					
Toluene	0.92	0.050	1.000	0	92.2	80	124					
Ethylbenzene	0.90	0.050	1.000	0	90.4	82.8	121					
Xylenes, Total	2.7	0.10	3.000	0	89.8	83.9	122					
Surr: 4-Bromofluorobenzene	0.91		1.000		91.0	80	120					

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 6 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE

Albuquerque, NM 87109

TEL: 595-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Order Num	ber: 1607627		RcptNo: 1
Received by/date:			
Logged By: Lindsay Mangin 7/14/2016 8:15:00	AM	July Mgo	
Completed By: Lindsay Mangin 7/14/2016 8:33:47	AM	Market Allen	
Reviewed By: 0. 07/14/1/		000	
Chain of Custody			
1. Custody seals intact on sample bottles?	Yes 🗆	No 🗆	Not Present V
2, Is Chain of Custody complete?	Yes 🗹	No 🗆	Not Present
3. How was the sample delivered?	Courier		
Log In			
Was an attempt made to cool the samples?	Yes 🗹	No 🗆	NA 🗆
5. Were all samples received at a temperature of >0° C to 6.0°C	Yes 🗹	No 🗌	NA 🗆
6. Sample(s) in proper container(s)?	Yes 🔽	No 🗆	
7. Sufficient sample volume for indicated test(s)?	Yes 🗸	No 🗌	
8. Are samples (except VOA and ONG) properly preserved?	Yes 🗸	No 🗌	
9. Was preservative added to bottles?	Yes 🗆	No 🗸	NA 🗆
10.VOA vials have zero headspace?	Yes 🗆	No 🗌	No VOA Vials
11, Were any sample containers received broken?	Yes 🗆	No 🗹	Waterweigh
The same of the sa			# of preserved bottles checked
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗹	No 🗌	for pH: (<2 or >12 unless note:
13. Are matrices correctly identified on Chain of Custody?	Yes V	No 🗌	Adjusted?
14. Is it clear what analyses were requested?	Yes 🗹	No 🗆	
15. Were all holding times able to be met?	Yes 🗸	No 🗆	Checked by:
(If no, notify customer for authorization.)			
Special Handling (if applicable)			
16. Was client notified of all discrepancies with this order?	Yes	No 🗆	NA 🗹
Person Notified: Date			
By Whom: Via:	eMail	Phone Fax	☐ In Person
Regarding:			
Client Instructions:			
17. Additional remarks:			
18. Cooler Information			
Cooler No Temp °C Condition Seal Intact Seal No	Seal Date	Signed By	



