This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Page 1

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Revised June 10, 2003

Operator	herron M	id con		Lease Na	me _	Rincon Uni	E Well 100
Location Of V	Well: Unit Letter _	A Sec 2	6 Twp 2				
	Name of Reso	ervoir or Pool	Type of Prod. (Oil or Gas)		1,500	Method of Prod. low or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	PC		6a5			Flow	thg
Lower Completion	mV		6a5			Art lift	Lbg
		Pro	e-Flow Shut-	In Pressure Da	ta		
Upper Completion	Hour, Date, Shut	In 29-16	Length of Time Shut-In		SI	Press. Psig	Stabilized? (Yes or No)
Lower				Length of Time Shut-In		Press. Psig	Stabilized (Yes or No)
		1	Flow T	est No. 1			
Commenced	at (hour, date)*			Zone producin	g (Up	oper or Lower):	
Time (Hour, Date)	Lapsed Time Since*	Upper Compl.	ssure Lower Comp	STATISTICS ALTONO	Prod. Zone Ren Temp.		
2:05m 9-2	5min	93	95	80		OIL CONS. DIV DIST. 3	
2110pm 92	1 40	88	95	80		SEP 28 2016	
2:15pm 9-1	15 min	82	95	80	-	part rest of the stanger	
2:20pm 9-	20min	76	95	76		crossed over in 20min	
Production rat	te during test						
Oil:	BOPD based or	Bbl D; Test thru (Orifi				_ Grav	GOR
7.1	How Data Cl. :			In Pressure Da		not not	C4-1-11 10 (N)
Upper Completion			Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)
Lower Completion	Hour, Date, Shut-In		Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)

(Continue on reverse side)

OIL CONS. DIV DIST. 3

SEP 27 2016

Flow Test No. 2

Commenced a	t (hour, date)**		Zo Zo	ne producing (U	pper or Lower):			
Time (Hour, Date)	Lapsed Time Since**	Pressure Upper Compl. Lower Com		Prod. Zone Temp.	Remarks			
				,				
Production rate Oil: Gas: Remarks:	BOPD base	ed on PD; Test thru (Ori	Bbls. In	Hrs	Grav	GOR		
I hereby certify	that the informa	tion herein contai	ned is true and con	iplete to the best	of my knowledge			
Approved 2	29-SEP	Division	20_16	Operator _	Levian			
By John	Duffer Populty Oil & C	M	20 <u>/6</u> _	By Len Title H.	ny Moor	æ		
		as Inspector.		E-mail Address				

- Northwest New Mexico Packer Leakage Test Instructions
- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).