

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

SEP 20 2016

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

5. Lease Serial No.

NMSF-078542

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well

☐ Oil Well

☒ Gas Well

☐ Other

2. Name of Operator

ConocoPhillips Company

3a. Address

PO Box 4289, Farmington, NM 87499

3b. Phone No. (include area code)

(505) 326-9700

7. If Unit of CA/Agreement, Name and/or No.

San Juan 32-7 Unit

8. Well Name and No.

San Juan 32-7 Unit 211 (POW)

9. API Well No.

30-045-28238

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UL K (NESW), 1334' FSL & 1679' FWL, Sec. 35, T32N, R7W

10. Field and Pool or Exploratory Area

Basin Fruitland Coal

11. Country or Parish, State

San Juan, New Mexico

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☒ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☒ Other

Pressure Observation

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.

If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

ConocoPhillips proposes to conduct a Mechanical Integrity Test and extend Temporary Abandonment status in order to continue using this well as a Pressure Observation Well per the attached procedure and wellbore diagram.

OIL CONS. DIV DIST. 3

SEP 26 2016

TA expires on 9/21/2017

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Kelly G. Roberts

Title

Regulatory Technician

Signature

Kelly G. Roberts

Date

9/20/16

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

William Tambakou

Title Petroleum Engineer

Date 9/21/2016

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office FFD

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ConocoPhillips
SAN JUAN 32-7 UNIT 211 POW
Expense - MIT

Lat 36° 56' 1.63" N

Long 107° 32' 21.012" W

PROCEDURE

1. Hold pre-job safety meeting. Comply with all NMOCD, BLM, and COP safety and environmental regulations. **NOTIFY OCD of the MIT 24hrs prior to conducting the MIT.**
2. Check casing, tubing, and bradenhead pressures and record them in WellView. If there is pressure on the BH, contact Wells Engineer.
3. Remove existing piping on casing valve. RU blow lines from casing valves and begin blowing down casing pressure.
4. Load casing with 2 % KCl water & corrosion inhibitor, as necessary. Perform MIT (Mechanical Integrity Test) above the packer at 3,005' to 560 psig for 30 minutes on a 2 hour chart with 1000 lb. spring. If the test passes, SI the well. RD pump truck and MOL. If the test fails, contact the Rig Superintendent and Wells Engineer.

Schematic - Current

SAN JUAN 32-7 UNIT #211

District NORTH	Field Name FC	API / UWI 3004528238	County SAN JUAN	State/Province NEW MEXICO
Original Spud Date 10/24/1990	Surface Legal Location 035-032N-007W-K	East/West Distance (ft) 1,679.13	East/West Reference FWL	North/South Distance (ft) 1,333.99
				North/South Reference FSL

Vertical - Original Hole, 9/20/2016 12:04:47 PM

