

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

~~30-31-05266~~ 30-031-20395

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.
Fee

7. Lease Name or Unit Agreement Name
Farris

8. Well Number ~~001~~ 3

9. OGRID Number

10. Pool name or Wildcat
Seven Lakes

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Farris Mines

3. Address of Operator
419 Palomino Lane, Bloomfield, NM 87413 505-632-8438

4. Well Location
Unit Letter P, 330 feet from the S line and 980 feet from the E line
Section 18 Township 18N Range 10W NMPM McKinley
County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
6540' GI

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Farris Mines Plugged and Abandoned this well on May 11, 2016 per the attached report by A-Plus Well Service.

Plug #1 with 56 sxs (66.08 cf) Class B cement from 400' to surface circulate good cement out casing valve and holes. Tag TOC at 30'.
Plug #2 with 10 sxs Class B cement top off casings and install on P&A marker with coordinates N 35° 47' 3" W 107° 56' 5".

5/9/16 MOL and rig up. Open up well; no pressures. LD 1 polish rod, 15 - 5/8" rods, 2— 4 pony rods. PU on tubing and remove slips. ND wellhead. Strip on tubing head, flange and BOP. LD 12 jnts 2-3/8" EUE tubing (had paraffin inside walls). Tally workstring. Round trip A-Plus 5-1/2" string mill to 405' and tag. Pump 4 bbls of water down casing, leaking. Dig out 5-1/2" casing, old 5-1/2" weld-on pin leaking/rotted away. SI well. SDFD. Note: Jonathan Kelly, NMOCD required to do watermelon mill on scrape run on all 3 wells due to heavy thick oil.

5/10/16 Open up well; no pressures. RU A-Plus wireline. Ran CBL from 400' to surface, ran CBL; found TOC at 40'. Run in with 12 jnts A-Plus 2-3/8" workstring to 400'. Spot plug #1 with TOC at surface. LD all tubing. ND BOP and companion flange. RD and MOL.

5/11/16 Travel to location. Dig out wellhead. Found TOC at 30' down 5-1/2" casing. Cut off wellhead. Spot plug #2 top off casings and install P&A marker with coordinates N 35° 47' 3" W 107° 56' 5".

OIL CONS. DIV DIST. 3

Spud Date:

Rig Release Date:

MAY 31 2016

*Well mixed up with Farris #1 during plugging. P/A marker will require update

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bill Randall TITLE A-Plus Field Supervisor DATE May 26, 2016

Type or print name Bill Randall E-mail address: bill@apluswell.com PHONE: 325-2627

For State Use Only

APPROVED BY: Bill Randall TITLE Deputy Oil & Gas Inspector, District #3 DATE 10/5/16

Conditions of Approval (if any):

AV

PNR only