District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

# Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the nvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: Burlington Resources Oil & Gas Company, LP_OGRID #:14538
DICT 3
Address: PO BOX 4289, Farmington, NM 87499  OIL CONS. DIV DIST.
APIN with harms: SAN JUAN 27-4 UNIT 5N
Facility or well name: SAN JUAN 27-4 UNIT 5N  API Number:
Center of Proposed Design: Latitude 36.586091 °N Longitude -107.291612 °W NAD: □1927 ☑ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Surface Owner:  Federal State Frivate Infoai Trust of Indian Allotment
Pit:       Subsection F, G or J of 19.15.17.11 NMAC         Temporary:       □ Drilling       □ Workover         □ Permanent       □ Emergency       □ Cavitation       □ P&A       □ Multi-Well Fluid Management       □ Low Chloride Drilling Fluid       □ yes □ no         □ Lined       □ Unlined       □ Liner type:       Thicknessmil       □ LLDPE       □ PVC       □ Other         □ String-Reinforced       □ Liner Seams:       □ Welded       □ Factory       □ Other       Volume: bbl Dimensions:       □ x W_x D     3.    Below-grade tank: Subsection I of 19.15.17.11 NMAC    Volume: 120
Tank Construction material: Metal
Secondary containment with leak detection  Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other
Liner type: Thicknessmil
4.  Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)
Four foot height, four strands of barbed wire evenly spaced between one and four feet
Alternate. Please specify

1 1	
6.  Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
☐ Screen ☐ Netting ☐ Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions:  Use Substitutions and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. <u>Siting Criteria (regarding permitting)</u> : 19.15.17.10 NMAC <u>Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below.</u> Siting criteria does not apply to drying pads or above-grade tanks.	otable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☑ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☑ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. ( <b>Does not apply to below grade tanks</b> )  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	☐ Yes ☑ No
<ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☑ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
<ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natural Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.    Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC   Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC   Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC   Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC   Previously Approved Design (attach copy of design)   API Number: or Permit Number:	O NMAC
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are				
attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Proposed Closure: 19.15.17.13 NMAC  Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.  Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Flance Alternative	uid Management Pit				
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method					
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the				
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P. 19.15.17.10 NMAC for guidance.					
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No				
Ground water is between 25-50 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No				
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells    Yes   NA					
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No				
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No				
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No				
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ 163 ☐ 140				

<ul> <li>adopted pursuant to NMSA 1978, Section 3-27-3, as amended.</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul>	
	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.	
<ul> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. FEMA map	☐ Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Name (Fine).	-
Signature: Date:	
e-mail address: Telephone:	
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
	26120110
OCD Representative Signature: Approval Date: 1012	26/2016
OCD Representative Signature: Approval Date: 1012	50 bm;9007 3010010
OCD Representative Signature: Approval Date: 10 2	the closure report.
OCD Representative Signature:  Title:  OCD Permit Number:  OCD Per	the closure report.
OCD Representative Signature:  Title:  OCD Permit Number:  OCD Per	the closure report.

Operator Closure Certification:  I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print) Crystal Walker Title: Regulatory Coordinator
- 1 0/1 0/2 halow
Signature: Date: 10/12/2016
e-mail address:crystal.walker@cop.com Telephone: (505) 326-9837

# Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Closure Report

Lease Name: San Juan 27-4 Unit 5N

API No.: 30-039-27632

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure of the below-grade tank referenced above. All proper documentation regarding closure activities is being included with the C-144.

#### General Plan:

1. BR shall close a below-grade tank within 60 days of cessation of operations per Subsection G.4 of 19.15.17.13 NMAC. This will include a) below-grade tanks that do not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC; b) an earlier date that the division requires because of imminent danger to fresh water, public health or the environment. For any closure, BR will file the C144 Closure Report as required.

The below-grade tank referenced above was permitted and closed within 60 days of cessation of the below-grade tanks operation.

 BR shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall dispose of the liquids and sludge in a division-approved facility. The facilities to be used will be Basin Disposal (Permit #NM-01-005), JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) and Envirotech Land Farm (Permit #NM-01-011). The liner after being cleaned well (Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC) will be disposed of at the San Juan County Regional Landfill located on CR 3100.

All recovered liquids were disposed of at Basin Disposal (Permit #NM-01-005) and any sludge or soil required to be removed to facilitate closure was hauled to Envirotech Land Farm (Permit #NM-01-011) and JFJ Landfarm % IEI (Permit #NM-01-0010B). The liner was cleaned per Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC was disposed of at the San Juan County Regional Landfill located on CR 3100.

BR will receive prior approval to remove the below-grade tank and dispose of it in a division-approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves.

The below-grade tank was disposed of in a division-approved manner.

If there is any on-site equipment associated with a below-grade tank, then BR shall remove the equipment, unless
the equipment is required for some other purpose.

All on-site equipment associated with the below-grade tank was moved to the twinned location San Juan 27-4 Unit 123P to share a below-grade tank.

5. BR will test the soils beneath the below-grade tank to determine whether a release has occurred. BR shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyzed for the constituents listed in Table I of 19.15.17.13 NMAC. COPC shall notify the division of its results on form C-141.

A five point composite sample was taken of the below-grade tank using sampling tools and all samples tested per Subsection B of 19.15.17.1 3(B)(1)(b). (Sample results attached). Form C-141 is attached.

Components	Tests Method	Limit (mg/kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	100
Chlorides	EPA 300.0	250

If BR or the division determines that a release has occurred, then BR shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.

#### A release was not determined for the above referenced well.

If the sampling program demonstrates that a release has not occurred or that any release does not exceed the
concentrations specified in Table I of 19.15.17.13 NMAC, then BR shall backfill the excavation with compacted,
non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the
site.

The below-grade tank area passed all requirements of Paragraph (4) of Subsection E of 19.15.17.13 NMAC and was backfilled with compacted, non-waste containing, earthen material.

- 8. Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email or verbally. The notification of closure will include the following:
  - i. Operator's name
  - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.

#### Notification was not found.

The surface owner shall be notified of BR's closing of the below-grade tank 72 hours, but not more than one week, prior to closure as per the approved closure plan via certified mail, return receipt requested.

#### The closure process notification to the landowner was not found.

10. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.

The below-grade tank area was re-contoured to match fit, shape, line, form and texture of the surrounding area. Re-shaping including drainage control, to prevent ponding and erosion. Natural drainages were unimpeded and water bars and/or silt traps were placed in areas where needed to prevent erosion on a large scale. Final recontour has a uniform appearance with smooth surface, fitting the natural landscape.

11. BR shall seed the disturbed areas the first favorable growing season following closure of a below-grade tank. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM stipulated seed mixes will be used on federally regulated lands and division-approved seed mixtures (administratively approved if required) will be utilized on all State or private lands. A uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre- disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds. If alternate seed mix is required by the state, private owner or tribe, it will be implemented with administrative approval if needed. COPC will repeat seeding or planting will be continued until successful vegetative growth occurs.

BR seeded disturbed areas from the BGT closure on the SJ 27-4 Unit 5N. The location is currently active and sharing a below-grade tank with the San Juan 27-4 Unit 123P.

12. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material, with chloride concentrations less than 600 mg/kg as analyzed by EPA Method 300.0, to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.

The below-grade tank area was backfilled and more than four feet of cover was achieved and the cover included one foot of suitable material to establish vegetation at the site.

- 13. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on C-144 and incorporate the following:
  - Soil Backfilling and Cover Installation (See Report)
  - Re-vegetation application rates and seeding techniques (See Report)
  - Photo documentation of the site reclamation (Included as an attachment)
  - Confirmation Sampling Results (Included as an attachment)
  - Proof of closure notice (Missing)

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505 Submit 1 Copy to appropriate District Office to accordance with 19.15.29 NMAC.

				Du	1100 1 0, 1 1111 0 70	00				
			Rele	ease Notific	ation and Co	rrective A	ction			
					OPERA'	ГOR	☐ Initi	al Report	$\boxtimes$	Final Repor
Name of Co	mpany B	urlington Re	sources (	O&G Company, 1	LP Contact Cr	ystal Walker		See College		
Address 340	01 East 30	th St, Farmin	gton, NM		Telephone 1	No.(505) 326-98	837			
Facility Nar	ne: San Ju	an 27-4 Uni	5N		Facility Typ	e: Gas Well				
Surface Ow	ner Feder	al		Mineral O	wner Federal		API No	. 30-039-2	7632	
				LOCA	TION OF REI	LEASE				
Unit Letter J	Section 7	Township 27N	Range 4W	Feet from the 2080	North/South Line South	Feet from the 2460	East/West Line East	County Rio Arrib	a	
			Lat	itude <u>36.58609</u> NAT	Longitude	107.291612 EASE				
Type of Rele	ase				Volume of	Release	Volume I	Recovered		
Source of Re	lease				Date and H	Iour of Occurrence	Date and	Hour of Dis	covery	
Was Immedia	ate Notice (	Given?	Yes [	No Not Rec	If YES, To	Whom?				

Date and Hour

If YES, Volume Impacting the Watercourse.

Describe Cause of Problem and Remedial Action Taken.\*

☐ Yes ☒ No

No release was encountered during the BGT Closure.

Describe Area Affected and Cleanup Action Taken.\*

If a Watercourse was Impacted, Describe Fully.\*

N/A

N/A

By Whom?

Was a Watercourse Reached?

I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.

Signature:

Printed Name: Crystal Walker

Approved by Environmental Specialist:

Title: Regulatory Coordinator

E-mail Address: crystal.walker@cop.com

Date: 10 12 10 Phone: (505) 326-9837

Attach Additional Sheets If Necessary



May 25, 2011

Project Number 92115-1689

Ms. Shelly Cook-Cowden ConocoPhillips 3401 East 30<sup>th</sup> Street Farmington, New Mexico 87401

Cell: (505) 320-0699

RE: BELOW-GRADE TANK CLOSURE DOCUMENTATION FOR THE SAN JUAN 27-4 #5N (HBR) WELL SITE, RIO ARRIBA COUNTY, NEW MEXICO

Dear Ms. Cook-Cowden:

Enclosed please find the field notes and analytical results for below-grade tank (BGT) closure activities conducted at the San Juan 27-4 #5N (hBr) well site located in Section 7, Township 27 North, Range 4 West, Rio Arriba County, New Mexico. Upon Envirotech personnel's arrival on May 3, 2011, one (1) five (5)-point composite sample was collected from directly beneath the former BGT; see attached *Field Notes*. The sample was analyzed in the field for total petroleum hydrocarbons (TPH) using USEPA Method 418.1, for organic vapors using a photoionization detector (PID) and for chlorides. Additionally, the sample was placed into a four (4)-ounce glass jar, capped headspace free, and transported on ice, under chain of custody, to Envirotech's Analytical Laboratory to be analyzed for benzene and total BTEX using USEPA Method 8021 and for chlorides using USEPA Method 4500. The sample returned results below the regulatory limits for all constituents analyzed, confirming a release did not occur; see attached *Analytical Results*. Envirotech, Inc. recommends no further action in regards to this incident.

We appreciate the opportunity to be of service. If you have any questions or require additional information, please contact our office at (505) 632-0615.

Respectfully submitted,

ENVIROTECH, INC.

Crystal Delgai

Environmental Field Technician cdelgai@envirotech-inc.com

Enclosures:

Field Notes

**Analytical Results** 

Cc:

Client File 92115

				- 1				
PAGE NO: OF	/	ENIVIE			CH INC	NEEDC		NMENTAL
		BIVVIN			Y 64 - 3014	INEEKS	SPECIAL	IST:
DATE STARTED:05 /03		FARMINGTON, NEW MEXICO 87401 LAT: 36.58538639						
ATE FINISHED: OF 10	3/11		PHO	NE: (505) 6	32-0615	- who are		107.2909436
	FIELD R	EPORT:	BGT / F	IT CLO	SURE VE	ERIFICA	TION	
	andoar	27-4	WELL#:		TEMP PIT:	PERMA	NENT PIT:	
EGAL ADD: UNIT:		SEC: 7	-	TWP: Z		RNG: 41		PM: NM
TR/FOOTAGE: 240	00 E Z	0805	CNTY:	20 Arri	ba	ST: Nes	w Mexi	20
XCAVATION APPROX:	NA	FT. X	NA	FT. X	NA	FT. DEEP		ARDAGE: NA
DISPOSAL FACILITY:		NA			TION METH		NA	
AND OWNER: ONSTRUCTION MATERI	AT.			03927	WITH LEAK	BGT/PIT		NA
OCATION APPROXIMAT							N:	
EPTH TO GROUNDWAT		con /	FT.	200	FROM WEL	LHEAD		
TEMPORARY PIT - G	ALCOHOL MANAGEMENT AND ADMINISTRATION OF THE PARTY OF THE	TER 50-100 F	EET DEEP	-				
BENZENE ≤ 0.2 mg/kg, B7					00 mg/kg, TPH	(418.1) ≤ 250	0 mg/kg, CH	LORIDES ≤ 500 mg/kg
TEMPORARY PIT - G								
BENZENE ≤ 0.2 mg/kg, BT				N (8015) ≤ 50	00 mg/kg, TPH	(418.1) ≤ 2500	mg/kg, CHI	ORIDES < 1000 mg/kg
PERMANENT PIT OR				, , , , , , , , , , , , , , , , , , , ,	-0.0	(11011) = 150		orange a root mg kg
BENZENE ≤ 0.2 mg/kg, I		/ke TPH (418	1) < 100 mg/	ke CHLORI	DES < 250 mg/	t a		
		, ng, 1111 (410.	1) 2 100 mg					
	TIME	SAMPLE I.D.	LAB NO.	WEIGHT (e	D 418.1 ANAL mL FREON	VSIS	READING	CALC. (mg/kg)
	12:03	200 STD				-	2/3	
	12:05	BGT	1	5	.20	4	20	80
			2					
			- 4	100	3			
			5	-				
DEDITA	TED.		6					
PERIME	SIER				S RESULTS		PRO	OFILE
<b>P</b>	Lieu	+	SAMPLE	READING	CALC.			
7	muster	W)	U-STD	0.005 a	(mg/kg)	1	- 15	-
A	1. 1		BGT	0.5	×28		-	
6	X	7						1 1
						1		1 1
		1				1 \		25'
	1	PICH	I	PID RESUI		1 \		1
			SAME	PLEID	RESULTS			1 1
	D)		B6T	4	(mg/kg) 3_0	1 4		
,	8		Im ST	D.	100	~	x512	eip
							36035.10	
						MIO	7017.4	874"
LAB SAMPLES	The second second	NOTES:		10 1-	V loke w	115000	with	Gabl rosulte
SAMPLE ID ANALYSIS BENZENE BIEX GRO & DRO	5	Shelle	z: car	lled 9	1447 11	ussage	wiju	field results
CHLORIDE								
		WORKORDE	R.#		WHO ORDER	ED		

•



# EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

ConocoPhillips

Project #:

92115-1689

Sample No.:

1

Date Reported:

5/6/2011

Sample ID:

**BGT** 

Date Sampled:

5/3/2011

Sample Matrix:

Soil

Date Analyzed;

5/3/2011

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

2		Det.
7 	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

80

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

San Juan 27-4 #5N (hBr)

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst |

Crystal Delgai

Printed

neview

Toni McKnight, EIT

Printed



# CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal. Date:

3-May-11

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
TPH	100		
	200	213	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Custal Delin	5/6/2011
Analyst	Date
Crystal Delgai	
Print Name	
Time Milmit	5/6/2011
Review	Date

**Print Name** 



### **Field Chloride**

Client:

ConocoPhillips

Project #:

92115-1689

Sample No .:

1

Date Reported:

5/6/2011

Sample ID:

BGT

Date Reported:

5/3/2011

Sample Matrix:

Soil

Date Analyzed:

5/3/2011

Preservative:

Cool

Analysis Needed:

Chloride

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Field Chloride** 

ND

28.0

ND = Parameter not detected at the stated detection limit.

References:

"Standard Methods for the Examination of Water and Wastewater", 18th ed., 1992

Hach Company Quantab Titrators for Chloride

Comments:

San Juan 27-4 #5N (hBr)

Crystal Delgai

Drintad

Toni McKnight, EIT

Printed



# EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	92115-1689
Sample ID:	<b>BGT Closure</b>	Date Reported:	05-04-11
Laboratory Number:	58065	Date Sampled:	05-03-11
Chain of Custody:	11641	Date Received:	05-03-11
Sample Matrix:	Soil	Date Analyzed:	05-04-11
Preservative:	Cool	Date Extracted:	05-03-11
Condition:	Intact	Analysis Requested:	BTEX
		Dilution:	10

	Dilution:	10	
Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	ND	0.9	
Toluene	ND	1.0	
Ethylbenzene	ND	1.0	
p,m-Xylene	ND	1.2	
o-Xylene	ND	0.9	
Total BTEX	ND		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
de facilità de la compansión de la compa	Fluorobenzene	102 %
	1,4-difluorobenzene	101 %
	Bromochlorobenzene	102 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

BGT Closure/San Juan 27-4 #5N (hBr)

Analyst

Ph (505) 632-0615 Fr (800) 362-1879 Fx (505) 632-1865 lab@envirotech-inc.com envirotech-inc.com



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

ND

0.1

Client: Sample ID: Laboratory Number: Sample Matrix: Preservative: Condition:	N/A 0504BBLK QA/Q0 58065 Soil N/A N/A	C	Project #: Date Reported: Date Sampled: Date Received: Date Analyzed: Analysis: Dilution:		N/A 05-04-11 N/A N/A 05-04-11 BTEX				
Calibration and	I-Cal RF:	C-Cal RF:	%Diff.	Blank	Detect.				
Detection Limits (ug/L)		Accept Ra	nge 0 - 15%	Conc	Limit				
Benzene	1,1676E+005	1.1700E+005	0.2%	ND	0.1				
Toluene	1.2834E+005	0.2%	ND	0.1					
Ethylbenzene	1.1325E+005	1.1348E+005	0.2%	ND	0.1				
p,m-Xylene	2,5762E+005	2,5813E+005	0.2%	ND	0.1				

Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect. Limit
Benzene	ND	ND	0.0%	0 - 30%	0.9
Toluene	ND	ND	0.0%	0 - 30%	1.0
Ethylbenzene	ND	ND	0.0%	0 - 30%	1.0
p,m-Xylene	ND	ND	0.0%	0 - 30%	1.2
o-Xylene	ND	ND	0.0%	0 - 30%	0.9

1.0783E+005

0.2%

Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	ND	500	500	100%	39 - 150
Toluene	ND	500	509	102%	46 - 148
Ethylbenzene	ND	500	494	98.9%	32 - 160
p,m-Xylene	ND	1000	993	99.3%	46 - 148
o-Xylene	ND	500	508	102%	46 - 148

ND - Parameter not detected at the stated detection limit.

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution,

1.0762E+005

References:

o-Xylene

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996,

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photolonization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 58041-58044, 58065-58069, 58072

Analyst



# Chloride

Client:

ConocoPhillips

Project #:

92115-1689

Sample ID:

**BGT Closure** 

Date Reported:

05/04/11

Lab ID#:

58065

Date Sampled:

05/03/11

Sample Matrix:

Soil

Date Received:

05/03/11

Preservative:

Cool

Date Analyzed:

05/04/11

Condition:

Intact

Chain of Custody:

11641

**Parameter** 

Concentration (mg/Kg)

**Total Chloride** 

60

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983.

Standard Methods For The Examination of Water And Waste Water\*, 18th ed., 1992.

Comments:

BGT Closure/San Juan 27-4 #5N (hBr)

Analyst

Review

Ph (505) 632-0615 Fr (800) 362-1879 Fx (505) 632-1865 lab@envirotech-inc.com envirotech-inc.com

CHAIN OF CUSTODY RECORD RUSH 11641

Client: ConocoPhillips Project Name / Location: BEST Closure San Juan 27-4#5						Va	Br)	)			ANAL	YSIS	/ PAR	AME	TERS			,				
Client Address:			Complex Nemes				BTEX (Method 8021)	60	sli	_					_							
							TPH (Method 8015)	(Metho	VOC (Method 8260)	RCRA 8 Metals	Cation / Anion		TCLP with H/P		TPH (418.1)	CHLORIDE			Sample Cool	Sample Intact		
Sample No./ Identification	Sample Date	Sampl Time	I lab No	Sample Matrix		No./Volume of Containers	Prese	rvativ	E	BEX	00	HCH/	Cation	RCI	TCLP	PAH	TH	CHLC			Samp	Samp
Closure	5/3/11	/Z=0	58065	Solid	Sludge Aqueous	1-402	,	1	1	/											Y	Y
				Soil Solid	Sludge Aqueous																	
				Soil Solid	Sludge Aqueous		П															
				Soil Solid	Sludge Aqueous																	
			Soil Sludge Solid Aqueous																			
				Soil Sludge Solid Aqueous																		
				Soil Solid	Sludge Aqueous																	
				Soil Solid	Sludge Aqueous																	
				Soil Solid	Sludge Aqueous																	
				Soll Solid	Sludge Aqueous																	
Relinquished by: (Signature)			5/3/11	Time /4=/7		Received by: (Signature) Received by: (Signature)						5/3/		Ti /4:1	me / <del>7</del>							
Relinquished by: (Signa	ituré						Re	ceiv	ed by:	(Signa	Jure)											
Relinquished by: (Signa	iture)						Received by: (Signature)									$\neg$						
				-	- >		_•	_	1	_					-				 	_		$\dashv$

X RUSHX



envirotech

Analytical Laboratory

5796 US Highway 64 • Farmington, NM 87401 • 505-632-0615 • lab@envirotech-inc.com

