OCT 0 3 2016

**Oil Conservation Division** 1220 South St. Francis Dr. Santa Fe, NM 87505

## GAS CAPTURE PLAN

Date: October 3, 2016

W ALAMITO UT

W ALAMITO UT

#464H

#465H

Original Operator & OGRID No.: WPX Energy Production, LLC OGRID No. 120782 Amended - Reason for Amendment: UPDATED MCFD

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC). Well(s)/Production Facility - Name of facility

UL:H 2091' FNL

UL:H 2089' FNL

& 1046' FEL

& 1086' FEL

947

877

Flared

Flared

The well(s) that will be located at the production facility are shown in the table below. Well Name API Well Expected Flared Comments Footages MCF/D Location or (ULSTR) Vented OIL CONS. DIV DIST. 3

Sec. 12, T22N,

Sec. 12, T22N,

**R8W** 

**R8W** 

**Gathering System and Pipeline Notification** 

30-045-

30-045-

35718

35717

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Gas Transporter and will be connected to Gas Transporter low/high pressure gathering system located in San Juan County, New Mexico. It will require 21,492.10' of pipeline to connect the facility to low/high pressure gathering system. Operator provides (periodically) to Gas Transporter a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Operator and Gas Transporter have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Gas Transporter Processing Plant located in Sec. See Below , Twn. , Rng. County. New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

## Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gas Transporter system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than

sold on a temporary basis.

## Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease ٠
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

**WPX Energy Production, LLC:** 

124

## Gas Capture Plan: Gas Transporter Processing Plant Information

WPX Energy Production, LLC has the ability to deliver to the below listed Gas Processing Plants at any time with the gathering infrastructure that is in place today.

1. Chaco Gas Plant

Section, 16, T26N, R12W San Juan County

New Mexico

2. Ignacio Gas Plant

Section 22, T35N, R9W La Plata County Colorado