District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources** Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Santa Fe, NM 87505 to the appropriate NMOCD District	to the appropriate NMOCD District Office.	
		Plan Application
☐ Permit of a pit ☐ Closure of a pi ☐ Modification to ☐ Closure plan of	or proposed alternative method t, below-grade tank, or proposed alternation o an existing permit/or registration	
• •	ation (Form C-144) per individual pit helow	grade tank or alternative request
Please be advised that approval of this request does not relieve t	he operator of liability should operations result i	n pollution of surface water, ground water or the
Operator: BP America Production Company	OGRID #:	OIL CONS. DIV DIST
Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application Permit of a pit or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permit/or registration Closure plan only submitted for an existing permit/or registration Closure plan only submitted for an existing permit/or registration Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank, or proposed alternative request Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank, or alternative request Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank, or alternative request Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank; not proposed learnative request Instructions I		
Facility or well name:GALLEGOS CANYON U	NIT 397	3 I 2016
API Number: 3004528118	Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application action:	
U/L or Qtr/Qtr K Section 36 Tov	wnship 29N Range 13W	County: San Juan
		NAD: □1927 ☑ 1983
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Lined ☐ Unlined Liner type: Thickness ☐ String-Reinforced	mil LLDPE HDPE PVC Ot	ther
Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permittor registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per Individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the movironment. Nor does approval relieve the operator of liability should operations result in pollution of surface water, ground water or the movironment. Nor does approval relieve the operator of liability should operations result in pollution of surface water, ground water or the movironment. Nor does approval relieve the operator of liability should operations result in pollution of surface water, ground water or the movironment. Nor does approval relieve the operator of liability should operations result in pollution of surface water, ground water or the movironment. Nor does approval relieve the operator of liability should operations result in pollution of surface water, ground water or the movironment. Nor does approval requested to comply with any other applicable governmental authority's rules, requisitions or ordinances. 1. Operator: BP America Production Company		
	rroduced water	
	a sidewalle lines 6 inch life and automater	and an shut off



Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	L les L No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	ruments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	15.17.9 NMAC
☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
is. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	П V П N-
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	Yes No
- FEMA map	L res L No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe to the less of my knowledge	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: OCD Permit Number:	3-16
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	
section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 9/2/2016	
section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 9/2/2016	
☐ Closure Completion Date: 9/2/2016	op systems only)

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure repo	rt is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicable closure requirement	
	The state of the s
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Blue Mun	
Signature:	Date: October 28, 2016
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497
e-mail address: Steven.moskai@op.com	Telephone: (303) 320-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 397 API No. 3004528118 Unit Letter K, Section 36, T29N, R13W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT.
 Evidence of mailing of the notice to the address of the surface owner shown in the
 county tax records demonstrates compliance with this requirement.
 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.024
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.095
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<49
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride with all concentrations below the stated limits. The field report and laboratory reports are attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

 If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed once the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

 BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

 Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action **OPERATOR** Initial Report Final Report Name of Company: BP Contact: Steve Moskal Address: 200 Energy Court, Farmington, NM 87401 Telephone No.: 505-326-9497 Facility Name: Gallegos Canyon Unit 397 Facility Type: Natural gas well Mineral Owner: State API No. 3004528118 Surface Owner: State LOCATION OF RELEASE Unit Letter Section Township Feet from the North/South Line Feet from the East/West Line County: San Juan Range K 36 13W 1,555 South 1,965

> Latituda 26 690020

100 160150 Longitudo

Latitude	Longitude108.10013		
NATURE	OF RELEASE		
Type of Release: none	Volume of Release: unknown	Volume R	ecovered: N/A
Source of Release: below grade tank – 95 bbl (A)	Date and Hour of Occurrence:	Date and I	lour of Discovery: none
	none		
Was Immediate Notice Given? ☐ Yes ☐ No ☐ Not Required	If YES, To Whom?		
By Whom?	Date and Hour		
Was a Watercourse Reached? ☐ Yes ☐ No	If YES, Volume Impacting the Wa	atercourse.	
If a Watercourse was Impacted, Describe Fully.*			
Describe Cause of Problem and Remedial Action Taken.* Sampling of the BTEX, TPH and chloride below BGT closure standards. Field reports at Describe Area Affected and Cleanup Action Taken.* No action necessary I hereby certify that the information given above is true and complete to the regulations all operators are required to report and/or file certain release in public health or the environment. The acceptance of a C-141 report by the should their operations have failed to adequately investigate and remediate the standard of the stand	nd laboratory results are attached. 7. Final laboratory analysis determine the best of my knowledge and understotifications and perform corrective a le NMOCD marked as "Final Report" te contamination that pose a threat to	d no remedial and that pursu ctions for relea does not relieground water,	action is required. ant to NMOCD rules and ases which may endanger eve the operator of liability surface water, human health
or the environment. In addition, NMOCD acceptance of a C-141 report of federal, state, or local laws and/or regulations.			
Signature: Oley Mu	OIL CONSER	VATION I	DIVISION
Printed Name: Steve Moskal	Approved by Environmental Special	ist:	
Title: Field Environmental Coordinator	Approval Date:	Expiration D	Pate:
E-mail Address: steven.moskal@bp.com Date: October 28, 2016 Phone: 505-326-9497	Conditions of Approval:		Attached
Attach Additional Sheets If Necessary			

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

August 29, 2016

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 397 API 30-045-28118 (K) Section 36 – T29N – R13W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around September 1, 2016.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

August 29, 2016

State Land Office Brandon Foley PO Box 3170 Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: GALLEGOS CANYON UNIT 397

API #: 3004528118

Dear Mr. Foley,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about September 1, 2016. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

CLIENT: BP	BLAGG E P.O. BOX 87, B		API #: 3004528		
		5) 632-1199		(if applicble):	
FIELD REPORT:	(circle one): BGT CONFIRMATION	RELEASE INVESTIGATION / (OTHER:	PAGE#:1 c	of
SITE INFORMATION	: SITE NAME: GCU #			DATE STARTED: 09/	01/16
QUAD/UNIT: K SEC: 36 TWP:	29N RNG: 13W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4-1/4/FOOTAGE: 1,555'S / 1,9	65'W NE/SW LEASE T	YPE: FEDERAL/STATE	/ FEE / INDIAN	ENVIRONMENTAL	
LEASE #:	PROD. FORMATION: MV C	ONTRACTOR: BP - J. GO	ONZALES	SPECIALIST(S):	JV
REFERENCE POINT	: WELL HEAD (W.H.) GPS	COORD.: 36.6799	99 X 108.16002	GL ELEV.:	5.473'
1) 95 BGT (DW/DB)		.68002 X 108.16015		RING FROM W.H.: 40', N8	
2)	GPS COORD.:				
3)				RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # C	OR LAB UŞED: HALL			OVM READING
1) SAMPLE ID: 5PC - TB @ 5	(95) SAMPLE DATE: 09/01			5B/8021B/300.0 (CI)	(ppm) NA
2) SAMPLE ID:					
3) SAMPLE ID:					
4) SAMPLE ID:	SAMPLE DATE:	SAMPLETIME:	LAB ANALYSIS:		
SOIL DESCRIPTION	SOIL TYPE- SAND SILTY SAND	SILT / SILTY CLAY / CLAY / CRAVA	EL /OTHER		
SOIL COLOR: DARK YELLOWISH OR		PLASTICITY (CLAYS): NON PLASTI		OHESIVE / MEDIUM PLASTIC / HIGH	HLY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY		DENSITY (COHESIVE CLAYS &			El l'Edilo
CONSISTENCY (NON COHESIVE SOILS): LC	and the state of t	HC ODOR DETECTED: YES NO	EXPLANATION -		
MOISTURE: DRY/SLIGHTLYMOIST/W SAMPLE TYPE: GRAB/COMPOSITE.					
DISCOLORATION/STAINING OBSERVED: YES		ANY AREAS DISPLAYING WETNE	SS: YES NO EXPLAN	NATION -	
SITE OBSERVATION		YES NO EXPLANATION -			
APPARENT EVIDENCE OF A RELEASE OBSERVE				2	
EQUIPMENT SET OVER RECLAIMED AREA:	YES NO EXPLANATION - 105 BB	SHALLOW LOW PROFILE	ABOVE-GRADE TAI	NK TO BE SET ATOP 95 BO	iT.
OTHER: NMOCD REP. PRESENT TO WIT	NESS CONFIRMATION SAMPLING	G. WELL PAD SHARED WIT	H BP'S GCU 189E G	SAS WELL.	
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X <u>NA</u> ft.	EXCAVATION EST	TIMATION (Cubic Yards) : _	NA
DEPTH TO GROUNDWATER: <50' N	EAREST WATER SOURCE: >1,000	NEAREST SURFACE WATER:	_<1,000' NMOC	D TPH CLOSURE STD: 10	00 ppm
SITE SKETCH	BGT Located: off on site	PLOT PLAN circ	cle: attached OVM	CALIB, READ, = NA pp	m RF=0.52
			♦ own	CALIB. GAS = NApp	
	BERM		N TIME	NA am/pm DATE:	NA.
	BERM		, =	MISCELL. NO	TES .
FENCE			l w	/O:	
			_	EF#: P-567	
	(xix) >		l v	ID: VHIXONEVB2	
PBGTL			P.	J#:	
T.B. ~ 5' — B.G.		W.H.	Pe	ermit date(s): 06/1	4/10
B.G.				CD Appr. date(s): 05/2	7/16
	EPARATOR -		Tan	ppm = parts per million	
	EFARATOR		Α	BGT Sidewalls Visible: Y /(
		Х	(- S.P.D.	BGT Sidewalls Visible: Y /	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO		ELOW; T.H. = TEST HOLE; ~ = APPROX.;	W.H. = WELL HEAD;	BGT Sidewalls Visible: Y /	_
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW SINGLE			WALL; NA - NOI	lagnetic declination: 10	ĬĔ
NOTES: GOOGLE EARTH IMAGE		ONSITE: 09/01/	16		

. . .

Analytical Report

Lab Order 1609070

Date Reported: 9/6/2016

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Project: GCU #397

Collection Date: 9/1/2016 10:50:00 AM

Lab ID: 1609070-001

Received Date: 9/2/2016 7:05:00 AM

Analyses	Result	PQL	Qual	Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS						Analyst	: LGT
Chloride	ND	30		mg/Kg	20	9/2/2016 12:08:25 PM	27331
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANIC	s				Analyst	: TOM
Diesel Range Organics (DRO)	11	9.8		mg/Kg	1	9/2/2016 9:42:33 AM	27322
Motor Oil Range Organics (MRO)	ND	49		mg/Kg	1	9/2/2016 9:42:33 AM	27322
Surr: DNOP	94.1	70-130		%Rec	1	9/2/2016 9:42:33 AM	27322
EPA METHOD 8015D: GASOLINE RAI	NGE					Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.7		mg/Kg	1	9/2/2016 12:54:33 PM	27312
Surr: BFB	86.6	68.3-144		%Rec	1	9/2/2016 12:54:33 PM	27312
EPA METHOD 8021B: VOLATILES						Analyst	: NSB
Benzene	ND	0.024		mg/Kg	1	9/2/2016 12:54:33 PM	27312
Toluene	ND	0.047		mg/Kg	1	9/2/2016 12:54:33 PM	27312
Ethylbenzene	ND	0.047		mg/Kg	1	9/2/2016 12:54:33 PM	27312
Xylenes, Total	ND	0.095		mg/Kg	1	9/2/2016 12:54:33 PM	27312
Surr: 4-Bromofluorobenzene	102	80-120		%Rec	1	9/2/2016 12:54:33 PM	27312

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

CI	hain-c	of-Cus	stody Record	l urn-Around	ime:	SAME				H	ALL	E	N	/IF	50	NI	ME	NT	ΓΑΙ	L	
lient:	BLAG	G ENGR.	. / BP AMERICA	☐ Standard	☑ Rush _	DAY)												ATO			
		=782		Project Name					684	w	ww.h	aller	nviro	nm	enta	l.cor	m				
lailing A	ddress:	P.O. BO	X 87		GCU # 39	97		490	01 H	awkin	s NE	- Al	buqı	uerq	ue,	NM	8710	09			
		BLOOM	FIELD, NM 87413	Project #:				Te	1. 50	5-345	-3975		Fax	505	-345	-410	07				
hone #:		(505) 63	2-1199								A	Anal	ysis	Red	ques	st					
mail or f	Fax#:			Project Mana	ger:								(7)				300.1)		T	Т	
A/QC Pa			Level 4 (Full Validation)		NELSON V	ELEZ	(80218)	+ TPH (Gas only)	/ MRO)		(S)		PO4,SC	/ 8082 PCB's			water - 30			e	
ccredita	tion:			Sampler:	NELSON V	ELEZ ny	8	f (Ga	8	न न	8270SIMS)		NO ₂	808			_		1	sample	
NELAF		□ Other		Property of the Control of the Contr	∀Yes	⊞ No	₽	直	2	418	827	<u>s</u>	တ္ခိ	es/		(A)	300.0			te s	or N
Date	Time	Matrix	Sample Request ID	Sample Temp A calcult Container Type and # Mooth Kd	erature: Preservative Type	HEALNO:	BTEX +-MTBE-	BTEX + MTBE	TPH 8015B (GRO / DRO	TPH (Method 418.1)	PAH (8310 or	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil -		Grab sample	5 pt. composite	Air Bubbles (Y or N)
11/16	1050	SOIL	5PC-TB @ 5 '(95)	4 oz 1	Cool	701	٧		٧		١,.						٧	П		٧	
									1										1	1	
																		П	T		
																			\top	\exists	
											T										
											Т		Г								
			1000								T										
ate: 9/1/16	Time:	Relinquish	hill	Received by:	Walte	Date Time 9/1/16 1426	Ren	narks	1/1	CORRES Van	11.71	NG VI	D&R	EFERE		WHE	N AP	THE WAY TO THE	BLE;	e	
ate:	Time:	Relinquish	ed by: Daller	Received by:	u 209	Date Time 102/16/0705	Ref	eren	VID: ce #		ONE\ - 567		VI	MOS	6HQI	FEC	v -	RITCJ	WFE	c -	

Hall Environmental Analysis Laboratory, Inc.

WO#:

1609070

06-Sep-16

Client:

Blagg Engineering

Project:

GCU #397

Sample ID MB-27331

SampType: MBLK Batch ID: 27331

TestCode: EPA Method 300.0: Anions

Client ID: **PBS**

RunNo: 36994

SPK value SPK Ref Val %REC LowLimit

Prep Date: 9/2/2016

Analysis Date: 9/2/2016

SeqNo: 1146344

Units: mg/Kg

HighLimit

RPDLimit

Qual

Analyte Chloride

Result PQL

Sample ID LCS-27331

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS Prep Date: 9/2/2016

Batch ID: 27331 Analysis Date: 9/2/2016

1.5

RunNo: 36994

SeqNo: 1146345

Units: mg/Kg

Page 2 of 5

Qual

Analyte Chloride

PQL 14

15.00

SPK value SPK Ref Val

%REC 94.3

90

LowLimit

110

HighLimit %RPD **RPDLimit**

%RPD

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank B
- E Value above quantitation range
- Analyte detected below quantitation limits J
- P Sample pH Not In Range
- Reporting Detection Limit RL
- Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1609070

06-Sep-16

Client:

Blagg Engineering

Project:

GCU #397

Sample ID LCS-27322	Samp	ype: LC	S	Tes	tCode: E	PA Method	8015M/D: Di	esel Rang	e Organics	
Client ID: LCSS	Batcl	h ID: 27	322	F	RunNo: 3	6957				
Prep Date: 9/2/2016 Analysis Date: 9/2/2016 SeqNo: 1145248 Units: mg/Kg										
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	46	10	50.00	0	91.6	62.6	124			
Surr: DNOP	4.6		5.000		92.7	70	130			
Sample ID MB-27322	SampT	ype: ME	BLK	Tes	Code: E	PA Method	8015M/D: Di	esel Rang	e Organics	
Client ID: PBS	Batch	ID: 27	322	F	tunNo: 3	6957				

Sample ID MB-27322	SampType: MBLK			Tes	TestCode: EPA Method 8015M/D: Diesel Range Organics							
Client ID: PBS	Batch	ID: 27	322	F	RunNo: 3							
Prep Date: 9/2/2016	Analysis D	ate: 9/	2/2016	8	SeqNo: 1	145249	Units: mg/K	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	ND	10										
Motor Oil Range Organics (MRO)	ND	50										
Surr: DNOP	9.9		10.00		99.5	70	130					

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1609070

06-Sep-16

Client:

Blagg Engineering

Project:

GCU #397

Sample ID MB-27312

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: 27312

PQL

5.0

RunNo: 36969

Prep Date:

Surr: BFB

9/1/2016

Analysis Date: 9/2/2016

SeqNo: 1146035

Units: mg/Kg

144

HighLimit

RPDLimit Qual

Analyte Gasoline Range Organics (GRO) Result ND 860

1000

SPK value SPK Ref Val %REC

85.7

68.3

LowLimit

%RPD

Sample ID LCS-27312

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS

Batch ID: 27312

RunNo: 36969

Prep Date: 9/1/2016 Analysis Date: 9/2/2016

SeqNo: 1146036 Units: mg/Kg

Analyte

Result PQL

SPK value SPK Ref Val %REC 101

HighLimit

Qual

%RPD **RPDLimit**

Surr: BFB

25 940

1000

94.3

120

Page 4 of 5

THE RESTOR

Gasoline Range Organics (GRO)

5.0 25.00

80 68.3

LowLimit

144

Oualifiers:

S

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank В
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1609070

06-Sep-16

Client:

Blagg Engineering

Project:

GCU #397

Sample ID MB-27312	SampType: MBLK Batch ID: 27312 Analysis Date: 9/2/2016			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS				F	tunNo: 3	6969				
Prep Date: 9/1/2016				SeqNo: 1146076			Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Kylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		103	80	120			

Sample ID LCS-27312	SampT	ype: LC	s	TestCode: EPA Method 8021B: Volatiles							
Client ID: LCSS	Batch	n ID: 27	312	F							
Prep Date: 9/1/2016	Analysis D)ate: 9/	2/2016	8	SeqNo: 1	146077	Units: mg/K	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	1.0	0.025	1.000	0	101	75.3	123				
Toluene	0.97	0.050	1.000	0	97.3	80	124				
Ethylbenzene	0.97	0.050	1.000	0	97.3	82.8	121				
Xylenes, Total	2.9	0.10	3.000	0	96.2	83.9	122				
Surr: 4-Bromofluorobenzene	1.1		1.000		106	80	120				

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 5 of 5

The same of the same



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Order Number: 1609070 RcptNo: 1 AT 09/02/16 Received by/date: Logged By: **Anne Thorne** 9/2/2016 7:05:00 AM Completed By: **Anne Thorne** 9/2/2016 9/02/16 Reviewed By: 10 Chain of Custody Not Present 1 Custody seals intact on sample bottles? Yes No 🗌 2. Is Chain of Custody complete? Yes V No 🔲 Not Present 3 How was the sample delivered? Courier Log In No 🗌 NA 🗌 Yes V 4. Was an attempt made to cool the samples? 5. Were all samples received at a temperature of >0° C to 6.0°C No 🗌 NA 🗌 No 🗌 Sample(s) in proper container(s)? Yes V No 🗌 7. Sufficient sample volume for indicated test(s)? Yes V 8. Are samples (except VOA and ONG) properly preserved? Yes V No 🗆 NA 🗆 9. Was preservative added to bottles? Yes 🗌 No V No VOA Vials 10.VOA vials have zero headspace? Yes No 🗌 Yes -No 🗸 11. Were any sample containers received broken? # of preserved bottles checked for pH: Yes V No 🔲 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) No 🗌 13. Are matrices correctly identified on Chain of Custody? Yes V Yes V No 🗌 14, is it clear what analyses were requested? Yes V No 🗌 Checked by: 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) Yes 16. Was client notified of all discrepancies with this order? NA V No 🗌 Person Notified: Date By Whom: ☐ eMail ☐ Phone ☐ Fax ☐ In Person Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp C Condition | Seal Intact | Seal No | Seal Date | Signed By 1.5 Good Yes



