District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505 Submit 1 Copy to appropriate District Office to accordance with 19.15.29 NMAC.

Salita	Fe, NW 87303
Release Notification and Corrective Action	
	OPERATOR
Name of Company ConocoPhillips Company	Contact Lisa Hunter
Address 3401 East 30th St, Farmington, NM	Telephone No. (505) 258-1607
Facility Name: San Juan 28-7 Unit 145M	Facility Type: Gas Well
racinty Name. San Juan 28-7 Cint 145M	Tacinty Type. Gas Well
Surface Owner Federal Mineral Owner	er Federal (SF 078972) API No. 3003925823
LOCATION OF RELEASE	
	rth/South Line Feet from the East/West Line County
D 10 27N 07W 790	North 880 West OH Rio Arriba
D 10 27N 07W 790 North 880 West OIL Rio Arriba Latitude 36.593601 Longitude -107. 56661	
NATURE OF RELEASE NOV 1 8 2016	
Type of Release Produced Water	Volume of Release 15bbl Volume Recovered 12bbl
Source of Release Below Grade Tank	Date and Hour of Occurrence Date and Hour of Discovery
	Unknown 11/16/16/ @ 2:00 pm
Was Immediate Notice Given?	If YES, To Whom?
☐ Yes ☐ No ☒ Not Requir	
By Whom? N/A	Date and Hour N/A
Was a Watercourse Reached?	If YES, Volume Impacting the Watercourse.
☐ Yes ⊠ No	N/A
If a Watercourse was Impacted, Describe Fully.* N/A	
Describe Cause of Problem and Remedial Action Taken.*	
Approximately 15 bbls of produced water released from Below Grade Tank into cribbing area, 12bbls recovered by water truck. Release	
remained on location. Well is shut in. Will vacuum collected and contaminated soil in cribbing area.	
Describe Area Affected and Cleanup Action Taken.*	
ConocoPhillips will assess the soil to determine a path forward for clean-up if necessary.	
I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and	
regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger	
public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability	
should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health	
	rt does not relieve the operator of responsibility for compliance with any other
federal, state, or local laws and/or regulations.	
	OIL CONSERVATION DIVISION
. 0 . 111	
Ish tot	
Signature:	Approved by Environmental Specialist:
Printed Name: Lisa Hunter	
	12/1/1
Title: Field Environmental Specialist	Approval Date: 12/16/16 Expiration Date:
E-mail Address: Lisa.Hunter@cop.com	Conditions of Approval: Sample For

* Attach Additional Sheets If Necessary

Date: November 18, 2016

Phone: (505) 258-1607 TRH (DRO-GRO-MRO), Blax chailes

TY #NUT 3216 326 25 720



Attached X

Operator/Responsible Party,

The OCD has received the form C-141 you provided on 1/18/16 regarding an unauthorized release. The information contained on that form has been entered into our incident database and remediation case number NUF1633625720 has been assigned. Please refer to this case number in all future correspondence.

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District III office in Aztec on or before 1/6/17. If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.
- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.
- Nominal detection limits for field and laboratory analyses must be provided.
- Composite sampling is not generally allowed.
- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- •Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.
- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.
- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring
 wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit
 either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should
 not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location
 and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold
OCD Environmental Bureau Chief
1220 South St. Francis Drive
Santa Fe, New Mexico 87505
505-476-3465
jim.griswold@state.nm.us