District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Proposed Alternative Method Permit or Closure Plan Application

Santa Fe, NM 87505

Type of action: Below grade tank registration Permit of a pit or proposed alternative method
Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: Barret A 010
API Number:OCD Permit Number:
U/L or Qtr/Qtr O Section 20 Township 31N Range 09W County: San Juan
Center of Proposed Design: Latitude <u>36.879204</u> Longitude <u>-107.799999</u> NAD: □1927 ☑ 1983
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management □ Low Chloride Drilling Fluid □ yes □ no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK B
Volume: 45 bbl Type of fluid: Produced water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other Single wall/ Double bottom; no visible sidewalls
Liner type: Thicknessmil
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

では、自然の意味を表現していた。 1971年 1983年	
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Flank Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	uid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P. 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
e-mail address: Telephone:	
e-mail address: Telephone:	5/901
e-mail address: DCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Title: OCD Permit Number:	5/9017
e-mail address: Telephone:	the closure report.
e-mail address: Telephone: OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: Title: OCD Permit Number: O	the closure report.
e-mail address: Telephone:	the closure report.
e-mail address: Telephone:	the closure report. to complete this pop systems only) adicate, by a check

22.	
Operator Closure Certification:	
	with this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicab	le closure requirements and conditions specified in the approved closure plan.
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
20.	
Signature: Mus Mus	Date: December 12, 2016
1,1	
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Barrett A 010 API No. 3004526826 Unit Letter O, Section 20, T31N, R09W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

 Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.018
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.071
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<222
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for BTEX and chloride with all concentrations below the stated limits. TPH exceeded the BGT closure standard but remained below the spill and release guidelines with a site ranking of 10. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release had occurred, but remained below the spill and release guidelines with a site ranking of 10. Attached is a laboratory report and

C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release had occurred, but remained below the spill and release guidelines with a site ranking of 10. Attached is a laboratory report and field report. The location will be reclaimed once the well is plugged and

abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

17 - 6			Rele	ease Notific	cation	and Co	rrective A	ction		8		* * * .
						OPERA'	ГOR		Initia	l Report	\boxtimes	Final Report
Name of Co			7.			Contact: Ste		***				
Address: 20			ngton, N	M 87401			No.: 505-326-94					. "
Facility Nan	ne: Barret	t A 010				Facility Typ	e: Natural gas v	well				
Surface Own	ner: Feder	al		Mineral C)wner: l	Federal		A	API No	. 30045268	326	
				LOCA	TION	OF RE	LEASE					
Unit Letter O	Section 20	Township 31N	Range 09W	Feet from the 1,105	North/ South	South Line	Feet from the 1.735	East/West East	Line	County: Sa	an Juan	1
				itude <u>36.879</u>		Longitue	de -107.799					7.5 3
					Ton Ton	OF REL						
Type of Relea	ase: none						Release: unknow	n Vo	olume R	ecovered: N	I/A	
Source of Rel	ease: belov	v grade tank –	45 bbl			Date and H	lour of Occurrenc	e: Da	ite and l	Hour of Dis	covery	none
Was Immedia	te Notice (Yes 🗵	No Not Re	equired	If YES, To	Whom?					***
By Whom?						Date and H						7.0
Was a Watero	course Read		Yes 🗵	No		If YES, Vo	lume Impacting t	he Waterco	urse.			6
If a Watercou	rse was Im	pacted, Descri	be Fully.	*			***					
BTEX and ch	loride belo	w BGT closur	e standaro	n Taken.* Sampli ds. TPH exceeded results are attache	the BG							
Describe Area	Affected a	and Cleanup A	Action Tak	cen.* No action no	ecessary.	Final labora	tory analysis deter	rmined no r	emedial	action is re	quired.	•
regulations al public health should their o	l operators or the envir perations h ment. In a	are required to ronment. The ave failed to a ddition, NMO	acceptant acceptant dequately CD accep	e is true and comp nd/or file certain r ce of a C-141 report investigate and restance of a C-141	elease no ort by the emediate	otifications as NMOCD m contaminati	nd perform correct arked as "Final Re on that pose a thre	tive actions eport" does eat to groun	for rele not relied water,	ases which eve the oper surface wa	may en ator of ter, hu	danger liability man health
Signature:	Menson	The same	×				OIL CONS	SERVAT	TION	DIVISIO	N	9 5 9 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
Printed Name						Approved by	Environmental Sp	pecialist:				
Title: Field E	nvironment	al Coordinato	r		1	Approval Dat	e:	Expi	iration I	Date:		
E-mail Addre	ss: steven.n	noskal@bp.co	m		(Conditions of	Approval:			Attached		
Date: Decem	her 12, 201	6	Pho	ne: 505-326-9497								

^{*} Attach Additional Sheets If Necessary

Moskal, Steven

From:

Railsback, Farrah (CH2M HILL)

Sent:

Monday, October 10, 2016 3:45 PM

To:

'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)'

Cc:

'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Moskal, Steven

Subject:

BP Pit Close Notification - BARRETT A 010

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

October 10, 2016

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BARRETT A 010 API 30-045-26826 (O) Section 20 – T31N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 45bbl BGT and a 21BBL BGT that will no longer be operational at this well site. We anticipate this work to start on or around October 13, 2016.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Railsback BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

October 10, 2016

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: BARRETT A 010

API#: 3004526826

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about October 13, 2016. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

				Ţ	
CHENT: BP		NGINEERING, IN		API#: 3004526	826
CLIENT:		LOOMFIELD, NN 5) 632-1199	VI 87413	TANK ID (if applicble):	Ø
			OTHER.	(п арриоло).	
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / C	JIHEK:	PAGE#: 1 o	f <u>1</u>
SITE INFORMATION	SITE NAME: BARRE	TT A #10		DATE STARTED: 10/1	17/16
QUAD/UNIT: O SEC: 20 TWP:	31N RNG: 9W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4-1/4/FOOTAGE: 1,105'S / 1,7	35'E SW/SE LEASE T		/ FEE / INDIAN	ENVIRONMENTAL	
LEASE #: SF078336B	PROD. FORMATION: PC CO	ONTRACTOR: BP - C. PA	ARKS	SPECIALIST(S):	JV
REFERENCE POINT	: WELL HEAD (W.H.) GPS	COORD.: 36.8793	37 X 107.80030	GL ELEV.: 6	,273'
1) 45 BGT (SW/DB) - B	GPS COORD.: 36.8	79204 X 107.799999	DISTANCE/BEA	RING FROM W.H.: 98.5', S	52.5E
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OF		•		OVM READING (ppm)
1) SAMPLE ID: 5PC - TB @ 5' (4			LAB ANALYSIS: 801	5B/8021B/300.0 (CI)	NA
2) SAMPLE ID: GRAB @ 8' - (beneat	th 45 BGT) SAMPLE DATE: 10/19/1	16 SAMPLETIME: 1155	LAB ANALYSIS:	8015B	NA
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		1
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND S	ILT / SILTY CLAY / CLAY / GRAVE	EL/OTHER	,	
SOIL COLOR: DARK YELLOW	MSH ORANGE	PLASTICITY (CLAYS): NON PLASTIC	C / SLIGHTLY PLASTIC / C	OHESIVE / MEDIUM PLASTIC / HIGH	LY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO	The state of the s	DENSITY (COHESIVE CLAYS &			٥
MOISTURE: DRY/SLIGHTLYMOIST/MOIST/WE		HC ODOR DETECTED: YES NO	EXPLANATION -		X
SAMPLE TYPE: GRAB COMPOSITE #	OF PTS	ANY AREAS DISPLAYING WETNES	SS: YES NO EXPLA	NATION -	1,10
DISCOLORATION/STAINING OBSERVED: YES N					. 0)
SITE OBSERVATION					
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:	DAND/OR OCCURRED: YES NO EXPLAYED NO EXPLANATION - 105 BBL	ANATION:SHALLOW LOW PROFILE AF	BOVE-GRADE TANK	TO BE SET ATOP 45 BGT LO	CATION.
OTHER: CONFIRMATION SAMPLE EXCEE	DED BGT PERMIT CLOSURE STANI	DARD FOR TPH. COLLECTE	ED GRAB SAMPLE A	T SOUTHEAST QUADRANT 8	k
BENEATH NEWLY INSTALLED ABOVE- (SOIL IMPACT DIMENSION ESTIMATION:	GRADE TANK BY ADVANCING HAND NA ft. X NA	D AUGER DIAGONALLY. NM ft. X NA ft.		SENT TO WITNESS SAMPLIN FIMATION (Cubic Yards) :	IG. NA
1 10 1 110 1 120	EAREST WATER SOURCE: >1,000'	NEAREST SURFACE WATER:		CD TPH CLOSURE STD:	-
SITE SKETCH	BGT Located : off on site			CALIB. READ. = NA ppr	
			OVIW	CALIB. GAS = NA ppr	111 0.02
TO.					NA
W.H.	SEPAR	ATOR	ું 'પ⊨	MISCELL. NOT	1
			I w	101130ELL. 1 1 01 <i>1</i> 0:	LO
HAND A	LIGER	FENCE	_	EF#: P - 680	2 2
GRAB S/ 10/19	AMPLE XX			ID: VHIXONEVB2	
	710	(95)		J#:	
	BERM	PBGTL T.B. ~ 5'	Pe	ermit date(s): 06/02	2/10
	BERW	B.G.		CD Appr. date(s): 08/17	
	DEHYDRATOR		Tar IC	ppm = parts per million	
			В		
4.			(- S.P.D.	BGT Sidewalls Visible: Y / I BGT Sidewalls Visible: Y / I	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO					
	WALL; DW-DOUBLE WALL; SB-SINGLE BOTT		W LLL, IVI-NOT	lagnetic declination: 10	<u> </u>
NOTES: GOOGLE EARTH IMAGE	RY DATE: 3/16/2016.	ONSITE: 10/17/	16, 10/19/16		.1



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

October 19, 2016

Nelson Velez

Blagg Engineering

P. O. Box 87

Bloomfield, NM 87413

TEL: (505) 632-1199

FAX (505) 632-3903

RE: BARRETT A #10

OrderNo.: 1610829

Dear Nelson Velez:

Hall Environmental Analysis Laboratory received 2 sample(s) on 10/18/2016 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to www.hallenvironmental.com or the state specific web sites. In order to properly interpret your results it is imperative that you review this report in its entirety. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. When necessary, data qualifiers are provided on both the sample analysis report and the QC summary report, both sections should be reviewed. All samples are reported, as received, unless otherwise indicated. Lab measurement of analytes considered field parameters that require analysis within 15 minutes of sampling such as pH and residual chlorine are qualified as being analyzed outside of the recommended holding time.

Please don't hesitate to contact HEAL for any additional information or clarifications.

ADHS Cert #AZ0682 -- NMED-DWB Cert #NM9425 -- NMED-Micro Cert #NM0190

Sincerely,

Andy Freeman

Laboratory Manager

4901 Hawkins NE

Albuquerque, NM 87109

Analytical Report

Lab Order 1610829

Date Reported: 10/19/2016

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 6' (21)-A

Project: BARRETT A #10

Collection Date: 10/17/2016 11:45:00 AM

Lab ID: 1610829-001 Matrix: SOIL

Received Date: 10/18/2016 8:00:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Anal	yst: LGT
Chloride	ND	30	mg/Kg	20	10/18/2016 11:23:28	8 AM 28137
EPA METHOD 8015M/D: DIESEL RAM	IGE ORGANIC	S			Anal	yst: TOM
Diesel Range Organics (DRO)	ND	9.5	mg/Kg	1	10/18/2016 10:32:41	AM 28121
Motor Oil Range Organics (MRO)	ND	48	mg/Kg	1	10/18/2016 10:32:41	AM 28121
Surr: DNOP	85.8	70-130	%Rec	1	10/18/2016 10:32:41	AM 28121
EPA METHOD 8015D: GASOLINE RA	NGE				Anal	yst: NSB
Gasoline Range Organics (GRO)	ND	5.1	mg/Kg	1	10/18/2016 9:59:46	AM 28094
Surr: BFB	91.8	68.3-144	%Rec	1	10/18/2016 9:59:46	AM 28094
EPA METHOD 8021B: VOLATILES					Anal	yst: NSB
Benzene	ND	0.025	mg/Kg	1	10/18/2016 9:59:46	AM 28094
Toluene	ND	0.051	mg/Kg	1	10/18/2016 9:59:46	AM 28094
Ethylbenzene	ND	0.051	mg/Kg	1	10/18/2016 9:59:46	AM 28094
Xylenes, Total	ND	0.10	mg/Kg	1	10/18/2016 9:59:46	AM 28094
Surr: 4-Bromofluorobenzene	107	80-120	%Rec	1.	10/18/2016 9:59:46	AM 28094

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- Value above quantitation range E
- Analyte detected below quantitation limits Page 1 of 6 J
- Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Analytical Report

Lab Order 1610829

Date Reported: 10/19/2016

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (45)-B

BARRETT A #10 Project:

Collection Date: 10/17/2016 12:30:00 PM

Lab ID: 1610829-002

Matrix: SOIL

Received Date: 10/18/2016 8:00:00 AM

Analyses	Result	PQL	Qual Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS		- p _{ii}		ê	Ana	lyst: LGT
Chloride	ND	30	mg/Kg	20	10/18/2016 11:35:5	3 AM 28137
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANI	cs			Ana	yst: TOM
Diesel Range Organics (DRO)	12	9.7	mg/Kg	1	10/18/2016 11:19:0	O AM 28121
Motor Oil Range Organics (MRO)	210	49	mg/Kg	1	10/18/2016 11:19:0	O AM 28121
Surr: DNOP	93.9	70-130	%Rec	1	10/18/2016 11:19:0	O AM 28121
EPA METHOD 8015D: GASOLINE RAI	NGE	nounce of the second			Ana	yst: NSB
Gasoline Range Organics (GRO)	ND	3.6	mg/Kg	1	10/18/2016 10:24:0	9 AM 28094
Surr: BFB	86.3	68.3-144	%Rec	1	10/18/2016 10:24:0	9 AM 28094
EPA METHOD 8021B: VOLATILES					Ana	yst: NSB
Benzene	ND	0.018	mg/Kg	1	10/18/2016 10:24:0	9 AM 28094
Toluene	ND	0.036	mg/Kg	1	10/18/2016 10:24:09	9 AM 28094
Ethylbenzene	ND	0.036	mg/Kg	1	10/18/2016 10:24:09	9 AM 28094
Xylenes, Total	ND	0.071	mg/Kg	1	10/18/2016 10:24:09	9 AM 28094
Surr: 4-Bromofluorobenzene	102	80-120	%Rec	1	10/18/2016 10:24:09	9 AM 28094

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits Page 2 of 6
- Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#

1610829

19-Oct-16

Client:

Blagg Engineering

Project:

BARRETT A #10

Sample ID MB-28137

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

10/18/2016

Batch ID: 28137

RunNo: 38039

Analysis Date: 10/18/2016

SeqNo: 1186061

Units: mg/Kg

HighLimit

PROBREGO SOCIETY WILL

Analyte

Prep Date:

PQL

%RPD

Qual

Chloride

ND

Sample ID LCS-28137

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID:

LCSS

Batch ID: 28137

RunNo: 38039

LowLimit

Prep Date: 10/18/2016 Analysis Date: 10/18/2016

1.5

SeqNo: 1186062

Units: mg/Kg HighLimit

Analyte

PQL SPK value SPK Ref Val

15.00

RPDLimit

Result 14

SPK value SPK Ref Val %REC LowLimit

110

Chloride

Result

%REC 94.4

%RPD **RPDLimit**

Qual

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Sample pH Not In Range
- RL Reporting Detection Limit Sample container temperature is out of limit as specified
- Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1610829

19-Oct-16

Client:

Blagg Engineering

Project:

BARRETT A #10

Sample ID MB-28121	TestCode: EPA Method 8015M/D: Diesel Range Organics									
Client ID: PBS	Batch	ID: 28	121	F	RunNo: 3	8007				
Prep Date: 10/18/2016	Analysis D	ate: 10	/18/2016	8	SeqNo: 1	184812	Units: mg/h	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10				iliniaila		100	21.0	200
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.0		10.00		90.2	70	130		gradings to the second	

Sample ID LCS-28121	SampT	ype: LC	s	TestCode: EPA Method 8015M/D: Diesel Range Organics										
Client ID: LCSS	Batch	ID: 28	121	R	RunNo: 3	8007								
Prep Date: 10/18/2016	Analysis D	ate: 10	0/18/2016	SeqNo: 1184829		Units: mg/k	(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Diesel Range Organics (DRO)	44	10	50.00	0 -	88.4	62.6	124	·	21	0				
Surr: DNOP	4.1		5.000		81.9	70	130							

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank В
- E
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Value above quantitation range

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1610829

19-Oct-16

Client:

Blagg Engineering

Project:

BARRETT A #10

Sample ID MB-28094

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: 28094

PQL

RunNo: 38022

LowLimit

68.3

Analyte

Prep Date: 10/17/2016

Analysis Date: 10/18/2016

SeqNo: 1185899

Units: mg/Kg **HighLimit**

Qual

Gasoline Range Organics (GRO) Surr: BFB

ND 890

1000

SPK value SPK Ref Val %REC

88.6

144

RPDLimit

TestCode: EPA Method 8015D: Gasoline Range

%RPD

Sample ID LCS-28094 Client ID: LCSS

SampType: LCS

Result

Batch ID: 28094

RunNo: 38022

%REC

Prep Date: 10/17/2016

Analysis Date: 10/18/2016

SeqNo: 1185900

Units: mg/Kg

Analyte Gasoline Range Organics (GRO) Result PQL

SPK value SPK Ref Val 25.00

111 96.2 74.6

%RPD

28 960 5.0

68.3

LowLimit

HighLimit 123

RPDLimit Qual

Page 5 of 6

Surr: BFB

1000

144

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1610829

9-Oct-1

Client:

Blagg Engineering

Project:

BARRETT A #10

Sample ID MB-28094	SampT	уре: МЕ	BLK	TestCode: EPA Method 8021B: Volatiles										
Client ID: PBS	Batch	ID: 28	094	F	RunNo: 3									
Prep Date: 10/17/2016	Analysis D	ate: 10	/18/2016	SeqNo: 1185924			Units: mg/k	K g						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	ND	0.025							1	15				
Toluene	ND	0.050												
Ethylbenzene	ND	0.050												
Kylenes, Total	ND	0.10												
Surr: 4-Bromofluorobenzene	1.0		1.000	and then	102	80	120			d American Science				
Sample ID LCS-28094	SampType: LCS			Tes	tCode: El	tiles	48							
Client ID: LCSS	Batch	ID: 28	094	+ F	RunNo: 3	8022								

Sample ID LCS-28094	TestCode: EPA Method 8021B: Volatiles											
Client ID: LCSS	Batc	h ID: 28	094	+ F	RunNo: 3	8022						
Prep Date: 10/17/2016	Analysis Date: 10/18/2016			- 5	SeqNo: 1	185925	Units: mg/k					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	0.95	0.025	1.000	0	95.4	75.2	115	Constitution of	1 1 4 5 182	CANA S. A.		
Toluene	0.93	0.050	1.000	0	93.3	80.7	112					
Ethylbenzene	0.90	0.050	1.000	0	89.8	78.9	117	7.346				
Xylenes, Total	2.8	0.10	3.000	0	94.3	79.2	115					
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120					

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

MA THE MAN

Page 6 of 6

calculation ar castillar



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Numb	er: 1610829		RcptNo:	:
Received by/date:	- 10/N/6		7,		2.1 ×
Logged By: Anne Thorr	30% 200	AM	anne Sham	_	96.5
Completed By: Anne Thorn	ne 10/18/2016		anne Am		
Reviewed By:	10/18/16		Clare Stran		
Chain of Custody					
1. Custody seals intact on sa	mple bottles?	Yes	No 🗆	Not Present	
2. Is Chain of Custody comple	ete?	Yes 🗹	No 🗆	Not Present	
3. How was the sample delive	ered?	Courier			
<u>Log In</u>					
4. Was an attempt made to c	cool the samples?	Yes 🗹	No 🗀	NA 🗆	
5. Were all samples received	at a temperature of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
6. Sample(s) in proper contain	ner(s)?	Yes 🗹	No 🗆		
7. Sufficient sample volume for	or indicated test(s)?	Yes 🗹	No 🗆		
8. Are samples (except VOA	and ONG) properly preserved?	Yes 🗹	No 🗆		
9. Was preservative added to	bottles?	Yes	No 🗹	NA 🗆	
10.VOA vials have zero heads	pace?	Yes	No 🗆	No VOA Vials	
11. Were any sample containe	ers received broken?	Yes	No 🗹	# of preserved	
12. Does paperwork match bot		Yes 🗹	No 🗆	bottles checked for pH:	
(Note discrepancies on cha		V 🔽	No 🗆	(<2 or Adjusted?	>12 unless noted)
 Are matrices correctly ident Is it clear what analyses we 	· ·	Yes ✓	No 🗆		
15. Were all holding times able	to be met?	Yes 🗹	No 🗆	Checked by:	
(If no, notify customer for a	uthorization.)		,		
Special Handling (if app	licable)				
16. Was client notified of all dis	crepancies with this order?	Yes	No 🗆	NA 🗹	
Person Notified:	Date	r			
By Whom:	Via:	eMail P	hone Fax	☐ In Person	
Regarding:	Andrew Programs and the Control of t			Ph	
Client Instructions:					
17. Additional remarks:					
18. Cooler Information Cooler No. Temp °C		Seal Date	Signed By	;	
1 1.0	Good Yes				

Chain-of-Custody Record Client: BLAGG ENGR. / BP AMERICA		Standard Rush DAY Project Name:				HALL ENVIRONMENTAL ANALYSIS LABORATORY www.hallenvironmental.com													•		
Vailing Ad	ddress:	P.O. BO	X 87	BARRETT A #10 Project#:				4901 Hawkins NE - Albuquerque, NM 87109													
		BLOOM	IFIELD, NM 87413					Te	1. 50	5-34	5-39	75	Fa	x 5	05-3	345-	410	7	~		
hone #:	The state of the s		32-1199	V								An	aly	sis	Req	ues	t				
email or Fax#:			Project Manager:								120		3				300.1)				
QA/QC Package: Standard Level 4 (Full Validation)		NEWON VELEZ			8+s (8021B)	草	/ MRO)	್ಷಕ		(S)		,PO4,S	2 PCB's	,¢		water - 30		e			
Accreditation:		Sampler: NELTON VELEZ) K		DRO	9 9	=	osi		NO	8082			_		amp	_		
NELAP Other		On ice X Yes II No Sample Temperature: . / , ()			1		(GRO/	(418.1)	8	827	2	Š	les/		(A)	98		ites	٥ ۲		
□ EDD (T Date	ype)	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No. 1010829	BTEX +-NATBE	BTEX + MTBE	TPH 8015B (G	TPH (Method	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0	Grab sample	5 pt. composite sample	Air Bubbles (Y or N)
31/11/01	1145	SOIL	SPC-TB@6(21)-A	4021	CooL	7001	V	2 ³ - 9	1				1					V	1	V	
0/17/16	1230	501L	5 PC-TB e5'(45)-B	4021	COOL	702	V		√				+					1		✓	p.
				-																	
	7,00																				
			207					E		,			1						+		
Date:	Time:	Relinquish Relinquish	lay-	Christy Water 19/7/		. 1	Ren	Remarks:			espor ince	NDING Hixor	VID	& REF	eve N	Vosk	WHEN cal		ABLE; n Ritcl		Ц
10/11/11	Time: 1846 f necessary,	/M	With all Environmental may be sui	Received by:	mon	1417/16		eren		1	-6	8 D				HQF	_		rCJWF alytical	_	



